

Expires: June 21, 2016

December 22, 2015

A YANG Data Model for Layer 1 Network Topology

[draft-zhang-ccamp-l1-topo-yang-02.txt](#)

Abstract

This draft describes a YANG data model to manipulate the topologies of a layer 1 Optical Transport Network (OTN). It is independent of control plane protocols and captures topology related information pertaining to OTN and also enables manipulation of an OTN network via the I2RS interface.

Status of this Memo

This Internet-Draft is submitted to IETF in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on June 21, 2016.

Copyright Notice

Copyright (c) 2015 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the [Trust Legal Provisions](#) and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
2.	Conventions used in this document.....	3
3.	Terminology and Notations.....	3
4.	YANG Data Model for Layer 1 Topology	4
4.1.	YANG Tree	4
4.1.1.	Augmentation.....	5
4.1.2.	The node and link list.....	5
4.1.3.	Notification.....	6
4.2.	YANG Code	6
5.	Security Considerations.....	17
6.	Manageability Considerations.....	18
7.	IANA Considerations	18
8.	Acknowledgements	18
9.	References	18
9.1.	Normative References	18
9.2.	Informative References	18
10.	Contributors' Address.....	19
	Authors' Addresses	19

[1. Introduction](#)

This document defines a data model of a layer one network topology, using YANG [[RFC6020](#)]. The model can be used by an application exposing to a management system. Moreover, it can also be used by an application via the I2RS interface [[draft-ietf-i2rs-architecture](#)], in the following ways (but not limited to):

- o to obtain a whole view of the network topology information of its interest e.g., via a network element or maybe a Path

Computation Element (PCE) or a network management system within the network ;

- o to receive notifications with regard to the information of the change of the network topology of its interest;

- o to enforce the establishment/update of a network topology with the characteristic specified in the data model, e.g., by a network controller or a client controller to manipulate the network provided by the provider for flexible control and management;

The YANG model defined in this draft is independent of control plane protocols and captures topology related information pertaining to an Optical Transport Networks (OTN) and also enables manipulation of an OTN network via the I2RS interface. Other network layers, such as fixed Dense Wavelength Switched Optical Network (WSN) and flexible optical networks (a.k.a., flexi-grid networks) are covered in [WSN-YANG] and [[Flexi-YANG](#)], respectively.

2. Conventions used in this document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC-2119](#) [[RFC2119](#)].

3. Terminology and Notations

A simplified graphical representation of the data model is used in this document. The meaning of the symbols in the YANG data tree presented later in this draft is defined in [[ietf-netmod-rfc6087bis](#)]. They are provided below for reference.

- o Brackets "[" and "]" enclose list keys.
- o Abbreviations before data node names: "rw" means configuration (read-write) and "ro" state data (read-only).
- o Symbols after data node names: "?" means an optional node, "!" means a presence container, and "*" denotes a list and leaf-list.
- o Parentheses enclose choice and case nodes, and case nodes are also marked with a colon (":").
- o Ellipsis ("...") stands for contents of subtrees that are not shown.

4. YANG Data Model for Layer 1 Topology

[Editor's note: It was agreed that the model presented in this draft will be augmenting from TE topology YANG, which is not available during the time of writing due to its revision to augment from the generic topology YANG produced in I2RS WG. So, this issue will be addressed in the further versions of this draft.]

4.1. YANG Tree

```
module: ietf-layer1topology
augment /nt:network/nt:network-types:
  +--rw l1-network!
augment /nt:network:
  +--rw l1-network-attributes
    +--rw name?    string
augment /nt:network/nt:node:
  +--rw l1-node-attributes
    +--rw name?          string
    +--rw connectivity-matrix* [id]
      | +--rw id          uint32
      | +--rw type?       enumeration
      | +--rw in-tp* [tp-ref]
      | | +--rw tp-ref    leafref
      | +--rw out-tp* [tp-ref]
      | | +--rw tp-ref    leafref
      | +--rw dir         enumeration
    +--ro oper-status?    enumeration
augment /nt:network/nt:node/nttopo:termination-point:
  +--rw physical-info
    +--rw shelf-id?      uint32
    +--rw board-id?      uint32
    +--rw subcard-id?    uint32
    +--rw port-id?       uint32
augment /nt:network/nttopo:link:
  +--rw l1-link-attributes!
    +--rw source-tp-type    enumeration
    +--rw admin-status?     enumeration
    +--rw link-protection-type? enumeration
    +--rw switching-capability? identityref
    +--rw encoding?         identityref
    +--rw srlg
      | +--rw srlg-values*  uint32
    +--rw (link-attributes)?
      | +--:(ODU)
      | | +--rw ODU-type?    uint32
      | | +--rw availabe-resources
```



```

| | | +--rw granularity          enumeration
| | | +--rw num?                  uint32
| | | +--rw availability-bitmap*  boolean
| | +--rw mapping-info
| |   +--rw mapping-list*        string
| +--:(client)
|   +--rw max-bandwidth?         uint32
|   +--rw unreserved-bandwidth?  uint32
|   +--rw local-ip?              inet:ip-address
|   +--rw remote-ip?             inet:ip-address
+--ro oper-status?               enumeration
notifications:
+--n link-failure
| +--ro topology-ref             leafref
| +--ro link-ref                 leafref
| +--ro admin_status?           leafref
| +--ro oper-status?            leafref
+--n node-failure
| +--ro topology-ref             leafref
| +--ro node-ref                 leafref
| +--ro oper-status?            leafref

```

4.1.1. Augmentation

As can be seen in the YANG module presented augments from a more generic network topology model, i.e., the ietf-network-topology YANG module as specified in [[draft-ietf-i2rs-yang-network-topo](#)]. This is to follow the network model structure suggested in [[draft-ietf-i2rs-yang-network-topo](#)] figure 1.

[Editor's note: how TE topo YANG fits in this figure has been discussed and yet to be updated in that draft.]

4.1.2. The node and link list

The module presented in this draft contains all the nodes and links information pertaining to a layer one network. As specified in the ietf-network YANG module, a node is identified by the node-id, which is unique within the network. Within the nodes, all the interfaces pertaining to this node and their potential capabilities/constraints SHOULD be present. Besides this, the constraints associated with a node as a whole SHOULD also be present, such as the connectivity constraints introduced due to abstraction or due to the hardware limitations.

Similarly, a link is identified by the link-id, which is unique within a node. It includes the association with nodes as well as

interfaces. Moreover, it includes information that is of interest to the management and I2RS client, for purposes, such as path computation, monitoring etc. For termination points, physical information is provided as an optional feature and it provides additional information to allow management/I2RS client to be better informed of this attribute and can help visualize and simplify the operation of termination points selection.

[editor's note]: for next update: any specific information related to an OTN interface has to be described in the context of technological specific extension of OTN-TDM ISCD".

Since for an optical transport network, its client interface attributes may be different with that of the links within the network. For full control purpose, this attributes and information are also captured and listed in this YANG module.

4.1.3. Notification

Two types of notifications are introduced: node failure and link failure.

4.2. YANG Code

```
<CODE BEGINS> file "ietf-layer1topology@2015-12-20.yang"
```

```
module ietf-layer1topology {
  yang-version 1;

  namespace "urn:ietf:params:xml:ns:yang:ietf-layer1topology";
  prefix "l1topo";

  import ietf-inet-types {
    prefix "inet";
  }
  import ietf-network {
    prefix "nd";
  }

  import ietf-network-topology {
    prefix "lnk";
  }

  import ietf-te-types {
    prefix "ietf-te-types";
  }
}
```



```
organization
  "Internet Engineering Task Force (IETF) CCAMP WG";
contact
  "ID-draft editor: zhang.xian@huawei.com";

description
  "This module defines a protocol independent Layer One/OTN
  topology data model.";

revision 2015-12-20{
  description
    "Initial version.";
  reference
    "draft-zhang-ccamp-l1-topo-yang-00.txt";
}

/*
Groupings
*/

grouping srlg-attributes {
  description
    "Shared Risk Link Group Attributes";
  reference
    "RFC 4203: OSPF Extensions in Support of Generalized
    Multi-Protocol Label Switching (GMPLS)";
  leaf-list srlg-values {
    type uint32;
    description "SRLG value list";
  }
}

grouping l1-network-type {
  container l1-network {
    presence "indicates a L1 network, i.e., Optical
    Transport Network (OTN).";
    description "l1 network type";
  }
  description "l1-network-type";
}

grouping l1-network-attributes {
  container l1-network-attributes {
    leaf name {
      type string;
      description "the network name";
    }
  }
}
```



```
    description "name attribute for l1 network";
  }
  description "l1-network-attributes";
}

grouping l1-node-attributes {
  description "l1-node-attributes";
  container l1-node-attributes {
    description "l1-node-attributes";
    leaf name {
      type string;
      description "a name for this node.";
    }
  }

  list connectivity-matrix {
    key "id";

    description
      "This describes the connectivity constraints within
      a node in the network. It can be one matrix or a set
      of matrixes. Further details, read the reference
      provided below.";
    reference
      "https://tools.ietf.org/html/draft-ietf-ccamp-general-
      -constraint-encode-16 Section 2.1";

    leaf id {
      type uint32;
      description "matrix id";
    }
    leaf type {
      type enumeration {
        enum fixed {
          value 0;
          description "Fixed";
        }
        enum dynamic {
          value 1;
          description "Dynamic/changeable";
        }
      }
    }
    description
      "This field describes the attribute of a
      connectivity matrix, i.e., whether it is
      fixed or switched.";
  }
  list in-tp {
```



```
key "tp-ref";

description
  "This list describes a (sub)-set of ingoing
  interfaces within a node that may have
  connectivity constraints.
  Note: directionality may not be relevant
  and it is decided by the dir parameter.";

leaf tp-ref {
  type leafref {
    path "../../../../../lnk:termination-point/"+
    "lnk:tp-id";
  }
  description "reference to an incoming interface,
  must be within the same node";
}
}
list out-tp {
  key "tp-ref";

  description
    "This list describes a (sub)-set of outgoing
    interfaces within a node that may have
    connectivity constraints.
    Note: directionality may not be relevant and
    it is decided by the dir parameter.";

  leaf tp-ref {
    type leafref {
      path "../../../../../lnk:termination-point"+
      "/lnk:tp-id";
    }
    description "reference to an outgoing interface,
    must be within the same node";
  }
}
}
leaf dir{
  type enumeration{
    enum "uni-dir"{
      description
        "the matrix is unidirectional.";
    }
    enum "bi-dir"{
      description
        "this matrix is bidirectional.";
    }
  }
}
```



```
    }
  }
  mandatory true;
  description
    "the directionality attribute of a connc. matrix.";
}
}

leaf oper-status {
  type enumeration {
    enum "unknown" {
      description "unknown - lost connect with control
        plane.";
    }
    enum "up" {
      description "normal";
    }
    enum "down" {
      description "not available";
    }
  }
}

config false;
description "operational status of a node";
}
}

grouping l1-link-attributes {
  description "l1-link-attributes";
  container l1-link-attributes {
    presence "L1 link attributes";
    description "l1 link attributes";
    leaf source-tp-type {
      type enumeration {
        enum "client-side" {
          description "client side";
        }
        enum "line-side" {
          description "line side";
        }
      }
    }
  }
  mandatory true;
  description
    "the type of a port:0-client side; 1 - line side";
}
```



```
leaf admin-status {
  type enumeration {
    enum "up" {
      description "up";
    }

    enum "down" {
      description "normal";
    }
  }
  description "administrative status of a link";
}

leaf link-protection-type {
  type enumeration {
    enum "extra-traffic" {
      description "Extra traffic";
    }
    enum "unprotected" {
      description "unprotected";
    }
    enum "shared" {
      description "Shared";
    }
    enum "1-for-1" {
      description "Dedicated one for one protection";
    }
    enum "1-plus-1" {
      description "Dedicated one plus one protection";
    }
    enum "enhanced" {
      description "a protection type that is more reliable
        than Dedicated 1+1, e.g., 4 fiber BLSR/MS-SPRING.";
    }
  }
  description
    "Link Protection Type configured for this link";
  reference
    "RFC3471: Generalized Multi-Protocol Label Switching
    (GMPLS) Signaling Functional Description.";
}

leaf switching-capability {
  type identityref {
    base ietf-te-types:switching-capabilities;
  }
}
```



```
    description
      "the switching capability supported by the link";
  }

  leaf encoding {
    type identityref {
      base ietf-te-types:lsp-encoding-types;
    }
    description
      "the encoding type supported by this link.";
  }

  container srlg {
    uses srlg-attributes;
    description " the SRLG values of a link";
  }

  choice link-attributes {
    case ODU {
      leaf ODU-type {
        type uint32;
        description "link capacity, subject to change
          to the type of enumeration";
      }
    }

    container availabe-resources {
      leaf granularity {
        type enumeration {
          enum "1.25G" {
            description "1.25G";
          }
          enum "2.5G" {
            description "2.5G";
          }
        }
        mandatory true;
        description "the base unit for unreserved-bandwidth
          description";
      }
      leaf num {
        type uint32;
        description "number * granularity = max-bandwidth";
      }
      leaf-list availability-bitmap {
        type boolean;
        description "0-avaialble, 1- unavaialbe";
      }
    }
  }
}
```



```
    }
    description "describe what is available in the unit
        of granularity";
}
container mapping-info {
    leaf-list mapping-list {
        type string;

        description "it can be one or multiple mapping route";
    }
    description "mapping supported by this link; subject
        to further change";
}
}
case client {
    leaf max-bandwidth {
        type uint32;
        description "max bandwidth supported by this client
            facing link";
    }
    leaf unreserved-bandwidth {
        type uint32;
        description "available bandwidth on this link";
    }
    leaf local-ip {
        type inet:ip-address;
        description "the local-end ip address of a link";
    }
    leaf remote-ip {
        type inet:ip-address;
        description "the remote-end ip address of a link";
    }
}
description "attributes for a client interface";
}

leaf oper-status {
    type enumeration {
        enum "unknown" {
            description "unknown-lost connection with control
                plane";
        }
        enum "normal" {
            description "normal";
        }
        enum "down" {
            description "down";
        }
    }
}
```



```
    }
    enum "degraded" {
        description "degraded, temporarily unusable";
    }
}

config false;

description "status of a link";
}
}
}

grouping l1-tp-attributes {
    description "l1-tp-attributes";
    container physical-info {
        description "physical info of an termination point/port";
        leaf shelf-id {
            type uint32;
            description "shelf-id of which this tp belongs to";
        }
        leaf board-id {
            type uint32;
            description "board-id of which this tp belongs to";
        }
        leaf subcard-id {
            type uint32;
            description "subcard id information, if no such info., "+
                "fill in 0xff.";
        }
        leaf port-id {
            type uint32;
            description "port-id of which this tp belongs to";
        }
    }
}

/*
 * Data nodes
 */

augment "/nd:networks/nd:network/nd:network-types" {
    uses l1-network-type;
    description "augment network types to include L1 newtork";
}

augment "/nd:networks/nd:network" {
```



```
when "nd:network-types/l1-network" {
  description "Augment only for L1 network";
}
uses l1-network-attributes;
description "Augment network configuration";
}

augment "/nd:networks/nd:network/nd:node" {

  when "nd:network-types/l1-network" {
    description "Augment only for L1 network";
  }
  description "Augment node configuration";

  uses l1-node-attributes;
}

augment "/nd:networks/nd:network/nd:node/lnk:termination-point" {
  when "nd:network-types/l1-network" {
    description "Augment only for L1 network";
  }
  description "Augment tp configuration";

  uses l1-tp-attributes;
}

augment "/nd:networks/nd:network/lnk:link" {
  when "nd:network-types/l1-network" {
    description "Augment only for L1 network.";
  }
  description "Augment link configuration";

  uses l1-link-attributes;
}

notification link-failure {
  leaf topology-ref {
    type leafref {
      path "/nd:networks/nd:network/nd:network-id";
    }
    mandatory true;
    description "the topology reference of which"
      +"this link belongs to";
  }
  leaf link-ref {
    type leafref {
      path "/nd:networks/nd:network[nd:network-id= current ()]";
    }
  }
}
```



```
        "/../topology-ref]/lnk:link/lnk:link-id";
    }
    mandatory true;
    description "";
}
leaf admin_status {
    type leafref {
        path
            "/nd:networks/nd:network/lnk:link[lnk:link-id =" +
                "current()/../link-ref]/l1-link-attributes/admin-status";
    }
    description "admin status of the reported link";
}
leaf oper-status {
    type leafref {
        path
            "/nd:networks/nd:network/lnk:link[lnk:link-id = current()"
            + "../link-ref]/l1-link-attributes/oper-status";
    }
    description "";
}
description
    "link failure information";
} //notification-link failure

notification node-failure {
    leaf topology-ref {
        type leafref {
            path "/nd:networks/nd:network/nd:network-id";
        }
        mandatory true;
        description "";
    }
    leaf node-ref {
        type leafref {
            path "/nd:networks/nd:network[nd:network-id= current ()"+
                "/../topology-ref]/nd:node/nd:node-id";
        }
        mandatory true;
        description "";
    }
    leaf oper-status {
        type leafref {
            path
                "/nd:networks/nd:network/nd:node[nd:node-id = current()"
                + "../node-ref]/l1-node-attributes/oper-status";
        }
    }
}
```



```
    }  
    description "";  
  }  
  description  
    "node failure information";  
}  
}  
<CODE ENDS>
```

5. Security Considerations

Since the data model defined in this draft is manipulated via the I2RS interface. The security concerns mentioned in [[draft-ietf-i2rs-architecture](#)] also applies to this draft.

The YANG module defined in this memo is designed to be accessed via the NETCONF protocol [[RFC6241](#)]. The lowest NETCONF layer is the secure transport layer and the mandatory-to-implement secure transport is SSH [[RFC6242](#)]. The NETCONF access control model [[RFC6536](#)] provides the means to restrict access for particular NETCONF users to a pre-configured subset of all available NETCONF protocol operations and content.

There are a number of data nodes defined in the YANG module which are writable/creatable/deletable (i.e., config true, which is the default). These data nodes may be considered sensitive or vulnerable in some network environments. Write operations (e.g., <edit-config>) to these data nodes without proper protection can have a negative effect on network operations.

[Editor's note: to List specific subtrees and data nodes and their sensitivity/vulnerability.]

6. Manageability Considerations

TBD.

7. IANA Considerations

TBD.

8. Acknowledgements

The initial YANG model specified in this draft is based on [draft-clemm-i2rs-yang-network-topo](#) but it is modified according to the features of the layer one networks.

We would like to thank the authors of the above mentioned draft for their helpful discussion during the creation of this draft.

9. References

9.1. Normative References

- [RFC2119] S. Bradner, "Key words for use in RFCs to indicate requirements levels", [RFC 2119](#), March 1997.
- [RFC6020] Bjorklund, M., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", [RFC 6020](#), October 2010.

9.2. Informative References

- [[draft-ietf-i2rs-architecture](#)] Atlas, A., Halpern, J., Hares, S., Ward, D., Nadeau T., "An Architecture for the Interface to the Routing System", [draft-ietf-i2rs-architecture-08](#), work in progress, January 2015;
- [[draft-ietf-i2rs-yang-network-topo](#)] Clemm A., Medved J., Tkacik T., Varga R., et al, "A YANG Data Model for Network Topologies", [draft-ietf-i2rs-yang-network-topo-01](#), work in progress, June 2015;
- [ietf-netmod-rfc6087bis] Bierman, A., "Guidelines for Authors and Reviewers of YANG Data Model Documents", [draft-ietf-netmod-rfc6087bis-01](#), work in progress, October 2014.

[RFC6241] Enns, R., Bjorklund, M., Schoenwaelder, J., and A. Bierman, "Network Configuration Protocol (NETCONF)", [RFC6241](#), June 2011.

[RFC6242] Wasserman, M., "Using the NETCONF Protocol over Secure Shell (SSH)", [RFC 6242](#), June 2011.

[RFC6536] Bierman, A. and M. Bjorklund, "Network Configuration Protocol (NETCONF) Access Control Model", [RFC 6536](#), March 2012.

[WSO-N-YANG] Lee, Y., et al, " A Yang Data Model for WSON Optical Networks", [draft-lee-ccamp-wson-yang-02](#), work in progress, July 2015.

[Flexi-YANG] Lopez de Varga, J.E., et al, "YANG data model for Flexi-Grid Optical Networks", [draft-vergara-ccamp-flexigrid-yang-01](#), work in progress, July 2015.

10. Contributors' Address

Sergio Belotti
Alcatel-Lucent
Sergio.belotti@alcatel-lucent.com

Authors' Addresses

Xian Zhang
Huawei Technologies
Email: zhang.xian@huawei.com

Baoquan Rao
Huawei Technologies
raobaoquan@huawei.com

Xufeng Liu
Ericsson
Xufeng.liu@ericsson.com