

Quality of Service Extensions to OSPF
or
Quality Of Service Path First Routing
(QOSPF)

Status Of This Memo

This document is an Internet-Draft. Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet- Drafts as reference material or to cite them other than as "work in progress".

To learn the current status of any Internet-Draft, please check the "IETF- abstracts.txt" listing contained in the Internet- Drafts Shadow Directo- ries on ds.internic.net (US East Coast), nic.nordu.net (Europe), ftp.isi.edu (US West Coast), or munnari.oz.au (Pacific Rim).

Abstract

This document describes a series of extensions for OSPF[1] and MOSPF[2] that can be used to provide Quality of Service (QoS) routing in conjunction with a resource reservation protocol such as RSVP[4] or other mechanisms that can notify routing of the QoS needs of a data flow. Advertisements indicating the resources available and the resources used are advertised to the OSPF routing domain and paths are computed based on topology in- formation, link resource information, and the resource requirements of a particular data flow.

[1.0](#) Introduction

QoS signalling protocols such as RSVP allow the instantiation of network state to provide a specific service level to a data flow. RSVP is specifically not a routing protocol but it does have

INTERNET DRAFT [draft-zhang-qos-ospf-00.txt](#)

June, 1996

interfaces to routing in order to determine the forwarding of its own state messages.

Existing routing protocols are usually concerned only with topology information and not network resources such as bandwidth, thus they all have their limitations in providing integrated services. The following figure is a simple illustration:

[Figure not in Text Version at this time.]

FIGURE 1. Example Topology

Suppose host H1 is sending data to host H3 at rate R. The routing protocol in use gives the shortest path as defined by the metrics, H1-->R1-->R3-->H3. However, even if R1 does not have adequate resources on its interface to R3 to handle the flow at the rate R, the route H1-->R2-->R3-->H3 that does have adequate resources available, is not used because the routing protocol always uses the shortest path.

One solution is to let the routing protocols consider network resource information as well as topology information when they calculate routes. With the OSPF protocol, complete topology information is used to calculate routes; in QOSPF, network resource information is added and used to calculate "QoS routes" that can provide the resources needed for the flow even though the route may not be strictly the shortest path.

[2.0](#) Protocol Overview

2.1 Network Resource Information

In QOSPF, routers advertise network resource information as well as topology information. A route for a data flow is calculated based on topology, network resource information, and QoS requirements (e.g. the TSpec of the RSVP PATH message) for the flow.

The network resource information includes available link resources on

a router as well as existing link resource reservations on the router. The resource information is advertised in Link Resource Advertisements (RES-LSAs) and Resource Reservation Advertisements (RRAs). Another type of advertisement, Deterministic Area Border Router Advertisements (DABRA), are needed for inter-area multicast

QOSPF.

There are a lot of ways to represent network resource information. In this document, we use Token Bucket parameters, as in the Controlled-Load Service model[5]. It is expected that resource advertisements that are related to other service models could be added over time.

The number of RRAs can easily get huge as the number of reserved flows and network size grows, presenting a scaling issue. A solution to this problem is addressed by Explicit Routing, discussed in [Section 6.0](#).

[2.2](#) Route Pinning

Topology and network resource information not only make it possible to calculate a shortest route that satisfies the required QoS for a flow, but also makes Route Pinning very easy to achieve. Route pinning means that an existing route with a reservation will not be replaced by a better route unless the existing one is no longer usable because of a topology change directly related to the existing route.

[2.3](#) Data-driven (Source, Destination) Route Computation

MOSPF uses data-driven (source, destination) routing. In other words, a route is computed when the first packet for a (source, group) pair is received. This is in contrast to unicast OSPF which pre-computes routes based on destination only.

In QOSPF, routing for QoS flows is based on (source, destination), and routing computations are triggered by external events regardless of whether the flow is unicast or multicast. The initial trigger for

QoS routing computation comes from a resource reservation protocol such as an RSVP PATH message.

There are two reasons for (source, destination) routing in unicast QOSPF:

- Resource reservations and RRAs are generally based on (source, destination);
- When (source, destination) routing is used, flows with the same destination but different sources can follow different paths when necessary.

Note the (source, destination) routing used in unicast QOSPF does not

Expires December, 1996

[Page 3]

INTERNET DRAFT [draft-zhang-qos-ospf-00.txt](#)

June, 1996

mean that the distribution tree must be rooted at the source. It only means that the routing table lookup is based upon (source, destination) rather than just the destination.

[3.0](#) Resource Advertisements

Available and reserved network resources are advertised via Link Resource Advertisements (RES-LSAs) and Resource Reserved Advertisements (RRAs), respectively.

[3.1](#) Link Resource Advertisement (RES-LSA)

A RES-LSA is very similar to a Router-LSA. The purpose of the RES-LSA is to advertise the link resources available for each router in the network. When calculating QoS routes, RES-LSAs are used instead of Router-LSAs.

Each QOSPF router originates a RES-LSA for each area, listing the largest amount of available resources for reservation on each of the router's interfaces in the area, along with the link's delay metric. This metric is roughly analogous to the standard OSPF cost metric but is independent of the standard TOS metric to better characterize the static delay properties of a link.

A new instance of RES-LSA is originated whenever a new Router-LSA instance is originated for the area, or whenever the available bandwidth resource or delay changes for a link in the area. An algorithm may be used so that a new RES-LSA is originated only when the available bandwidth resource changes significantly.

Like Router-LSAs, RES-LSAs are flooded throughout a single area.

The format of RES-LSAs is shown in Figure 2

[Figure not in Text Version at this time.]

FIGURE 2. Resource LSA

The RES-LSA header is the same as all other LSA headers.

The "rtype" field is the same as that in a Router LSA.

The "number of links" is the count of links included in the LSA. For each link the link type, link ID and link data are the same as for the Router LSA.

The available link resource is represented by token bucket parameters, in IEEE single precision floating point format, as in the Controlled-Load Service model[5].

The link delay is a static delay metric for the link, in units of milliseconds.

[3.2](#) Resource Reservation Advertisement (RRA)

A Resource Reservation Advertisement describes a router's reservations for a particular flow (source, destination) on its interfaces within an area. The purpose of the RRA is to indicate the resources used by a flow such that other routers are aware of the resources and path used by the flow when calculate or recalculate the tree for the flow. A new RRA is originated whenever one or more of the reservations change.

Like RES-LSAs, RRAs are flooded throughout a single area.

The format of RRAs is shown in Figure 3.

[Figure not in Text Version at this time.]

FIGURE 3. Resource Reservation Advertisement with its Opaque LSA header

RRAs are encapsulated in Opaque LSAs with type = 11. The Opaque ID is chosen by the advertising router and the flooding scope is "area-local".

In RRAs, the Source is the IP address of the source of the data flow.

The number of links value is the count of links included in the RRA. For each link, the link type, link ID and link data are identical to the values used in the Router LSA.

The pin-flag is used for partial route-pinning discussed in [Section 5.2](#).

The reserved bandwidth resource is represented by token bucket parameters, in IEEE single precision floating point format, as in the

Controlled-Load Service model[5].

The src_prefix_mask and dest_prefix_mask correspond to the network mask length of the source and destination respectively.

The reservation information comes from a resource reservation protocol, such as RSVP or some other mechanism for reserving resources on the node. Whenever a reservation is made or canceled, QOSPF will originate a new instance of the RRA for the flow. RSVP SE style reservations can cause multiple RRAs to be originated depending on the number of PATH state that is matched, and a RSVP WF style reservation will cause a RRA with a wildcard source (0) to be originated.

[4.0](#) QOSPF Route Calculation

Input to the QOSPF Dijkstra calculation includes the source and destination address and the QoS requirements for the flow, which are currently the token bucket parameters from the RSVP PATH message but could also come from other triggers.

The QOSPF Dijkstra calculation for an area is performed by processing the area's RES-LSAs, Network-LSAs, RRAs, and Group-Membership-LSAs. The latter is only used for the multicast case.

The key difference between the QOSPF Dijkstra and the normal OSPF/MOSPF Dijkstra is that a router's RES-LSA rather than Router-LSA is used to discover its neighbors, and links will be ignored if they do not have sufficient resources (either available or already reserved) for the flow.

To calculate the best or lowest-delay path, the static delay metric is used in the same way OSPF uses the TOS zero cost metric of the Router LSA.

[4.1](#) Multicast QOSPF

[4.1.1](#) Intra-area Multicast QOSPF

Like in normal MOSPF, the intra-area QoS SPF tree is forward-linked.

Expires December, 1996

[Page 6]

INTERNET DRAFT [draft-zhang-qos-ospf-00.txt](#)

June, 1996

This means that the best path is chosen based on the delay metrics from the source to the target.

[4.1.2](#) Inter-Area Multicast QOSPF

In MOSPF, for a (source, group) pair, a tree has to be calculated for

each area and then the trees are combined into a global tree. When calculating a tree for an area, if the source is in another area, the root of the tree is set to all the ABRs that support MOSPF and have valid Summary LSAs containing the source.

As shown in Figure 4, suppose the source is in area 0.0.0.0. When R5 and R6 calculate their trees for area 0.0.0.1, they will root the trees at R2, R3, and R4.

[Figure not in Text Version at this time.]

FIGURE 4. A Tree

In QOSPF, links without adequate resources for a data flow are not considered. So, in Figure 1, suppose the link R1->R3 does not have enough bandwidth, then R3 will not be on the multicast tree for area 0.0.0.0 so it will not get the packets. Now when R5 and R6 calculate trees for area 0.0.0.1, they should root the trees only at R2 and R4.

For this reason, after R2 and R4 finishes calculation for area 0.0.0.0, they should notify routers in area 0.0.0.1 how to root the tree via Deterministic ABR-Advertisements (DABRA).

[Figure not in Text Version at this time.]

FIGURE 5. DABRA with its Opaque LSA header

Each ABR on the QoS tree for the "source area" of a flow originates a DABRA, listing all the ABRs on the tree, and floods it throughout all "downstream areas". If the source of the flow is in one of the router's directly attached areas, then the area is the "source area" and all other areas are "downstream" areas; otherwise (the source is in an area not directly attached to the router), the backbone area is the "source area" and all non- backbone areas are "downstream areas".

Similar to the inter-area case, there should be a notification about how to root the tree. The details are not explored in this document.

[4.1.4](#) Detailed Multicast QOSPF Dijkstra Calculation

The following is a modification to [section 12.2](#) in the Multicast Extensions to OSPF, [RFC 1584](#).

1. Initialize the algorithm's data structures.

Same as [RFC 1584](#).

2. Initialize the candidate list.

If the source is in another OSPF area, the candidate list is initialized with the set of area border routers that are both in the DABRA (assuming that a DABRA has been received at this point) and in the calculating area. Otherwise, candidate list is initialized as discussed in [RFC 1584](#).

3. If the candidate list is empty, the algorithm terminates.

Same as [RFC 1584](#).

4. Move the closest candidate vertex to the shortest-path tree.

Same as [RFC 1584](#).

5. Examine Vertex V's neighbors for possible inclusion in the candidate list

If the vertex V just moved from the candidate list to the SPF tree is a router vertex then lookup the router's Resource-LSA (the Resource-LSA is used rather than the Router LSA to determine the router's neighbors). If it is not found then go to step 4. Also lookup the router's Resource Reservation Advertisement for the flow. This may or may not be found.

Each link (link L) in the RES-LSA describes a connection to a neighboring vertex (Vertex W). A link is eligible if either an existing reservation for the flow or the remaining bandwidth is enough to meet the required bandwidth.

For the eligible links perform the following steps on vertex W.

a. If W is already on the SPF tree, or if W's LSA does not contain a link back to vertex V (if vertex W is a router vertex use vertex W's Router LSA to make this determination as it is irrelevant whether or not there is reserved bandwidth in the reverse direction), or if W's LSA has LS age of MaxAge, or if W is not multicast capable (indicated by the MC-bit in W's originators Router LSA or RES-LSA's options field), or if W does not support QOSPF (indicated by the Q-bit [See [Section 7.2](#)] in W's originators Router LSA or RES-LSA's options field), do not use this link.

b. If vertex V is a router vertex, the delay to associate with link L is the delay metric from vertex V's RES-LSA. If both V and W are routers there may be multiple links and the link with the least delay is used (providing that the link meets the bandwidth requirements.) The delay metric is always in the forward direction. If vertex V is a network the delay is zero.

c. The delay from the source to W is the sum of the delay from the source to V and the delay of the link from V to W. Let this sum be delay C. If vertex W is not yet on the candidate list then install W on the candidate list and modify it's parameters as described in step 5d below. Otherwise W is already on the candidate list. In this case if:

1) C is less than W's current delay. In this case processing is the same as in [RFC1584](#).

2) C is equal to W's current delay. In this case processing is the same as in [RFC 1584](#).

3) C is greater than W's current delay. Examine the next link in V's LSA.

d. This section is the same as [RFC 1584](#) except that the delay is used rather than the OSPF cost metric.

6. go to step 3.

After the tree for area A is built, the calculating router determines if area A is used to determine the upstream node in the same way as described by [RFC 1548](#), and if the router is an ABR and area A is the "source area" for the flow, a DABRA is originated and flooded throughout "downstream areas".

[4.2](#) Unicast QOSPF

In terms of adding to and moving from the candidate list, unicast

Expires December, 1996

[Page 9]

INTERNET DRAFT [draft-zhang-qos-ospf-00.txt](#)

June, 1996

QOSPF Dijkstra is very similar to multicast QOSPF so the Dijkstra details are not discussed here.

[4.2.1](#) Unicast QOSPF Dijkstra is needed in only one area

If the calculating router has multiple areas, then the best effort route to the destination has to be found first to identify the area that needs to run the Dijkstra:

1. If the route is an intra-area route, then the area that the route belongs needs to run the Dijkstra to find a QoS route to the destination network.
2. If the route is an inter-area route, then backbone area needs to run the Dijkstra to find a QoS route to one of the ABRs that advertises the best effort route.
3. Suppose the route is an external route. If the ASBR used by the external route is within one of the router's directly attached areas, then that area needs to run the Dijkstra to find out a QoS route to the ASBR; otherwise, backbone area needs to run the Dijkstra to find out a QoS route to one of the ABRs that advertise the ASBR.

Unlike best-effort Dijkstra, a complete tree for the area is not needed. Once the shortest path to the destination network or the ABR or the ASBR is found, the Dijkstra terminates.

[4.2.2](#) Inter-area and Inter-AS Unicast QOSPF

In the case that the destination is not in a directly attached area, things are more complicated because OSPF areas hide detailed topology and network resource information. Using the topology in Figure 1 again; when R1 calculate a QoS route for (H, H2), it finds a QoS route to ABR R2 that has a shortest best-effort route the

destination, but R2 can not find a QoS route to the destination. R3 has a QoS route to the destination but the QoS route from R1 to R3 was not calculated.

One way to solve the problem is let R2 send a "summary" to area 0.0.0.0 indicating that it does not have a QoS route for the particular flow, so R1 will try to find a QoS route to R3. A router should send the summary to each area that it sends the Type 3 Summary LSAs for the destination network.

Expires December, 1996

[Page 10]

INTERNET DRAFT [draft-zhang-qos-ospf-00.txt](#)

June, 1996

However this may not be good idea because there may be a large number of such summaries.

[4.3](#) QOSPF Dijkstra Recalculation

Recalculation occurs upon one or more of the following situations:

- New instances of conventional OSPF/MOSPF LSAs, namely Network-LSAs, Summary-LSAs, AS External LSAs and Group-Membership-LSAs in multicast case.
- New instances of DABRAs in multicast case.
- New instances of RES-LSAs.

[5.0](#) QOSPF Route Pinning

Route Pinning means that once reservations on a route from a source to a destination have been made, the route will not be replaced with a better route, unless the first route is no longer usable. Therefore, a pinned path may not continue to be the shortest path or the one with the most available resources. Control over route pinning can be from a number of sources, such as configuration, flags in RSVP RESV messages or other administrative controls.

Because Resource Reservation Advertisements describe existing reservations, the route pinning algorithm can be accomplished with a simple modification to the QOSPF Dijkstra algorithm:

When the Dijkstra is run for a flow, if the links from the RRAs for the flow are used in preference to links from the RES-LSAs the original path is automatically preserved when possible. This will occur even if a new and better path is available.

[5.1](#) Route Pinning Dijkstra Modification

There are two changes that are made to the QOSPF Dijkstra algorithm to implement route pinning.

Expires December, 1996

[Page 11]

INTERNET DRAFT [draft-zhang-qos-ospf-00.txt](#)

June, 1996

[5.1.1](#) Adding vertices to the candidate list

When adding a vertex to the candidate list, if its parent has a reservation for the flow on the link that leads to the vertex, the vertex is marked as "reserved"; or, if its parent is a network vertex marked as "reserved", it is also marked as "reserved".

If a neighbor W, of a vertex V that is just moved to the SPF tree, is already on the candidate list and it would not be updated in the normal OSPF/ MOSPF Dijkstra, it still is updated if it is not marked as "reserved" and there is a reservation for the flow on the link from V to W.

[5.1.2](#) Moving a vertex from the candidate list to the SPF tree

A vertex marked as "reserved" is chosen with the smallest delay, even if there is an un-reserved vertex with a smaller delay. Vertices that are un-reserved are only moved to the SPF tree when there are no more "reserved" vertices on the candidate list.

[5.2](#) Partial Route Pinning

The previous section assumes that all QoS paths are to be pinned. However, sometimes it is desirable that only part of a QoS distribution tree is pinned because it is possible to have some receivers that desire pinning and some that do not. This can also be easily achieved if RSVP or some dynamic mechanism can signal the desire for route pinning.

Suppose a router/host sends a RESV message to its previous hop router A, and it indicates in the RESV message that it wants the path to be pinned. Router A makes the reservation and notifies QOSPF that the path should be pinned. When A originates an RRA for the flow, it sets a pin-flag in the reservation for the link. When the route is recalculated, instead of preferring all links with reservations, only those links with "pinned" reservation are preferred, hence only part of the route is pinned.

[6.0](#) Explicit Routing OSPF (EROSPF)

Expires December, 1996

[Page 12]

INTERNET DRAFT [draft-zhang-qos-ospf-00.txt](#)

June, 1996

QOSPF needs both available resource information and existing resource reservation information in addition to the normal topology and membership information. When the size of a routing domain or the number of QoS data flows increases, there is a scaling problem because it takes a lot of bandwidth, memory and CPU power to flood, store and process the resource reservation information even though many of the routers may not be interested in the information.

To alleviate this scaling problem, Explicit Routing (ER) can be used: for a flow (source, destination) only the source router(s) (see [Section 6.1.1](#) and [Section 6.2](#)) calculate a route, and then the forwarding information is distributed to the downstream routers along the path.

Because other routers do not need to perform the Dijkstra calculation, they are saved from this possible CPU-intensive computation. In the QOSPF case, the resource reservation information only needs to be kept on the source routers, thus saving bandwidth,

memory, and CPU cycles. EROSPF is also applicable to standard MOSPF to reduce the computational needs of the transit routers.

[6.1](#) Multicast Explicit Routing

The following discussion is in terms of a single area. In the multi-area case, each area maintains a forwarding table, and a global forwarding table comes from the merge of all the areas' forwarding tables.

[6.1.1](#) Source Router Determination

The source router for a flow in an area is determined by one of the following conditions:

- the source of a flow is on a directly connected network within the area.
- the router is an ABR and the source is not in the area.

In other words, explicit routes are only calculated by the source router and the border routers that the flow travels through. It is very possible to have multiple source routers for a (source, destination) pair. In this case, each source router will calculate the tree separately, and then distribute forwarding information

(i.e., its subtree) to the downstream routers on its subtree.

[6.1.2](#) Explicit Routing Advertisements (ERAs)

The forwarding information for a (source, destination) pair is contained in an Explicit Routing Advertisement (ERA), which is passed in an Opaque LSA along the subtree described by the ERA. The passing scope is determined by information contained in the ERA.

There are two kinds of ERAs. One is an Installation-ERA, used to distribute forwarding information and the other is a Flushing-ERA, used to flush obsolete forwarding information.

[6.1.2.1](#) Format of Installation-ERA

The Format of Installation-ERAs is shown in Figure 6:

[Figure not in Text Version at this time.]

FIGURE 6. Format of Installation-ERA

ERAs are carried in Opaque LSAs with the Opaque type 10. The Opaque ID is chosen by its originator. The flooding scope is no-flooding, meaning that the receiver should not flood it out. However, when the receiver parses the ERA, it will build new ERA(s) off the received one and send out the new ones with the same Opaque LSA header and ERA header (see [Section 6.1.6](#)).

The no-flooding scope is not supported in the current Opaque LSA specification, but we are seeking to include it in future specification.

The source and destination masks are represented as prefix lengths.

Each ERA describes routers on a route tree. For each router, its incoming interface and a list of outgoing interfaces are listed. The interface type is the same as in OSPF Router LSAs. The interface is represented as one of the following:

- for a numbered interface, it is the ip address of the upstream (for

incoming interface) or downstream (for outgoing interface) neighbor.

- for an unnumbered point-to-point interface, it is the interface index.

The offset fields (adjust offset and child offset) are used to encode the subtree into the ERA body, as explained in [Section 6.1.3](#) and [Section 6.1.6](#).

[6.1.2.2](#) Flushing-ERA

A Flushing-ERA is used to flush a previously advertised Installation-ERA when the route changes (see [Section 6.1.8](#)). The flushing-ERA uses the MaxAge instance of the previously advertised ERA with an empty ERA body.

[6.1.3](#) Creating Installation-ERAs

After a source router finishes a route calculation, it builds an ERA to encode the subtree that has the router itself as the root. The subtree is traversed in "preorder". In the example in Figure 7 (numbers are interface addresses or indices), the source router A will build an ERA listing routers in the order of A,B,D,E,C.

[Figure not in text version at this time.]

FIGURE 7. An example

The "adjust offset" is set to 0 by the source router. Except for the first router placed into the ERA, when a router is added to the ERA, the "child offset" of the parent's outgoing interface leading to the router is set to the offset of the router in the ERA body. Note that all offsets are relative to the ERA body. After building the whole ERA, the source router builds one ERA for each subtree under itself and unicasts the ERA to the root of the subtree, which is the first router listed in the ERA. For example, router A will build an ERA for the subtree rooted at B and unicast it to B, and build an ERA for the subtree rooted at C and unicasts it to C. This building process is pretty simple and is described in [Section 6.1.6](#). However, the source router only stores the ERA for the whole tree and not the newly built ERAs. The ERA for the subtree rooted at A is shown in Figure 8.

[Figure not in Text Version at this time.]

FIGURE 8. The ERA for the subtree in Figure 7

[6.1.4](#) Using Multiple ERAs for Long Routes

The structure and processing of the ERA allows the router computing the route to encode as much of the route as can fit in a packet. The source router can send an ERA to a downstream router that is not an immediate neighbor providing the subtree that continues from the downstream router. It is not likely that this facility would be used often in many networks.

[6.1.5](#) Transmitting, acknowledging, and storing of ERAs:

A source router stores in its database ERAs (together with their Opaque LSA header) for trees with itself as the root. An ERA built for an immediate downstream neighbor is unicast to the incoming interface of the first router in the ERA (the first router in the ERA is always the receiver), encapsulated in an Opaque LSA.

A router also stores in its database ERAs received from its parents, but not those ERAs built for its downstream neighbors.

The acknowledgment and retransmission mechanism is the same as that used for conventional LSAs. Since the transmission and acknowledgment of OSPF LSAs are between adjacent neighbors while sometimes ERAs and DABRAs need to be sent to non-adjacent routers, a special pair of update/ack packets are needed for ERAs for DABRAs. See [Section 7.3](#)

[6.1.6](#) Processing of Installation-ERAs:

The first listed router in a received ERA is always the receiver itself.

Upon ERA receipt, the forwarding entry for a (source, destination) pair is installed (or updated) and associated with the ERA.

If there is a previous instance of the Installation-ERA, to each

immediate downstream neighbor listed in the previous instance of the

Expires December, 1996

[Page 16]

INTERNET DRAFT [draft-zhang-qos-ospf-00.txt](#)

June, 1996

ERA but not in the new ERA, send a Flushing-ERA with the same header as that of the previous instance.

For each immediate downstream neighbor listed in the received ERA, a new ERA is constructed from the received ERA and sent to the incoming interface of the first listed router in the newly constructed ERA. The Opaque LSA header and the ERA header remain the same, however. The new ERA's "adjust offset" is set to the "child offset" associated with the outgoing interface in the received ERA that leads to the neighbor. The child offsets are not changed in the new ERA. The subtree for the neighbor is then copied into the new ERA. The subtree is in the following range of the RECEIVED ERA BODY:

[child offset - old adjust offset, next child offset - old adjust offset]

If there is no "next child", then the remaining portion of the ERA body is copied. Notice that the encoding work done by the source, and the offset fields make the downstream routers' job a matter of copying and shifting.

In the example in Figure 7, A will build two ERAs from the ERA for itself, one for B and the other for C. The two ERAs are illustrated in Figure 9.

[Figure not in Text Version at this time.]

FIGURE 9. ERAs built by A for B and C

[6.1.7](#) Processing of Flushing-ERAs

Upon receipt of a Flushing-ERA, the corresponding Installation-ERA is found and a MaxAge Flushing-ERA is constructed and sent out with same header as the existing ERA for each immediate downstream neighbor in the Installation- ERA. If a forwarding entry exists for the

corresponding Installation-ERA, the forwarding entry's incoming interface is set to NULL (so that no packets for the (source, group) will be accepted on the interface) if there are no other Installation-ERAs for the (s, g). If other Installation-ERAs exist, a new forwarding entry is constructed for the (source, group) pair. If there is no forwarding entry for the (source, group), forwarding entry with a NULL incoming interface is installed to prevent forwarding of any received packet for the (source, group) pair.

Expires December, 1996

[Page 17]

INTERNET DRAFT [draft-zhang-qos-ospf-00.txt](#)

June, 1996

[6.1.8](#) Route Change

For all routers, if the upstream neighbor or interface of the first router in an ERA goes down, a MaxAge Flushing-ERA is immediately sent to each immediate downstream neighbor to flush the ERA. This does not need to wait until the source finishes recalculation.

When there is a topology change, the source routers recalculate the tree, and send updated ERAs along their subtrees. New ERAs are carried in the Opaque LSAs with the same Opaque ID as in the old ones, but with a larger sequence number.

For all routers, if a previous downstream neighbor is no longer listed in a newer ERA, a Flushing-ERA with the same header of the previous instance of the new ERA is sent to the neighbor to flush its corresponding Installation-ERA.

[6.2](#) Unicast Explicit Routing

While Multicast ER makes sense even if QOSPF is not used, Unicast Explicit Routing is needed only for QoS routing.

A router is a source router for a unicast flow (source, destination) when one of the following conditions exists:

- The source is on one of the router's directly connected networks in the area that needs the Dijkstra, or
- The source is not in the area, and the router is an ABR.

The multicast ERA is also used for unicast, but in the unicast case, the "MOSPF IL Type", "MOSPF Init Case", and incoming interface are not used, and the number of outgoing interface is always 1.

[6.3](#) Changes of behavior of QOSPF if Explicit Routing is used

Explicit Routing is introduced to address QOSPF's scaling problem, but QOSPF does not logically depend on Explicit Routing. The discussions in [Section 3.0](#) and [Section 4.0](#) have been assuming that no ER is used.

Expires December, 1996

[Page 18]

INTERNET DRAFT [draft-zhang-qos-ospf-00.txt](#)

June, 1996

When ER is used, the following behaviors of QOSPF are changed:

[6.3.1](#) Flooding scope of RRAs

RRAs are no longer flooded throughout an area. Instead, they are sent to the source router(s) using opaque "no-flooding" scope. The source routers then can use opaque "link-local" scope to flood the RRAs to other routers on the source network.

[6.3.2](#) Flooding scope of DABRAs

DABRAs are no longer flooded throughout "downstream areas" of the "source area". Instead, a DABRA is sent to all the ABRs on the route in the "source area".

[6.4](#) Quick Scaling Performance Analysis

The Scaling problems with QOSPF are primarily caused by RRAs, so let's do a scaling analysis in terms of number of RRAs flooded per second, based on the following area configuration:

Number of routers in the area: R

Average number of routers on a multicast tree: $M = \text{abs}(\text{sqr_root}(R))$

Average number of flows that sources from a router: F

Period of time during which to set up all the flows: $T = 10$ seconds

For each flow, each router has to originate a RRA, so there will be $(R * M * F)$ RRAs originated.

If explicit routing (ER) is not used, each router will get all the RRAs, so the R routers will receive $(R * F * M - F)$ RRAs (a router does not need to receive its own RRAs), i.e, $(R * F * M - F)/10$ RRAs have to be transmitted per second.

If ER is used, only the source routers will receive the RRAs. Assuming those RRAs are sent to the source router following the reversed multicast path, then at most $(1 + 2 + \dots + (M - 2) + (M -$

Expires December, 1996

[Page 19]

INTERNET DRAFT [draft-zhang-qos-ospf-00.txt](#)

June, 1996

1)) transmissions are needed for each flow, or $F * (1 + 2 + \dots + (M - 2) + (M - 1))/10$ RRAs have to be transmitted per second.

Changing the value of R , we have the following result:

Number of routers (R):	9	16	25	36	49	64
Number of RRAs per sec w/ ER:	0.3F	0.6F	1.0F	1.5F	2.1F	2.8F
Number of RRAs per sec w/o ER:	2.6F	6.3F	9.9F	21.5F	34.2F	51.1F

It is clear that QOSPF does not scale without ER but it scales well with ER.

[7.0](#) Changes to OSPF to accommodate QOSPF/ER

Because of the new functionality and new types of LSAs, the following changes are needed to accommodate QOSPF or ER.

7.1 Database Exchange

In OSPF, when a router exchanges its database with a neighbor, it only sends the neighbor those types of LSAs that the neighbor understands. This is done by checking the Options field in the neighbors' Database Description packets.

A new bit must be added to the Options field: the Q-bit. If set, means the router supports QOSPF and understands RES-LSAs. The Options field is almost full now. Fortunately there are two unused bytes ahead of the Option field and they can be used for more options.

7.2 "Rtype" field in Router/RES LSAs

A new bit, P-bit, in the "Rtype" field of Router LSAs and RES-LSAs must be set if the router is configured to do route pinning for QMOSPF, so that all routers in the same area can agree on using or disabling route pinning and to compute identical multicast trees. Additionally, a Q-bit, indicating that a router supports QOSPF is needed.

7.3 New Types of OSPF packets

OSPF requires that any LSAs be exchanged between neighbors that are supposed to become adjacent and a Link State Update/Ack packet would simply be discarded if it is from a neighbor with a state less than ExStart.

However, when ER is used, the RRAs and ERAs may be sent to non-adjacent routers. The solution is to invent a new pair of update/ack packets that do not require adjacency to transmit/acknowledge RRAs and ERAs when ER is used. The same acknowledgment/retransmission

scheme as those between adjacent neighbors can be used to ensure reliable transmission of RRAs and ERAs.

8.0 Security Considerations

Given that QOSPF could be triggered by RSVP, it is expected that the security mechanisms for RSVP will provide authorization and access control for QOSPF routing calculations. Additionally, the OSPF security mechanisms for authenticating neighbors and data received are very important for explicit routing since ER packets can change forwarding state in a very direct manner. Especially, since an ERA can be sent to a router on a different network, ERA packets' authentication should be per area instead of per interface.

9.0 Acknowledgments

The authors gratefully acknowledge the following people/organizations for making this protocol come together:

- Tim Trapp of Thompson International for the initial problem, constraints, as well as constructive discussions.
- E-Systems, Inc. Particularly, Hai Nguyen, Gerry Rosen, and Thomas Grill for their patience and perserverence during some of the difficult design and development phases.
- Richard Over, Brad Noblet, and the Custom Services Software Engineering team at Bay Networks for sheltering and nurturing the design and development team.

Expires December, 1996

[Page 21]

INTERNET DRAFT [draft-zhang-qos-ospf-00.txt](#)

June, 1996

- The IP group at Bay Networks for lots of support and code modification to multicast routing and RSVP to support QOSPF.
- John Krawczyk, Ross Callon, Mohd Bashar, Mike Davis, and Dennis Baker for useful design comments.

[10.0](#) Notice Regarding Intellectual Property Rights

Bay Networks may seek patent or other intellectual property protection for some or all of the technologies disclosed in this document. If any standards arising from this disclosure are or become protected by one or more patents assigned to Bay Networks, Bay Networks intends to disclose those patents and license them on reasonable and non-discriminatory terms. Future revisions of this draft may contain additional information regarding specific intellectual property protection sought or received.

[11.0](#) References

1. J. Moy, OSPF Version 2, Request for Comments (RFC) [1583](#)
2. J. Moy, Multicast Extensions to OSPF, Request for Comments(RFC) 1584, March 1994.
3. R. Coltun, The OSPF Opaque LSA Option, Internet Draft, [draft-coltun-ospf-opaque-01.txt](#)
4. R. Braden, L. Zhang, S. Berson, S. Herzog, S. Jamin. Resource ReSerVation Protocol (RSVP) - Version 1 Functional Specification, Internet Draft, [draft-ietf-rsvp-spec-12.txt](#), May 1996.
5. J. Wroclawski, Specification of the Controlled-Load Network Element Service, Internet Draft, [draft-ietf-intserv-ctrl-load-svc-01.txt](#), November, 1995.

12.0 Authors' Address

Zhaohui (Jeffrey) Zhang
Bay Networks, Inc.
2 Federal Street
Billerica, MA 01821
+1 508-670-8888
zzhang@baynetworks.com

Cheryl Sanchez
Bay Networks, Inc.
3 Federal Street
Billerica, MA 01821
+1 508-670-8888
csanchez@baynetworks.com

Bill Salkewicz
Bay Networks, Inc.
3 Federal Street
Billerica, MA 01821
+1 508-670-8888
bsalkewi@baynetworks.com

Eric S. Crawley
Bay Networks, Inc.
3 Federal Street
Billerica, MA 01821
+1 508-670-8888
esc@baynetworks.com

