

**SNMPv2 Management Information Base
for the User Datagram Protocol using SMIv2**

Status of this Memo

This document specifies an Internet standards track protocol for the Internet community, and requests discussion and suggestions for improvements. Please refer to the current edition of the "Internet Official Protocol Standards" (STD 1) for the standardization state and status of this protocol. Distribution of this memo is unlimited.

IESG Note:

The IP, UDP, and TCP MIB modules currently support only IPv4. These three modules use the InetAddress type defined as an OCTET STRING of length 4 to represent the IPv4 32-bit internet addresses. (See [RFC 1902](#), SMI for SNMPv2.) They do not support the new 128-bit IPv6 internet addresses.

Table of Contents

1. Introduction	1
2. Definitions	2
2.1 The UDP Group	3
2.2 Conformance Information	5
2.2.1 Compliance Statements	5
2.2.2 Units of Conformance	5
3. Acknowledgements	6
4. References	6
5. Security Considerations	6
6. Editor's Address	6

[1. Introduction](#)

A management system contains: several (potentially many) nodes, each with a processing entity, termed an agent, which has access to management instrumentation; at least one management station; and, a management protocol, used to convey management information between the agents and management stations. Operations of the protocol are carried out under an administrative framework which defines authentication, authorization, access control, and privacy policies.

Management stations execute management applications which monitor and control managed elements. Managed elements are devices such as hosts, routers, terminal servers, etc., which are monitored and controlled via access to their management information.

Management information is viewed as a collection of managed objects, residing in a virtual information store, termed the Management Information Base (MIB). Collections of related objects are defined in MIB modules. These modules are written using a subset of OSI's Abstract Syntax Notation One (ASN.1) [1], termed the Structure of Management Information (SMI) [2].

This document is the MIB module which defines managed objects for managing implementations of the User Datagram Protocol (UDP) [3].

The managed objects in this MIB module were originally defined using the SNMPv1 framework as a part of MIB-II [4]. This document defines the same objects for UDP using the SNMPv2 framework.

2. Definitions

UDP-MIB DEFINITIONS ::= BEGIN

IMPORTS

```
MODULE-IDENTITY, OBJECT-TYPE, Counter32,
IpAddress, mib-2                  FROM SNMPv2-SMI
MODULE-COMPLIANCE, OBJECT-GROUP     FROM SNMPv2-CONF;
```

udpMIB MODULE-IDENTITY

```
LAST-UPDATED "9411010000Z"
ORGANIZATION "IETF SNMPv2 Working Group"
CONTACT-INFO
    "          Keith McCloghrie
```

```
Postal: Cisco Systems, Inc.
        170 West Tasman Drive
        San Jose, CA 95134-1706
        US
```

```
Phone: +1 408 526 5260
Email: kzm@cisco.com"
```

McCloghrie

Standards Track

[Page 2]

```
DESCRIPTION
    "The MIB module for managing UDP implementations."
REVISION      "9103310000Z"
DESCRIPTION
    "The initial revision of this MIB module was part of MIB-
II."
 ::= { mib-2 50 }

-- the UDP group

udp      OBJECT IDENTIFIER ::= { mib-2 7 }

udpInDatagrams OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The total number of UDP datagrams delivered to UDP users."
 ::= { udp 1 }

udpNoPorts OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The total number of received UDP datagrams for which there
        was no application at the destination port."
 ::= { udp 2 }

udpInErrors OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of received UDP datagrams that could not be
        delivered for reasons other than the lack of an application
        at the destination port."
 ::= { udp 3 }

udpOutDatagrams OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The total number of UDP datagrams sent from this entity."
 ::= { udp 4 }
```

McCloghrie

Standards Track

[Page 3]

```
-- the UDP Listener table

-- The UDP listener table contains information about this
-- entity's UDP end-points on which a local application is
-- currently accepting datagrams.

udpTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF UdpEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A table containing UDP listener information."
    ::= { udp 5 }

udpEntry OBJECT-TYPE
    SYNTAX      UdpEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Information about a particular current UDP listener."
    INDEX      { udpLocalAddress, udpLocalPort }
    ::= { udpTable 1 }

UdpEntry ::= SEQUENCE {
    udpLocalAddress  InetAddress,
    udpLocalPort     INTEGER
}

udpLocalAddress OBJECT-TYPE
    SYNTAX      InetAddress
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The local IP address for this UDP listener. In the case of
         a UDP listener which is willing to accept datagrams for any
         IP interface associated with the node, the value 0.0.0.0 is
         used."
    ::= { udpEntry 1 }

udpLocalPort OBJECT-TYPE
    SYNTAX      INTEGER (0..65535)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The local port number for this UDP listener."
    ::= { udpEntry 2 }
```

McCloghrie

Standards Track

[Page 4]

-- conformance information

udpMIBConformance OBJECT IDENTIFIER ::= { udpMIB 2 }

udpMIBCompliances OBJECT IDENTIFIER ::= { udpMIBConformance 1 }
udpMIBGroups OBJECT IDENTIFIER ::= { udpMIBConformance 2 }

-- compliance statements

udpMIBCompliance MODULE-COMPLIANCE

STATUS current

DESCRIPTION

"The compliance statement for SNMPv2 entities which
implement UDP."

MODULE -- this module

MANDATORY-GROUPS { udpGroup
}

::= { udpMIBCompliances 1 }

-- units of conformance

udpGroup OBJECT-GROUP

OBJECTS { udpInDatagrams, udpNoPorts,
udpInErrors, udpOutDatagrams,
udpLocalAddress, udpLocalPort }

STATUS current

DESCRIPTION

"The udp group of objects providing for management of UDP
entities."

::= { udpMIBGroups 1 }

END

3. Acknowledgements

This document contains a modified subset of [RFC 1213](#).

4. References

- [1] Information processing systems - Open Systems Interconnection Specification of Abstract Syntax Notation One (ASN.1), International Organization for Standardization. International Standard 8824, (December, 1987).
- [2] McCloghrie, K., Editor, "Structure of Management Information for version 2 of the Simple Network Management Protocol (SNMPv2)", [RFC 1902](#), Cisco Systems, January 1996.
- [3] Postel, J., "User Datagram Protocol", STD 6, [RFC 768](#), USC-ISI, August 1980.
- [4] McCloghrie, K., and Rose, M., "Management Information Base for Network Management of TCP/IP-based internets: MIB-II", STD 17, [RFC 1213](#), March 1991.

5. Security Considerations

Security issues are not discussed in this memo.

6. Editor's Address

Keith McCloghrie
Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
US

Phone: +1 408 526 5260
Email: kzm@cisco.com

