

Network Working Group
Internet Draft
Document: [draft-myers-imap-quota-00.txt](#)

J. Myers
Carnegie Mellon
December 1995

IMAP4 QUOTA extension

Status of this Memo

This document is an Internet Draft. Internet Drafts are working documents of the Internet Engineering Task Force (IETF), its Areas, and its Working Groups. Note that other groups may also distribute working documents as Internet Drafts.

Internet Drafts are draft documents valid for a maximum of six months. Internet Drafts may be updated, replaced, or obsoleted by other documents at any time. It is not appropriate to use Internet Drafts as reference material or to cite them other than as a ``working draft'' or ``work in progress''.

To learn the current status of any Internet-Draft, please check the `1id-abstracts.txt` listing contained in the Internet-Drafts Shadow Directories on `ds.internic.net`, `nic.nordu.net`, `ftp.isi.edu`, or `munari.oz.au`.

A revised version of this draft document will be submitted to the RFC editor as a Proposed Standard for the Internet Community. Discussion and suggestions for improvement are requested. This document will expire before April 1996. Distribution of this draft is unlimited.

Internet DRAFT

QUOTA

December 14, 1995

1. Abstract

The QUOTA extension of the Internet Message Access Protocol [[IMAP4](#)] permits administrative limits on resource usage (quotas) to be manipulated through the IMAP protocol.

2. Conventions Used in this Document

In examples, "C:" and "S:" indicate lines sent by the client and server respectively.

3. Introduction and Overview

The QUOTA extension is present in any IMAP4 implementation which returns "QUOTA" as one of the supported capabilities to the CAPABILITY command.

An IMAP4 server which supports the QUOTA capability may support limits on any number of resources. Each resource has an atom name and an implementation-defined interpretation which evaluates to an integer. Examples of such resources are:

Name	Interpretation
STORAGE	Sum of messages' RFC822 .SIZE, in units of 1024 octets
MESSAGE	Number of messages

Each mailbox has zero or more implementation-defined named "quota roots". Each quota root has zero or more resource limits. All mailboxes that share the same named quota root share the resource limits of the quota root.

Quota root names do not necessarily have to match the names of existing mailboxes.

Internet DRAFT

QUOTA

December 14, 1995

[4.](#) Commands

[4.1.](#) SETQUOTA Command

Arguments: quota root
list of resource limits

Data: untagged responses: QUOTA

Result: OK - setquota completed
NO - setquota error: can't set that data
BAD - command unknown or arguments invalid

The SETQUOTA command takes the name of a mailbox quota root and a list of resource limits. The resource limits for the named quota root are changed to be the specified limits. Any previous resource limits for the named quota root are discarded.

If the named quota root did not previously exist, an implementation may optionally create it and change the quota roots for any number of existing mailboxes in an implementation-defined manner.

Example: C: A001 SETQUOTA "" (STORAGE 512)
S: * QUOTA "" (STORAGE 10 512)
S: A001 OK Setquota completed

[4.2.](#) GETQUOTA Command

Arguments: quota root

Data: untagged responses: QUOTA

Result: OK - getquota completed

NO - getquota error: no such quota root, permission denied
BAD - command unknown or arguments invalid

The GETQUOTA command takes the name of a quota root and returns the quota root's resource usage and limits in an untagged QUOTA response.

Example: C: A003 GETQUOTA ""
S: * QUOTA "" (STORAGE 10 512)
S: A003 OK Getquota completed

J. Myers

[Page 3]

Internet DRAFT

QUOTA

December 14, 1995

[4.3.](#) GETQUOTAROOT Command

Arguments: mailbox name

Data: untagged responses: QUOTAROOT, QUOTA

Result: OK - getquota completed
NO - getquota error: no such mailbox, permission denied
BAD - command unknown or arguments invalid

The GETQUOTAROOT command takes the name of a mailbox and returns the list of quota roots for the mailbox in an untagged QUOTAROOT response. For each listed quota root, it also returns the quota root's resource usage and limits in an untagged QUOTA response.

Example: C: A003 GETQUOTAROOT INBOX
S: * QUOTAROOT INBOX ""
S: * QUOTA "" (STORAGE 10 512)
S: A003 OK Getquota completed

[5.](#) Responses

[5.1.](#) QUOTA Response

Data: quota root name
list of resource names, usages, and limits

This response occurs as a result of a GETQUOTA or GETQUOTAROOT command. The first string is the name of the quota root for which this quota applies.

The name is followed by a S-expression format list of the resource usage and limits of the quota root. The list contains zero or more triplets. Each triplet contains a resource name, the current usage of the resource, and the resource limit.

Resources not named in the list are not limited in the quota root. Thus, an empty list means there are no administrative resource limits in the quota root.

Example: S: * QUOTA "" (STORAGE 10 512)

[5.2.](#) QUOTAROOT Response

Data: mailbox name
 zero or more quota root names

This response occurs as a result of a GETQUOTAROOT command. The first string is the mailbox and the remaining strings are the names of the quota roots for the mailbox.

Example: S: * QUOTAROOT INBOX ""
 S: * QUOTAROOT comp.mail.mime

[6.](#) Formal syntax

The following syntax specification uses the augmented Backus-Naur Form (BNF) notation as specified in [RFC 822](#) with one exception; the delimiter used with the "#" construct is a single space (SP) and not one or more commas.

Except as noted otherwise, all alphabetic characters are case-insensitive. The use of upper or lower case characters to define

token strings is for editorial clarity only. Implementations MUST accept these strings in a case-insensitive fashion.

getquota ::= "GETQUOTA" SP astring

getquotaroot ::= "GETQUOTAROOT" SP astring

quota_list ::= "(" #quota_resource ")"

quota_resource ::= atom SP number SP number

quota_response ::= "QUOTA" SP astring SP quota_list

quotaroot_response
::= "QUOTAROOT" SP astring *(SP astring)

setquota ::= "SETQUOTA" SP astring SP setquota_list

setquota_list ::= "(" 0#setquota_resource ")"

setquota_resource ::= atom SP number

7. References

[IMAP4] Crispin, M., "Internet Message Access Protocol - Version 4", [RFC 1730](#), University of Washington, December 1994.

J. Myers

[Page 5]

Internet DRAFT

QUOTA

December 14, 1995

[RFC-822] Crocker, D., "Standard for the Format of ARPA Internet Text Messages", STD 11, [RFC 822](#).

8. Security Considerations

Implementors should be careful to make sure the implementation of these commands does not violate the site's security policy. The resource usage of other users is likely to be considered confidential information and should not be divulged to unauthorized persons.

9. Author's Address

John G. Myers
Carnegie-Mellon University
5000 Forbes Ave.

Pittsburgh PA, 15213-3890

Email: jgm+@cmu.edu

J. Myers

[Page 6]

Internet DRAFT

QUOTA

December 14, 1995

Table of Contents

Status of this Memo	i
---------------------------	-------------------

1.	Abstract	2
2.	Conventions Used in this Document	2
3.	Introduction and Overview	2
4.	Commands	3
4.1.	SETQUOTA Command	3
4.2.	GETQUOTA Command	3
4.3.	GETQUOTAROOT Command	4
5.	Responses	4
5.1.	QUOTA Response	4
5.2.	QUOTAROOT Response	4
6.	Formal syntax	5
7.	References	5
8.	Security Considerations	6
9.	Author's Address	6