

Dynamic Hostname Exchange Mechanism for IS-IS

Status of this Memo

This memo provides information for the Internet community. It does not specify an Internet standard of any kind. Distribution of this memo is unlimited.

Copyright Notice

Copyright (C) The Internet Society (2000). All Rights Reserved.

Abstract

Currently, there does not exist a simple and dynamic mechanism for routers running IS-IS to learn about symbolic hostnames. This document defines a new TLV which allows the IS-IS routers to flood their name to system ID mapping information across the IS-IS network.

1. Introduction

IS-IS uses a 1-8 byte system ID (normally 6 bytes) to represent a node in the network. For management and operation reasons, network operators need to check the status of IS-IS adjacencies, entries in the routing table and the content of the IS-IS link state database. It is obvious that, when looking at diagnostics information, hexadecimal representations of systemIDs and LSP identifiers are less clear than symbolic names.

One way to overcome this problem is to define a name-to-systemID mapping on a router. This mapping can be used bidirectionally. E.g., to find symbolic names for systemIDs, and to find systemIDs for symbolic names. One way to build this table of mappings is by static definitions. Among network administrators who use IS-IS as their IGP it is current practice to define such static mappings.

Thus every router has to maintain a table with mappings between router names and systemIDs. These tables need to contain all names and systemIDs of all routers in the network.

There are several ways one could build such a table. One is via static configurations. Another scheme that could be implemented is via DNS lookups. In this document we propose a third solution. We hope the proposed solution is easier and more manageable than static mapping or DNS schemes.

2. Possible solutions

The obvious drawback of static configuration of mappings is the issue of scalability and maintainability. The network operators have to maintain the name tables. They have to maintain an entry in the table for every router in the network. They have to maintain this table on each router in the network. The effort to create and maintain these static tables grows with the total number of routers on the network. Changing the name or systemID of one router, or adding one new router introduced will affect the configurations of all the other routers on the network. This will make it very likely that those static tables are outdated.

Having one table that can be updated in a centralized place would be helpful. One could imagine using the DNS system for this. A drawback is that during the time of network problems, the response time of DNS services might not be satisfactory or the DNS services might not even be available. Another possible drawback might be the added complexity of DNS. Also, some DNS implementations might not support A and PTR records for CLNS NSAPs.

A third way to build dynamic mappings would be to use the transport mechanism of the routing protocol itself to advertise symbolic names in IS-IS link-state PDU. This document defines a new TLV which allows the IS-IS routers to include the name to systemID mapping information in their LSPs. This will allow simple and reliable transport of name mapping information across the IS-IS network.

3. The Dynamic Hostname TLV

The Dynamic hostname TLV is defined here as TLV type 137.

LENGTH - total length of the value field.

VALUE - a string of 1 to 255 bytes.

The Dynamic hostname TLV is optional. This TLV may be present in any fragment of a non-pseudo node LSP. The value field identifies the symbolic name of the router originating the LSP. This symbolic name can be the FQDN for the router, it can be a subset of the FQDN or any string operators want to use for the router. The use of FQDN or a

subset of it is strongly recommended. The content of this value is a domain name, see [RFC 2181](#). The string is not null-terminated. The systemID of this router can be derived from the LSP identifier.

If this TLV is present in a pseudo node LSP, then it should not be interpreted as the DNS hostname of the router.

4. Implementation

The Dynamic Hostname TLV is optional. When originating an LSP, a router may decide to include this TLV in its LSP. Upon receipt of an LSP with the dynamic hostname TLV, a router may decide to ignore this TLV, or to install the symbolic name and systemID in its hostname mapping table.

A router may also optionally insert this TLV in it's pseudo node LSP for the association of a symbolic name to a local LAN.

5. Security Considerations

This document raises no new security issues for IS-IS. However, it is encouraged to use authentications for IS-IS routing protocol. The authentication mechanism for IS-IS protocol is specified in [\[1\]](#) and it is being enhanced within IETF in [\[2\]](#).

6. Acknowledgments

The authors would like to thank Enke Chen and Yakov Rekhter for their comments on this work.

7. References

- [1] ISO, "Intermediate system to Intermediate system routing information exchange protocol for use in conjunction with the Protocol for providing the Connectionless-mode Network Service (ISO 8473)," ISO/IEC 10589:1992.
- [2] Li, T., "IS-IS HMAC-MD5 Authentication", Work in Progress.

8. Authors' Addresses

Naiming Shen
Siara Systems, Inc.
1195 Borregas Avenue
Sunnyvale, CA, 94089

EMail: naiming@siara.com

Henk Smit
Cisco Systems, Inc.
170 Tasman Drive
San Jose, CA, 95134

EMail: hsmit@cisco.com

9. Full Copyright Statement

Copyright (C) The Internet Society (2000). All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Acknowledgement

Funding for the RFC Editor function is currently provided by the Internet Society.

