

Network Working Group
Request for Comments: 3485
Category: Standards Track

M. Garcia-Martin
Ericsson
C. Bormann
J. Ott
TZI/Uni Bremen
R. Price
Siemens/Roke Manor
A. B. Roach
dynamicsoft
February 2003

The Session Initiation Protocol (SIP) and Session Description Protocol (SDP) Static Dictionary for Signaling Compression (SigComp)

Status of this Memo

This document specifies an Internet standards track protocol for the Internet community, and requests discussion and suggestions for improvements. Please refer to the current edition of the "Internet Official Protocol Standards" (STD 1) for the standardization state and status of this protocol. Distribution of this memo is unlimited.

Copyright Notice

Copyright (C) The Internet Society (2003). All Rights Reserved.

Abstract

The Session Initiation Protocol (SIP) is a text-based protocol for initiating and managing communication sessions. The protocol can be compressed by using Signaling Compression (SigComp). Similarly, the Session Description Protocol (SDP) is a text-based protocol intended for describing multimedia sessions for the purposes of session announcement, session invitation, and other forms of multimedia session initiation. This memo defines the SIP/SDP-specific static dictionary that SigComp may use in order to achieve higher efficiency. The dictionary is compression algorithm independent.

Table of Contents

1.	Introduction.....	2
2.	Design considerations.....	3
3.	Binary representation of the SIP/SDP dictionary.....	5
4.	Security Considerations.....	13
5.	IANA Considerations.....	13
6.	Acknowledgements.....	14
7.	References.....	14
7.1	Normative References.....	14
7.2	Informative References.....	14
Appendix A.	SIP input strings to the SIP/SDP static dictionary.....	17
Appendix B.	SDP input strings to the SIP/SDP static dictionary.....	26
	Authors' Addresses.....	29
	Full Copyright Statement.....	30

[1.](#) Introduction

SIP [[3](#)] and SDP [[24](#)] are text-based protocols that use the UTF-8 charset ([RFC 2279](#) [[5](#)]). SIP and SDP were designed for rich bandwidth links. However, when SIP/SDP is run over narrow bandwidth links, such as radio interfaces or low speed serial links, the session setup time increases substantially, compared to an operation over a rich bandwidth link.

The session setup time can decrease dramatically if the SIP/SDP signaling is compressed. The signaling compression mechanisms specified in SigComp [[1](#)] provide a multiple compression/decompression algorithm framework to compress and decompress text-based protocols such as SIP and SDP.

When compression is used in SIP/SDP, the compression achieves its maximum rate once a few message exchanges have taken place. This is due to the fact that the first message the compressor sends to the decompressor is only partially compressed, as there is not a previous stored state to compress against. As the goal is to reduce the session setup time as much as possible, it seems sensible to investigate a mechanism to boost the compression rate from the first message.

In this memo we introduce the static dictionary for SIP and SDP. The dictionary is to be used in conjunction with SIP, SDP and SigComp. The static SIP/SDP dictionary constitutes a SigComp state that can be

referenced in the first SIP message that the compressor sends out.

[2.](#) Design considerations

The static SIP/SDP dictionary is a collection of well-known strings that appear in most of the SIP and SDP messages. The dictionary is not a comprehensive list of reserved words, but it includes many of the strings that appear in SIP and SDP signaling.

The static dictionary is unique and MUST be available in all SigComp implementations for SIP/SDP. The dictionary is not intended to evolve as SIP or SDP evolve. It is defined once, and stays as is forever. This solves the problems of updating, upgrading and finding out the dictionary that is supported at the remote end when several versions of the same dictionary coexist.

[Appendix A](#) contains the collection of strings that SIP contributed to the static dictionary. The appendix includes references to the documents that define those strings.

[Appendix B](#) contains the collection of strings that SDP contributed to the static dictionary. Again, the appendix includes references to the documents that define those strings.

While these appendices are of an informative nature, [Section 3](#) gives the normative binary form of the SIP/SDP dictionary. This is the dictionary that is included in the SigComp implementation. This dictionary has been formed from the collection of individual dictionaries given in appendices A and B.

The two input collections are collections of UTF-8 encoded character strings. In order to facilitate the readability, the appendices describe them in one table for each collection. In these tables, each row represents an entry. Each entry contains the string that actually occurs in the dictionary, its priority (see below), its offset from the first octet and its length (both in hexadecimal), and one or more references that elucidate why this string is expected to occur in SIP/SDP messages. Note: Length in this document always

refers to octets.

The columns in the tables are described as follows:

String: represents the UTF-8 string that is inserted into the dictionary. Note that the quotes (") are not part of the string itself. Note also that the notation [CRLF] represents a Carriage Return character (ASCII code 0x0D) followed by a Line Feed character (ASCII code 0x0A).

Pr: indicates the priority of this string within the dictionary. Some compression algorithms, such as DEFLATE, offer an increased efficiency when the most commonly used strings are located at the bottom of the dictionary. To facilitate generating a dictionary that has the most frequently occurring strings further down at the bottom, we have decided to allocate a priority to each string in the dictionary. Priorities range from 1 until 5. A low number in the priority column (e.g., 1) indicates that we believe in a high probability of finding the string in SIP or SDP messages. A high number in the priority column (e.g., 5) indicates lower probability of finding the string in a SIP or SDP message. This is typically the case for less frequent error codes or optional infrequent tags.

Off: indicates the hexadecimal offset of the entry with respect to the first octet in the dictionary. Note that several strings in the collections can share space in the dictionary if they exhibit suitable common substrings.

Len: the length of the string (in octets, in hexadecimal).

References: contains one or more references to the specification and the section within the specification where the string is defined.

Note that the strings stored in the dictionary are case sensitive. (Again, the strings do not comprise the quotes ("), they are just shown here to increase the readability.) Where the string is a header field, we also included the colon ":" and the amount of white space expected to occur. Note that this means that not all messages that conform to the SIP Augmented BNF, which allows other

combinations (e.g., a white space or horizontal tabulator before the colon (":") sign), will benefit as much from the dictionary -- the best increase in compression performance is to be expected for messages that use the recommended formatting guidelines for SIP.

Some strings appear followed by an equal sign and some others do not. This depends on whether the string is part of a parameter name or a parameter value.

In a SIP message, all the SIP headers terminate with a CRLF pair of characters. As these characters are appended to the end of each SIP header line, right after the header values, and because the header values are typically not part of the static SIP dictionary, we cannot include the terminating CRLF as part of the SIP static dictionary. Instead, the approach we have taken is to include in each header field entry the CRLF from the previous line that prefixes every header field. We have represented CRLF by the notation [CRLF]. Therefore, in generating the actual binary dictionary, an entry in the dictionary represented as: "[CRLF]From: " has been interpreted as

an entry whose value is CR, LF, the word From, a colon and a whitespace.

Note that most SIP header field names are included with the full string from CRLF to the colon-blank pair. However, in certain situations, when the likelihood of occurrence is not considered high (as indicated by a priority value of 3 to 5), and when there are common substrings shared by a number of headers, we have added one entry with the common substring and several entries with the non-common substrings remaining. An example is the "Proxy-Authenticate" and "Proxy-Authorization" headers. There are three entries in the dictionary: the common substring "[CRLF]Proxy-", and the non-common substrings "Authenticate: " and "Authorization: ". This allows the re-use of the non-common substrings by other entries and may save a number of bytes in the binary form of the dictionary. Note that this splitting mechanism does not apply with strings that are likely to occur very often (those whose priority is set to 1 or 2).

SIP responses start with a status code (e.g., "302") and a reason phrase (e.g., "Moved Temporarily"). The status code is a normative part, whereas the reason phrase is not normative, it is just a suggested text. For instance, both "302 Moved Temporarily" and "302

Redirect" are valid beginnings of SIP responses.

In the SIP dictionary we have included two entries per response code, one including only the status code and a space (e.g., "302 ") and another one including both the status code and the suggested reason phrase (e.g., "302 Moved Temporarily"). The former can be used when the SIP response changed the suggested reason phrase to another one. The latter can be used when the suggested reason phrase is part of the response. In this way, we accommodate both alternatives. (Note that in the actual dictionary, both strings occupy the same space in the string subset, but have two separate entries in the table subset.)

[3.](#) Binary representation of the SIP/SDP dictionary

This section contains the result of combining the SIP and the SDP dictionaries described in appendices A and B in order to create a single dictionary that is loaded into SigComp as a state.

The binary SigComp dictionary is comprised of two parts, the concatenation of which serves as the state value of the state item: A string subset, which contains all strings in the contributing collections as a substring (roughly ordered such that strings with low priority numbers occur at the end), and a table subset, which contains pairs of length and offset values for all the strings in the contributing collections. In each of these pairs, the length is

stored as a one-byte value, and the offset is stored as a two-byte value that has had 1024 added to the offset (this allows direct referencing from the stored value if the dictionary state has been loaded at address 1024).

The intention is that all compression algorithms will be able to use the (or part of the) string subset, and some compression methods, notably those that are related to the LZ78 family, will also use the table in order to form an initial set of tokens for that compression method. The text below therefore gives examples for referencing both the table subset and the string subset of the dictionary state item.

As defined in [section 3.3.3](#) in the Signaling Compression specification [1], a SigComp state is characterized by a certain set of information. For the static SIP/SDP dictionary, the information

in the following Table 1 fully characterizes the state item.

Note that the string subset of the dictionary can be accessed using:

```
STATE-ACCESS (%ps, 6, 0, 0x0D8C, %sa, 0),
```

and the table subset can be accessed using:

```
STATE-ACCESS (%ps, 6, 0x0D8C, 0x0558, %sa, 0),
```

where %ps points to UDVM memory containing

```
0xfbe507dfe5e6
```

and %sa is the desired destination address in UDVM memory (with UDVM byte copying rules applied).

If only a subset of the dictionary up to a specific priority is desired (e.g., to save UDVM space), the values for the third and forth operand in these STATE-ACCESS instructions can be changed to:

Priorities desired	String offset	String length	Table offset	Table length
=====	=====	=====	=====	=====
1 only	0x0CB2	0x00DA	0x0D8C	0x003F
1..2	0x0920	0x046C	0x0D8C	0x0147
1..3	0x07B8	0x05D4	0x0D8C	0x01A7
1..4	0x0085	0x0D07	0x0D8C	0x044A
1..5	0x0000	0x0D8C	0x0D8C	0x0558

The state item consists of the following elements:

Name:	Value:
=====	=====
state_identifier	0xfbe507dfe5e6aa5af2abb914ceaa05f99ce61ba5
state_length	0x12E4
state_address	0 (not relevant for the dictionary)
state_instruction	0 (not relevant for the dictionary)

minimum_access_length 6
state_value Representation of the table below.

0000	0d0a	5265	6a65	6374	2d43	6f6e	7461	6374	..Reject-Contact
0010	3a20	0d0a	4572	726f	722d	496e	666f	3a20	: ..Error-Info:
0020	0d0a	5469	6d65	7374	616d	703a	200d	0a43	..Timestamp: ..C
0030	616c	6c2d	496e	666f	3a20	0d0a	5265	706c	all-Info: ..Repl
0040	792d	546f	3a20	0d0a	5761	726e	696e	673a	y-To: ..Warning:
0050	200d	0a53	7562	6a65	6374	3a20	3b68	616e	..Subject: ;han
0060	646c	696e	673d	696d	6167	653b	7075	7270	dling=image;purp
0070	6f73	653d	3b63	6175	7365	3d3b	7465	7874	ose=;cause=;text
0080	3d63	6172	6433	3030	204d	756c	7469	706c	=card300 Multipl
0090	6520	4368	6f69	6365	736d	696d	6573	7361	e Choicesmimessa
00A0	6765	2f73	6970	6672	6167	3430	3720	5072	ge/sipfrag407 Pr
00B0	6f78	7920	4175	7468	656e	7469	6361	7469	oxy Authenticati
00C0	6f6e	2052	6571	7569	7265	6469	6765	7374	on Requiredigest
00D0	2d69	6e74	6567	7269	7479	3438	3420	4164	-integrity484 Ad
00E0	6472	6573	7320	496e	636f	6d70	6c65	7465	dress Incomplete
00F0	6c65	7068	6f6e	652d	6576	656e	7473	3439	lephone-events49
0100	3420	5365	6375	7269	7479	2041	6772	6565	4 Security Agree
0110	6d65	6e74	2052	6571	7569	7265	6465	6163	ment Requiredeac
0120	7469	7661	7465	6434	3831	2043	616c	6c2f	tivated481 Call/
0130	5472	616e	7361	6374	696f	6e20	446f	6573	Transaction Does
0140	204e	6f74	2045	7869	7374	616c	653d	3530	Not Existale=50
0150	3020	5365	7276	6572	2049	6e74	6572	6e61	0 Server Interna
0160	6c20	4572	726f	726f	6275	7374	2d73	6f72	l Errorobust-sor
0170	7469	6e67	3d34	3136	2055	6e73	7570	706f	ting=416 Unsuppo
0180	7274	6564	2055	5249	2053	6368	656d	6572	rted URI Schemer
0190	6765	6e63	7934	3135	2055	6e73	7570	706f	gency415 Unsuppo
01A0	7274	6564	204d	6564	6961	2054	7970	656e	rted Media Typen
01B0	6469	6e67	3438	3820	4e6f	7420	4163	6365	ding488 Not Acce
01C0	7074	6162	6c65	2048	6572	656a	6563	7465	ptable Herejecte
01D0	6434	3233	2049	6e74	6572	7661	6c20	546f	d423 Interval To
01E0	6f20	4272	6965	6672	6f6d	2d74	6167	512e	o Brieffrom-tagQ.
01F0	3835	3035	2056	6572	7369	6f6e	204e	6f74	8505 Version Not
0200	2053	7570	706f	7274	6564	3430	3320	466f	Supported403 Fo
0210	7262	6964	6465	6e6f	6e2d	7572	6765	6e74	rbiddenon-urgent
0220	3432	3920	5072	6f76	6964	6520	5265	6665	429 Provide Refe
0230	7272	6f72	2049	6465	6e74	6974	7934	3230	rror Identity420
0240	2042	6164	2045	7874	656e	7369	6f6e	6f72	Bad Extensionor

0250 6573 6f75 7263 650d 0a61 3d6b 6579 2d6d esource...a=key-m

0260	676d	743a	6d69	6b65	794f	5054	494f	4e53	gmt:mikeyOPTIONS
0270	204c	616e	6775	6167	653a	2035	3034	2053	Language: 504 S
0280	6572	7665	7220	5469	6d65	2d6f	7574	6f2d	erver Time-outo-
0290	7461	670d	0a41	7574	6865	6e74	6963	6174	tag..Authenticat
02A0	696f	6e2d	496e	666f	3a20	4465	6320	3338	ion-Info: Dec 38
02B0	3020	416c	7465	726e	6174	6976	6520	5365	0 Alternative Se
02C0	7276	6963	6535	3033	2053	6572	7669	6365	rvice503 Service
02D0	2055	6e61	7661	696c	6162	6c65	3432	3120	Unavailable421
02E0	4578	7465	6e73	696f	6e20	5265	7175	6972	Extension Requir
02F0	6564	3430	3520	4d65	7468	6f64	204e	6f74	ed405 Method Not
0300	2041	6c6c	6f77	6564	3438	3720	5265	7175	Allowed487 Requ
0310	6573	7420	5465	726d	696e	6174	6564	6175	est Terminatedau
0320	7468	2d69	6e74	6572	6c65	6176	696e	673d	th-interleaving=
0330	0d0a	6d3d	6170	706c	6963	6174	696f	6e20	..m=application
0340	4175	6720	3531	3320	4d65	7373	6167	6520	Aug 513 Message
0350	546f	6f20	4c61	7267	6536	3837	2044	6961	Too Large687 Dia
0360	6c6f	6720	5465	726d	696e	6174	6564	3330	log Terminated30
0370	3220	4d6f	7665	6420	5465	6d70	6f72	6172	2 Moved Temporar
0380	696c	7933	3031	204d	6f76	6564	2050	6572	ily301 Moved Per
0390	6d61	6e65	6e74	6c79	6d75	6c74	6970	6172	manentlymultipar
03A0	742f	7369	676e	6564	0d0a	5265	7472	792d	t/signed..Retry-
03B0	4166	7465	723a	2047	4d54	6875	2c20	3430	After: GMThu, 40
03C0	3220	5061	796d	656e	7420	5265	7175	6972	2 Payment Requir
03D0	6564	0d0a	613d	6f72	6965	6e74	3a6c	616e	ed..a=orient:lan
03E0	6473	6361	7065	3430	3020	4261	6420	5265	dscape400 Bad Re
03F0	7175	6573	7472	7565	3439	3120	5265	7175	questrue491 Requ
0400	6573	7420	5065	6e64	696e	6735	3031	204e	est Pending501 N
0410	6f74	2049	6d70	6c65	6d65	6e74	6564	3430	ot Implemented40
0420	3620	4e6f	7420	4163	6365	7074	6162	6c65	6 Not Acceptable
0430	3630	3620	4e6f	7420	4163	6365	7074	6162	606 Not Acceptab
0440	6c65	0d0a	613d	7479	7065	3a62	726f	6164	le..a=type:broad
0450	6361	7374	6f6e	6534	3933	2055	6e64	6563	castone493 Undec
0460	6970	6865	7261	626c	650d	0a4d	494d	452d	ipherable..MIME-
0470	5665	7273	696f	6e3a	204d	6179	2034	3832	Version: May 482
0480	204c	6f6f	7020	4465	7465	6374	6564	0d0a	Loop Detected..
0490	4f72	6761	6e69	7a61	7469	6f6e	3a20	4a75	Organization: Ju
04A0	6e20	6d6f	6465	2d63	6861	6e67	652d	6e65	n mode-change-ne
04B0	6967	6862	6f72	3d63	7269	7469	6361	6c65	ighbor=criticale
04C0	7274	6370	2d66	6234	3839	2042	6164	2045	rtcp-fb489 Bad E
04D0	7665	6e74	6c73	0d0a	556e	7375	7070	6f72	ventls..Unsuppor
04E0	7465	643a	204a	616e	2035	3032	2042	6164	ted: Jan 502 Bad
04F0	2047	6174	6577	6179	6d6f	6465	2d63	6861	Gatewaymode-cha
0500	6e67	652d	7065	7269	6f64	3d0d	0a61	3d6f	nge-period=..a=o
0510	7269	656e	743a	7365	6173	6361	7065	0d0a	rient:seascape..
0520	613d	7479	7065	3a6d	6f64	6572	6174	6564	a=type:moderated
0530	3430	3420	4e6f	7420	466f	756e	6433	3035	404 Not Found305
0540	2055	7365	2050	726f	7879	0d0a	613d	7479	Use Proxy..a=ty

0550 7065 3a72 6563 766f 6e6c 790d 0a61 3d74 pe:recvonly..a=t
0560 7970 653a 6d65 6574 696e 670d 0a6b 3d70 ype:meeting..k=p
0570 726f 6d70 743a 0d0a 5265 6665 7272 6564 rompt:...Referred
0580 2d42 793a 200d 0a49 6e2d 5265 706c 792d -By: ..In-Reply-
0590 546f 3a20 5452 5545 6e63 6f64 696e 673a To: TRUEncoding:
05A0 2031 3832 2051 7565 7565 6441 7574 6865 182 QueuedAuthe
05B0 6e74 6963 6174 653a 200d 0a55 7365 722d nticate: ..User-
05C0 4167 656e 743a 200d 0a61 3d66 7261 6d65 Agent: ..a=frame
05D0 7261 7465 3a0d 0a41 6c65 7274 2d49 6e66 rate:...Alert-Inf
05E0 6f3a 2043 414e 4345 4c20 0d0a 613d 6d61 o: CANCEL ..a=ma
05F0 7870 7469 6d65 3a3b 7265 7472 792d 6166 xptime;;retry-af
0600 7465 723d 7561 6368 616e 6e65 6c73 3d34 ter=uachannels=4
0610 3130 2047 6f6e 650d 0a52 6566 6572 2d54 10 Gone..Refer-T
0620 6f3a 200d 0a50 7269 6f72 6974 793a 200d o: ..Priority: .
0630 0a6d 3d63 6f6e 7472 6f6c 200d 0a61 3d71 .m=control ..a=q
0640 7561 6c69 7479 3a0d 0a61 3d73 6470 6c61 uality:...a=sdpla
0650 6e67 3a0d 0a61 3d63 6861 7273 6574 3a0d ng:...a=charset..
0660 0a52 6570 6c61 6365 733a 2052 4546 4552 .Replaces: REFER
0670 2069 7073 6563 2d69 6b65 3b74 7261 6e73 ipsec-ike;trans
0680 706f 7274 3d0d 0a61 3d6b 6579 7764 733a port=...a=keywds:
0690 0d0a 6b3d 6261 7365 3634 3a3b 7265 6672 ..k=base64;;refr
06A0 6573 6865 723d 0d0a 613d 7074 696d 653a esher=...a=ptime:
06B0 0d0a 6b3d 636c 6561 723a 3b72 6563 6569 ..k=clear;;recei
06C0 7665 643d 3b64 7572 6174 696f 6e3d 0d0a ved=;duration=..
06D0 4163 6365 7074 3a20 0d0a 613d 6772 6f75 Accept: ..a=grou
06E0 703a 4641 4c53 453a 2049 4e46 4f20 0d0a p:FALSE: INFO ..
06F0 4163 6365 7074 2d0d 0a61 3d6c 616e 673a Accept-...a=lang:
0700 0d0a 6d3d 6461 7461 206d 6f64 652d 7365 ..m=data mode-se
0710 743d 0d0a 613d 746f 6f6c 3a54 4c53 756e t=...a=tool:TLSun
0720 2c20 0d0a 4461 7465 3a20 0d0a 613d 6361 , ..Date: ..a=ca
0730 743a 0d0a 6b3d 7572 693a 0d0a 5072 6f78 t:...k=uri:...Prox
0740 792d 3b72 6561 736f 6e3d 3b6d 6574 686f y-;reason=;metho
0750 643d 0d0a 613d 6d69 643a 3b6d 6164 6472 d=...a=mid;;maddr
0760 3d6f 7061 7175 653d 0d0a 4d69 6e2d 3b61 =opaque=..Min;a
0770 6c67 3d4d 6f6e 2c20 5475 652c 2057 6564 lg=Mon, Tue, Wed
0780 2c20 4672 692c 2053 6174 2c20 3b74 746c , Fri, Sat, ;ttl
0790 3d61 7574 733d 0d0a 723d 0d0a 7a3d 0d0a =auts=...r=...z=..
07A0 653d 3b69 643d 0d0a 693d 6372 633d 0d0a e;;id=...i=crc=..
07B0 753d 3b71 3d75 6173 3431 3420 5265 7175 u;;q=uas414 Requ
07C0 6573 742d 5552 4920 546f 6f20 4c6f 6e67 est-URI Too Long
07D0 6976 6575 7072 6976 6163 7975 6470 7265 iveupprivacyudpre
07E0 6665 7236 3030 2042 7573 7920 4576 6572 fer600 Busy Ever
07F0 7977 6865 7265 7175 6972 6564 3438 3020 ywherequired480
0800 5465 6d70 6f72 6172 696c 7920 556e 6176 Temporarily Unav
0810 6169 6c61 626c 650d 0a61 3d74 7970 653a ailable..a=type:
0820 482e 3333 3230 3220 4163 6365 7074 6564 H.33202 Accepted

0830	0d0a	5365	7373	696f	6e2d	4578	7069	7265	..Session-Expire
0840	733a	200d	0a53	7562	7363	7269	7074	696f	s: ..Subscriptio

[RFC 3485](#)

SIP and SDP Static Dictionary for SigComp

February 2003

0850	6e2d	5374	6174	653a	204e	6f76	200d	0a53	n-State: Nov ..S
0860	6572	7669	6365	2d52	6f75	7465	3a20	5365	ervice-Route: Se
0870	7020	0d0a	416c	6c6f	772d	4576	656e	7473	p ..Allow-Events
0880	3a20	4665	6220	0d0a	613d	696e	6163	7469	: Feb ..a=inacti
0890	7665	5254	502f	5341	5650	2052	5450	2f41	veRTP/SAVP RTP/A
08A0	5650	4620	416e	6f6e	796d	6f75	7369	7073	VPF Anonymousips
08B0	3a0d	0a61	3d74	7970	653a	7465	7374	656c	...a=type:testel
08C0	3a4d	4553	5341	4745	200d	0a61	3d72	6563	:MESSAGE ..a=rec
08D0	766f	6e6c	790d	0a61	3d73	656e	646f	6e6c	vonly..a=sendonl
08E0	790d	0a63	3d49	4e20	4950	3420	0d0a	5265	y..c=IN IP4 ..Re
08F0	6173	6f6e	3a20	0d0a	416c	6c6f	773a	200d	ason: ..Allow: .
0900	0a45	7665	6e74	3a20	0d0a	5061	7468	3a20	.Event: ..Path:
0910	3b75	7365	723d	0d0a	623d	4153	2043	5420	;user=..b=AS CT
0920	0d0a	5757	572d	4175	7468	656e	7469	6361	..WWW-Authentica
0930	7465	3a20	4469	6765	7374	200d	0a61	3d73	te: Digest ..a=s
0940	656e	6472	6563	7669	6465	6f63	7465	742d	endrecvideoctet-
0950	616c	6967	6e3d	6170	706c	6963	6174	696f	align=applicatio
0960	6e2f	7364	7061	7468	6561	6465	7273	7061	n/sdpatheaderspa
0970	7574	683d	0d0a	613d	6f72	6965	6e74	3a70	uth=..a=orient:p
0980	6f72	7472	6169	7469	6d65	6f75	7474	722d	ortraitimeouttr-
0990	696e	7469	636f	6e63	3d34	3833	2054	6f6f	inticonc=483 Too
09A0	204d	616e	7920	486f	7073	6c69	6e66	6f70	Many Hopslinfop
09B0	7469	6f6e	616c	676f	7269	7468	6d3d	3630	tionalgorithm=60
09C0	3420	446f	6573	204e	6f74	2045	7869	7374	4 Does Not Exist
09D0	2041	6e79	7768	6572	6573	706f	6e73	653d	Anywheresponse=
09E0	0d0a	0d0a	5265	7175	6573	742d	4469	7370Request-Disp
09F0	6f73	6974	696f	6e3a	204d	4435	3830	2050	osition: MD580 P
0A00	7265	636f	6e64	6974	696f	6e20	4661	696c	recondition Fail
0A10	7572	6570	6c61	6365	7334	3232	2053	6573	ureplaces422 Ses
0A20	7369	6f6e	2049	6e74	6572	7661	6c20	546f	sion Interval To
0A30	6f20	536d	616c	6c6f	6361	6c31	3831	2043	o Smallocal181 C
0A40	616c	6c20	4973	2042	6569	6e67	2046	6f72	all Is Being For
0A50	7761	7264	6564	6f6d	6169	6e3d	6661	696c	wardedomain=fail
0A60	7572	656e	6465	7265	616c	6d3d	5355	4253	urenderealm=SUBS
0A70	4352	4942	4520	7072	6563	6f6e	6469	7469	CRIBE preconditi
0A80	6f6e	6f72	6d61	6c69	7073	6563	2d6d	616e	onormalipsecc-man
0A90	6461	746f	7279	3431	3320	5265	7175	6573	datory413 Reques
0AA0	7420	456e	7469	7479	2054	6f6f	204c	6172	t Entity Too Lar
0AB0	6765	3265	3138	3320	5365	7373	696f	6e20	ge2e183 Session

0AC0	5072	6f67	7265	7373	6374	7034	3836	2042	Progressct	486 B
0AD0	7573	7920	4865	7265	6d6f	7465	726d	696e	usy Herem	termin
0AE0	6174	6564	414b	4176	312d	4d44	352d	7365	atedAKAv1	-MD5-se
0AF0	7373	696f	6e6f	6e65	0d0a	4175	7468	6f72	ssionone..	Author
0B00	697a	6174	696f	6e3a	2036	3033	2044	6563	ization: 603	Dec
0B10	6c69	6e65	7874	6e6f	6e63	653d	3438	3520	linextnonce=	485
0B20	416d	6269	6775	6f75	7365	726e	616d	653d	Ambiguous	username=
0B30	6175	6469	6f0d	0a43	6f6e	7465	6e74	2d54	audio..Content-	T
0B40	7970	653a	204d	6172	200d	0a52	6563	6f72	ype: Mar ..	Recor

0B50	642d	526f	7574	653a	204a	756c	2034	3031	d-Route: Jul	401
0B60	2055	6e61	7574	686f	7269	7a65	640d	0a52	Unauthorized..	R
0B70	6571	7569	7265	3a20	0d0a	743d	3020	302e	equire: ..t=0	0.
0B80	302e	302e	300d	0a53	6572	7665	723a	2052	0.0.0..Server: R	
0B90	4547	4953	5445	5220	0d0a	633d	494e	2049	EGISTER ..c=IN	I
0BA0	5036	2031	3830	2052	696e	6769	6e67	3130	P6 180 Ringing	10
0BB0	3020	5472	7969	6e67	763d	300d	0a6f	3d55	0 Tryingv=0..o=U	
0BC0	5044	4154	4520	4e4f	5449	4659	200d	0a53	PDATE NOTIFY ..	S
0BD0	7570	706f	7274	6564	3a20	756e	6b6e	6f77	upported: unknow	
0BE0	6e41	4d52	5450	2f41	5650	200d	0a50	7269	nAMRTP/AVP ..Pri	
0BF0	7661	6379	3a20	0d0a	5365	6375	7269	7479	vacy: ..Security	
0C00	2d0d	0a45	7870	6972	6573	3a20	0d0a	613d	-..Expires: ..a=	
0C10	7274	706d	6170	3a0d	0a6d	3d76	6964	656f	rtpmap:..m=video	
0C20	200d	0a6d	3d61	7564	696f	200d	0a73	3d20	..m=audio ..s=	
0C30	6661	6c73	650d	0a61	3d63	6f6e	663a	3b65	false..a=conf:;e	
0C40	7870	6972	6573	3d0d	0a52	6f75	7465	3a20	xpires=..Route:	
0C50	0d0a	613d	666d	7470	3a0d	0a61	3d63	7572	..a=fmtp:..a=cur	
0C60	723a	436c	6965	6e74	3a20	5665	7269	6679	r:Client: Verify	
0C70	3a20	0d0a	613d	6465	733a	0d0a	5241	636b	: ..a=des:..RAck	
0C80	3a20	0d0a	5253	6571	3a20	4259	4520	636e	: ..RSeq: BYE cn	
0C90	6f6e	6365	3d31	3030	7265	6c75	7269	3d71	once=100reluri=q	
0CA0	6f70	3d54	4350	5544	5071	6f73	786d	6c3b	op=TCPUDPqosxml;	
0CB0	6c72	0d0a	5669	613a	2053	4950	2f32	2e30	lr..Via: SIP/2.0	
0CC0	2f54	4350	2034	3038	2052	6571	7565	7374	/TCP 408 Request	
0CD0	2054	696d	656f	7574	696d	6572	7073	6970	Timeoutimerpsip	
0CE0	3a0d	0a43	6f6e	7465	6e74	2d4c	656e	6774	...Content-Lengt	
0CF0	683a	204f	6374	200d	0a56	6961	3a20	5349	h: Oct ..Via: SI	
0D00	502f	322e	302f	5544	5020	3b63	6f6d	703d	P/2.0/UDP ;comp=	
0D10	7369	6763	6f6d	7072	6f62	6174	696f	6e61	sigcomprobationa	
0D20	636b	3b62	7261	6e63	683d	7a39	6847	3462	ck;branch=z9hG4b	
0D30	4b0d	0a4d	6178	2d46	6f72	7761	7264	733a	K..Max-Forwards:	
0D40	2041	7072	2053	4354	5052	4143	4b20	494e	Apr SCTPRACK IN	

0D50	5649	5445	200d	0a43	616c	6c2d	4944	3a20	VITE ..Call-ID:
0D60	0d0a	436f	6e74	6163	743a	2032	3030	204f	..Contact: 200 0
0D70	4b0d	0a46	726f	6d3a	200d	0a43	5365	713a	K..From: ..CSeq:
0D80	200d	0a54	6f3a	203b	7461	673d	0410	dd10	..To: ;tag=....
0D90	1131	0d11	0a07	10b9	0c10	fe12	10e1	0611	.1.....
0DA0	4e07	114e	0311	4a04	114a	0710	b208	1179	N..N..J..J.....y
0DB0	0611	810f	1122	0b11	5506	116b	0b11	6013"..U..k..`.
0DC0	10b2	0811	7105	1187	1310	f709	0e8d	080dq.....
0DD0	ae0c	10b9	0710	8e03	0d96	0310	8a04	108a
0DE0	090d	d70a	0f12	080f	8f09	0f8f	080d	6c06l.
0DF0	0e66	090e	6c0a	0e6c	060f	c607	0fc6	0511	.f..l..l.....
0E00	4806	1148	060f	bf07	0fbf	070e	5506	0f16	H..H.....U...
0E10	040e	f403	0eb1	0310	a609	1050	0310	a30aP....
0E20	0db4	050e	3606	0ed6	030d	f911	0ef8	040c6.....
0E30	d908	0eea	0409	5303	0a4b	040e	e410	0f35S..K..... 5
0E40	090e	e408	0d3f	030f	e10b	1001	0310	ac06?.....

0E50	1095	0c0e	760b	0feb	0a0f	ae05	102b	0410v.....+..
0E60	2b08	107a	100f	4907	0fb8	0910	3e0b	100c	+..z..I.....>...
0E70	070f	780b	0f6d	0910	4708	1082	0b0f	f608	..x..m..G.....
0E80	1062	080f	8708	106a	040f	780d	0fcd	080d	.b.....j..x.....
0E90	ae10	0f5d	0b0f	9814	0d20	1b0d	2004	0de0	...].
0EA0	140e	b40b	0fa3	0b07	340f	0d56	040e	f4034..V....
0EB0	10af	070d	3409	0f27	0410	9b04	109f	09104..'.
0EC0	5908	1072	0910	350a	1021	0a10	1708	0fe3	Y..r..5..!.
0ED0	0310	a905	0cac	040c	bd07	0cc1	080c	c109
0EE0	0cf6	100c	720c	0c86	040d	640c	0cd5	090cr.....d.....
0EF0	ff1b	0bfc	110c	5d13	0c30	090c	a40c	0c24]. ..0.....\$
0F00	0c0d	3b03	0d1a	030d	1d16	0c43	090c	9209	..;.....C....
0F10	0c9b	0d0e	cb04	0d16	060d	1005	04f2	0b0c
0F20	e105	0bde	0a0c	ec13	0be3	070b	d408	0d08
0F30	0c0c	c909	0c3a	040a	e50c	0a23	080b	3a0e:.....#...:
0F40	09ab	0f0e	fa09	0f6f	0c0a	170f	0976	0c0ao.....v..
0F50	5f17	0de2	0f07	a80a	0f85	0f08	d60e	09b9	_.....
0F60	0b0a	7a03	0bdb	0308	c104	0ec7	0308	d302	..z.....
0F70	048d	080b	4a05	0b8c	070b	6106	0548	0407J.....a..H..
0F80	f405	1030	0407	1e08	071e	050b	9110	04ca	...0.....
0F90	090a	7109	0e87	0504	9805	0b6e	0b04	9b0f	..q.....n....
0FA0	049b	0704	9b03	04a3	0704	a310	0798	0907
0FB0	9805	0b73	050b	7805	0b7d	0507	b905	0b82	...s..x..}.....
0FC0	050b	8705	0b1d	0508	e405	0c81	050f	4405D.
0FD0	1140	0508	7805	089d	050f	5805	073f	050c	..@..x.....X..?..

0FE0	6d05	10f2	050c	5805	06a9	0407	b609	058c	m.....X.....
0FF0	0606	1a06	0e81	0a06	160a	0ac4	070b	5a0aZ.
1000	0aba	030b	1b04	1145	060c	8c07	05ad	0a0eE.....
1010	da08	0b42	0d09	f70b	051c	0911	1608	05c9	...B.....
1020	070d	8606	0bcf	0a06	4d04	0ba2	0606	8d08M.....
1030	05e6	080e	110b	0a9b	030a	0403	0bb5	0510
1040	d704	0994	050a	e203	0bb2	060d	6704	0d11g...
1050	0808	b71b	0e3b	0a09	a114	0485	1507	8315;
1060	076e	0d09	3d17	06ae	0f07	e614	07be	0d06	.n..=.....
1070	0a0d	0930	1606	f212	081e	2104	aa13	10c5	...0.....!
1080	080a	0f1c	0e96	180b	b81a	0595	1a05	7511u.
1090	063d	1606	dc1e	0e19	1605	d11d	0620	2305	.=..... #.
10A0	2711	087d	110d	9916	04da	0d0f	1c16	0708	'...}.....
10B0	1705	b40d	08c7	1307	f812	0857	1f04	fe19W....
10C0	054e	1308	0b0f	08e9	1706	c513	067b	1905	.N.....{..
10D0	f115	0744	180d	fb0b	0f09	1b0d	be12	0830	...D..... 0
10E0	1507	5904	0ba6	040b	ae04	0b9e	040b	9604	..Y.....
10F0	0b9a	0a0a	b00b	0a90	080b	320b	096b	080b2..k..
1100	2a0b	0a85	090b	120a	0aa6	0d09	ea13	0d74	*.....t
1110	1407	d213	090b	1208	4210	095b	1209	1e0dB..[....
1120	0cb1	0e0c	1711	094a	0c0a	530c	0a47	090aJ..S..G..
1130	f70e	09c7	0c0a	3b07	0669	0806	6906	09e3;..i..i...
1140	080b	520a	0ad8	1206	570d	0657	0709	e304	..R.....W..W....

1150	0ae9	1007	3009	0b00	0c0a	2f05	0ae9	050a0...../.....
1160	6b06	0a6b	0a0a	ce09	0aee	030b	db07	0f7e	k..k.....~
1170	0a09	970a	0671	0e09	d517	0693	070e	5c07q.....\.
1180	0fda	0a0f	350d	0dec	0a09	970a	0671	080b5.....q..
1190	220f	0985	060b	680c	0d4a	090b	0913	08f8	".....h..J.....
11A0	1508	a204	0baa	0f05	660d	0723	090a	060bf..#.....
11B0	0d4a	0f04	ee06	04f8	0409	2b04	0853	0708	.J.....+..S..
11C0	c003	111f	0411	1e07	0d8c	0307	3404	10db4...
11D0	0307	3603	0da9	0d04	200b	0451	0c04	3a04	..6..... ..Q...:
11E0	0bb8	040c	2404	0595	0404	7c04	0575	0404\$.u..
11F0	8504	096b	0406	3d06	047b	0406	dc04	0783	...k..=..{.....
1200	040e	1912	0400	1008	8e10	0869	0e04	120di....
1210	042d	0310	b904	05d1	0407	6e04	0620	0704	.-.....n.. ..
1220	7404	0bfc	0a04	5c04	0527	0409	3d04	087d	t.....\'..=..}
1230	040f	ae04	0d99	0406	ae04	04da	0904	0908
1240	1122	040f	1c04	07e6	040e	cb05	08bd	0407	..".
1250	0804	0fa3	0406	5704	05b4	040f	5d04	08c7W.....]...
1260	080b	f404	07f8	0407	3004	07be	0408	57050.....W.

1270	0d46	0404	fe04	060a	0405	4e04	0e3b	0408	.F.....N...;
1280	0b04	0930	0408	e905	05ee	0406	c504	06f2	...0.....
1290	0406	7b04	09a1	0405	f104	081e	0407	4404	..{.....D.
12A0	0bdd	040d	fb04	04aa	040b	e307	0eee	040f
12B0	0904	0eb4	040d	be04	10c5	0408	3005	0f300..0
12C0	0407	5904	0a0f	060e	6104	0481	040d	ab04	..Y.....a.....
12D0	0d93	0411	6b04	0e96	0504	6609	046b	0b04k.....f..k..
12E0	4604	0ce1							F...

Table 1: binary representation of the static SIP/SDP dictionary for SigComp

[4.](#) Security Considerations

The security considerations of [\[1\]](#) apply. This memo does not introduce any known additional security risk.

[5.](#) IANA Considerations

None.

[6.](#) Acknowledgements

The authors would like to thank Lars-Erik Jonsson, Zhigang C. Liu and Jonathan Rosenberg for their valuable comments.

[7.](#) References

[7.1](#) Normative References

- [1] Price, R., Bormann, C., Christoffersson, J., Hannu, H., Liu, Z. and J. Rosenberg, "Signaling Compression (SigComp)", [RFC 3320](#), January 2003.
- [2] Bradner, S., "Key words for use in RFCs to indicate requirement levels", [BCP 14](#), [RFC 2119](#), March 1997.

7.2 Informative References

- [3] Rosenberg, J., Schulzrinne, H., Camarillo, G., Johnston, A., Peterson, J., Sparks, R., Handley, M. and E. Schooler, "SIP: Session Initiation Protocol", [RFC 3261](#), June 2002.
- [4] Garcia-Martin, M., "3rd-Generation Partnership Project (3GPP) Release 5 requirements on the Session Initiation Protocol (SIP)", Work in Progress.
- [5] Yergeau, F., "UTF-8, a transformation format of ISO 10646", [RFC 2279](#), January 1998.
- [6] Franks, J., Hallam-Baker, P., Hostetler, J., Lawrence, S., Leach, P., Luotonen, A. and L. Stewart, "HTTP Authentication: Basic and Digest Access Authentication", [RFC 2617](#), June 1999.
- [7] Vaha-Sipila, A., "URLs for telephone calls", [RFC 2806](#), April 2000.
- [8] Donovan, S., "The SIP INFO Method", [RFC 2976](#), October 2000.
- [9] Roach, A. B., "Session Initiation Protocol (SIP)-Specific Event Notification", [RFC 3265](#), June 2002.
- [10] Rosenberg, J. and H. Schulzrinne, "Reliability of Provisional Responses in Session Initiation Protocol (SIP)", [RFC 3262](#), June 2002.
- [11] Rosenberg, J., "The Session Initiation Protocol UPDATE Method", [RFC 3311](#), October 2002.
- [12] Camarillo, G., Ed., Marshall, W., Ed. and J. Rosenberg, "Integration of Resource Management and Session Initiation Protocol (SIP)", [RFC 3312](#), October 2002.
- [13] Sparks, R., "The SIP Refer Method", Work in Progress.

- [14] Mahy, R., Biggs, B. and R. Dean, "The Session Initiation Protocol (SIP) "Replaces" Header", Work in Progress.
- [15] Sparks, R., "Internet Media Type message/sipfrag", [RFC 3420](#),

November 2002.

- [16] Willis, D. and B. Hoeneisen, "Session Initiation Protocol (SIP) Extension Header Field for Registering Non-Adjacent Contacts", [RFC 3327](#), December 2002.
- [17] Schulzrinne, H., Oran, D. and G. Camarillo, "The Reason Header Field for the Session Initiation Protocol (SIP)", [RFC 3326](#), December 2002.
- [18] Donovan, S., and J. Rosenberg, "Session Timers in the Session Initiation Protocol (SIP)", Work in Progress.
- [19] Niemi, A., Arkko, J. and V. Torvinen , "Hypertext Transfer Protocol (HTTP) Digest Authentication Using Authentication and Key Agreement (AKA)", [RFC 3310](#), September 2002.
- [20] Arkko, J., Torvinen, V., Camarillo, G., Niemi A. and T. Haukka, "Security Mechanism Agreement for the Session Initiation Protocol (SIP)", [RFC 3329](#), January 2003.
- [21] Campbell, B., Rosenberg, J., Schulzrinne, H., Huitema, C. and D. Gurle, "Session Initiation Protocol (SIP) Extension for Instant Messaging", [RFC 3428](#), December 2002.
- [22] Schulzrinne, H. and J. Rosenberg, "Session Initiation Protocol (SIP) Caller Preferences and Callee Capabilities", Work in Progress.
- [23] Camarillo, G., "Compressing the Session Initiation Protocol (SIP)", [RFC 3486](#), February 2003.
- [24] Handley, M., Jacobson, V. and C. Perkins, "SDP: Session Description Protocol", Work in Progress.
- [25] Sjoberg, J., Westerlund, M., Lakaniemi, A. and Q. Xie, "Real-Time Transport Protocol payload format and file storage format for the Adaptive Multi-Rate (AMR) and Adaptive Multi-Rate Wideband (AMR-WB) audio codecs", [RFC 3267](#), June 2002.
- [26] Camarillo, G., Eriksson, G., Holler, J. and H. Schulzrinne, "Grouping of Media Lines in the Session Description Protocol (SDP)", [RFC 3388](#), December 2002.

- [27] Schulzrinne, H. and S. Petrack, "RTP Payload for DTMF Digits, Telephony Tones and Telephony Signals", [RFC 2833](#), May 2000.
- [28] Arkko, J., Carrara, E., Lindholm, F., Naslund, M. and K. Norrman, "Key Management Extensions for SDP and RTSP", Work in Progress.
- [29] Arkko, J., Carrara, E., Lindholm, F., Naslund, M. and K. Norrman, "MIKEY: Multimedia Internet KEYing", Work in Progress.
- [30] Baugher, M., Blom, R., Carrara, E., McGrew, D., Naslund, M., Norrman, K. and D. Oran, "The Secure Real Time Transport Protocol", Work in Progress.
- [31] Ott, J., Wenger, S., Fukunaga, S., Sato, N., Burmeister, C., and Rey, J., "Extended RTP Profile for RTCP-based feedback (RTP/AVPF)", Work in Progress.
- [32] Rosenberg, J. and H. Schulzrinne, "An Offer/Answer Model with Session Description Protocol (SDP)", [RFC 3264](#), June 2002.
- [33] Peterson, J., "A Privacy Mechanism for the Session Initiation Protocol (SIP)", [RFC 3323](#), November 2002.
- [34] Sparks, R., "The Referred-By mechanism", Work in Progress.
- [35] Willis, D. and B. Hoeneisen, "Session Initiation Protocol Extension Header Field for Service Route Discovery During Registration", Work in Progress.

[Appendix A](#). SIP input strings to the SIP/SDP static dictionary

For reference, this section lists the SIP input strings that were used in generating the dictionary, as well as a priority value, the offset of the string in the generated dictionary, the length of the string, and one or more references into the referenced documents that motivate the presence of this string. Note that the notation "[CRLF]" stands for a sequence of two bytes with the values 0x0d and 0x0a, respectively.

The priority value is used for determining the position of the string in the dictionary. Lower priority values (higher priorities) cause the string to occur at a later position in the dictionary, making it more efficient to reference the string in certain compression algorithms. Hence, lower priority values were assigned to strings more likely to occur.

String	Pr	Off	Len	References
=====	==	====	====	=====
"sip:"	1	0CDD	0004	[3] 19.1.1
"sips:"	3	08AC	0005	[3] 19.1.1
"tel:"	3	08BD	0004	[7] 2.2
"SIP/2.0"	1	0CB9	0007	[3] 25.1
"SIP/2.0/UDP "	1	0CFE	000C	[3] 25.1
"SIP/2.0/TCP "	2	0CB9	000C	[3] 25.1
"INVITE"	1	0D4E	0006	[3] 25.1
"INVITE "	1	0D4E	0007	[3] 25.1
"ACK"	1	0D4A	0003	[3] 25.1
"ACK "	1	0D4A	0004	[3] 25.1
"OPTIONS"	4	0269	0007	[3] 25.1
"OPTIONS "	4	0269	0008	[3] 25.1
"BYE"	2	0C8A	0003	[3] 25.1
"BYE "	2	0C8A	0004	[3] 25.1
"CANCEL"	4	05E3	0006	[3] 25.1
"CANCEL "	4	05E3	0007	[3] 25.1
"REGISTER"	2	0B8F	0008	[3] 25.1
"REGISTER "	2	0B8F	0009	[3] 25.1
"INFO"	4	06E9	0004	[8] 2
"INFO "	4	06E9	0005	[8] 2
"SUBSCRIBE"	2	0A6C	0009	[9] 8.1.1

"SUBSCRIBE "	2 0A6C 000A	[9]	8.1.1
"NOTIFY"	2 0BC6 0006	[9]	8.1.2
"NOTIFY "	2 0BC6 0007	[9]	8.1.2
"PRACK"	2 0D48 0005	[10]	6
"PRACK "	2 0D48 0006	[10]	6
"UPDATE"	2 0BBF 0006	[11]	7, 10
"UPDATE "	2 0BBF 0007	[11]	7, 10
"REFER"	4 066B 0005	[13]	2.1, 7

"REFER "	4 066B 0006	[13]	2.1, 7
"MESSAGE"	3 08C1 0007	[21]	9
"MESSAGE "	3 08C1 0008	[21]	9
"[CRLF]Accept: "	4 06CE 000A	[3]	20.1
"[CRLF]Accept-"	4 06EE 0009	[22]	5,
		[3]	20.2, 20.3
"Contact: "	5 0009 0009	[22]	5
"Encoding: "	4 0597 000A	[3]	20.2,
		[3]	20.12
"Language: "	4 0271 000A	[3]	20.3,
		[3]	20.13
"[CRLF]Alert-Info: "	4 05D5 000E	[3]	20.4
"[CRLF]Allow: "	3 08F6 0009	[3]	20.5
"[CRLF]Allow-Events: "	3 0872 0010	[9]	8.2.1
"[CRLF]Authentication-Info: "	4 0293 0017	[3]	20.6
"[CRLF]Authorization: "	2 0AF8 0011	[3]	20.7
"[CRLF]Call-ID: "	1 0D55 000B	[3]	20.8
"[CRLF]Call-Info: "	5 002D 000D	[3]	20.9
"[CRLF]Contact: "	1 0D60 000B	[3]	20.10
"[CRLF]Content-"	4 0B35 000A	[3]	20.11,
			20.12, 20.13, [3] 20.14,
			20.15
"Disposition: "	4 09EC 000D	[3]	20.11
"Encoding: "	4 0597 000A	[3]	20.2,
		[3]	20.12
"Language: "	4 0271 000A	[3]	20.3,
		[3]	20.13
"[CRLF]Content-Length: "	1 0CE1 0012	[3]	20.14
"[CRLF]Content-Type: "	2 0B35 0010	[3]	20.15
"[CRLF]CSeq: "	1 0D79 0008	[3]	20.16
"[CRLF]Date: "	4 0722 0008	[3]	20.17
"[CRLF]Error-Info: "	5 0012 000E	[3]	20.18
"[CRLF]Event: "	3 08FF 0009	[9]	8.2.1

"[CRLF]Expires: "	2	0C01 000B	[3]	20.19
"[CRLF]From: "	1	0D71 0008	[3]	20.20
"[CRLF]In-Reply-To: "	4	0585 000F	[3]	20.21
"[CRLF]Max-Forwards: "	1	0D31 0010	[3]	20.22
"[CRLF]Min-"	4	0768 0006	[3]	20.23,
			[18]	5
"Expires: "	4	083A 0009	[3]	20.23
"SE: "	4	06E5 0004	[18]	5
"[CRLF]MIME-Version: "	5	0469 0010	[3]	20.24
"[CRLF]Organization: "	5	048E 0010	[3]	20.25
"[CRLF]Path: "	3	0908 0008	[16]	3
"[CRLF]Priority: "	4	0623 000C	[3]	20.26
"[CRLF]Privacy: "	2	0BEB 000B	[33]	4.2
"[CRLF]Proxy-"	4	073A 0008	[3]	20.27,
				20.28, 20.29

"Authenticate: "	4	05AB 000E	[3]	20.27
"Authorization: "	4	0AFA 000F	[3]	20.28
"Require: "	4	0B6F 0009	[3]	20.29
"[CRLF]RAck: "	2	0C7A 0008	[10]	7.2
"[CRLF]Reason: "	3	08EC 000A	[17]	2
"[CRLF]Record-Route: "	2	0B49 0010	[3]	20.30
"[CRLF]Refer-To: "	4	0617 000C	[13]	2.1, 7
"[CRLF]Referred-By: "	4	0576 000F	[34]	9
"[CRLF]Reject-Contact: "	5	0000 0012	[22]	5
"[CRLF]Replaces: "	4	065F 000C	[14]	3.1
"[CRLF]Reply-To: "	5	003A 000C	[3]	20.31
"[CRLF]Request-Disposition: "	4	09E2 0017	[22]	5
"[CRLF]Require: "	2	0B6D 000B	[3]	20.32
"[CRLF]Retry-After: "	4	03A8 000F	[3]	20.33
"[CRLF]Route: "	2	0C47 0009	[3]	20.34
"[CRLF]RSeq: "	2	0C82 0008	[10]	7.1
"[CRLF]Security-"	2	0BF6 000B	[20]	3.3
"Client: "	2	0C62 0008	[20]	3.3
"Server: "	2	0B87 0008	[20]	3.3
"Verify: "	2	0C6A 0008	[20]	3.3
"[CRLF]Server: "	4	0B85 000A	[3]	20.35
"[CRLF]Service-Route: "	3	085D 0011	[35]	
"[CRLF]Session-Expires: "	3	0830 0013	[18]	4
"[CRLF]Subject: "	5	0051 000B	[3]	20.36
"[CRLF]Subscription-State: "	3	0843 0016	[9]	8.2.3
"[CRLF]Supported: "	2	0BCD 000D	[3]	20.37

"[CRLF]Timestamp: "	5 0020 000D	[3]	20.38
"[CRLF]To: "	1 0D81 0006	[3]	20.39
"[CRLF]Unsupported: "	4 04D6 000F	[3]	20.40
"[CRLF]User-Agent: "	4 05B9 000E	[3]	20.41
"[CRLF]Via: "	1 0CB2 0007	[3]	20.42
"[CRLF]Via: SIP/2.0/UDP "	1 0CF7 0013	[3]	20.42
"[CRLF]Via: SIP/2.0/TCP "	1 0CB2 0013	[3]	20.42
"[CRLF]Warning: "	5 0046 000B	[3]	20.43
"[CRLF]WWW-Authenticate: "	2 0920 0014	[3]	20.44
"[CRLF]WWW-Authenticate: Digest "	2 0920 001B	[3]	20.44
"[CRLF][CRLF]"	2 09E0 0004	[3]	7
";transport="	4 067A 000B	[3]	25.1
"udp"	4 07DB 0003	[3]	25.1,
		[24]	A, [3] 25.1, [24] A
"tcp"	4 04C1 0003	[3]	25.1
"sctp"	4 0AC7 0004	[3]	25.1
"tls"	4 04D3 0003	[3]	25.1,
		[20]	3.3
";user="	3 0910 0006	[3]	25.1
"phone"	3 00F2 0005	[3]	25.1
"ip"	4 008D 0002	[3]	25.1
";method="	4 074A 0008	[3]	25.1

";ttl="	4 078C 0005	[3]	25.1
";lr"	2 0CAF 0003	[3]	25.1
"Digest "	2 0934 0007	[6]	3.2.1,
			3.2.2
"username="	2 0B27 0009	[6]	3.2.2
"uri="	2 0C9B 0004	[6]	3.2.2
"qop="	2 0C9F 0004	[6]	3.2.1,
			3.2.2
"cnonce="	2 0C8E 0007	[6]	3.2.2
"nc="	2 0996 0003	[6]	3.2.2
"response="	2 09D7 0009	[6]	3.2.2
"nextnonce="	2 0B12 000A	[6]	3.2.3
"rspauth="	2 096C 0008	[6]	3.2.3
"realm="	2 0A66 0006	[6]	3.2.1
"domain="	2 0A55 0007	[6]	3.2.1
"nonce="	2 0B16 0006	[6]	3.2.1
"opaque="	4 0761 0007	[6]	3.2.1
"stale="	4 0148 0006	[6]	3.2.1
"true"	4 03F4 0004	[6]	3.2.1

"false"	4 0C30 0005	[6]	3.2.1
"algorithm="	2 09B4 000A	[6]	3.2.1,
		[19]	3.1
"MD5"	2 09F9 0003	[6]	3.2.1,
		[19]	3.1
"MD5-sess"	2 0AEA 0008	[6]	3.2.1,
		[19]	3.1
"auth"	4 031E 0004	[6]	3.2.1
"auth-int"	4 031E 0008	[6]	3.2.1
"AKAv"	2 0AE4 0004	[19]	3.1, 6
"AKAv1-MD5"	2 0AE4 0009	[19]	3.1, 6
"auts="	4 0791 0005	[19]	3.4
"digest-integrity"	4 00CA 0010	[20]	3.3
"ipsec-ike"	4 0671 0009	[20]	3.3
"ipsec-man"	4 0A87 0009	[20]	3.3
"smime"	4 0098 0005	[20]	3.3
";alg="	4 076E 0005	[20]	3.3
";purpose="	5 006B 0009	[3]	20.9
"icon"	5 0993 0004	[3]	20.9, 20.11
"info"	5 09AB 0004	[3]	20.9
"card"	5 0081 0004	[3]	20.9
";expires="	2 0C3E 0009	[3]	25.1,
		[9]	8.4
"render"	5 0A61 0006	[3]	20.11
"session"	5 0AEE 0007	[3]	20.11,
		[33]	4.2
"alert"	5 04BD 0005	[3]	20.11
";handling="	5 005C 000A	[3]	20.11
"optional"	2 09AE 0008	[3]	20.11,

		[12]	4, [3]	20.11, [12]	4
"required"	5 07F4 0008	[3]	20.11		
"text"	5 007C 0004	[3]	25.1		
"image"	5 0066 0005	[3]	25.1		
"audio"	5 0B30 0005	[3]	25.1		
"video"	5 0946 0005	[3]	25.1		
"application"	2 0334 000B	[3]	25.1		
"application/sdp"	2 0956 000F	[3]	25.1		
"message/sip"	4 009B 000B	[3]	27.5		
"message/sipfrag"	4 009B 000F	[15]	2		
"message"	4 009B 0007	[3]	27.5,		
		[15]	2		

"sip"	4	00A3	0003	[3]	27.5
"sipfrag"	4	00A3	0007	[15]	2
"multipart/signed"	4	0398	0010	[3]	23.3
"multipart"	4	0398	0009	[3]	25.1, 7.4.1
"sdp"	2	064B	0003		
"xml"	2	0CAC	0003		
"Mon, "	4	0773	0005	[3]	25.1
"Tue, "	4	0778	0005	[3]	25.1
"Wed, "	4	077D	0005	[3]	25.1
"Thu, "	4	03B9	0005	[3]	25.1
"Fri, "	4	0782	0005	[3]	25.1
"Sat, "	4	0787	0005	[3]	25.1
"Sun, "	4	071D	0005	[3]	25.1
" Jan "	4	04E4	0005	[3]	25.1
" Feb "	4	0881	0005	[3]	25.1
" Mar "	4	0B44	0005	[3]	25.1
" Apr "	4	0D40	0005	[3]	25.1
" May "	4	0478	0005	[3]	25.1
" Jun "	4	049D	0005	[3]	25.1
" Jul "	4	0B58	0005	[3]	25.1
" Aug "	4	033F	0005	[3]	25.1
" Sep "	4	086D	0005	[3]	25.1
" Oct "	4	0CF2	0005	[3]	25.1
" Nov "	4	0858	0005	[3]	25.1
" Dec "	4	02A9	0005	[3]	25.1
" GMT"	4	03B6	0004	[3]	25.1
";tag="	1	0D87	0005	[3]	25.1
"emergency"	4	018C	0009	[3]	20.26
"urgent"	4	021A	0006	[3]	20.26
"normal"	4	0A81	0006	[3]	20.26
"non-urgent"	4	0216	000A	[3]	20.26
";duration="	4	06C4	000A	[3]	20.33
";maddr="	4	075A	0007	[3]	20.42
";received="	4	06BA	000A	[3]	20.42
";branch="	5	0D22	0008	[3]	20.42
";branch=z9hG4bK"	1	0D22	000F	[3]	8.1.1.7

"SIP"	5	0CB9	0003	[3]	25.1, [17] 2
"UDP"	2	0CA6	0003	[3]	20.42
"TCP"	2	0CA3	0003	[3]	20.42
"TLS"	4	071B	0003	[3]	20.42

"SCTP"	4	0D45	0004	[3]	20.42
"active"	4	088C	0006	[9]	8.4
"pending"	4	01AD	0007	[9]	8.4
"terminated"	4	0ADA	000A	[9]	8.4
";reason="	4	0742	0008	[9]	8.4
";retry-after="	4	05F7	000D	[9]	8.4
"deactivated"	4	011C	000B	[9]	8.4
"probation"	4	0D16	0009	[9]	8.4
"rejected"	4	01C9	0008	[9]	8.4
"timeout"	4	0986	0007	[9]	8.4
"giveup"	4	07CF	0006	[9]	8.4
"noresource"	4	024D	000A	[9]	8.4
";id="	4	07A2	0004	[9]	8.4
"100rel"	2	0C95	0006	[10]	8.1
"precondition"	2	0A76	000C	[12]	8
"refer"	3	07DE	0005	[13]	3.1, 7
"to-tag"	4	028D	0006	[14]	3.2
"from-tag"	4	01E6	0008	[14]	3.2
"replaces"	4	0A11	0008	[14]	3.4
"Q.850"	5	01EE	0005	[17]	2
";cause="	5	0074	0007	[17]	2
";text="	5	007B	0006	[17]	2
"path"	3	0964	0004	[16]	3
";refresher="	4	069B	000B	[18]	4
"uac"	4	0604	0003	[18]	4
"uas"	4	07B5	0003	[18]	4
"timer"	4	0CD7	0005	[18]	7.1
"pref"	5	07DD	0004	[22]	4.1
"TRUE"	4	0594	0004	[22]	6.2
"FALSE"	4	06E2	0005	[22]	6.2
";q="	4	07B2	0003	[3]	25.1,
				[22]	6.2, [20] 3.3
";comp=sigcomp"	1	0D0A	000D	[23]	6
"privacy"	3	07D4	0007	[33]	4.2
"header"	4	0967	0006	[33]	4.2
"user"	4	0911	0004	[33]	4.2
"none"	2	0AF4	0004	[33]	4.2,
				[12]	4
"critical"	4	04B7	0008	[33]	4.2
"100 "	5	0BAE	0004	[3]	21.1.1
"100 Trying"	2	0BAE	000A	[3]	21.1.1
"180 "	5	0BA3	0004	[3]	21.1.2
"180 Ringing"	2	0BA3	000B	[3]	21.1.2

"181 "	5	0A3B 0004	[3]	21.1.3
"181 Call Is Being Forwarded"	4	0A3B 001B	[3]	21.1.3
"182 "	5	05A1 0004	[3]	21.1.4
"182 Queued"	4	05A1 000A	[3]	21.1.4
"183 "	5	0AB4 0004	[3]	21.1.5
"183 Session Progress"	2	0AB4 0014	[3]	21.1.5
"200 "	5	0D6B 0004	[3]	21.2.1
"200 OK"	1	0D6B 0006	[3]	21.2.1
"202 "	5	0824 0004	[9]	8.3.1
"202 Accepted"	3	0824 000C	[9]	8.3.1
"300 "	5	0085 0004	[3]	21.3.1
"300 Multiple Choices"	4	0085 0014	[3]	21.3.1
"301 "	5	0383 0004	[3]	21.3.2
"301 Moved Permanently"	4	0383 0015	[3]	21.3.2
"302 "	5	036E 0004	[3]	21.3.3
"302 Moved Temporarily"	4	036E 0015	[3]	21.3.3
"305 "	5	053D 0004	[3]	21.3.4
"305 Use Proxy"	4	053D 000D	[3]	21.3.4
"380 "	5	02AE 0004	[3]	21.3.5
"380 Alternative Service"	4	02AE 0017	[3]	21.3.5
"400 "	5	03E6 0004	[3]	21.4.1
"400 Bad Request"	4	03E6 000F	[3]	21.4.1
"401 "	5	0B5D 0004	[3]	21.4.2
"401 Unauthorized"	2	0B5D 0010	[3]	21.4.2
"402 "	5	03BE 0004	[3]	21.4.3
"402 Payment Required"	4	03BE 0014	[3]	21.4.3
"403 "	5	020A 0004	[3]	21.4.4
"403 Forbidden"	4	020A 000D	[3]	21.4.4
"404 "	5	0530 0004	[3]	21.4.5
"404 Not Found"	4	0530 000D	[3]	21.4.5
"405 "	5	02F2 0004	[3]	21.4.6
"405 Method Not Allowed"	4	02F2 0016	[3]	21.4.6
"406 "	5	041E 0004	[3]	21.4.7
"406 Not Acceptable"	4	041E 0012	[3]	21.4.7
"407 "	5	00AA 0004	[3]	21.4.8
"407 Proxy Authentication Required"	4	00AA 0021	[3]	21.4.8
"408 "	5	0CC5 0004	[3]	21.4.9
"408 Request Timeout"	4	0CC5 0013	[3]	21.4.9
"410 "	5	060F 0004	[3]	21.4.10
"410 Gone"	4	060F 0008	[3]	21.4.10
"413 "	5	0A96 0004	[3]	21.4.11
"413 Request Entity Too Large"	4	0A96 001C	[3]	21.4.11
"414 "	5	07B8 0004	[3]	21.4.12
"414 Request-URI Too Long"	4	07B8 0018	[3]	21.4.12
"415 "	5	0195 0004	[3]	21.4.13
"415 Unsupported Media Type"	4	0195 001A	[3]	21.4.13
"416 "	5	0175 0004	[3]	21.4.14
"416 Unsupported URI Scheme"	4	0175 001A	[3]	21.4.14

[RFC 3485](#)

SIP and SDP Static Dictionary for SigComp

February 2003

"420 "	5	023D 0004	[3]	21.4.15
"420 Bad Extension"	4	023D 0011	[3]	21.4.15
"421 "	5	02DC 0004	[3]	21.4.16
"421 Extension Required"	4	02DC 0016	[3]	21.4.16
"422 "	5	0A19 0004	[18]	6, 12.1
"422 Session Interval Too Small"	4	0A19 001E	[18]	6, 12.2
"423 "	5	01D1 0004	[3]	21.4.17
"423 Interval Too Brief"	4	01D1 0016	[3]	21.4.17
"429 "	5	0220 0004	[34]	9
"429 Provide Referror Identity"	4	0220 001D	[34]	9
"480 "	5	07FC 0004	[3]	21.4.18
"480 Temporarily Unavailable"	3	07FC 001B	[3]	21.4.18
"481 "	5	0127 0004	[3]	21.4.19
"481 Call/Transaction Does Not Exist"	4	0127 0023	[3]	21.4.19
"482 "	5	047D 0004	[3]	21.4.20
"482 Loop Detected"	4	047D 0011	[3]	21.4.20
"483 "	5	0999 0004	[3]	21.4.21
"483 Too Many Hops"	4	0999 0011	[3]	21.4.21
"484 "	5	00DA 0004	[3]	21.4.22
"484 Address Incomplete"	4	00DA 0016	[3]	21.4.22
"485 "	5	0B1C 0004	[3]	21.4.23
"485 Ambiguous"	4	0B1C 000D	[3]	21.4.23
"486 "	5	0ACB 0004	[3]	21.4.24
"486 Busy Here"	3	0ACB 000D	[3]	21.4.24
"487 "	5	0308 0004	[3]	21.4.25
"487 Request Terminated"	4	0308 0016	[3]	21.4.25
"488 "	5	01B4 0004	[3]	21.4.26
"488 Not Acceptable Here"	4	01B4 0017	[3]	21.4.26
"489 "	5	04C7 0004	[9]	8.3.2
"489 Bad Event"	4	04C7 000D	[9]	8.3.2
"491 "	5	03F8 0004	[3]	21.4.27
"491 Request Pending"	4	03F8 0013	[3]	21.4.27
"493 "	5	0457 0004	[3]	21.4.28
"493 Undecipherable"	4	0457 0012	[3]	21.4.28
"494 "	5	00FE 0004	[20]	3.3.1
"494 Security Agreement Required"	4	00FE 001F	[20]	3.3.1
"500 "	5	014E 0004	[3]	21.5.1
"500 Server Internal Error"	4	014E 0019	[3]	21.5.1
"501 "	5	040B 0004	[3]	21.5.2
"501 Not Implemented"	4	040B 0013	[3]	21.5.2
"502 "	5	04E9 0004	[3]	21.5.3
"502 Bad Gateway"	4	04E9 000F	[3]	21.5.3

"503 "	5	02C5	0004	[3]	21.5.4
"503 Service Unavailable"	4	02C5	0017	[3]	21.5.4
"504 "	5	027B	0004	[3]	21.5.5
"504 Server Time-out"	4	027B	0013	[3]	21.5.5
"505 "	5	01F1	0004	[3]	21.5.6
"505 Version Not Supported"	4	01F1	0019	[3]	21.5.6

"513 "	5	0344	0004	[3]	21.5.7
"513 Message Too Large"	4	0344	0015	[3]	21.5.7
"580 "	5	09FB	0004	[12]	8
"580 Precondition Failure"	4	09FB	0018	[12]	8
"600 "	5	07E3	0004	[3]	21.6.1
"600 Busy Everywhere"	3	07E3	0013	[3]	21.6.1
"603 "	5	0B09	0004	[3]	21.6.2
"603 Decline"	4	0B09	000B	[3]	21.6.2
"604 "	5	09BE	0004	[3]	21.6.3
"604 Does Not Exist Anywhere"	4	09BE	001B	[3]	21.6.3
"606 "	5	0430	0004	[3]	21.6.4
"606 Not Acceptable"	4	0430	0012	[3]	21.6.4
"687 "	5	0359	0004	[14]	3.5
"687 Dialog Terminated"	4	0359	0015	[14]	3.5
"Anonymous"	3	08A4	0009	[3]	8.1.1.3

Table A.1: SIP input strings for the SIP/SDP dictionary

[Appendix B](#). SDP input strings to the SIP/SDP static dictionary

For reference, this section lists the SDP input strings that were used in generating the dictionary, as well as a priority value, the offset of the string in the generated dictionary, the length of the string, and one or more references into the referenced documents that motivate the presence of this string. Note that the notation "[CRLF]" stands for a sequence of two bytes with the values 0x0d and 0x0a, respectively.

The priority value is used for determining the position of the string in the dictionary. Lower priority values (higher priorities) cause the string to occur at a later position in the dictionary, making it more efficient to reference the string in certain compression algorithms. Hence, lower priority values were assigned to strings more likely to occur.

String	Pr	Off	Len	References
=====	==	=====	=====	=====
"v=0[CRLF]o="	2	0BB8	0007	[24] 6
"[CRLF]s="	2	0C2B	0004	[24] 6
"[CRLF]s= "	2	0C2B	0005	[32] 5
"[CRLF]i="	4	07A6	0004	[24] 6
"[CRLF]u="	4	07AE	0004	[24] 6
"[CRLF]e="	4	079E	0004	[24] 6
"[CRLF]c=IN IP4 "	3	08E1	000B	[24] 6
"[CRLF]c=IN IP6 "	2	0B98	000B	[24] 6
"[CRLF]c="	5	08E1	0004	[24] 6

"[CRLF]b="	3	0916	0004	[24]	6
"[CRLF]t="	2	0B78	0004	[24]	6
"[CRLF]t=0 0"	2	0B78	0007	[32]	5
"[CRLF]r="	4	0796	0004	[24]	6
"[CRLF]z="	4	079A	0004	[24]	6
"[CRLF]k=clear:"	4	06B0	000A	[24]	6
"[CRLF]k=base64:"	4	0690	000B	[24]	6
"[CRLF]k=uri:"	4	0732	0008	[24]	6
"[CRLF]k=prompt:"	4	056B	000B	[24]	6
"[CRLF]k="	5	056B	0004	[24]	6
"[CRLF]a=cat:"	4	072A	0008	[24]	6
"[CRLF]a=keywds:"	4	0685	000B	[24]	6
"[CRLF]a=tool:"	4	0712	0009	[24]	6
"[CRLF]a=ptime:"	4	06A6	000A	[24]	6
"[CRLF]a=maxptime:"	4	05EA	000D	[24]	6
"[CRLF]a=rtpmap:"	2	0C0C	000B	[24]	6, [32] 5
"[CRLF]a=recvonly"	3	08C9	000C	[24]	6
"[CRLF]a=sendrecv"	3	093B	000C	[24]	6
"[CRLF]a=sendonly"	3	08D5	000C	[24]	6
"[CRLF]a=inactive"	3	0886	000C	[24]	6

"[CRLF]a=orient:portrait"	4	0974	0013	[24]	6
"[CRLF]a=orient:landscape"	4	03D2	0014	[24]	6
"[CRLF]a=orient:seascape"	4	050B	0013	[24]	6
"[CRLF]a=type:broadcast"	4	0442	0012	[24]	6
"[CRLF]a=type:meeting"	4	055B	0010	[24]	6
"[CRLF]a=type:moderated"	4	051E	0012	[24]	6
"[CRLF]a=type:test"	4	08B1	000D	[24]	6
"[CRLF]a=type:H.332"	4	0817	000E	[24]	6
"[CRLF]a=type:recvonly"	4	054A	0011	[24]	6
"[CRLF]a=charset:"	4	0653	000C	[24]	6
"[CRLF]a=sdplang:"	4	0647	000C	[24]	6
"[CRLF]a=lang:"	4	06F7	0009	[24]	6
"[CRLF]a=framerate:"	4	05C7	000E	[24]	6
"[CRLF]a=quality:"	4	063B	000C	[24]	6
"[CRLF]a=fmtp:"	2	0C50	0009	[24]	6
"[CRLF]a=curr:"	2	0C59	0009	[12]	4
"[CRLF]a=des:"	2	0C72	0008	[12]	4
"[CRLF]a=conf:"	2	0C35	0009	[12]	4
"[CRLF]a=mid:"	4	0752	0008	[26]	3
"[CRLF]a=group:"	4	06D8	000A	[26]	3
"[CRLF]a=key-mgmt:mikey"	4	0257	0012	[28]	2.1,

	[29]	6	
"[CRLF]a=key-mgmt:"	4	0257 000D	[28] 2.1
"[CRLF]a="	5	0257 0004	[24] 6
"[CRLF]m=audio "	2	0C21 000A	[24] 6
"[CRLF]m=video "	2	0C17 000A	[24] 6
"[CRLF]m=application "	4	0330 0010	[24] 6
"[CRLF]m=data "	4	0700 0009	[24] 6
"[CRLF]m=control "	4	062F 000C	[24] 6
"[CRLF]m="	5	0330 0004	[24] 6
"AS "	3	091A 0003	[24] 6
"CT "	3	091D 0003	[24] 6
"RTP/AVP "	2	0BE3 0008	[24] A
"RTP/SAVP "	3	0892 0009	[30] 12
"RTP/AVPF "	3	089B 0009	[31] 4.1
"udp"	4	07DB 0003	[3] 25.1, [24] A, [3] 25.1, [24] A
"0.0.0.0"	4	0B7E 0007	[24] A
"qos"	2	0CA9 0003	[12] 4
"mandatory"	2	0A8D 0009	[12] 4
"optional"	2	09AE 0008	[3] 20.11, [12] 4, [3] 20.11, [12] 4
"none"	2	0AF4 0004	[33] 4.2, [12] 4
"failure"	4	0A5C 0007	[12] 4
"unknown"	4	0BDA 0007	[12] 4
"e2e"	2	0AB1 0003	[12] 4
"local"	2	0A36 0005	[12] 4

"remote"	2	0AD6 0006	[12] 4
"send"	2	08D9 0004	[12] 4
"recv"	2	0553 0004	[12] 4
"sendrecv"	2	093F 0008	[12] 4
"AMR"	2	0BE1 0003	[25] 8
"octet-align="	4	094A 000C	[25] 8
"mode-set="	4	0709 0009	[25] 8
"mode-change-period="	4	04F8 0013	[25] 8
"mode-change-neighbor="	4	04A2 0015	[25] 8
"crc="	4	07AA 0004	[25] 8
"robust-sorting="	4	0166 000F	[25] 8
"interleaving="	4	0323 000D	[25] 8
"channels="	4	0606 0009	[25] 8
"octet-align"	4	094A 000B	[25] 8

"telephone-event"	4	00EE	000F	[27]	3.3, 6.1
"events"	4	00F8	0006	[27]	6.1
"rate"	4	052B	0004	[27]	6.1, 6.2
"tone"	4	0453	0004	[27]	6.2
"rtcp-fb"	4	04C0	0007	[31]	4
"ack"	4	0D1F	0003	[31]	4
"nack"	4	0D1E	0004	[31]	4
"ttr-int"	4	098C	0007	[31]	4
"app"	4	0334	0003	[31]	4
"rpsi"	4	0CDB	0004	[31]	4
"pli"	4	0336	0003	[31]	4
"sli"	4	09A9	0003	[31]	4

Table B.1: SDP input strings for the SIP/SDP dictionary

Authors' Addresses

Miguel A. Garcia-Martin
Ericsson
Hirsalantie 11
FIN-02420, Jorvas, Finland

Phone: +358 9299 3553
EMail: miguel.a.garcia@ericsson.com

Carsten Bormann
Universitaet Bremen TZI
Postfach 330440
D-28334 Bremen, Germany

Phone: +49 421 218 7024
EMail: cabo@tzi.org

Joerg Ott
Universitaet Bremen TZI
Postfach 330440
D-28334 Bremen, Germany

Phone: +49.421.201-7028
EMail: jo@tzi.org

Richard Price
Roke Manor Research Ltd
Romsey, Hants, S051 0ZN, United Kingdom

Phone: +44 1794 833681
EMail: richard.price@roke.co.uk

Adam Roach
dynamicsoft
5100 Tennyson Parkway, Suite 1200
Plano, TX 75024, USA

EMail: adam@dynamicsoft.com

Full Copyright Statement

Copyright (C) The Internet Society (2003). All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Acknowledgement

Funding for the RFC Editor function is currently provided by the Internet Society.

