

INTERNET-DRAFT
February 26, 2003

R. Hinden, Nokia
S. Deering, Cisco
E. Nordmark, Sun

IPv6 Global Unicast Address Format

<[draft-ietf-ipv6-unicast-aggr-v2-02.txt](#)>

Status of this Memo

This document is an Internet-Draft and is subject to all provisions of [Section 10 of RFC2026](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/lid-abstracts.html>

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>

This internet draft expires on August 26, 2003.

Abstract

[RFC2374](#) "An IPv6 Aggregatable Global Unicast Address Format" defined an IPv6 address allocation structure that includes TLA (Top Level Aggregator) and NLA (Next Level Aggregator). This document replaces [RFC2374](#), and makes [RFC 2374](#) and the TLA/NLA structure historic.

INTERNET-DRAFT

IPv6 Global Unicast Address Format

February 2003

[1.0](#) Introduction

[RFC2374](#) "An IPv6 Aggregatable Global Unicast Address Format" defined an IPv6 address allocation structure that includes TLA (Top Level Aggregator) and NLA (Next Level Aggregator). This document replaces [RFC2374](#), and makes [RFC 2374](#) and the TLA/NLA structure historic.

[2.0](#) TLA/NLA Made Historic

The TLA/NLA scheme has been replaced by a coordinated allocation policy defined by the Regional Internet Registries (RIRs) [[IPV6RIR](#)].

Part of the motivation for obsoleting the TLA/NLA structure is technical; for instance, there is concern that TLA/NLA is not the technically best approach at this stage of the deployment of IPv6. Moreover, the allocation of IPv6 addresses is related to policy and to the stewardship of the IP address space and routing table size, which the RIRs have been managing for IPv4. It is likely that the RIRs' policy will evolve as IPv6 deployment proceeds.

The IETF has provided technical input to the RIRs (for example, [[RFC3177](#)]), which the RIRs have taken into account when defining their address allocation policy.

[RFC2374](#) was the definition of addresses for Format Prefix 001 (2000::/3) which is formally made historic by this document. Even though currently only 2000::/3 is being delegated by the IANA, implementations should not make any assumptions about 2000::/3 being special, since the IANA might later be directed to delegate currently unassigned parts of the IPv6 address space to the purpose of Global Unicast as well.

The SLA (subnet local aggregator) field in [RFC2374](#) remains in function but with a different name in [[ARCH](#)]. Its new name is "subnet ID".

This document replaces [RFC2374](#), "An IPv6 Aggregatable Global Unicast Address Format". [RFC2374](#) will become historic.

[3.0](#) Address Format

The general format for IPv6 global unicast addresses as defined in "IP Version 6 Addressing Architecture" [\[ARCH\]](#) is as follows:

[draft-ietf-ipv6-unicast-aggr-v2-02.txt](#)

[Page 2]

INTERNET-DRAFT

IPv6 Global Unicast Address Format

February 2003

	n bits		m bits		128-n-m bits	
+	-----	+	-----	+	-----	+
	global routing prefix		subnet ID		interface ID	
+	-----	+	-----	+	-----	+

where the global routing prefix is a (typically hierarchically-structured) value assigned to a site (a cluster of subnets/links), the subnet ID is an identifier of a subnet within the site, and the interface ID is as defined in section 2.5.1 of [\[ARCH\]](#).

[\[ARCH\]](#) also requires that all unicast addresses, except those that start with binary value 000, have Interface IDs that are 64 bits long and to be constructed in Modified EUI-64 format. The format of global unicast address in this case is:

	n bits		64-n bits		64 bits	
+	-----	+	-----	+	-----	+
	global routing prefix		subnet ID		interface ID	
+	-----	+	-----	+	-----	+

where the routing prefix is a value assigned to identify a site (a cluster of subnets/links), the subnet ID is an identifier of a subnet within the site, and the interface ID is in modified EUI-64 format as defined in [\[ARCH\]](#).

An example of the resulting format of global unicast address under the 2000::/3 prefix that is currently being delegated by the IANA and consistent with the recommendations in [RFC3177](#) is:

	3		45 bits		16 bits		64 bits	
+	---	+	-----	+	-----	+	-----	+
	001		global routing prefix		subnet ID		interface ID	
+	---	+	-----	+	-----	+	-----	+

INTERNET-DRAFT

IPv6 Global Unicast Address Format

February 2003

[4.0](#) Acknowledgments

The authors would like to express our thanks to Alain Durand, Brian Carpenter, Fred Templin, Julian Sellers, Jun-ichiro itojun Hagino, Margaret Wasserman, Michel Py, Pekka Savola, Tatuya Jinmei, and Thomas Narten for their review and constructive comments.

[5.0](#) References

Normative

[ARCH] Hinden, R., "IP Version 6 Addressing Architecture", Internet Draft, <[draft-ietf-ipngwg-addr-arch-v3-11.txt](#)>, October 2002.

[IPV6] Deering, S., R. Hinden, "Internet Protocol, Version 6 (IPv6) Specification", [RFC2460](#), December 1998.

Non-Normative

[IPV6RIR] APNIC, ARIN, RIPE NCC, "IPv6 Address Allocation and Assignment Policy", Document ID: ripe-267, <http://www.ripe.net/ripe/docs/ipv6policy.html>, January 22, 2003.

[RFC3177] IAB/IESG, "Recommendations on IPv6 Address Allocations to Sites" [RFC3177](#), September 2001.

[6.0](#) Security Considerations

IPv6 addressing documents do not have any direct impact on Internet infrastructure security.

[7.0](#) Authors' Addresses

Robert M. Hinden
Nokia
313 Fairchild Drive
Mountain View, CA
US

email: bob.hinden@nokia.com

Stephen E. Deering
Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
US

email: deering@cisco.com

Erik Nordmark
Sun Microsystems Laboratories
180, avenue de l'Europe
38334 SAINT ISMIER Cedex
France

email: erik.nordmark@sun.com

