

Power Ethernet MIB

<[draft-ietf-hubmib-power-ethernet-mib-08.txt](#)>

Status of this Memo

This document is an Internet-Draft and is in full conformance with all provisions of [Section 10 of RFC2026](#). Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

To view the list Internet-Draft Shadow Directories, see <http://www.ietf.org/shadow.html>.

Copyright Notice

Copyright (C) The Internet Society (2003). All Rights Reserved.

Abstract

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. The document proposes an extension to the Ethernet-like Interfaces MIB with a set of objects for managing a Power Source Equipment (PSE).

Distribution of this memo is unlimited.

Table of Contents

Status of this Memo	1
Abstract	1
1 Introduction	2
2 The Internet-Standard Management Framework	2

INTERNET DRAFT

Power Ethernet MIB

June 2003

3 Overview	2
4 MIB Structure	3
5 Definitions	3
6 Acknowledgements	17
7 Normative References	17
8 Informative References	18
9 Intellectual Property	18
10 Security Considerations	18
11 Authors Addresses	20
A Full Copyright Statement	20

1. Introduction

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it defines a set of MIB objects to manage a Power Ethernet [[IEEE-802.3af](#)] Source Equipment (PSE).

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

2. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to [section 7 of RFC 3410](#) [[RFC3410](#)].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIV2, which is described in STD 58, [RFC 2578](#) [[RFC2578](#)], STD 58, [RFC 2579](#) [[RFC2579](#)] and STD 58, [RFC 2580](#) [[RFC2580](#)].

3. Overview

The emergence of IP telephony as an application that allows for voice applications to be run over the same infrastructure as data applications led to the emergence of Ethernet IP phones, with similar

functions and characteristics as the traditional phones. Powering a phone is one of these functions that are being taken as granted. The IEEE 802.3 Working Group initiated a standard work on this subject, currently known as the IEEE 802.3af work [[IEEE-802.3af](#)].

The IEEE 802.3af WG did not define a full management interface, but only the hardware registers that will allow for a management interfaces to be built for a powered Ethernet device. The MIB module defined in this document extends the Ethernet-like Interfaces MIB [[RFC2665](#)] with the management objects required for the management of the powered Ethernet devices and ports.

The following abbreviations are defined in [[IEEE-802.3af](#)] and will be used with the same significance in this document:

PSE - Power Sourcing Equipment;

PD - Powered Device

[4.](#) MIB Structure

This MIB objects are included in three MIB groups.

The pethPsePortTable defines the objects used for the configuration and describing the status of ports on a PSE device. Examples of PSE devices are Ethernet switches that support power Ethernet and mid-span boxes.

The pethMainPseObjects MIB group defines the management objects for a managed main power source in a PSE device. Ethernet switches are one example of boxes that would support these objects.

The pethNotificationControlTable includes objects that control the transmission of notifications by the agent to a management application.

[5.](#) Definitions

POWER-ETHERNET-MIB DEFINITIONS ::= BEGIN

IMPORTS

MODULE-IDENTITY, mib-2, OBJECT-TYPE, Integer32,
Gauge32, Counter32, NOTIFICATION-TYPE
FROM SNMPv2-SMI
TruthValue
FROM SNMPv2-TC
MODULE-COMPLIANCE, OBJECT-GROUP, NOTIFICATION-GROUP
FROM SNMPv2-CONF

Ethernet MIB WG

Expires December 2003

[Page 3]

INTERNET DRAFT

Power Ethernet MIB

June 2003

SnmpAdminString
FROM SNMP-FRAMEWORK-MIB;

powerEthernetMIB MODULE-IDENTITY

LAST-UPDATED "200306220000Z" -- June 22, 2003
ORGANIZATION "IETF Ethernet Interfaces and Hub MIB
Working Group"

CONTACT-INFO

"

WG Charter:

<http://www.ietf.org/html.charters/hubmib-charter.html>

Mailing lists:

General Discussion: hubmib@ietf.org
To Subscribe: hubmib-requests@ietf.org
In Body: subscribe your_email_address

Chair: Dan Romascanu

Avaya

Tel: +972-3-645-8414

Email: dromasca@avaya.com

Editor: Avi Berger

PowerDsine Inc.

Tel: 972-9-7755100 Ext 307

Fax: 972-9-7755120

E-mail: avib@PowerDsine.com

"

DESCRIPTION

"The MIB module for managing Power Source Equipment (PSE) working according to the IEEE 802.af Powered Ethernet (DTE Power via MDI) standard.

The following terms are used throughout this MIB module. For complete formal definitions, the IEEE 802.3 standards should be consulted wherever possible:

Group - A recommended, but optional, entity defined by the IEEE 802.3 management standard, in order to support a modular numbering scheme. The classical example allows an implementor to represent field-replaceable units as groups of ports, with the port numbering matching the modular hardware implementation.

Ethernet MIB WG

Expires December 2003

[Page 4]

INTERNET DRAFT

Power Ethernet MIB

June 2003

Port - This entity identifies the port within the group for which this entry contains information. The numbering scheme for ports is implementation specific.

Copyright (c) The Internet Society (2003). This version of this MIB module is part of RFC yyyy; See the RFC itself for full legal notices.

-- RFC Ed.: replace yyyy with the actual RFC number & remove this notice.
"

REVISION "200306220000Z" -- June 22, 2003

DESCRIPTION "Initial version, published as RFC yyyy."

-- RFC Ed.: replace yyyy with actual RFC number & remove this notice

::= { mib-2 XXX }

-- RFC Ed.: replace XXX with IANA-assigned number & remove this notice

pethNotifications OBJECT IDENTIFIER ::= { powerEthernetMIB 0 }
pethObjects OBJECT IDENTIFIER ::= { powerEthernetMIB 1 }
pethConformance OBJECT IDENTIFIER ::= { powerEthernetMIB 2 }

-- PSE Objects

```
pethPsePortTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF PethPsePortEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A table of objects that display and control the power
        characteristics power Ethernet ports on a Power Source
        Entity (PSE) device. This group will be implemented in
        managed power Ethernet switches and mid-span devices.
        Values of all read-write objects in this table are
        persistent at restart/reboot."
    ::= { pethObjects 1 }
```

```
pethPsePortEntry OBJECT-TYPE
    SYNTAX      PethPsePortEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A set of objects that display and control the power
        characteristics of a power Ethernet PSE port."
    INDEX      { pethPsePortGroupIndex , pethPsePortIndex }
    ::= { pethPsePortTable 1 }
```

```
PethPsePortEntry ::= SEQUENCE {
    pethPsePortGroupIndex
        Integer32,
    pethPsePortIndex
        Integer32,
    pethPsePortAdminEnable
        TruthValue,
    pethPsePortPowerPairsControlAbility
        TruthValue,
    pethPsePortPowerPairs
        INTEGER,
    pethPsePortDetectionStatus
        INTEGER,
    pethPsePortPowerPriority
        INTEGER,
```

```

    pethPsePortMPSAbsentCounter
        Counter32,
    pethPsePortInvalidSignatureCounter
        Counter32,
    pethPsePortPowerDeniedCounter
        Counter32,
    pethPsePortOverLoadCounter
        Counter32,
    pethPsePortShortCounter
        Counter32,
    pethPsePortType
        SnmpAdminString,
    pethPsePortPowerClassifications
        INTEGER
}

```

```

pethPsePortGroupIndex OBJECT-TYPE
    SYNTAX      Integer32 (1..2147483647)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This variable uniquely identifies the group
        containing the port to which a power Ethernet PSE is
        connected. Group means box in the stack, module in a
        rack and the value 1 MUST be used for non-modular devices.
        Furthermore, the same value MUST be used in this variable,
        pethMainPseGroupIndex, and pethNotificationControlGroupIndex
        to refer to a given box in a stack or module in the rack."
    ::= { pethPsePortEntry 1 }

```

```

pethPsePortIndex OBJECT-TYPE
    SYNTAX      Integer32 (1..2147483647)
    MAX-ACCESS  not-accessible

```

```

STATUS      current
DESCRIPTION
    "This variable uniquely identifies the power Ethernet PSE
    port within group pethPsePortGroupIndex to which the
    power Ethernet PSE entry is connected."
    ::= { pethPsePortEntry 2 }

```

pethPsePortAdminEnable OBJECT-TYPE
 SYNTAX TruthValue
 MAX-ACCESS read-write
 STATUS current
 DESCRIPTION
 "true (1) An interface which can provide the PSE functions.
 false(2) The interface will act as it would if it had no PSE
 function."
 REFERENCE
 "IEEE Std 802.3af [Section 30.9.1.1.2](#) aPSEAdminState"
 ::= { pethPsePortEntry 3 }

pethPsePortPowerPairsControlAbility OBJECT-TYPE
 SYNTAX TruthValue
 MAX-ACCESS read-only
 STATUS current
 DESCRIPTION
 "Describes the capability of controlling the power pairs
 functionality to switch pins for sourcing power.
 The value true indicate that the device has the capability
 to control the power pairs. When false the PSE Pinout
 Alternative used cannot be controlled through the
 PethPsePortAdminEnabe attribute."
 REFERENCE
 "IEEE Std 802.3af [Section 30.9.1.1.3](#)
 aPSEPowerPairsControlAbility"
 ::= { pethPsePortEntry 4 }

pethPsePortPowerPairs OBJECT-TYPE
 SYNTAX INTEGER {
 signal(1),
 spare(2)
 }
 MAX-ACCESS read-write
 STATUS current
 DESCRIPTION
 "Describes or controls the pairs in use. If the value of
 pethPsePortPowerPairsControl is true, this object is
 writable.
 A value of signal(1) menas that the signal pairs

A value of spare(2) means that the spare pairs only are in use."

REFERENCE

"IEEE Std 802.3af [Section 30.9.1.1.4](#) aPSEPowerPairs"
 ::= { pethPsePortEntry 5 }

pethPsePortDetectionStatus OBJECT-TYPE
SYNTAX INTEGER {
 disabled(1),
 searching(2),
 deliveringPower(3),
 fault(4),
 test(5),
 otherFault(6)
}

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Describes the operational status of the port PD detection.
A value of disabled(1)- indicates that the PSE State diagram is in the state DISABLED.
A value of deliveringPower(3) - indicates that the PSE State diagram is in the state POWER_ON for a duration greater than tlim max (see IEEE Std 802.3af Table 33-5 tlim).
A value of fault(4) - indicates that the PSE State diagram is in the state TEST_ERROR.
A value of test(5) - indicates that the PSE State diagram is in the state TEST_MODE.
A value of otherFault(6) - indicates that the PSE State diagram is in the state IDLE due to the variable error_conditions.
A value of searching(2)- indicates the PSE State diagram is in a state other than those listed above."

REFERENCE

"IEEE Std 802.3af [Section 30.9.1.1.5](#)
 aPSEPowerDetectionStatus"
 ::= { pethPsePortEntry 6 }

pethPsePortPowerPriority OBJECT-TYPE
SYNTAX INTEGER {
 critical(1),
 high(2),
 low(3)
}

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"This object controls the priority of the port from the point of view of a power management algorithm. The priority that is set by this variable could be used by a control mechanism that prevents over current situations by disconnecting first ports with lower power priority. Ports that connect devices critical to the operation of the network - like the E911 telephones ports - should be set to higher priority."

::= { pethPsePortEntry 7 }

pethPsePortMPSAbsentCounter OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"This counter is incremented when the PSE state diagram transitions directly from the state POWER_ON to the state IDLE due to tmpdo_timer_done being asserted."

REFERENCE

"IEEE Std 802.3af [Section 30.9.1.1.11](#)
aPSEMPSAbsentCounter"

::= { pethPsePortEntry 8 }

pethPsePortType OBJECT-TYPE

SYNTAX SnmpAdminString

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"A manager will set the value of this variable to indicate the type of powered device that is connected to the port. The default value supplied by the agent if no value has ever been set should be a zero-length octet string."

::= { pethPsePortEntry 9 }

pethPsePortPowerClassifications OBJECT-TYPE

SYNTAX INTEGER {
 class0(1),
 class1(2),
 class2(3),
 class3(4),
 class4(5)
}

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Classification is a way to tag different terminals on the Power over LAN network according to their power consumption.

Devices such as IP telephones, WLAN access points and others, will be classified according to their power requirements.

The meaning of the classification labels is defined in the IEEE specification.

This variable is valid only while a PD is being powered, that is, while the attribute pethPsePortDetectionStatus is reporting the enumeration deliveringPower."

REFERENCE

"IEEE Std 802.3af [Section 30.9.1.1.6](#)
aPSEPowerClassification"
 ::= { pethPsePortEntry 10 }

pethPsePortInvalidSignatureCounter OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION

"This counter is incremented when the PSE state diagram enters the state SIGNATURE_INVALID."

REFERENCE

"IEEE Std 802.3af [Section 30.9.1.1.7](#)
aPSEInvalidSignatureCounter"
 ::= { pethPsePortEntry 11 }

pethPsePortPowerDeniedCounter OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION

"This counter is incremented when the PSE state diagram enters the state POWER_DENIED."

REFERENCE

"IEEE Std 802.3af [Section 30.9.1.1.8](#)
aPSEPowerDeniedCounter"
 ::= { pethPsePortEntry 12 }

pethPsePortOverLoadCounter OBJECT-TYPE

SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "This counter is incremented when the PSE state diagram
 enters the state ERROR_DELAY_OVER."
REFERENCE
 "IEEE Std 802.3af [Section 30.9.1.1.9](#)
 aPSEOverLoadCounter"

Ethernet MIB WG

Expires December 2003

[Page 10]

INTERNET DRAFT

Power Ethernet MIB

June 2003

::= { pethPsePortEntry 13 }

 pethPsePortShortCounter OBJECT-TYPE
 SYNTAX Counter32
 MAX-ACCESS read-only
 STATUS current
 DESCRIPTION
 "This counter is incremented when the PSE state diagram
 enters the state ERROR_DELAY_SHORT."
 REFERENCE
 "IEEE Std 802.3af [Section 30.9.1.1.10](#)
 aPSEShortCounter"
 ::= { pethPsePortEntry 14 }

-- Main PSE Objects

pethMainPseObjects OBJECT IDENTIFIER ::= { pethObjects 3 }

pethMainPseTable OBJECT-TYPE

 SYNTAX SEQUENCE OF PethMainPseEntry

 MAX-ACCESS not-accessible

 STATUS current

 DESCRIPTION

 "A table of objects that display and control attributes
 of the main power source in a PSE device. Ethernet
 switches are one example of boxes that would support
 these objects.

 Values of all read-write objects in this table are
 persistent at restart/reboot."

```
::= { pethMainPseObjects 1 }
```

```
pethMainPseEntry OBJECT-TYPE
```

```
SYNTAX      PethMainPseEntry
```

```
MAX-ACCESS  not-accessible
```

```
STATUS      current
```

```
DESCRIPTION
```

```
    "A set of objects that display and control the Main  
    power of a PSE. "
```

```
INDEX       { pethMainPseGroupIndex }
```

```
::= { pethMainPseTable 1 }
```

```
PethMainPseEntry ::= SEQUENCE {
```

```
    pethMainPseGroupIndex
```

```
        Integer32,
```

```
    pethMainPsePower
```

Ethernet MIB WG

Expires December 2003

[Page 11]

INTERNET DRAFT

Power Ethernet MIB

June 2003

```
        Gauge32 ,  
    pethMainPseOperStatus  
        INTEGER,  
    pethMainPseConsumptionPower  
        Gauge32,  
    pethMainPseUsageThreshold  
        Integer32
```

```
}
```

```
pethMainPseGroupIndex OBJECT-TYPE
```

```
SYNTAX      Integer32 (1..2147483647)
```

```
MAX-ACCESS  not-accessible
```

```
STATUS      current
```

```
DESCRIPTION
```

```
    "This variable uniquely identifies the group to which  
    power Ethernet PSE is connected. Group means (box in  
    the stack, module in a rack) and the value 1 MUST be  
    used for non-modular devices. Furthermore, the same  
    value MUST be used in this variable, pethPsePortGroupIndex,  
    and pethNotificationControlGroupIndex to refer to a  
    given box in a stack or module in a rack."
```

```
::= { pethMainPseEntry 1 }
```

```
pethMainPsePower OBJECT-TYPE
```

```
SYNTAX      Gauge32 (1..65535)
```

```
UNITS      "Watts"
```

MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The nominal power of the PSE expressed in Watts."
 ::= { pethMainPseEntry 2 }

pethMainPseOperStatus OBJECT-TYPE
 SYNTAX INTEGER {
 on(1),
 off(2),
 faulty(3)
 }
 MAX-ACCESS read-only
 STATUS current
 DESCRIPTION
 "The operational status of the main PSE."
 ::= { pethMainPseEntry 3 }

pethMainPseConsumptionPower OBJECT-TYPE
 SYNTAX Gauge32
 UNITS "Watts"
 MAX-ACCESS read-only

STATUS current
DESCRIPTION
 "Measured usage power expressed in Watts."
 ::= { pethMainPseEntry 4 }

pethMainPseUsageThreshold OBJECT-TYPE
 SYNTAX Integer32 (1..99)
 UNITS "%"
 MAX-ACCESS read-write
 STATUS current
 DESCRIPTION
 "The usage threshold expressed in percents for
 comparing the measured power and initiating
 an alarm if the threshold is exceeded."
 ::= { pethMainPseEntry 5 }

-- Notification Control Objects

pethNotificationControl OBJECT IDENTIFIER ::= { pethObjects 4 }

pethNotificationControlTable OBJECT-TYPE

SYNTAX SEQUENCE OF PethNotificationControlEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"A table of objects that display and control the Notification on a PSE device.

Values of all read-write objects in this table are persistent at restart/reboot."

::= { pethNotificationControl 1 }

pethNotificationControlEntry OBJECT-TYPE

SYNTAX PethNotificationControlEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"A set of objects that control the Notification events."

INDEX { pethNotificationControlGroupIndex }

::= { pethNotificationControlTable 1 }

PethNotificationControlEntry ::= SEQUENCE {

pethNotificationControlGroupIndex

Integer32,

pethNotificationControlEnable

TruthValue

}

pethNotificationControlGroupIndex OBJECT-TYPE

SYNTAX Integer32 (1..2147483647)

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This variable uniquely identifies the group. Group means box in the stack, module in a rack and the value 1 MUST be used for non-modular devices. Furthermore, the same value MUST be used in this variable,

```
    pethPsePortGroupIndex, and
    pethMainPseGroupIndex to refer to a given box in a
    stack or module in a rack. "
 ::= { pethNotificationControlEntry 1 }
```

```
pethNotificationControlEnable OBJECT-TYPE
SYNTAX          TruthValue
MAX-ACCESS      read-write
STATUS          current
DESCRIPTION
    "This object controls, on a per-group basis, whether
    or not notifications from the agent are enabled. The
    value true(1) means that notifications are enabled; the
    value false(2) means that they are not."
 ::= { pethNotificationControlEntry 2 }
```

```
--
-- Notifications Section
--
--
```

```
pethPsePortOnOffNotification NOTIFICATION-TYPE
OBJECTS          { pethPsePortDetectionStatus }
STATUS          current
DESCRIPTION
    " This Notification indicates if Pse Port is delivering or
    not power to the PD. This Notification SHOULD be sent on
    every status change except in the searching mode.
    At least 500 msec must elapse between notifications
    being emitted by the same object instance."
 ::= { pethNotifications 1 }
```

```
pethMainPowerUsageOnNotification NOTIFICATION-TYPE
OBJECTS          { pethMainPseConsumptionPower }
STATUS          current
DESCRIPTION
```



```

        " This Notification indicate PSE Threshold usage
          indication is on, the usage power is above the
          threshold. At least 500 msec must elapse between
          notifications being emitted by the same object
          instance."
 ::= { pethNotifications 2 }

pethMainPowerUsageOffNotification NOTIFICATION-TYPE
OBJECTS      { pethMainPseConsumptionPower }
STATUS      current
DESCRIPTION
    " This Notification indicates PSE Threshold usage indication
      off, the usage power is below the threshold.
      At least 500 msec must elapse between notifications being
      emitted by the same object instance."
 ::= { pethNotifications 3 }

--
-- Conformance Section
--
pethCompliances OBJECT IDENTIFIER ::= { pethConformance 1 }
pethGroups      OBJECT IDENTIFIER ::= { pethConformance 2 }

pethCompliance MODULE-COMPLIANCE
STATUS current
DESCRIPTION
    "Describes the requirements for conformance to the
    Power Ethernet MIB."
MODULE -- this module
MANDATORY-GROUPS { pethPsePortGroup,
                   pethPsePortNotificationGroup,
                   pethNotificationControlGroup
                   }
GROUP pethMainPseGroup
DESCRIPTION
    "The pethMainPseGroup is mandatory for PSE systems
    that implement a main power supply."
GROUP pethMainPowerNotificationGroup
DESCRIPTION
    "The pethMainPowerNotificationGroup is mandatory for

```

```
        PSE systems that implement a main power supply."  
 ::= { pethCompliances 1 }
```

```
pethPsePortGroup OBJECT-GROUP  
  OBJECTS {  
    pethPsePortAdminEnable,  
    pethPsePortPowerPairsControlAbility,  
    pethPsePortPowerPairs,  
    pethPsePortDetectionStatus,  
    pethPsePortPowerPriority,  
    pethPsePortMPSAbsentCounter,  
    pethPsePortInvalidSignatureCounter,  
    pethPsePortPowerDeniedCounter,  
    pethPsePortOverLoadCounter,  
    pethPsePortShortCounter,  
    pethPsePortType,  
    pethPsePortPowerClassifications  
  }  
  STATUS current  
  DESCRIPTION  
    "PSE Port objects."  
 ::= { pethGroups 1 }
```

```
pethMainPseGroup OBJECT-GROUP  
  OBJECTS {  
    pethMainPsePower,  
    pethMainPseOperStatus,  
    pethMainPseConsumptionPower,  
    pethMainPseUsageThreshold  
  }  
  STATUS current  
  DESCRIPTION  
    "Main PSE Objects. "  
 ::= { pethGroups 2 }
```

```
pethNotificationControlGroup OBJECT-GROUP  
  OBJECTS {  
    pethNotificationControlEnable  
  }  
  STATUS current  
  DESCRIPTION  
    "Notification Control Objects. "  
 ::= { pethGroups 3 }
```

```
NOTIFICATIONS { pethPsePortOnOffNotification}
STATUS          current
DESCRIPTION     "Pse Port Notifications."
 ::= { pethGroups 4 }
```

```
pethMainPowerNotificationGroup NOTIFICATION-GROUP
  NOTIFICATIONS { pethMainPowerUsageOnNotification,
                  pethMainPowerUsageOffNotification}
STATUS          current
DESCRIPTION     "Main PSE Notifications."
 ::= { pethGroups 5 }
```

END

6. Acknowledgements

This document is the product of the Ethernet Interfaces and Hub MIB WG. The authors would like to recognize the special contributions of C.M. Heard and David Law.

7. Normative References

- [RFC2026] Bradner, S., "The Internet Standards Process - Revision 3", [BCP 9](#), [RFC 2026](#), October 1996.
- [RFC2578] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M. and S. Waldbusser, "Structure of Management Information Version 2 (SMIv2)", STD 58, [RFC 2578](#), April 1999.
- [RFC2579] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M. and S. Waldbusser, "Textual Conventions for SMIv2", STD 58, [RFC 2579](#), April 1999.
- [RFC2580] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M. and S. Waldbusser, "Conformance Statements for SMIv2", STD 58, [RFC 2580](#), April 1999.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate

Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.

[RFC2665] Flick, J., and J. Johnson, "Definitions of Managed Objects for the Ethernet-like Interface Types", [RFC 2665](#), August 1999.

NOTE - This RFC is under revision by the WG, and may be obsolete by the time of the publication. The RFC editor should replace it with

Ethernet MIB WG

Expires December 2003

[Page 17]

INTERNET DRAFT

Power Ethernet MIB

June 2003

the revised version, if available.

[RFC3411] Harrington, D., Presuhn, R. and B. Wijnen, "An Architecture for Describing Simple Network Management Protocol (SNMP) Management Frameworks", [RFC 3411](#), December 2002.

[IEEE-802.3af] IEEE 802.3 Working Group, "Data Terminal Equipment (DTE)Power via Media Dependent Interface (MDI)", publication date TBD

NOTE - This normative reference will be replaced with the IEEE 802.3af Standard as soon as the IEEE will ratify it (expected date - July 2003)

[8.](#) Informative References

[RFC3410] Case, J., Mundy, R., Partain, D. and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework", [RFC 3410](#), December 2002

9. Intellectual Property

The IETF takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on the IETF's procedures with respect to rights in standards-track and standards-related documentation can be found in [BCP-11](#). Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to

obtain a general license or permission for the use of such proprietary rights by implementors or users of this specification can be obtained from the IETF Secretariat.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights which may cover technology that may be required to practice this standard. Please address the information to the IETF Executive Director.

10. Security Considerations

There are a number of management objects defined in this MIB module with a MAX-ACCESS clause of read-write. Such objects may be

Ethernet MIB WG

Expires December 2003

[Page 18]

INTERNET DRAFT

Power Ethernet MIB

June 2003

considered sensitive or vulnerable in some network environments. The support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations.

Setting the following object to incorrect values can result in improper operation of the PSE, including the possibility that the PD does not receive power from the PSE port:

```
pethPsePortAdminEnable
pethPsePortPowerPairs
pethPsePortPowerPriority
pethPsePortType
```

Setting the following objects to incorrect values can result in an excessive number of traps being sent to network management stations:

```
pethMainPseUsageThreshold
pethNotificationControlEnable
```

Some of the readable objects in this MIB module (i.e., objects with a MAX-ACCESS other than not-accessible) may be considered sensitive or vulnerable in some network environments. These are:

```
pethPsePortPowerPairsControlAbility
pethPsePortPowerPriority
pethPsePortPowerClassifications
```

It is thus important to control even GET and/or NOTIFY access to these objects and possibly to even encrypt their values when sending them over the network via SNMP.

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure (for example by using IPSec), even then, there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB module.

It is RECOMMENDED that implementers consider the security features as provided by the SNMPv3 framework (see [\[RFC3410\], section 8](#)), including full support for the SNMPv3 cryptographic mechanisms (for authentication and privacy).

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate

rights to indeed GET or SET (change/create/delete) them.

11. Authors Addresses

Avi Berger
PowerDsine Inc.
1, Hanagar St., P.O. Box 7220
Hod Hasharon 45421,
Israel
Tel: +972-9-7755100 Ext 307
Fax: +972-9-7755120
E-mail: avib@PowerDsine.com

Dan Romascanu
Avaya
Atidim Technology Park, Bldg. #3
Tel Aviv, 61131
Israel

Tel: +972-3-645-8414
Email: dromasca@avaya.com

A. Full Copyright Statement

Copyright (c) The Internet Society (2003). All Rights Reserved

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION

Ethernet MIB WG

Expires December 2003

[Page 20]

INTERNET DRAFT

Power Ethernet MIB

June 2003

HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

