

INTERNET-DRAFT
[draft-ietf-idr-bgp-analysis-07.txt](#)
Category
Expires: June 2005

D. Meyer
K. Patel
Informational
December 2004

BGP-4 Protocol Analysis
<[draft-ietf-idr-bgp-analysis-07.txt](#)>

Status of this Memo

Status of this Memo

This document is an Internet-Draft and is subject to all provisions of [section 3 of RFC 3667](#). By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she become aware will be disclosed, in accordance with [RFC 3668](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/lid-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This document is a product of the IDR Working Group WG. Comments should be addressed to the authors, or the mailing list at idr@ietf.org.

Copyright Notice

Copyright (C) The Internet Society (2004). All Rights Reserved.

Abstract

The purpose of this report is to document how the requirements for advancing a routing protocol from Draft Standard to full Standard have been satisfied by Border Gateway Protocol version 4 (BGP-4).

This report satisfies the requirement for "the second report", as described in [Section 6.0 of \[RFC1264\]](#). In order to fulfill the requirement, this report augments [\[RFC1774\]](#) and summarizes the key features of BGP-4 protocol, and analyzes the protocol with respect to scaling and performance.

INTERNET-DRAFT

Expires: June 2005

December 2004

Table of Contents

1.	Introduction	4
2.	Key Features and algorithms of the BGP protocol.	4
2.1.	Key Features.	4
2.2.	BGP Algorithms.	5
2.3.	BGP Finite State Machine (FSM).	6
3.	BGP Capabilities	7
4.	BGP Persistent Peer Oscillations	7
5.	Implementation Guidelines.	7
6.	BGP Performance characteristics and Scalability.	8
6.1.	Link bandwidth and CPU utilization.	8
6.1.1.	CPU utilization.	9
6.1.2.	Memory requirements.	10
7.	BGP Policy Expressiveness and its Implications	11
7.1.	Existence of Unique Stable Routings	12
7.2.	Existence of Stable Routings.	13
8.	Applicability.	14
9.	Acknowledgments.	15
10.	Security Considerations	16
11.	IANA Considerations	17
12.	References.	17
12.1.	Normative References	17
12.2.	Informative References	18
13.	Author's Addresses.	19

INTERNET-DRAFT

Expires: June 2005

December 2004

[1.](#) Introduction

BGP-4 is an inter-autonomous system routing protocol designed for TCP/IP internets. Version 1 of the BGP-4 protocol was published in [\[RFC1105\]](#). Since then BGP versions 2, 3, and 4 have been developed.

Version 2 was documented in [[RFC1163](#)]. Version 3 is documented in [[RFC1267](#)]. Version 4 is documented in the [[BGP4](#)] (version 4 of BGP will hereafter be referred to as BGP). The changes between versions are explained in [Appendix A](#) of [[BGP4](#)]. Possible applications of BGP in the Internet are documented in [[RFC1772](#)].

BGP introduced support for Classless Inter-Domain Routing [[RFC1519](#)]. Since earlier versions of BGP lacked the support for CIDR, they are considered obsolete and unusable in today's Internet.

[2.](#) Key Features and algorithms of the BGP protocol

This section summarizes the key features and algorithms of the BGP protocol. BGP is an inter-autonomous system routing protocol; it is designed to be used between multiple autonomous systems. BGP assumes that routing within an autonomous system is done by an intra-autonomous system routing protocol. BGP also assumes that data packets are routed from source towards destination independent of the source. BGP does not make any assumptions about intra-autonomous system routing protocols deployed within the various autonomous systems. Specifically, BGP does not require all autonomous systems to run the same intra-autonomous system routing protocol (i.e., interior gateway protocol or IGP).

Finally, note that BGP is a real inter-autonomous system routing protocol, and as such it imposes no constraints on the underlying interconnect topology of the autonomous systems. The information exchanged via BGP is sufficient to construct a graph of autonomous systems connectivity from which routing loops may be pruned and many routing policy decisions at the autonomous system level may be enforced.

[2.1.](#) Key Features

The key features of the protocol are the notion of path attributes and aggregation of Network Layer Reachability Information (NLRI).

Path attributes provide BGP with flexibility and extensibility. Path attributes are partitioned into well-known and optional. The provision for optional attributes allows experimentation that may involve a group of BGP routers without affecting the rest of the Internet. New optional attributes can be added to the protocol in much the same way that new options are added to, say, the Telnet protocol [[RFC854](#)].

One of the most important path attributes is the Autonomous System Path, or AS_PATH. As the reachability information traverses the Internet, this (AS_PATH) information is augmented by the list of autonomous systems that have been traversed thus far, forming the AS_PATH. The AS_PATH allows straightforward suppression of the looping of routing information. In addition, the AS_PATH serves as a powerful and versatile mechanism for policy-based routing.

BGP enhances the AS_PATH attribute to include sets of autonomous systems as well as lists via the AS_SET attribute. This extended format allows generated aggregate routes to carry path information from the more specific routes used to generate the aggregate. It should be noted however, that as of this writing, AS_SETs are rarely used in the Internet [[ROUTEVIEWS](#)].

[2.2.](#) BGP Algorithms

BGP uses an algorithm that is neither a pure distance vector algorithm or a pure link state algorithm. It is instead a modified distance vector algorithm referred to as a "Path Vector" algorithm that uses path information to avoid traditional distance vector problems. Each route within BGP pairs destination with path information to that destination. Path information (also known as AS_PATH information) is stored within the AS_PATH attribute in BGP. The path information assists BGP in detecting AS loops thereby allowing BGP speakers select loop free routes.

BGP uses an incremental update strategy in order to conserve bandwidth and processing power. That is, after initial exchange of complete routing information, a pair of BGP routers exchanges only changes to that information. Such an incremental update design requires reliable transport between a pair of BGP routers to function correctly. BGP solves this problem by using TCP for reliable transport.

In addition to incremental updates, BGP has added the concept of route aggregation so that information about groups of

that use hierarchical address assignment (e.g., CIDR) may be aggregated and sent as a single Network Layer Reachability (NLRI).

Finally, note that BGP is a self-contained protocol. That is, BGP specifies how routing information is exchanged both between BGP speakers in different autonomous systems, and between BGP speakers within a single autonomous system.

[2.3.](#) BGP Finite State Machine (FSM)

The BGP FSM is a set of rules that are applied to a BGP speaker's set of configured peers for the BGP operation. A BGP implementation requires that a BGP speaker must connect to and listen on TCP port 179 for accepting any new BGP connections from its peers. The BGP Finite State Machine, or FSM, must be initiated and maintained for each new incoming and outgoing peer connections. However, in steady state operation, there will be only one BGP FSM per connection per peer.

There may be a short period during which a BGP peer may have separate incoming and outgoing connections resulting in the creation of two different BGP FSMs relating to a peer (instead of one). This can be resolved by following the BGP connection collision rules defined in the [[BGP4](#)] specification.

The BGP FSM has the following states associated with each of its peers:

- | | |
|-----------|--|
| IDLE: | State when BGP peer refuses any incoming connections. |
| CONNECT: | State in which BGP peer is waiting for its TCP connection to be completed. |
| ACTIVE: | State in which BGP peer is trying to acquire a peer by listening and accepting TCP connection. |
| OPENSENT: | BGP peer is waiting for OPEN message from its |

peer.

OPENCONFIRM: BGP peer is waiting for KEEPALIVE or NOTIFICATION message from its peer.

ESTABLISHED: BGP peer connection is established and exchanges UPDATE, NOTIFICATION, and KEEPALIVE messages with

its peer.

There are a number of BGP events that operate on above mentioned states of the BGP FSM for BGP peers. Support of these BGP events are either mandatory or optional. They are triggered by the protocol logic as part of the BGP or using an operator intervention via a configuration interface to the BGP protocol.

These BGP events are of following types: Optional events linked to Optional Session attributes, Administrative Events, Timer Events, TCP Connection based Events, and BGP Message-based Events. Both the FSM and the BGP events are explained in detail in [[BGP4](#)].

[3](#). BGP Capabilities

The BGP Capability mechanism [[RFC2842](#)] provides an easy and flexible way to introduce new features within the protocol. In particular, the BGP capability mechanism allows a BGP speaker to advertise to its peers during startup various optional features supported by the speaker (and receive similar information from the peers). This allows the base BGP protocol to contain only essential functionality, while at the same time providing a flexible mechanism for signaling protocol extensions.

[4](#). BGP Persistent Peer Oscillations

Whenever a BGP speaker detects an error in any peer connection, it shuts down the peer and changes its FSM state to IDLE. BGP speaker requires a Start event to re-initiate its idle peer connection. If the error remains persistent and BGP speaker generates Start event automatically then it may result in persistent peer flapping. However, although peer oscillation is found to be wide-spread in BGP implementations, methods for preventing persistent peer oscillations are outside the scope of base BGP protocol specification.

[5.](#) Implementation Guidelines

A robust BGP implementation is work conserving. This means that if the number of prefixes is bounded, arbitrarily high levels of route

change can be tolerated with bounded impact on route convergence for occasional changes in generally stable routes.

A robust implementation of BGP should have the following characteristics:

1. It is able to operate in almost arbitrarily high levels of route flap without losing peerings (failing to send keepalives) or losing other protocol adjacencies as a result of BGP load.
2. Instability of a subset of routes should not affect the route advertisements or forwarding associated with the set of stable routes.
3. High levels of instability and peers of different CPU speed or load resulting in faster or slower processing of routes should not cause instability and should have a bounded impact on the convergence time for generally stable routes.

Numerous robust BGP implementations exist. Producing a robust implementation is not a trivial matter but clearly achievable.

[6.](#) BGP Performance characteristics and Scalability

In this section, we provide "order of magnitude" answers to the questions of how much link bandwidth, router memory and router CPU cycles the BGP protocol will consume under normal conditions. In particular, we will address the scalability of BGP and its limitations.

[6.1.](#) Link bandwidth and CPU utilization

Immediately after the initial BGP connection setup, BGP peers exchange complete set of routing information. If we denote the total number of routes in the Internet by N , the total path attributes (for all N routes) received from a peer as A , and assume that the networks are uniformly distributed among the autonomous systems, then the worst case amount of bandwidth consumed during the initial exchange between a pair of BGP speakers (P) is

$$BW = O((N + A) * P)$$

BGP-4 was created specifically to reduce the size of the set of NLRI entries which have to be carried and exchanged by border routers. The aggregation scheme, defined in [[RFC1519](#)], describes the provider-based aggregation scheme in use in today's Internet.

Due to the advantages of advertising a few large aggregate blocks instead of many smaller class-based individual networks, it is difficult to estimate the actual reduction in bandwidth and processing that BGP-4 has provided over BGP-3. If we simply enumerate all aggregate blocks into their individual class-based networks, we would not take into account "dead" space that has been reserved for future expansion. The best metric for determining the success of BGP's aggregation is to sample the number NLRI entries in the globally connected Internet today and compare it to projected growth rates before BGP was deployed.

At the time of this writing, the full set of exterior routes carried by BGP is approximately 134,000 network entries [[ROUTEVIEWS](#)].

[6.1.1.](#) CPU utilization

An important and fundamental feature of BGP is that BGP's CPU utilization depends only on the stability of its network which relates to BGP in terms of BGP UPDATE message announcements. If the BGP network is stable: all the BGP routers within its network are in the steady state; then the only link bandwidth and router CPU cycles consumed by BGP are due to the exchange of the BGP KEEPALIVE messages. The KEEPALIVE messages are exchanged only between peers. The suggested frequency of the exchange is 30 seconds. The KEEPALIVE messages are quite short (19 octets), and require virtually no processing. As a result, the bandwidth consumed by the KEEPALIVE messages is about 5 bits/sec. Operational experience confirms that the overhead (in terms of bandwidth and CPU) associated with the KEEPALIVE messages should be viewed as negligible.

During periods of network instability, BGP routers within the network are generating routing updates that are exchanged using the BGP UPDATE messages. The greatest overhead per UPDATE message occurs when each UPDATE message contains only a single network. It should be pointed out that in practice routing changes exhibit strong locality with respect to the route attributes. That is, routes that change are likely to have common route attributes. In this case, multiple networks can be grouped into a single UPDATE message, thus significantly reducing the amount of bandwidth required (see also

[Appendix F.1](#) of [[BGP4](#)]).

[6.1.2.](#) Memory requirements

To quantify the worst case memory requirements for BGP, we denote the total number of networks in the Internet by N , the mean AS distance

of the Internet by M (distance at the level of an autonomous system, expressed in terms of the number of autonomous systems), the total number of unique AS paths as A. Then the worst case memory requirements (MR) can be expressed as

$$MR = O(N + (M * A))$$

Since a mean AS distance M is a slow moving function of the interconnectivity ("meshiness") of the Internet, for all practical purposes the worst case router memory requirements are on the order of the total number of networks in the Internet times the number of peers the local system is peering with. We expect that the total number of networks in the Internet will grow much faster than the average number of peers per router. As a result, BGP's memory scaling properties are linearly related to the total number of networks in the Internet.

The following table illustrates typical memory requirements of a router running BGP. We denote average number of routes advertised by each peer as N, the total number of unique AS paths as A, the mean AS distance of the Internet as M (distance at the level of an autonomous system, expressed in terms of the number of autonomous systems), number of octets required to store a network as R, and number of bytes required to store one AS in an AS path as P. It is assumed that each network is encoded as four bytes, each AS is encoded as two bytes, and each networks is reachable via some fraction of all of the peers (# BGP peers/per net). For purposes of the estimates here, we will calculate $MR = ((N * R) + (M * A) * P) * S$.

# Networks (N)	Mean AS Distance (M)	# AS's (A)	# BGP peers/per net (P)	Memory Req (MR)
100,000	20	3,000	20	10,400,000
100,000	20	15,000	20	20,000,000
120,000	10	15,000	100	78,000,000

In analyzing BGP's memory requirements, we focus on the size of the BGP RIB table (ignoring implementation details). In particular, we derive upper bounds for the size of the BGP RIB table. For example, at the time of this writing, the BGP RIB tables of a typical backbone router carry on the order of 120,000 entries. Given this number, one might ask whether it would be possible to have a functional router with a table that will have 1,000,000 entries. Clearly the answer to this question is more related to how BGP is implemented. A robust BGP implementation with a reasonable CPU and memory should not have issues scaling to such limits.

7. BGP Policy Expressiveness and its Implications

BGP is unique among deployed IP routing protocols in that routing is determined using semantically rich routing policies. Although routing policies are usually the first thing that comes to a network operator's mind concerning BGP, it is important to note that the languages and techniques for specifying BGP routing policies are not actually a part of the protocol specification ([[RFC2622](#)] for an example of such a policy language). In addition, the BGP specification contains few restrictions, either explicitly or implicitly, on routing policy languages. These languages have typically been developed by vendors and have evolved through interactions with network engineers in an environment lacking vendor-independent standards.


The complexity of typical BGP configurations, at least in provider networks, has been steadily increasing. Router vendors typically provide hundreds of special commands for use in the configuration of BGP, and this command set is continually expanding. For example, BGP communities [[RFC1997](#)] allow policy writers to selectively attach tags to routes and use these to signal policy information to other BGP-speaking routers. Many providers allow customers, and sometimes peers, to send communities that determine the scope and preference of their routes. These developments have increasingly given the task of writing BGP configurations aspects associated with open-ended programming. This has allowed network operators to encode complex policies in order to address many unforeseen situations, and has opened the door for a great deal of creativity and experimentation in routing policies. This policy flexibility is one of the main reasons why BGP is so well suited to the commercial environment of the current Internet.

INTERNET-DRAFT

Expires: June 2005

December 2004

That is, the AS3-AS4 link is intended to be used only when the AS2-AS4 link is down (for outbound traffic, AS4 simply gives routes from AS2 a higher local preference). This is a common scenario in today's Internet. But note that this configuration has another stable solution:



In this case, AS3 does not translate the "depref my route" community received from AS4 into a "depref my route" community for AS1, and so if AS1 hears the route to AS4 that transits AS3 it will prefer that route (since AS3 is a customer). This state could be reached, for example, by starting in the "correct" backup routing shown first, bringing down the AS2-AS4 BGP session, and then bringing it back up. In general, BGP has no way to prefer the "intended" solution over the anomalous one, and which is picked will depend on the unpredictable order of BGP messages.

While this example is relatively simple, many operators may fail to recognize that the true source of the problem is that the BGP policies of ASes can interact in unexpected ways, and that these interactions can result in multiple stable routings. One can imagine that the interactions could be much more complex in the real Internet. We suspect that such anomalies will only become more common as BGP continues to evolve with richer policy expressiveness. For example, extended communities provide an even more flexible means of signaling information within and between autonomous systems than is possible with [RFC1997](#) communities. At the same time, applications of communities by network operators are evolving to address complex issues of inter-domain traffic engineering.

[7.2.](#) Existence of Stable Routings

One can also construct a set of policies for which BGP can not guarantee that a stable routing exists (or worse, that a stable routing will ever be found). For example, [[RFC3345](#)] documents several scenarios that lead to route oscillations associated with the use of the Multi-Exit Discriminator or MED, attribute. Route

oscillation will happen in BGP when a set of policies has no solution. That is, when there is no stable routing that satisfies the constraints imposed by policy, then BGP has no choice but to keep trying. In addition, BGP configurations can have a stable routing, yet the protocol may not be able to find it; BGP can "get trapped" down a blind alley that has no solution.

Protocol divergence is not, however, a problem associated solely with use of the MED attribute. This potential exists in BGP even without the use of the MED attribute. Hence, like the unintended nondeterminism described in the previous section, this type of protocol divergence is an unintended consequence of the unconstrained nature of BGP policy languages.

[8.](#) Applicability

In this section we identify the environments for which BGP well suited, and for which environments it is not suitable. This question is partially answered in [Section 2](#) of BGP [[BGP4](#)], which states:

"To characterize the set of policy decisions that can be enforced using BGP, one must focus on the rule that an AS advertises to its neighbor ASs only those routes that it itself uses. This rule reflects the "hop-by-hop" routing paradigm generally used throughout the current Internet. Note that some policies cannot be supported by the "hop-by-hop" routing paradigm and thus require techniques such as source routing to enforce. For example, BGP does

not enable one AS to send traffic to a neighbor AS intending that the traffic take a different route from that taken by traffic originating in the neighbor AS. On the other hand, BGP can support any policy conforming to the "hop-by-hop" routing paradigm. Since the current Internet uses only the "hop-by-hop" routing paradigm and since BGP can support any policy that conforms to that paradigm, BGP is highly applicable as an inter-AS routing protocol for the current Internet."

One of the important points here is that the BGP protocol contains only the functionality that is essential, while at the same time providing a flexible mechanism within the protocol that allows us to extend its functionality. For example, BGP capabilities provide an easy and flexible way to introduce new features within the protocol. Finally, since BGP was designed with flexibility and extensibility in mind, new and/or evolving requirements can be addressed via existing mechanisms.

To summarize, BGP is well suited as an inter-autonomous system routing protocol for any internet that is based on IP [[RFC791](#)] as the internet protocol and "hop-by-hop" routing paradigm.

[9](#). Acknowledgments

We would like to thank Paul Traina for authoring previous versions of this document. Elwyn Davies, Tim Griffin, Randy Presuhn, Curtis Villamizar and Atanu Ghosh also provided many insightful comments on earlier versions of this document.

[10](#). Security Considerations

BGP provides flexible mechanisms with varying levels of complexity for security purposes. BGP sessions are authenticated using BGP session addresses and the assigned AS number. Since BGP sessions use TCP (and IP) for reliable transport, BGP sessions are further authenticated and secured by any authentication and security mechanisms used by TCP and IP.

BGP uses TCP MD5 option for validating data and protecting against spoofing of TCP segments exchanged between its sessions. The usage of TCP MD5 option for BGP is described at length in [[RFC 2385](#)]. The TCP MD5 Key management is discussed in [[RFC 3562](#)]. BGP data encryption is provided using IPsec mechanism which encrypts the IP

payload data (including TCP and BGP data). The IPsec mechanism can be used in both, the transport mode as well as the tunnel mode. The IPsec mechanism is described in [[RFC 2406](#)]. Both, the TCP MD5 option and the IPsec mechanism are not widely deployed security mechanisms for BGP in today's Internet and hence it is difficult to gauge their real performance impact when using with BGP. However, since both the mechanisms are TCP and IP based security mechanisms, the Link Bandwidth, CPU utilization and router memory consumed by BGP protocol using it would be same as any other TCP and IP based protocols.

BGP uses IP TTL value to protect its External BGP (EBGP) sessions from any TCP (or IP) based CPU intensive attacks. It is a simple mechanism which suggests the use of filtering BGP (TCP) segments using the IP TTL value carried within the IP header of BGP (TCP) segments exchanged between the EBGP sessions. The BGP TTL mechanism is described in [[RFC3682](#)]. Usage of [[RFC3682](#)] impacts performance in a similar way as using any ACL policies for BGP.

Such flexible TCP and IP based security mechanisms, allow BGP to prevent insertion/deletion/modification of BGP data, any snooping of the data, session stealing, etc. However, BGP is vulnerable to the same security attacks that are present in TCP. The [[BGP-VUL](#)] explains in depth about the BGP security vulnerability. At the time of this writing, several efforts are underway for creating and defining an appropriate security infrastructure within the BGP protocol to provide authentication and security for its routing information; some of which include [[SBGP](#)] and [[SOBGP](#)].

[11](#). IANA Considerations

This document presents an analysis of the BGP protocol and hence presents no new IANA considerations.

12. References

12.1. Normative References

- [BGP4] Rekhter, Y., T. Li., and S. Hares, Editors, "A Border Gateway Protocol 4 (BGP-4)", [draft-ietf-idr-bgp4-2.txt](#). Work in progress.
- [RFC1519] Fuller, V., Li, T., Yu, J., and K. Varadhan, "Classless Inter-Domain Routing (CIDR): an Address Assignment and Aggregation Strategy", [RFC 1519](#), September, 1993.
- [RFC791] "INTERNET PROTOCOL", DARPA INTERNET PROGRAM PROTOCOL SPECIFICATION, [RFC 791](#), September, 1981.
- [RFC1997] Chandra. R, and T. Li, "BGP Communities Attribute", [RFC 1997](#), August, 1996.
- [RFC2385] Heffernan, A., "Protection of BGP Sessions via the TCP MD5 Signature Option", [RFC 2385](#), August, 1998.
- [RFC2842] Chandra, R. and J. Scudder, "Capabilities Advertisement with BGP-4", [RFC 2842](#), May 2000.
- [RFC3345] McPherson, D., Gill, V., Walton, D., and A. Retana, "Border Gateway Protocol (BGP) Persistent Route Oscillation Condition", [RFC 3345](#), August, 2002.
- [RFC3562] Leech, M., "Key Management Considerations for the TCP MD5 Signature Option", [RFC 3562](#), July, 2003.

- [RFC3682] Gill, V., Heasley, J., and D. Meyer, "The

- Generalized TTL Security Mechanism (GTSM)", [RFC 3682](#), February, 2004.
- [SOBGP] White, R., "Architecture and Deployment Considerations for Secure Origin BGP (soBGP)", [draft-white-sobgp-architecture-00.txt](#). Work in Progress.
- [BGP_VULN] Murphy, S., "BGP Security Vulnerabilities Analysis", [draft-ietf-idr-bgp-vuln-01.txt](#). Work in progress
- [SBGP] Lynn, C., Mikkelson, J., and K. Seo, "Secure BGP S-BGP", Internet-Draft, Work in Progress.

12.2. Informative References

- [RFC854] Postel, J. and J. Reynolds, "TELNET PROTOCOL SPECIFICATION", [RFC 854](#), May, 1983.
- [RFC1105] Loughheed, K., and Y. Rekhter, "Border Gateway Protocol BGP", [RFC 1105](#), June 1989.
- [RFC1163] Loughheed, K., and Rekhter, Y, "Border Gateway Protocol BGP", [RFC 1105](#), June 1990.
- [RFC1264] Hinden, R., "Internet Routing Protocol Standardization Criteria", [RFC 1264](#), October 1991.
- [RFC1267] Loughheed, K., and Rekhter, Y, "Border Gateway Protocol 3 (BGP-3)", [RFC 1105](#), October 1991.
- [RFC1771] Rekhter, Y., and T. Li, "A Border Gateway Protocol 4 (BGP-4)", [RFC 1771](#), March 1995.
- [RFC1772] Rekhter, Y., and P. Gross, Editors, "Application of the Border Gateway Protocol in the Internet", [RFC 1772](#), March 1995.
- [RFC1774] Traina, P., "BGP-4 protocol analysis", [RFC 1774](#), March, 1995.
- [RFC2622] Alaettinoglu, C., et. al., "Routing Policy Specification Language (RPSL)" [RFC 2622](#), May, 1998.

[RFC2406] Kent, S., Atkinson, R., "IP Encapsulating Security Payload (ESP)", [RFC 2406](#), November, 1998.

[ROUTEVIEWS] Meyer, D., "The Route Views Project",
<http://www.routeviews.org>

13. Author's Addresses

David Meyer
Email: dmm@1-4-5.net

Keyur Patel
Cisco Systems
Email: keyupate@cisco.com

Intellectual Property Statement

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

Disclaimer of Validity

This document and the information contained herein are provided on an

Meyer and Patel

[Section 13](#). [Page 19]

INTERNET-DRAFT

Expires: June 2005

December 2004

"AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Copyright Statement

Copyright (C) The Internet Society (2004). This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

Acknowledgment

Funding for the RFC Editor function is currently provided by the Internet Society.

