

Network Working Group
Internet-Draft
Expires: March 6, 2006

A. Patel
K. Leung
Cisco Systems
M. Khalil
H. Akhtar
Nortel Networks
K. Chowdhury
Starent Networks
September 2, 2005

Mobile Node Identifier Option for MIPv6
draft-ietf-mip6-mn-ident-option-03

Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/lid-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on March 6, 2006.

Copyright Notice

Copyright (C) The Internet Society (2005).

Abstract

Mobile IPv6 defines a new Mobility header which is used by mobile nodes, correspondent nodes, and home agents in all messaging related to the creation and management of bindings. Mobile IPv6 nodes need

Internet-Draft Mobile Node Identifier Option for MIPv6 September 2005

the capability to identify themselves using an identity other than the default home IP address. Some examples of identifiers include NAI, FQDN, IMSI, MSISDN, etc. This document defines a new mobility option that can be used by Mobile IPv6 entities to identify themselves in messages containing a mobility header.

Table of Contents

1.	Introduction	3
2.	Terminology	4
3.	Mobile Node Identifier option	5
3.1.	MN-NAI mobility option	6
3.2.	Processing Considerations	6
4.	Security Considerations	7
4.1.	General Considerations	7
4.2.	MN NAI consideration	7
5.	IANA Considerations	8
6.	IPR Disclosure Acknowledgement	9
7.	Acknowledgements	10
8.	Normative References	10
	Authors' Addresses	11
	Intellectual Property and Copyright Statements	13

Internet-Draft Mobile Node Identifier Option for MIPv6 September 2005

1. Introduction

The base specification of Mobile IPv6 [[RFC3775](#)] identifies mobility entities using an IPv6 address. It is essential to have a mechanism wherein mobility entities can be identified using other identifiers (for example, a network access identifier (NAI) [[RFC 2486bis](#)], International Mobile Station Identifier (IMSI), an application/deployment specific opaque identifier etc).

The capability to identify a mobility entity via identifiers other than the IPv6 address can be leveraged for performing various functions, eg.

- o authentication and authorization using an existing AAA (Authentication, Authorization and Accounting) infrastructure or via an HLR/AuC (Home Location Register/Authentication Center),
- o dynamic allocation of a mobility anchor point,
- o dynamic allocation of a home address etc.

This document defines an option with subtype number which denotes a specific type of identifier. One instance of subtype, the NAI is defined in [Section 3.1](#). It is anticipated that other identifiers will be defined for use in the mobility header in the future.

This option SHOULD be used when IKE/IPsec is not used for protecting binding update or binding acknowledgements as specified in [[RFC3775](#)]. It is typically used with authentication option [[auth_id](#)]. But this option may be used independently. For example, the identifier can provide accounting and billing services.

Internet-Draft Mobile Node Identifier Option for MIPv6 September 2005

2. Terminology


The keywords "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#).

Internet-Draft Mobile Node Identifier Option for MIPv6 September 2005

3. Mobile Node Identifier option

The Mobile node identifier option is a new optional data field that is carried in the Mobile IPv6 defined messages which includes the mobility header. Various forms of identifiers can be used to identify a MN. Some examples include a Network Access Identifier (NAI) [[RFC 2486bis](#)], an opaque identifier applicable to a particular application, etc. The subtype field in the option defines the specific type of identifier.

This option can be used in mobility messages containing a mobility header. The subtype field in the option is used to interpret the specific type of identifier.



Option Type:

MN-ID-OPTION-TYPE to be defined by IANA. An 8-bit identifier of the type mobility option.

Option Length:

8-bit unsigned integer, representing the length in octets of the Subtype and Identifier fields.

Subtype:

Subtype field defines the specific type of identifier included in the identifier field.

Identifier:

A variable length identifier of type as specified by the subtype field of this option.

This option does not have any alignment requirements.

[3.1.](#) MN-NAI mobility option

The MN-NAI mobility option uses the general format of the Mobile Node Identifier option as defined in [Section 3](#). This option uses the

subtype value of 1. The MN-NAI mobility option is used to identify the mobile node.

The MN-NAI mobility option uses an identifier of the form user@realm [[RFC_2486bis](#)]. This option MUST be implemented by the entities implementing this specification.

3.2. Processing Considerations

The location of the MN identifier option is as follows: When present, this option MUST appear before any authentication related option in a message containing a mobility header.

4. Security Considerations

4.1. General Considerations

Mobile IPv6 already contains one mechanism for identifying mobile nodes, the Home Address Option [[RFC3775](#)]. As a result, the vulnerabilities of the new option defined in this document are similar to those that already exist for Mobile IPv6. In particular,

the use of a permanent, stable identifier may compromise the privacy of the user, making it possible to track a particular device or user as it moves through different locations.

[4.2.](#) MN NAI consideration

Since a Mobile Node Identifier option [Section 3](#) reveals the home affiliation of a user, it may assist an attacker in determining the identity of the user, help the attacker in targeting specific victims, or assist in further probing of the username space.

These vulnerabilities can be addressed through various mechanisms, such as those discussed below:

- o Encrypting traffic at link layer such that other users on the same link do not see the identifiers. This mechanism does not help against attackers on the rest of the path between the mobile node and its home agent.

- o Encrypting the whole packet, such as when using IPsec to protect the communications with the home agent [[RFC3776](#)].

- o Using an authentication mechanism that enables the use of privacy NAIs [[RFC 2486bis](#)] or temporary, changing "pseudonyms" as identifiers.

In any case, it should be noted that as the identifier option is only needed on the first registration at the home agent and subsequent registrations can use the home address, the window of privacy vulnerability in this document is reduced as compared to the [[RFC3775](#)]. In addition, this document is a part of a solution to allow dynamic home addresses to be used. This is an improvement to privacy as well, and affects both communications with the home agent and the correspondent nodes, both of which have to be told the home address.

[5.](#) IANA Considerations

IANA services are required for this document. The values for new mobility options must be assigned from the Mobile IPv6 [[RFC3775](#)] numbering space.

The values for Mobility Option types MN-ID-OPTION-TYPE as defined in [Section 3](#) need to be assigned. The suggested value is 7 for the MN-ID-OPTION-TYPE.

IANA should record a value for this new mobility option.

In addition, IANA needs to create a new namespace for the subtype field of the Mobile Node Identifier Option. The currently allocated values are as follows:

NAI (defined in this document) [1]

New values for this namespace can be allocated using Standards Action [[RFC2434](#)].

6. IPR Disclosure Acknowledgement

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Internet-Draft Mobile Node Identifier Option for MIPv6 September 2005

[7.](#) Acknowledgements

The authors would like to thank Basavaraj Patil for his review and suggestions on this draft. Thanks to Jari Arkko for review and suggestions regarding security considerations and various other aspects of the document.

[8.](#) Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2434] Narten, T. and H. Alvestrand, "Guidelines for Writing an IANA Considerations Section in RFCs", [BCP 26](#), [RFC 2434](#), October 1998.
- [RFC3775] Johnson, D., Perkins, C., and J. Arkko, "Mobility Support in IPv6", [RFC 3775](#), June 2004.
- [RFC3776] Arkko, J., Devarapalli, V., and F. Dupont, "Using IPsec to Protect Mobile IPv6 Signaling Between Mobile Nodes and Home Agents", [RFC 3776](#), June 2004.
- [RFC_2486bis] Aboba, et. al., B., "The Network Access Identifier", [draft-ietf-radext-rfc2486bis-03.txt](#) (work in progress), November 2004.
- [auth_id] Patel et. al., A., "Authentication Protocol for Mobile IPv6", [draft-ietf-mip6-mn-ident-option-04.txt](#) (work in progress), February 2005.

Internet-Draft Mobile Node Identifier Option for MIPv6 September 2005

Authors' Addresses

Alpesh Patel
Cisco Systems
170 W. Tasman Drive
San Jose, CA 95134
US

Phone: +1 408-853-9580
Email: alpesh@cisco.com

Kent Leung
Cisco Systems
170 W. Tasman Drive
San Jose, CA 95134
US

Phone: +1 408-526-5030
Email: kleung@cisco.com

Mohamed Khalil
Nortel Networks
2221 Lakeside Blvd.
Richardson, TX 75082
US

Phone: +1 972-685-0574
Email: mkhalil@nortel.com

Haseeb Akhtar
Nortel Networks
2221 Lakeside Blvd.
Richardson, TX 75082
US

Phone: +1 972-684-4732
Email: haseebak@nortel.com

Patel, et al.

Expires March 6, 2006

[Page 11]

Internet-Draft Mobile Node Identifier Option for MIPv6 September 2005

Kuntal Chowdhury
Starent Networks
30 International Place
Tewksbury, MA 01876
US

Phone: +1 214 550 1416
Email: kchowdhury@starentnetworks.com

Internet-Draft Mobile Node Identifier Option for MIPv6 September 2005

Intellectual Property Statement

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

Disclaimer of Validity

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Copyright Statement

Copyright (C) The Internet Society (2005). This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

Acknowledgment

Funding for the RFC Editor function is currently provided by the Internet Society.