

Network Working Group
Internet-Draft
Obsoletes: RFC [2619](#) (if approved)
Expires: December 28, 2006

D. Nelson
Enterasys Networks
June 26, 2006

RADIUS Authentication Server MIB for IPv6
draft-ietf-radext-rfc2619bis-04.txt

Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/lid-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on December 28, 2006.

Copyright Notice

Copyright (C) The Internet Society (2006).

Abstract

This memo defines a set of extensions, which instrument RADIUS authentication server functions. These extensions represent a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. Using these extensions IP-based management stations can manage RADIUS authentication servers.

This memo obsoletes [RFC 2619](#) by deprecating the MIB table containing

Internet-Draft

RADIUS Auth Server MIB (IPv6)

June 2006

IPv4-only address formats and defining a new table to add support for version neutral IP address formats. The remaining MIB objects from [RFC 2619](#) are carried forward into this document. This memo also adds UNITS and Reference clauses to selected objects.

Table of Contents

1.	Terminology	3
2.	Introduction	3
3.	The Internet-Standard Management Framework	3
4.	Scope of Changes	3
5.	Structure of the MIB Module	4
6.	Deprecated Objects	5
7.	Definitions	5
8.	IANA Considerations	22
9.	Security Considerations	22
10.	References	23
10.1.	Normative References	23
10.2.	Informative References	23
Appendix A.	Acknowledgments	24
	Author's Address	25
	Intellectual Property and Copyright Statements	26

1. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

This document uses terminology from [RFC 2865](#) [[RFC2865](#)].

This document uses the word "malformed" with respect to RADIUS packets, particularly in the context of counters of "malformed packets". While [RFC 2865](#) does not provide an explicit definition of "malformed", malformed generally means that the implementation has determined the packet does not match the format defined in [RFC 2865](#). Some implementations may determine that packets are malformed when the Vendor Specific Attribute (VSA) format does not follow the [RFC 2865](#) recommendations for VSAs. Those implementations are used in deployments today, and thus set the de-facto definition of "malformed".

2. Introduction

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. The objects defined within this memo relate to the Remote Authentication Dial-In User Service (RADIUS) Authentication Server as defined in [RFC 2865](#) [[RFC2865](#)].

3. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to [section 7 of RFC 3410](#) [[RFC3410](#)].

Managed objects are accessed via a virtual information store, termed

the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIV2, which is described in STD 58, [RFC 2578](#) [[RFC2578](#)], STD 58, [RFC 2579](#) [[RFC2579](#)] and STD 58, [RFC 2580](#) [[RFC2580](#)].

4. Scope of Changes

This document obsoletes [RFC 2619](#) [[RFC2619](#)], RADIUS Authentication

Nelson

Expires December 28, 2006

[Page 3]

Internet-Draft

RADIUS Auth Server MIB (IPv6)

June 2006

Server MIB, by deprecating the radiusAuthClientTable table and adding a new table, radiusAuthClientExtTable, containing radiusAuthClientInetAddressType and radiusAuthClientInetAddress. The purpose of these added MIB objects is to support version neutral IP addressing formats. The existing table containing radiusAuthClientAddress is deprecated. The remaining MIB objects from [RFC 2619](#) are carried forward into this document. This memo also adds UNITS and REFERENCE clauses to selected objects.

[RFC 4001](#) [[RFC4001](#)], which defines the SMI Textual Conventions for version neutral IP addresses, contains the following recommendation.

'In particular, when revising a MIB module that contains IPv4 specific tables, it is suggested to define new tables using the textual conventions defined in this memo [[RFC4001](#)] that support all versions of IP. The status of the new tables SHOULD be "current", whereas the status of the old IP version specific tables SHOULD be changed to "deprecated". The other approach, of having multiple similar tables for different IP versions, is strongly discouraged.'

5. Structure of the MIB Module

The RADIUS authentication protocol, described in [RFC 2865](#) [[RFC2865](#)], distinguishes between the client function and the server function. In RADIUS authentication, clients send Access-Requests, and servers reply with Access-Accepts, Access-Rejects, and Access-Challenges. Typically NAS devices implement the client function, and thus would be expected to implement the RADIUS authentication client MIB, while

RADIUS authentication servers implement the server function, and thus would be expected to implement the RADIUS authentication server MIB.

However, it is possible for a RADIUS authentication entity to perform both client and server functions. For example, a RADIUS proxy may act as a server to one or more RADIUS authentication clients, while simultaneously acting as an authentication client to one or more authentication servers. In such situations, it is expected that RADIUS entities combining client and server functionality will support both the client and server MIBs. The server MIB is defined in this document, and the client MIB is defined in [[2618bis](#)].

RFC Editor: Replace the above I-D reference with the assigned RFC number at the time of publication and delete this note.

This MIB module contains fourteen scalars as well as a single table, the RADIUS Authentication Client Table, which contains one row for each RADIUS authentication client with which the server shares a secret. Each entry in the RADIUS Authentication Client Table

Nelson

Expires December 28, 2006

[Page 4]

Internet-Draft

RADIUS Auth Server MIB (IPv6)

June 2006

includes thirteen columns presenting a view of the activity of the RADIUS authentication server.

[6.](#) Deprecated Objects

The deprecated table in this MIB is carried forward from [RFC 2619](#) [[RFC2619](#)]. There are two conditions under which it MAY be desirable for managed entities to continue to support the deprecated table:

1. The managed entity only supports IPv4 address formats.
2. The managed entity supports both IPv4 and IPv6 address formats, and the deprecated table is supported for backwards compatibility with older management stations. This option SHOULD only be used when the IP addresses in the new table are in IPv4 format and can accurately be represented in both the new table and the deprecated table.

Managed entities SHOULD NOT instantiate row entries in the deprecated table, containing IPv4-only address objects, when the RADIUS client address represented in such a table row is not an IPv4 address.

Managed entities SHOULD NOT return inaccurate values of IP address or

SNMP object access errors for IPv4-only address objects in otherwise populated tables. When row entries exist in both the deprecated IPv4-only table and the new IP version neutral table that describe the same RADIUS client, the row indexes SHOULD be the same for the corresponding rows in each table, to facilitate correlation of these related rows by management applications.

7. Definitions

```
RADIUS-AUTH-SERVER-MIB DEFINITIONS ::= BEGIN
```

```
IMPORTS
```

```
    MODULE-IDENTITY, OBJECT-TYPE, OBJECT-IDENTITY,
    Counter32, Integer32,
    IPAddress, TimeTicks, mib-2          FROM SNMPv2-SMI
    SnmpAdminString                     FROM SNMP-FRAMEWORK-MIB
    InetAddressType, InetAddress       FROM INET-ADDRESS-MIB
    MODULE-COMPLIANCE, OBJECT-GROUP    FROM SNMPv2-CONF;
```

```
radiusAuthServMIB MODULE-IDENTITY
```

```
    LAST-UPDATED "200605100000Z" -- 10 May 2006
    ORGANIZATION "IETF RADIUS Extensions Working Group."
    CONTACT-INFO
        " Bernard Aboba
        Microsoft
```

Nelson

Expires December 28, 2006

[Page 5]

Internet-Draft

RADIUS Auth Server MIB (IPv6)

June 2006

```
    One Microsoft Way
    Redmond, WA 98052
    US
    Phone: +1 425 936 6605
    EMail: bernarda@microsoft.com"
```

```
DESCRIPTION
```

```
"The MIB module for entities implementing the server
side of the Remote Authentication Dial-In User
Service (RADIUS) authentication protocol. Copyright
(C) The Internet Society (2006). This version of this
MIB module is part of RFC xxxx; see the RFC itself for
full legal notices."
```

```
-- RFC Editor: replace xxxx with actual RFC number at the time of
-- publication, and remove this note.
```

REVISION "200605100000Z" -- 10 May 2006

DESCRIPTION

"Revised version as published in RFC xxxx. This version obsoletes that of [RFC 2619](#) by deprecating the MIB table containing IPv4-only address formats and defining a new table to add support for version neutral IP address formats. The remaining MIB objects from [RFC 2619](#) are carried forward into this version."

-- RFC Editor: replace xxxx with actual RFC number at the time of
-- publication, and remove this note.

REVISION "199906110000Z" -- 11 Jun 1999

DESCRIPTION "Initial version as published in [RFC 2619](#)."

::= { radiusAuthentication 1 }

radiusMIB OBJECT-IDENTITY

STATUS current

DESCRIPTION

"The OID assigned to RADIUS MIB work by the IANA."

::= { mib-2 67 }

radiusAuthentication OBJECT IDENTIFIER ::= {radiusMIB 1}

radiusAuthServMIBObjects OBJECT IDENTIFIER

::= { radiusAuthServMIB 1 }

radiusAuthServ OBJECT IDENTIFIER

::= { radiusAuthServMIBObjects 1 }

radiusAuthServIdent OBJECT-TYPE

Nelson

Expires December 28, 2006

[Page 6]

Internet-Draft

RADIUS Auth Server MIB (IPv6)

June 2006

SYNTAX SnmpAdminString

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The implementation identification string for the RADIUS authentication server software in use on the system, for example; `FNS-2.1`"

::= {radiusAuthServ 1}

radiusAuthServUpTime OBJECT-TYPE

SYNTAX TimeTicks

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"If the server has a persistent state (e.g., a process), this value will be the time elapsed (in hundredths of a second) since the server process was started. For software without persistent state, this value will be zero."

::= {radiusAuthServ 2}

radiusAuthServResetTime OBJECT-TYPE

SYNTAX TimeTicks

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"If the server has a persistent state (e.g., a process) and supports a `reset` operation (e.g., can be told to re-read configuration files), this value will be the time elapsed (in hundredths of a second) since the server was `reset.` For software that does not have persistence or does not support a `reset` operation, this value will be zero."

::= {radiusAuthServ 3}

radiusAuthServConfigReset OBJECT-TYPE

SYNTAX INTEGER { other(1),
reset(2),
initializing(3),
running(4)}

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"Status/action object to reinitialize any persistent server state. When set to reset(2), any persistent server state (such as a process) is reinitialized as if the server had just been started. This value will never be returned by a read operation. When read,

other(1) - server in some unknown state;
initializing(3) - server (re)initializing;
running(4) - server currently running."
 ::= {radiusAuthServ 4}

radiusAuthServTotalAccessRequests OBJECT-TYPE
SYNTAX Counter32
UNITS "packets"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The number of packets received on the
 authentication port."
REFERENCE "[RFC 2865 section 4.1](#)"
 ::= { radiusAuthServ 5}

radiusAuthServTotalInvalidRequests OBJECT-TYPE
SYNTAX Counter32
UNITS "packets"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The number of RADIUS Access-Request packets
 received from unknown addresses."
REFERENCE "[RFC 2865 section 4.1](#)"
 ::= { radiusAuthServ 6 }

radiusAuthServTotalDupAccessRequests OBJECT-TYPE
SYNTAX Counter32
UNITS "packets"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The number of duplicate RADIUS Access-Request
 packets received."
REFERENCE "[RFC 2865 section 4.1](#)"
 ::= { radiusAuthServ 7 }

radiusAuthServTotalAccessAccepts OBJECT-TYPE
SYNTAX Counter32
UNITS "packets"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The number of RADIUS Access-Accept packets sent."
REFERENCE "[RFC 2865 section 4.2](#)"
 ::= { radiusAuthServ 8 }

```
radiusAuthServTotalAccessRejects OBJECT-TYPE
    SYNTAX Counter32
    UNITS "packets"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of RADIUS Access-Reject packets sent."
    REFERENCE "RFC 2865 section 4.3"
    ::= { radiusAuthServ 9 }

radiusAuthServTotalAccessChallenges OBJECT-TYPE
    SYNTAX Counter32
    UNITS "packets"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of RADIUS Access-Challenge packets sent."
    REFERENCE "RFC 2865 section 4.4"
    ::= { radiusAuthServ 10 }

radiusAuthServTotalMalformedAccessRequests OBJECT-TYPE
    SYNTAX Counter32
    UNITS "packets"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of malformed RADIUS Access-Request
        packets received. Bad authenticators
        and unknown types are not included as
        malformed Access-Requests."
    REFERENCE "RFC 2865 section 4.1"
    ::= { radiusAuthServ 11 }

radiusAuthServTotalBadAuthenticators OBJECT-TYPE
    SYNTAX Counter32
    UNITS "packets"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of RADIUS Authentication-Request packets
        which contained invalid Message Authenticator
        attributes received."
    REFERENCE "RFC 2865 section 3"
    ::= { radiusAuthServ 12 }

radiusAuthServTotalPacketsDropped OBJECT-TYPE
```

SYNTAX Counter32
UNITS "packets"

Nelson

Expires December 28, 2006

[Page 9]

Internet-Draft

RADIUS Auth Server MIB (IPv6)

June 2006

MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The number of incoming packets
 silently discarded for some reason other
 than malformed, bad authenticators or
 unknown types."
REFERENCE "[RFC 2865 section 3](#)"
::= { radiusAuthServ 13 }

radiusAuthServTotalUnknownTypes OBJECT-TYPE
SYNTAX Counter32
UNITS "packets"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The number of RADIUS packets of unknown type which
 were received."
REFERENCE "[RFC 2865 section 4](#)"
::= { radiusAuthServ 14 }

radiusAuthClientTable OBJECT-TYPE
SYNTAX SEQUENCE OF RadiusAuthClientEntry
MAX-ACCESS not-accessible
STATUS deprecated
DESCRIPTION
 "The (conceptual) table listing the RADIUS
 authentication clients with which the server shares
 a secret."
::= { radiusAuthServ 15 }

radiusAuthClientEntry OBJECT-TYPE
SYNTAX RadiusAuthClientEntry
MAX-ACCESS not-accessible
STATUS deprecated
DESCRIPTION
 "An entry (conceptual row) representing a RADIUS

authentication client with which the server shares a secret."

```
INDEX      { radiusAuthClientIndex }  
 ::= { radiusAuthClientTable 1 }
```

```
RadiusAuthClientEntry ::= SEQUENCE {  
    radiusAuthClientIndex      Integer32,  
    radiusAuthClientAddress    IPAddress,  
    radiusAuthClientID        SnmpAdminString,
```

Nelson

Expires December 28, 2006

[Page 10]

Internet-Draft

RADIUS Auth Server MIB (IPv6)

June 2006

```
radiusAuthServAccessRequests      Counter32,  
radiusAuthServDupAccessRequests   Counter32,  
radiusAuthServAccessAccepts      Counter32,  
radiusAuthServAccessRejects      Counter32,  
radiusAuthServAccessChallenges   Counter32,  
radiusAuthServMalformedAccessRequests Counter32,  
radiusAuthServBadAuthenticators  Counter32,  
radiusAuthServPacketsDropped     Counter32,  
radiusAuthServUnknownTypes       Counter32  
}
```

radiusAuthClientIndex OBJECT-TYPE

SYNTAX Integer32 (1..2147483647)

MAX-ACCESS not-accessible

STATUS deprecated

DESCRIPTION

"A number uniquely identifying each RADIUS authentication client with which this server communicates."

::= { radiusAuthClientEntry 1 }

radiusAuthClientAddress OBJECT-TYPE

SYNTAX IPAddress

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The NAS-IP-Address of the RADIUS authentication client referred to in this table entry."

REFERENCE "[RFC 2865 section 2](#)"

::= { radiusAuthClientEntry 2 }

radiusAuthClientID OBJECT-TYPE

SYNTAX SnmpAdminString
MAX-ACCESS read-only
STATUS deprecated
DESCRIPTION
 "The NAS-Identifier of the RADIUS authentication client referred to in this table entry. This is not necessarily the same as sysName in MIB II."
REFERENCE "[RFC 2865 section 5.32](#)"
::= { radiusAuthClientEntry 3 }

-- Server Counters

--

-- Responses = AccessAccepts + AccessRejects + AccessChallenges

--

-- Requests - DupRequests - BadAuthenticators - MalformedRequests -

Nelson

Expires December 28, 2006

[Page 11]

Internet-Draft

RADIUS Auth Server MIB (IPv6)

June 2006

-- UnknownTypes - PacketsDropped - Responses = Pending

--

-- Requests - DupRequests - BadAuthenticators - MalformedRequests -

-- UnknownTypes - PacketsDropped = entries logged

radiusAuthServAccessRequests OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

 "The number of packets received on the authentication port from this client."

REFERENCE "[RFC 2865 section 4.1](#)"

::= { radiusAuthClientEntry 4 }

radiusAuthServDupAccessRequests OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

 "The number of duplicate RADIUS Access-Request packets received from this client."

REFERENCE "[RFC 2865 section 4.1](#)"

::= { radiusAuthClientEntry 5 }

radiusAuthServAccessAccepts OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of RADIUS Access-Accept packets sent to this client."

REFERENCE "[RFC 2865 section 4.2](#)"

::= { radiusAuthClientEntry 6 }

radiusAuthServAccessRejects OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of RADIUS Access-Reject packets sent to this client."

REFERENCE "[RFC 2865 section 4.3](#)"

::= { radiusAuthClientEntry 7 }

Nelson

Expires December 28, 2006

[Page 12]

Internet-Draft

RADIUS Auth Server MIB (IPv6)

June 2006

radiusAuthServAccessChallenges OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of RADIUS Access-Challenge packets sent to this client."

REFERENCE "[RFC 2865 section 4.4](#)"

::= { radiusAuthClientEntry 8 }

radiusAuthServMalformedAccessRequests OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of malformed RADIUS Access-Request

packets received from this client.

Bad authenticators and unknown types are not included as malformed Access-Requests."

REFERENCE "[RFC 2865 section 3](#)"

::= { radiusAuthClientEntry 9 }

radiusAuthServBadAuthenticators OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of RADIUS Authentication-Request packets which contained invalid Message Authenticator attributes received from this client."

REFERENCE "[RFC 2865 section 3](#)"

::= { radiusAuthClientEntry 10 }

radiusAuthServPacketsDropped OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of incoming packets from this client silently discarded for some reason other than malformed, bad authenticators or unknown types."

REFERENCE "[RFC 2865 section 3](#)"

::= { radiusAuthClientEntry 11 }

radiusAuthServUnknownTypes OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of RADIUS packets of unknown type which were received from this client."

REFERENCE "[RFC 2865 section 4](#)"

::= { radiusAuthClientEntry 12 }

-- New MIB objects added in this revision

```
radiusAuthClientExtTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF RadiusAuthClientExtEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The (conceptual) table listing the RADIUS
         authentication clients with which the server shares
         a secret."
    ::= { radiusAuthServ 16 }
```

```
radiusAuthClientExtEntry OBJECT-TYPE
    SYNTAX      RadiusAuthClientExtEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An entry (conceptual row) representing a RADIUS
         authentication client with which the server shares a
         secret."
    INDEX       { radiusAuthClientExtIndex }
    ::= { radiusAuthClientExtTable 1 }
```

```
RadiusAuthClientExtEntry ::= SEQUENCE {
    radiusAuthClientExtIndex          Integer32,
    radiusAuthClientInetAddressType  InetAddressType,
    radiusAuthClientInetAddress      InetAddress,
    radiusAuthClientExtID             SnmpAdminString,
    radiusAuthServExtAccessRequests  Counter32,
    radiusAuthServExtDupAccessRequests Counter32,
    radiusAuthServExtAccessAccepts   Counter32,
    radiusAuthServExtAccessRejects   Counter32,
    radiusAuthServExtAccessChallenges Counter32,
    radiusAuthServExtMalformedAccessRequests Counter32,
    radiusAuthServExtBadAuthenticators Counter32,
    radiusAuthServExtPacketsDropped  Counter32,
    radiusAuthServExtUnknownTypes    Counter32,
```

Nelson

Expires December 28, 2006

[Page 14]

Internet-Draft

RADIUS Auth Server MIB (IPv6)

June 2006

```
    radiusAuthServCounterDiscontinuity    TimeTicks
}
```

```
radiusAuthClientExtIndex OBJECT-TYPE
```


SYNTAX Integer32 (1..2147483647)
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
 "A number uniquely identifying each RADIUS
 authentication client with which this server
 communicates."
 ::= { radiusAuthClientExtEntry 1 }

radiusAuthClientInetAddressType OBJECT-TYPE

SYNTAX InetAddressType
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The type of address format used for the
 radiusAuthClientInetAddress object."
 ::= { radiusAuthClientExtEntry 2 }

radiusAuthClientInetAddress OBJECT-TYPE

SYNTAX InetAddress
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The IP address of the RADIUS authentication
 client referred to in this table entry, using
 the version neutral IP address format."
 ::= { radiusAuthClientExtEntry 3 }

radiusAuthClientExtID OBJECT-TYPE

SYNTAX SnmpAdminString
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The NAS-Identifier of the RADIUS authentication client
 referred to in this table entry. This is not
 necessarily the same as sysName in MIB II."
REFERENCE "[RFC 2865 section 5.32](#)"
 ::= { radiusAuthClientExtEntry 4 }

-- Server Counters

--

```
-- Responses = AccessAccepts + AccessRejects + AccessChallenges
--
-- Requests - DupRequests - BadAuthenticators - MalformedRequests -
-- UnknownTypes - PacketsDropped - Responses = Pending
--
-- Requests - DupRequests - BadAuthenticators - MalformedRequests -
-- UnknownTypes - PacketsDropped = entries logged

radiusAuthServExtAccessRequests OBJECT-TYPE
    SYNTAX Counter32
    UNITS "packets"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of packets received on the authentication
        port from this client. This counter may experience a
        discontinuity when the RADIUS Server module within the
        managed entity is reinitialized, as indicated by the
        current value of radiusAuthServCounterDiscontinuity."
    REFERENCE "RFC 2865 section 4.1"
    ::= { radiusAuthClientExtEntry 5 }

radiusAuthServExtDupAccessRequests OBJECT-TYPE
    SYNTAX Counter32
    UNITS "packets"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of duplicate RADIUS Access-Request
        packets received from this client. This counter may
        experience a discontinuity when the RADIUS Server
        module within the managed entity is reinitialized, as
        indicated by the current value of
        radiusAuthServCounterDiscontinuity."
    REFERENCE "RFC 2865 section 4.1"
    ::= { radiusAuthClientExtEntry 6 }

radiusAuthServExtAccessAccepts OBJECT-TYPE
    SYNTAX Counter32
    UNITS "packets"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of RADIUS Access-Accept packets
        sent to this client. This counter may experience a
        discontinuity when the RADIUS Server module within the
        managed entity is reinitialized, as indicated by the
```

current value of radiusAuthServCounterDiscontinuity."

Nelson

Expires December 28, 2006

[Page 16]

Internet-Draft

RADIUS Auth Server MIB (IPv6)

June 2006

REFERENCE "[RFC 2865 section 4.2](#)"
 ::= { radiusAuthClientExtEntry 7 }

radiusAuthServExtAccessRejects OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of RADIUS Access-Reject packets sent to this client. This counter may experience a discontinuity when the RADIUS Server module within the managed entity is reinitialized, as indicated by the current value of radiusAuthServCounterDiscontinuity."

REFERENCE "[RFC 2865 section 4.3](#)"
 ::= { radiusAuthClientExtEntry 8 }

radiusAuthServExtAccessChallenges OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of RADIUS Access-Challenge packets sent to this client. This counter may experience a discontinuity when the RADIUS Server module within the managed entity is reinitialized, as indicated by the current value of radiusAuthServCounterDiscontinuity."

REFERENCE "[RFC 2865 section 4.4](#)"
 ::= { radiusAuthClientExtEntry 9 }

radiusAuthServExtMalformedAccessRequests OBJECT-TYPE

SYNTAX Counter32

UNITS "packets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of malformed RADIUS Access-Request packets received from this client. Bad authenticators and unknown types are not included as malformed

Access-Requests. This counter may experience a discontinuity when the RADIUS Server module within the managed entity is reinitialized, as indicated by the current value of radiusAuthServCounterDiscontinuity."
REFERENCE "[RFC 2865](#) sections [3](#), [4.1](#)"
 ::= { radiusAuthClientExtEntry 10 }

radiusAuthServExtBadAuthenticators OBJECT-TYPE

Nelson

Expires December 28, 2006

[Page 17]

Internet-Draft

RADIUS Auth Server MIB (IPv6)

June 2006

SYNTAX Counter32
UNITS "packets"
MAX-ACCESS read-only
STATUS current
DESCRIPTION

"The number of RADIUS Authentication-Request packets which contained invalid Message Authenticator attributes received from this client. This counter may experience a discontinuity when the RADIUS Server module within the managed entity is reinitialized, as indicated by the current value of radiusAuthServCounterDiscontinuity."

REFERENCE "[RFC 2865 section 3](#)"
 ::= { radiusAuthClientExtEntry 11 }

radiusAuthServExtPacketsDropped OBJECT-TYPE

SYNTAX Counter32
UNITS "packets"
MAX-ACCESS read-only
STATUS current
DESCRIPTION

"The number of incoming packets from this client silently discarded for some reason other than malformed, bad authenticators or unknown types. This counter may experience a discontinuity when the RADIUS Server module within the managed entity is reinitialized, as indicated by the current value of radiusAuthServCounterDiscontinuity."

REFERENCE "[RFC 2865 section 3](#)"
 ::= { radiusAuthClientExtEntry 12 }

radiusAuthServExtUnknownTypes OBJECT-TYPE

SYNTAX Counter32

```
UNITS "packets"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "The number of RADIUS packets of unknown type which
    were received from this client. This counter may
    experience a discontinuity when the RADIUS Server
    module within the managed entity is reinitialized, as
    indicated by the current value of
    radiusAuthServCounterDiscontinuity."
REFERENCE "RFC 2865 section 4"
 ::= { radiusAuthClientExtEntry 13 }
```

```
radiusAuthServCounterDiscontinuity OBJECT-TYPE
    SYNTAX TimeTicks
```

Nelson Expires December 28, 2006 [Page 18]

Internet-Draft RADIUS Auth Server MIB (IPv6) June 2006

```
UNITS "centiseconds"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "The number of centiseconds since the last
    discontinuity in the RADIUS Server counters.
    A discontinuity may be the result of a
    reinitialization of the RADIUS Server module
    within the managed entity."
 ::= { radiusAuthClientExtEntry 14 }
```

-- conformance information

```
radiusAuthServMIBConformance OBJECT IDENTIFIER
 ::= { radiusAuthServMIB 2 }
```

```
radiusAuthServMIBCompliances OBJECT IDENTIFIER
 ::= { radiusAuthServMIBConformance 1 }
```

```
radiusAuthServMIBGroups OBJECT IDENTIFIER
 ::= { radiusAuthServMIBConformance 2 }
```

-- compliance statements

```
radiusAuthServMIBCompliance MODULE-COMPLIANCE
```

```

STATUS deprecated
DESCRIPTION
    "The compliance statement for authentication
    servers implementing the RADIUS Authentication
    Server MIB. Implementation of this module is for
    IPv4-only entities, or for backwards compatibility
    use with entities that support both IPv4 and
    IPv6."
MODULE -- this module
MANDATORY-GROUPS { radiusAuthServMIBGroup }

OBJECT      radiusAuthServConfigReset
WRITE-SYNTAX INTEGER { reset(2) }
DESCRIPTION "The only SETable value is 'reset' (2)."
```

```
 ::= { radiusAuthServMIBCompliances 1 }
```

radiusAuthServMIBExtCompliance MODULE-COMPLIANCE

```

STATUS current
DESCRIPTION
    "The compliance statement for authentication
```

Nelson

Expires December 28, 2006

[Page 19]

Internet-Draft

RADIUS Auth Server MIB (IPv6)

June 2006

```

servers implementing the RADIUS Authentication
Server IPv6 Extensions MIB. Implementation of
this module is for entities that support IPv6,
or support IPv4 and IPv6."
MODULE -- this module
MANDATORY-GROUPS { radiusAuthServExtMIBGroup }

OBJECT      radiusAuthServConfigReset
WRITE-SYNTAX INTEGER { reset(2) }
DESCRIPTION "The only SETable value is 'reset' (2)."
```

```

OBJECT radiusAuthClientInetAddressType
SYNTAX InetAddressType { ipv4(1), ipv6(2) }
DESCRIPTION
    "An implementation is only required to support
    IPv4 and globally unique IPv6 addresses."

OBJECT radiusAuthClientInetAddress
SYNTAX InetAddress ( SIZE (4|16) )
```

DESCRIPTION

"An implementation is only required to support IPv4 and globally unique IPv6 addresses."

::= { radiusAuthServMIBCompliances 2 }

-- units of conformance

radiusAuthServMIBGroup OBJECT-GROUP

OBJECTS {radiusAuthServIdent,
radiusAuthServUpTime,
radiusAuthServResetTime,
radiusAuthServConfigReset,
radiusAuthServTotalAccessRequests,
radiusAuthServTotalInvalidRequests,
radiusAuthServTotalDupAccessRequests,
radiusAuthServTotalAccessAccepts,
radiusAuthServTotalAccessRejects,
radiusAuthServTotalAccessChallenges,
radiusAuthServTotalMalformedAccessRequests,
radiusAuthServTotalBadAuthenticators,
radiusAuthServTotalPacketsDropped,
radiusAuthServTotalUnknownTypes,
radiusAuthClientAddress,
radiusAuthClientID,
radiusAuthServAccessRequests,
radiusAuthServDupAccessRequests,
radiusAuthServAccessAccepts,

Nelson

Expires December 28, 2006

[Page 20]

Internet-Draft

RADIUS Auth Server MIB (IPv6)

June 2006

radiusAuthServAccessRejects,
radiusAuthServAccessChallenges,
radiusAuthServMalformedAccessRequests,
radiusAuthServBadAuthenticators,
radiusAuthServPacketsDropped,
radiusAuthServUnknownTypes
}

STATUS deprecated

DESCRIPTION

"The collection of objects providing management of a RADIUS Authentication Server."

::= { radiusAuthServMIBGroups 1 }

```

radiusAuthServExtMIBGroup OBJECT-GROUP
    OBJECTS {radiusAuthServIdent,
        radiusAuthServUpTime,
        radiusAuthServResetTime,
        radiusAuthServConfigReset,
        radiusAuthServTotalAccessRequests,
        radiusAuthServTotalInvalidRequests,
        radiusAuthServTotalDupAccessRequests,
        radiusAuthServTotalAccessAccepts,
        radiusAuthServTotalAccessRejects,
        radiusAuthServTotalAccessChallenges,
        radiusAuthServTotalMalformedAccessRequests,
        radiusAuthServTotalBadAuthenticators,
        radiusAuthServTotalPacketsDropped,
        radiusAuthServTotalUnknownTypes,
        radiusAuthClientInetAddressType,
        radiusAuthClientInetAddress,
        radiusAuthClientExtID,
        radiusAuthServExtAccessRequests,
        radiusAuthServExtDupAccessRequests,
        radiusAuthServExtAccessAccepts,
        radiusAuthServExtAccessRejects,
        radiusAuthServExtAccessChallenges,
        radiusAuthServExtMalformedAccessRequests,
        radiusAuthServExtBadAuthenticators,
        radiusAuthServExtPacketsDropped,
        radiusAuthServExtUnknownTypes,
        radiusAuthServCounterDiscontinuity
    }
STATUS current
DESCRIPTION
    "The collection of objects providing management of
    a RADIUS Authentication Server."
 ::= { radiusAuthServMIBGroups 2 }

```

END

This document requires no new IANA assignments.

9. Security Considerations

There are a number of management objects defined in this MIB that have a MAX-ACCESS clause of read-write and/or read-create. Such objects may be considered sensitive or vulnerable in some network environments. The support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations. These are:

radiusAuthServConfigReset This object can be used to reinitialize the persistent state of any server. When set to reset(2), any persistent server state (such as a process) is reinitialized as if the server had just been started. Depending on the server implementation details, this action may or may not interrupt the processing of pending request in the server. Abuse of this object may lead to a Denial of Service attack on the server.

There are a number of managed objects in this MIB that may contain sensitive information. These are:

radiusAuthClientIPAddress This can be used to determine the address of the RADIUS authentication client with which the server is communicating. This information could be useful in mounting an attack on the authentication client.

radiusAuthClientInetAddress This can be used to determine the address of the RADIUS authentication client with which the server is communicating. This information could be useful in mounting an attack on the authentication client.

It is thus important to control even GET access to these objects and possibly to even encrypt the values of these object when sending them over the network via SNMP. Not all versions of SNMP provide features for such a secure environment.

SNMP versions prior to SNMPv3 do not provide a secure environment. Even if the network itself is secure (for example by using IPsec), there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB.

It is RECOMMENDED that implementers consider the security features as provided by the SNMPv3 framework (see [\[RFC3410\]](#), [section 8](#)), including full support for the SNMPv3 cryptographic mechanisms (for authentication and privacy).

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them

[10.](#) References

[10.1.](#) Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIv2)", STD 58, [RFC 2578](#), April 1999.
- [RFC2579] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIv2", STD 58, [RFC 2579](#), April 1999.
- [RFC2580] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Conformance Statements for SMIv2", STD 58, [RFC 2580](#), April 1999.
- [RFC2865] Rigney, C., Willens, S., Rubens, A., and W. Simpson, "Remote Authentication Dial In User Service (RADIUS)", [RFC 2865](#), June 2000.
- [RFC4001] Daniele, M., Haberman, B., Routhier, S., and J. Schoenwaelder, "Textual Conventions for Internet Network Addresses", [RFC 4001](#), February 2005.

[10.2.](#) Informative References

- [2618bis] Nelson, D., "RADIUS Authentication Client MIB for IPv6", [draft-ietf-radext-rfc2618bis-04.txt](#) (work in progress), June 2006.
- [RFC2619] Zorn, G. and B. Aboba, "RADIUS Authentication Server MIB",

[RFC 2619](#), June 1999.

[RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart,
"Introduction and Applicability Statements for Internet-
Standard Management Framework", [RFC 3410](#), December 2002.

[Appendix A](#). Acknowledgments

The authors of the original MIB are Bernard Aboba and Glen Zorn.

Many thanks to all reviewers, especially to David Harrington, Dan Romascanu, C.M. Heard, Bruno Pape, Greg Weber and Bert Wijnen.

Nelson

Expires December 28, 2006

[Page 24]

Internet-Draft

RADIUS Auth Server MIB (IPv6)

June 2006

Author's Address

David B. Nelson
Enterasys Networks
50 Minuteman Road
Andover, MA 01810
USA

Email: dnelson@enterasys.com

Intellectual Property Statement

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

Disclaimer of Validity

This document and the information contained herein are provided on an

"AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Copyright Statement

Copyright (C) The Internet Society (2006). This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

Acknowledgment

Funding for the RFC Editor function is currently provided by the Internet Society.