

SIPPING WG
Internet-Draft
Intended status: Informational
Expires: April 14, 2008

V. Gurbani
Bell Laboratories, Alcatel-Lucent
C. Boulton
Ubiquity Software Corporation
R. Sparks
Estacado Systems
October 12, 2007

Session Initiation Protocol (SIP) Torture Test Messages for Internet
Protocol Version 6 (IPv6)
draft-ietf-sipping-ipv6-torture-tests-04

Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/lid-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on April 14, 2008.

Copyright Notice

Copyright (C) The IETF Trust (2007).

Abstract

This document provides examples of Session Initiation Protocol (SIP) test messages designed to exercise and "torture" the code of an IPv6-enabled SIP implementation.

This work is being discussed on the sipping@ietf.org mailing list.

Table of Contents

1.	Overview	3
2.	Document conventions	3
3.	SIP and IPv6 network configuration	4
4.	Parser torture tests	4
4.1.	Valid SIP message with an IPv6 reference	5
4.2.	Invalid SIP message with an IPv6 reference	5
4.3.	Port ambiguous in a SIP URI	6
4.4.	Port unambiguous in a SIP URI	7
4.5.	IPv6 reference delimiters in Via header	7
4.6.	SIP request with IPv6 addresses in Session Description Protocol (SDP) body	9
4.7.	Multiple IP addresses in SIP headers	9
4.8.	Multiple IP addresses in SDP	10
4.9.	IPv4-mapped IPv6 addresses	11
4.10.	IPv6 reference bug in RFC3261 ABNF	11
5.	Security considerations	12
6.	IANA considerations	13
7.	Acknowledgments	13
8.	References	13
8.1.	Normative references	13
8.2.	Informative references	14
Appendix A.	Bit-exact archive of each test message	14
A.1.	Encoded reference messages	15
	Authors' Addresses	16
	Intellectual Property and Copyright Statements	18

Internet-Draft

SIP IPv6 Torture Tests

October 2007

1. Overview

This document is informational, and is NOT NORMATIVE on any aspect of SIP.

This document contains test messages based on the current version (2.0) of the Session Initiation Protocol as defined in [[RFC3261](#)].

This document is expected to be used as a companion document to the more general SIP torture test document [[RFC4475](#)], which does not include specific tests for IPv6 network identifiers.

This document does not attempt to catalog every way to make an invalid message, nor does it attempt to be comprehensive in exploring unusual, but valid, messages. Instead, it tries to focus on areas that may cause interoperability problems in IPv6 deployments.

2. Document conventions

This document contains many examples of SIP messages with IPv6 network identifiers. The appendix contains an encoded binary form containing the bit-exact representation of all the messages and the script needed to decode them into separate files.

The IPv6 addresses used in this document correspond to the 2001:DB8::/32 address prefix reserved for documentation [[RFC3489](#)]. Likewise, the IPv4 addresses used in this document correspond to the 192.0.2.0/24 address block as described in [[RFC3330](#)].

Although SIP is a text-based protocol, some of these examples cannot be unambiguously rendered without additional markup due to the constraints placed on the formatting of RFCs. This document uses the <allOneLine/> markup convention established in [[RFC4475](#)] to avoid ambiguity and meet the Internet-Draft layout requirements. For the sake of completeness, the text defining this markup from [Section 2.1](#)

[of \[RFC4475\]](#) is reproduced in its entirety below:

"Several of these examples contain unfolded lines longer than 72 characters. These are captured between <allOneLine/> tags. The single unfolded line is reconstructed by directly concatenating all lines appearing between the tags (discarding any line feeds or carriage returns). There will be no whitespace at the end of lines. Any whitespace appearing at a fold-point will appear at the beginning of a line.

"The following represent the same string of bits:

Gurbani, et al.

Expires April 14, 2008

[Page 3]

Internet-Draft

SIP IPv6 Torture Tests

October 2007

Header-name: first value, reallylongsecondvalue, third value

```
<allOneLine>
Header-name: first value,
  reallylongsecondvalue
, third value
</allOneLine>
```

```
<allOneLine>
Header-name: first value,
  reallylong
second
value,
  third value
</allOneLine>
```

"Note that this is NOT SIP header-line folding, where different strings of bits have equivalent meaning."

3. SIP and IPv6 network configuration

System-level issues like deploying a dual-stack proxy server, populating DNS with A and AAAA Resource Records (RRs), zero-configuration discovery of outbound proxies for IPv4 and IPv6 networks, when should a dual-stack proxy Record-Route itself, and media issues also play a major part in the transition to IPv6. This document does not, however, address these issues. Instead, a

companion document [[ID.sip-trans](#)] provides more guidance on these issues.

4. Parser torture tests

The test messages are organized into several sections. Some stress only a SIP parser and others stress both the parser and the application above it. Some messages are valid, and some are not. Each example clearly calls out what makes any invalid messages incorrect.

Please refer to the complete Augmented Backus-Naur Form (ABNF) in [[RFC3261](#)] on representing IPv6 references in SIP messages. IPv6 references are delimited by a "[" and "]". When an IPv6 reference is part of a SIP Uniform Resource Identifier (URI), [RFC3261](#) mandates that the "IPv6reference" production rule be used to recognize tokens that comprise an IPv6 reference. More specifically, the ABNF states:

Gurbani, et al.

Expires April 14, 2008

[Page 4]

Internet-Draft

SIP IPv6 Torture Tests

October 2007

```
SIP-URI      = "sip:" [ userinfo ] hostport
              uri-parameters [ headers ]
hostport    = host [ ":" port ]
host        = hostname / IPv4address / IPv6reference
IPv4address = 1*3DIGIT "." 1*3DIGIT "." 1*3DIGIT "." 1*3DIGIT
IPv6reference = "[" IPv6address "]"
IPv6address = hexpart [ ":" IPv4address ]
hexpart     = hexseq / hexseq "::" [ hexseq ] / "::" [ hexseq ]
hexseq      = hex4 *( ":" hex4)
hex4        = 1*4HEXDIG
```

[4.1.](#) Valid SIP message with an IPv6 reference

The request below is well-formatted according to the grammar in [[RFC3261](#)]. An IPv6 reference appears in the Request-URI (R-URI), Via header field, and Contact header field.

Message Details: ipv6-good

```
REGISTER sip:[2001:db8::10] SIP/2.0
To: sip:user@example.com
From: sip:user@example.com;tag=81x2
```

Via: SIP/2.0/UDP [2001:db8::9:1];branch=z9hG4bKas3-111
Call-ID: SSG9559905523997077@hlau_4100
Max-Forwards: 70
Contact: "Caller" <sip:caller@[2001:db8::1]>
CSeq: 98176 REGISTER
Content-Length: 0

[4.2.](#) Invalid SIP message with an IPv6 reference

The request below is not well-formatted according to the grammar in [\[RFC3261\]](#). The IPv6 reference in the R-URI does not contain the mandated delimiters for an IPv6 reference ("[" and "]").

A SIP implementation receiving this request should respond with a 400 Bad Request error.

Message Details: ipv6-bad

```
REGISTER sip:2001:db8::10 SIP/2.0
To: sip:user@example.com
From: sip:user@example.com;tag=81x2
Via: SIP/2.0/UDP [2001:db8::9:1];branch=z9hG4bKas3-111
Call-ID: SSG9559905523997077@hlau_4100
Max-Forwards: 70
Contact: "Caller" <sip:caller@[2001:db8::1]>
CSeq: 98176 REGISTER
Content-Length: 0
```

[4.3.](#) Port ambiguous in a SIP URI

IPv6 uses the colon to delimit octets. This may lead to ambiguity if the port number on which to contact a SIP server is inadvertently

conflated with the IPv6 reference. Consider the REGISTER request below. The sender of the request intended to specify a port number (5070) to contact a server, but inadvertently, inserts the port number inside the closing "]" of the IPv6 reference. Unfortunately, since the IPv6 address in the R-URI is compressed, the intended port number becomes the last octet of the reference.

From a parsing perspective, the request below is well-formed. However, from a semantic point of view, it will not yield the desired result. Implementations must ensure that when a raw IPv6 address appears in a SIP URI, then a port number, if required, appears outside the closing "]" delimiting the IPv6 reference. Raw IPv6 addresses can appear in the "sent-by" production rule of the Via header field, the Contact header field, the Route and Record-Route headers, among other headers. Implementers are urged to consult the ABNF in [[RFC3261](#)] for a complete list of fields where a SIP URI can appear.

Message Details: port-ambiguous

```
REGISTER sip:[2001:db8::10:5070] SIP/2.0
To: sip:user@example.com
From: sip:user@example.com;tag=81x2
Via: SIP/2.0/UDP [2001:db8::9:1];branch=z9hG4bKas3-111
Call-ID: SSG9559905523997077@hlau_4100
Contact: "Caller" <sip:caller@[2001:db8::1]>
Max-Forwards: 70
CSeq: 98176 REGISTER
Content-Length: 0
```

[4.4.](#) Port unambiguous in a SIP URI

In contrast to the example in [Section 4.3](#), the following REGISTER request leaves no ambiguity whatsoever on where the IPv6 address ends and the port number begins. This REGISTER request is well formatted per the grammar in [[RFC3261](#)].

Message Details: port-unambiguous

```
REGISTER sip:[2001:db8::10]:5070 SIP/2.0
To: sip:user@example.com
From: sip:user@example.com;tag=81x2
Via: SIP/2.0/UDP [2001:db8::9:1];branch=z9hG4bKas3-111
Call-ID: SSG9559905523997077@hlau_4100
Contact: "Caller" <sip:caller@[2001:db8::1]>
Max-Forwards: 70
CSeq: 98176 REGISTER
Content-Length: 0
```

[4.5.](#) IPv6 reference delimiters in Via header

IPv6 references can also appear in Via header fields; more specifically in the "sent-by" production rule and the "via-received" production rule. In the "sent-by" production rule, the sequence of octets comprising the IPv6 address is defined to appear as an "IPv6reference" non-terminal, thereby mandating the "[" and "]" delimiters. However, this is not the case for the "via-received" non-terminal. The "via-received" production rule is defined thusly:

```
via-received = "received" EQUAL (IPv4address / IPv6address)
```

The "IPv6address" non-terminal is defined not to include the delimiting "[" and "]". This has led to the situation documented during the 18th SIP Interoperability Event [[Email-SIPit](#)]:

Those testing IPv6 made different assumptions about enclosing literal v6 addresses in Vias in []. By the end of the event, most implementations were accepting either. Its about 50/50 on what gets sent.

While it would be beneficial if the same non-terminal ("IPv6reference") was used for both the "sent-by" and "via-received" production rules, there has not been a consensus in the working group to that effect. Thus, the best that can be suggested is that implementations must follow the Robustness Principle [[RFC1122](#)] and be liberal in accepting a "received" parameter with or without the delimiting "[" and "]" tokens. When sending a request,

implementations must not put the delimiting "[" and "]" tokens.

The two test cases below are designed to stress this behavior. A SIP implementation receiving either of these messages must parse them successfully.

The request below contains an IPv6 address in the Via "received" parameter. The IPv6 address is delimited by "[" and "]". Even though this is not a valid request based on a strict interpretation of the grammar in [\[RFC3261\]](#), robust implementations must nonetheless be able to parse the topmost Via header field and continue processing the request.

Message Details: via-received-param-with-delim

```
BYE sip:[2001:db8::10] SIP/2.0
To: sip:user@example.com;tag=bd76ya
From: sip:user@example.com;tag=81x2
<allOneLine>
Via: SIP/2.0/UDP [2001:db8::9:1];received=[2001:db8::9:255];
branch=z9hG4bKas3-111
</allOneLine>
Call-ID: SSG9559905523997077@hlau_4100
Max-Forwards: 70
CSeq: 321 BYE
Content-Length: 0
```

The OPTIONS request below contains an IPv6 address in the Via "received" parameter without the adorning "[" and "]". This request is valid according to the grammar in [\[RFC3261\]](#).

Message Details: via-received-param-no-delim

```
OPTIONS sip:[2001:db8::10] SIP/2.0
To: sip:user@example.com
From: sip:user@example.com;tag=81x2
<allOneLine>
Via: SIP/2.0/UDP [2001:db8::9:1];received=2001:db8::9:255;
branch=z9hG4bKas3
</allOneLine>
Call-ID: SSG95523997077@hlau_4100
Max-Forwards: 70
Contact: "Caller" <sip:caller@[2001:db8::9:1]>
CSeq: 921 OPTIONS
Content-Length: 0
```

[4.6.](#) SIP request with IPv6 addresses in Session Description Protocol (SDP) body

This request below is valid and well-formed according to the grammar in [[RFC3261](#)]. Note that the IPv6 addresses in the SDP [[RFC4566](#)] body do not have the delimiting "[" and "]".

Message Details: ipv6-in-sdp

```
INVITE sip:user@[2001:db8::10] SIP/2.0
To: sip:user@[2001:db8::10]
From: sip:user@example.com;tag=81x2
Via: SIP/2.0/UDP [2001:db8::20];branch=z9hG4bKas3-111
Call-ID: SSG9559905523997077@hlau_4100
Contact: "Caller" <sip:caller@[2001:db8::20]>
CSeq: 8612 INVITE
Max-Forwards: 70
Content-Type: application/sdp
Content-Length: 268
```

```
v=0
o=assistant 971731711378798081 0 IN IP6 2001:db8::20
s=Live video feed for today's meeting
c=IN IP6 2001:db8::20
t=3338481189 3370017201
m=audio 6000 RTP/AVP 2
a=rtpmap:2 G726-32/8000
m=video 6024 RTP/AVP 107
a=rtpmap:107 H263-1998/90000
```

[4.7.](#) Multiple IP addresses in SIP headers

This request below is valid and well-formed according to the grammar in [[RFC3261](#)]. The Via list contains a mix of IPv4 addresses and IPv6 references.

Message Details: mult-ip-in-header

Internet-Draft

SIP IPv6 Torture Tests

October 2007

```
BYE sip:user@host.example.net SIP/2.0
Via: SIP/2.0/UDP [2001:db8::9:1]:6050;branch=z9hG4bKas3-111
Via: SIP/2.0/UDP 192.0.2.1;branch=z9hG4bKjhja8781hjuaij65144
<allOneLine>
Via: SIP/2.0/TCP [2001:db8::9:255];branch=z9hG4bK451jj;
received=192.0.2.200
</allOneLine>
Call-ID: 997077@lau_4100
Max-Forwards: 70
CSeq: 89187 BYE
To: sip:user@example.net;tag=9817--94
From: sip:user@example.com;tag=81x2
Content-Length: 0
```

[4.8.](#) Multiple IP addresses in SDP

The request below is valid and well-formed according to the grammar in [[RFC3261](#)]. The SDP contains multiple media lines, and each media line is identified by a different network connection address.

Message Details: mult-ip-in-sdp

```
INVITE sip:user@[2001:db8::10] SIP/2.0
To: sip:user@[2001:db8::10]
From: sip:user@example.com;tag=81x2
Via: SIP/2.0/UDP [2001:db8::9:1];branch=z9hG4bKas3-111
Call-ID: SSG9559905523997077@hlau_4100
Contact: "Caller" <sip:caller@[2001:db8::9:1]>
Max-Forwards: 70
CSeq: 8912 INVITE
Content-Type: application/sdp
Content-Length: 181

v=0
o=bob 280744730 28977631 IN IP4 host.example.com
s=
t=0 0
m=audio 22334 RTP/AVP 0
```

```
c=IN IP4 192.0.2.1
m=video 6024 RTP/AVP 107
c=IN IP6 2001:db8::1
a=rtpmap:107 H263-1998/90000
```

[4.9.](#) IPv4-mapped IPv6 addresses

An IPv4-mapped IPv6 address is usually represented with the last 32-bits appearing as a dotted-decimal IPv4 address; e.g., ::ffff:192.0.2.1. A SIP implementation receiving a message that contains such a mapped address must be prepared to parse it successfully. An IPv4-mapped IPv6 address may appear in signaling, or the SDP carried by the signaling message, or in both. If a port number is part of the URI represented by the IPv4-mapped IPv6 address, then it must appear outside the delimiting "]" (cf. [Section 4.4](#)).

The message below is well-formed according to the grammar in [\[RFC3261\]](#). The Via list contains two Via headers, both of which include an IPv4-mapped IPv6 address. An IPv4-mapped IPv6 address also appears in the Contact header and the SDP. The topmost Via header includes a port number that is appropriately delimited by "]"

Message Details: ipv4-mapped-ipv6

```
INVITE sip:user@example.com SIP/2.0
To: sip:user@example.com
From: sip:user@east.example.com;tag=81x2
Via: SIP/2.0/UDP [::ffff:192.0.2.10]:19823;branch=z9hG4bKbh19
Via: SIP/2.0/UDP [::ffff:192.0.2.2];branch=z9hG4bKas3-111
Call-ID: SSG9559905523997077@hlau_4100
Contact: "T. desk phone" <sip:ted@[::ffff:192.0.2.2]>
CSeq: 612 INVITE
Max-Forwards: 70
Content-Type: application/sdp
Content-Length: 236
```

v=0

```
o=assistant 971731711378798081 0 IN IP6 ::ffff:192.0.2.2
s=Call me soon, please!
c=IN IP6 ::ffff:192.0.2.2
t=3338481189 3370017201
m=audio 6000 RTP/AVP 2
a=rtpmap:2 G726-32/8000
m=video 6024 RTP/AVP 107
a=rtpmap:107 H263-1998/90000
```

4.10. IPv6 reference bug in [RFC3261](#) ABNF

It is possible to follow the IPv6reference production rule of [RFC3261](#) ABNF -- the relevant portion of which is reproduced at the top of [Section 4](#) -- and arrive at the following construct:

```
[2001:db8:::192.0.2.1]
```

Gurbani, et al.

Expires April 14, 2008

[Page 11]

Internet-Draft

SIP IPv6 Torture Tests

October 2007

Note the extra colon before the IPv4 address in the above construct. The correct construct, of course, is:

```
[2001:db8::192.0.2.1]
```

The ABNF pertaining to IPv6 references in [RFC3261](#) was derived from [RFC 2373](#) [[RFC2373](#)], which has been obsoleted by [RFC 4291](#) [[RFC4291](#)]. The specific behavior of inserting an extra colon was inherited from [RFC 2373](#), and has been remedied in [RFC 4291](#). However, following the Robustness Principle [[RFC1122](#)], an implementation must tolerate both of the above constructs.

The message below includes an extra colon in the IPv6 reference. A SIP implementation receiving such a message may exhibit robustness by successfully parsing the IPv6 reference (it can choose to delete the extra colon when parsing the IPv6 reference.)

Message Details: ipv6-bug-abnf-3-colons

```
OPTIONS sip:user@[2001:db8:::192.0.2.1] SIP/2.0
To: sip:user@[2001:db8:::192.0.2.1]
From: sip:user@example.com;tag=810x2
Via: SIP/2.0/UDP lab1.east.example.com;branch=z9hG4bKas3-111
Call-ID: G9559905523997077@hlau_4100
CSeq: 689 OPTIONS
```

Max-Forwards: 70
Content-Length: 0

The next message has the correct syntax for the IPv6 reference in the R-URI.

Message Details: ipv6-correct-abnf-2-colons

```
OPTIONS sip:user@[2001:db8::192.0.2.1] SIP/2.0
To: sip:user@[2001:db8::192.0.2.1]
From: sip:user@example.com;tag=810x2
Via: SIP/2.0/UDP lab1.east.example.com;branch=z9hG4bKas3-111
Call-ID: G9559905523997077@hlau_4100
CSeq: 689 OPTIONS
Max-Forwards: 70
Content-Length: 0
```

[5.](#) Security considerations

This document presents examples of SIP messages with IPv6 references contained in the signaling headers and SDP payload. While this document may clarify the behavior of SIP elements processing a

message with IPv6 references, it does not normatively change the base SIP [[RFC3261](#)] specification in any way. Consequently, all security considerations in [[RFC3261](#)] apply.

Parsers must carefully consider edge conditions and malicious input as part of their design. Attacks on many Internet systems use crafted input to cause implementations to behave in undesirable ways. Many of the messages in this draft are designed to stress a parser implementation at points traditionally used for such attacks. This document does not, however, attempt to be comprehensive. It contains some common pitfalls that the authors have discovered while parsing IPv6 identifiers in SIP implementations.

[6.](#) IANA considerations

This document does not contain any actions for IANA.

7. Acknowledgments

The authors thank Jeroen van Bommel, Dennis Bijwaard, Gonzalo Camarillo, Bob Gilligan, Alan Jeffrey, Larry Kollasch, Erik Nordmark, Kumiko Ono, Pekka Pessi, Jon Peterson and other members of the SIP-related working groups for input provided during the construction of the document and discussion of the test cases.

A.B. Nataraju and A.C. Mahendran provided working group last call comments.

Mohamed Boucadair and Brian Carpenter suggested new test cases for inclusion in the document.

8. References

8.1. Normative references

- [RFC1122] Braden, R., "Requirements for Internet Hosts - Communication Layers", STD 3, [RFC 1122](#), October 1989.
- [RFC3261] Rosenberg, J., Schulzrinne, H., Camarillo, G., Johnston, A., Peterson, J., Sparks, R., Handley, M., and E. Schooler, "SIP: Session Initiation Protocol", [RFC 3261](#), June 2002.
- [RFC3330] IANA, "Special-Use IPv4 Addresses", [RFC 3330](#), September 2002.

Gurbani, et al. Expires April 14, 2008 [Page 13]

Internet-Draft SIP IPv6 Torture Tests October 2007

- [RFC3489] Rosenberg, J., Weinberger, J., Huitema, C., and R. Mahy, "STUN - Simple Traversal of User Datagram Protocol (UDP) Through Network Address Translators (NATs)", [RFC 3489](#), March 2003.
- [RFC4475] Sparks, R., Hawrylyshen, A., Johnston, A., Rosenberg, J., and H. Schulzrinne, "Session Initiation Protocol (SIP) Torture Test Messages", [RFC 4475](#), May 2006.
- [RFC4566] Handley, M., Jacobson, V., and C. Perkins, "SDP: Session Description Protocol", [RFC 4566](#), July 2006.

8.2. Informative references

[RFC2373] Hinden, R. and S. Deering, "IP Version 6 Addressing Architecture", [RFC 2373](#), July 1998.

[RFC4291] Hinden, R. and S. Deering, "IP Version 6 Addressing Architecture", [RFC 4291](#), February 2006.

[ID.sip-trans]

Camarillo, G., El Malki, K., and V. Gurbani, "IPv6 Transition in the Session Initiation Protocol (SIP)", [draft-ietf-sipping-v6-transition-07.txt](#) (work in progress), August 2007.

[Email-SIPit]

Sparks, R., "preliminary report: SIPit 18", Electronic Mail archived at <http://www1.ietf.org/mail-archive/web/sip/current/msg14103.html>, April 2006.

Appendix A. Bit-exact archive of each test message

The following text block is an encoded, gzip compressed TAR archive of files that represent each of the example messages discussed in [Section 4](#).

To recover the compressed archive file intact, the text of this document may be passed as input to the following Perl script (the output should be redirected to a file or piped to "tar -xzvf -").

Gurbani, et al.

Expires April 14, 2008

[Page 14]

Internet-Draft

SIP IPv6 Torture Tests

October 2007

```
#!/usr/bin/perl
use strict;
my $bdata = "";
use MIME::Base64;
```



```
while(<>) {
  if (/-- BEGIN MESSAGE ARCHIVE --/ .. /-- END MESSAGE ARCHIVE --/) {
    if ( m/^\s*[\s]+\s*$/) {
      $bdata = $bdata . $_;
    }
  }
}
print decode_base64($bdata);
```

Alternatively, the base-64 encoded block can be edited by hand to remove document structure lines and fed as input to any base-64 decoding utility.

[A.1.](#) Encoded reference messages

-- BEGIN MESSAGE ARCHIVE --

H4sICPujD0cAA21zZy50YXIA7Vpbc6M2GPUzv0Ldl74UWzckIHUnbXY39XS760ncz
HQ6mY5sFBuvDRSwN+mvrwAb303c2GQ34byAjYSEpH0+i1Rv1E40CCnkEKorRJyl1+
R2dk1RQ6oE4RhxRNT/CCHGa8bpu1arTaJYhKrJ6ef+3nJ+PJDhufzD8ku+LidPB3
qDTeYUn0sgkA6urpnx28DIggZpbvmHyFOF/NPWTl/FFFcg8fvyiZe+fy3Pt600u9A
5Ab2JLHubwX42Ak6z1/DK5b7QauQ63j21sLa09Df7z8SERxfen5WSz6TRPdY+3GF
fb8dY0/3rbBX7Z9p2Ajs/1Tx3UEb9W9icLZNxReb9D81xpc0u5v3QGYimvj27VqIi
K60hDtQoxGeutqn19aRmGZUHDwMSy00T8fDASk7+pWpvahe/Fohfb4E2nDhwZfQb
BwPfkG/Bj8m2xdM43W/xJu7iW/9iAIQyyQdR+F/f6ez/8IkInsgHP3iu9W088BNIG
imIjtydi1/cakRPkTz9Irx8PbIAJ07RpE2p+U0SRq9a1Fw0LI06UKiLCTW6Z0EQAq
vZAq83Aep+0qJl8MBhLEPm+9wNQ8yAi+Z3Wa+6qETcJISY1ETItQAHPGIoh0sZNMX
FchZC1lsFVp934+aYNSCaaYRworbAxu0SY6QQ3TFVCFZ+6jkyKY5oXV5ReVFA/wK+
YqWmxLLNhJRzRnnvtV5jP907wjldGwX6DyKlSv8Z5AZEmPNE/7FBWKX/JeDq3WXR
uvPuKlVxrEbedrqmreh6uPo/TvgXbVg2eqJubxXcTMiTn8hwpuC99Mf5Utso12/LV
GsSzIdhQ5Sh9rJlasb/vu+fTgCK+W8s+I9pyn90Kv+vDKzWf5kg8LZSgFegADP+u5
6uXNITtVEU/0G05/zHkKX2X7m8v0J/CViP/x4jAatlnqwCGB4tfCvgvGppTnrziHE
bMw+L25Y7pGK2D+5Ugix+upPSAXd+CGLfEQ/fRyqUk7Hr9RcR3ErdKnqr8ETUG+PJ
KNbdIDEBAymcvSL3/1Dk/6l1l+s/wjDN/xECK/0vAb/8uST+A38pgefJ0Jf/Iif0Z
tCA00R8o26e81urMBwMhclNNBhOhDtkBqJ0tXlnYq1hbBjrpoMaaDg8C2VPKlV1mn
mmKzETc2syMyB7nMjMRFjI5EAN0HYHwI1Pat8S91HXLfoo0/jV0Zcr/D+RC1jEf85
Zzn+MMv9PwC6K/yXgK/D/nh4FPtoBtNKwbzffc5fwMA8QmWjuAXb9LsAm5JRyAtWd
pRY3QZnnR8GKwCYRdNRUthwEMHFZMCZk4YTbueNHf6q5213b4iSiIh+u3gj8MNbFu
0v2J/4k0sUaK8z/GLn9R4Rl9l+NYMX/ErA7/2MbkH8bSaCDcj47yP9ak0Az/k+8Ey
rAIfynGKX8p8So+F8C9uR/UwGo+P/S+T91hT6Pl/RAHGKse77uyJE7PlIbhfxni/1
fg6X7Pwzzav+nDhxqd1qfPl4/3/ZPHqqvBfabkrAuB0fdDrKWN4QwArNxefFCsJX/
X9x4cEQFKOQ/Xth/I4v/GcMV/8vAPP93IPdTgncdzh7EkWwGKMh35A3iLOJEUTzJ7
L10ehdifv5r0tdF17vTid7zR7531CigmP/Z+W/MGUvPfsUygKvzX2Vg2f6vJ/cWp3
OLE4FLZYsFAW5ThJHoovrGeeIC8u8NC7LzuaaVG/OdG70L+j/3fJSNGf97fqqUOM4
0AB9ZAwR5j1j0f+UFpPZfsUDF/xKwj/8H0L9if4UKFSp8Y/gPJmWg1AA6AAA=
-- END MESSAGE ARCHIVE --

Authors' Addresses

Vijay K. Gurbani
Bell Laboratories, Alcatel-Lucent
2701 Lucent Lane
Rm 9F-546
Lisle, IL 60532
USA

Phone: +1 630 224 0216
Email: vkg@alcatel-lucent.com

Internet-Draft

SIP IPv6 Torture Tests

October 2007

Chris Boulton
Ubiquity Software Corporation
Building 3
West Fawr Lane
St Mellons
Cardiff, South Wales CF3 5EA

Email: cboulton@ubiquitysoftware.com

Robert J. Sparks
Estacado Systems

Email: RjS@estacado.net

Full Copyright Statement

Copyright (C) The IETF Trust (2007).

This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY, THE IETF TRUST AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Intellectual Property

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at

<http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

Acknowledgment

Funding for the RFC Editor function is provided by the IETF Administrative Support Activity (IASA).