

MAGMA WG
Internet-Draft
Intended status: Standards Track
Expires: August 13, 2009

J. Chesterfield
University of Cambridge
B. Haberman, Ed.
JHU/APL
February 9, 2009

Multicast Group Membership Discovery MIB
draft-ietf-magma-mgmd-mib-15

Status of This Memo

This Internet-Draft is submitted to IETF in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/lid-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on August 13, 2009.

Copyright Notice

Copyright (c) 2009 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document.

Abstract

This memo defines a portion of the Management Information Base (MIB)

Internet-Draft

MGMD MIB

February 2009

for use with network management protocols in the Internet community. In particular, it describes objects used for managing the Internet Group Management Protocol (IGMP) and the Multicast Listener Discovery (MLD) protocol.

Table of Contents

1.	Introduction	3
2.	The Internet-Standard Management Framework	3
3.	Conventions	3
4.	Overview	3
5.	Definitions	5
6.	Security Considerations	38
7.	IANA Considerations	39
8.	Contributors	40
9.	Acknowledgements	40
10.	References	40
10.1.	Normative References	40
10.2.	Informative References	41

Internet-Draft

MGMD MIB

February 2009

1. Introduction

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes objects used for managing the Internet Group Management Protocol (IGMP), version 1 [[RFC1112](#)], version 2 [[RFC2236](#)] or version 3 [[RFC3376](#)] and the Multicast Listener Discovery (MLD) protocol version 1 [[RFC2710](#)] or version 2 [[RFC3810](#)]. Both protocols provide multicast membership discovery capability. IGMP pertains to IP version 4 clients, and MLD for IP version 6 clients. This version of the MIB obsoletes both [RFC 2933](#) [[RFC2933](#)] and [RFC 3019](#) [[RFC3019](#)], incorporating a generic interface for both IGMP and MLD implementations, and changes to enable "source filtering" in multicast clients. The MIB encompasses both router and host nodes with relevant management objects defined for each.

2. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to [section 7 of RFC 3410](#) [[RFC3410](#)].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIV2, which is described in STD 58, [RFC 2578](#) [[RFC2578](#)], STD 58, [RFC 2579](#) [[RFC2579](#)] and STD 58, [RFC 2580](#) [[RFC2580](#)].

3. Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

[4.](#) Overview

This Multicast Group Membership Discovery (MGMD) MIB module contains eight tables:

1. the MGMD Host Interface Table which contains one row for each interface on which IGMP or MLD is enabled on a host,
2. the MGMD Router Interface Table which contains one row for each interface on which MGMD is enabled on a router,

3. the MGMD Host Cache Table which contains one row for each IP multicast group for which there are members on a particular interface on a host,
4. the MGMD Router Cache Table which contains one row for each IP multicast group for which there are members on a particular interface on a router,
5. the reverse MGMD Host Table which contains one row for each interface for which there are active multicast groups on a host,
6. the reverse MGMD Router Table which contains one row for each interface for which there are active multicast groups on a router,
7. the MGMD HostSrcList Table which contains one row for each entry in the source filter record for an interface and multicast group pair on a host.
8. the MGMD RouterSrcList Table which contains one row for each entry in the source filter record for an interface and multicast group pair on a router.

All tables are intended for EITHER router OR host functionality as indicated by the name and corresponding description, although it is anticipated that there would be scenarios where both terms might apply to a device, e.g. a router which joins a multicast group also as a host for measurement purposes. The source list tables provide an extension to the cache tables to indicate the source specific

includes or excludes associated with each IP Multicast group on each specific interface. This functionality is only supported in IGMPv3 and MLDv2 capable nodes.

Incorporated within the MGMD MIB tables are objects for the management of IGMP and MLD proxy devices as described in [RFC 4605](#) [RFC4605]. Proxy devices can be used in simple topologies where it is not necessary to run a full multicast routing protocol. A proxy device can make forwarding decisions based on IGMP or MLD group membership activity.

The MIB references InterfaceIndex and InterfaceIndexOrZero objects as defined in [RFC 2863](#) [RFC2863], the MIB which describes generic objects for network interface sub-layers.

Extensive references to the InetAddress and InetAddressType objects are made as defined in [RFC 4001](#) [RFC4001].

5. Definitions

Chesterfield & Haberman Expires August 13, 2009

[Page 4]

Internet-Draft

MGMD MIB

February 2009

MGMD-STD-MIB DEFINITIONS ::= BEGIN

IMPORTS

```
MODULE-IDENTITY, OBJECT-TYPE, mib-2, Counter32, Gauge32,
Unsigned32, TimeTicks                FROM SNMPv2-SMI
InetAddress, InetAddressType          FROM INET-ADDRESS-MIB
RowStatus                             FROM SNMPv2-TC
MODULE-COMPLIANCE, OBJECT-GROUP      FROM SNMPv2-CONF
InterfaceIndexOrZero,
InterfaceIndex                        FROM IF-MIB;
```

mgmdStdMIB MODULE-IDENTITY

```
LAST-UPDATED "200901270000Z" -- January 27, 2009
ORGANIZATION "INTERNET ENGINEERING TASK FORCE MULTICAST and
ANYCAST GROUP MEMBERSHIP Working
Group.
```

```
www: http://www.ietf.org/html.charters/magma-charter.html
EMail: magma@ietf.org"
```

CONTACT-INFO

```
"Julian Chesterfield
University of Cambridge,
Computer Laboratory,
```

15 JJ Thompson Avenue,
Cambridge,
CB3 0FD
UK

EMail: julian.chesterfield@cl.cam.ac.uk"

DESCRIPTION

"The MIB module for MGMD management.
A new version of MGMD combining [RFC 2933](#) and [RFC 3019](#).
Includes IGMPv3 and MLDv2 source filtering changes.

Copyright (c) 2009 IETF Trust and the persons identified
as the document authors. All rights reserved.

This version of this MIB module is part of RFC yyyy;
see the RFC itself for full legal notices."

-- RFC Ed.: replace yyyy with actual RFC number & remove this note

REVISION "200901270000Z" -- January 27, 2009

DESCRIPTION

"This MIB obsoletes both [RFC 2933](#) and [RFC 3019](#)."

::= { mib-2 XXX }

mgmdMIBObjects OBJECT IDENTIFIER ::= { mgmdStdMIB 1 }

Chesterfield & Haberman Expires August 13, 2009

[Page 5]

Internet-Draft

MGMD MIB

February 2009

--

-- The MGMD Host Interface Table

--

mgmdHostInterfaceTable OBJECT-TYPE

SYNTAX SEQUENCE OF MgmdHostInterfaceEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The (conceptual) table listing the interfaces on which
IGMP or MLD is enabled."

::= { mgmdMIBObjects 1 }

mgmdHostInterfaceEntry OBJECT-TYPE

SYNTAX MgmdHostInterfaceEntry
 MAX-ACCESS not-accessible
 STATUS current
 DESCRIPTION
 "An entry (conceptual row) representing an interface on
 which IGMP or MLD is enabled."
 INDEX { mgmdHostInterfaceIfIndex,
 mgmdHostInterfaceQuerierType }

 ::= { mgmdHostInterfaceTable 1 }

MgmdHostInterfaceEntry ::= SEQUENCE {
 mgmdHostInterfaceIfIndex InterfaceIndex,
 mgmdHostInterfaceQuerierType InetAddressType,
 mgmdHostInterfaceQuerier InetAddress,
 mgmdHostInterfaceStatus RowStatus,
 mgmdHostInterfaceVersion Unsigned32,
 mgmdHostInterfaceVersion1QuerierTimer TimeTicks,
 mgmdHostInterfaceVersion2QuerierTimer TimeTicks,
 mgmdHostInterfaceVersion3Robustness Unsigned32
 }

mgmdHostInterfaceIfIndex OBJECT-TYPE

SYNTAX InterfaceIndex
 MAX-ACCESS not-accessible
 STATUS current
 DESCRIPTION
 "The ifIndex value of the interface for which IGMP or MLD
 is enabled. The table is indexed by the ifIndex value and
 the InetAddressType to allow for interfaces which may be
 configured in both IPv4 and IPv6 modes."

::= { mgmdHostInterfaceEntry 1 }

mgmdHostInterfaceQuerierType OBJECT-TYPE

SYNTAX InetAddressType { ipv4(1), ipv6(2) }
 MAX-ACCESS not-accessible
 STATUS current
 DESCRIPTION

 "The address type of this interface. This entry along with

the ifIndex value acts as an index to the mgmdHostInterface table. A physical interface may be configured in multiple modes concurrently, e.g. in IPv4 and IPv6 modes connected to the same interface, however the traffic is considered to be logically separate."

::= { mgmdHostInterfaceEntry 2 }

mgmdHostInterfaceQuerier OBJECT-TYPE

SYNTAX InetAddress (SIZE(4|16))

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The address of the IGMP or MLD Querier on the IP subnet to which this interface is attached. The InetAddressType, e.g. IPv4 or IPv6, is identified by the mgmdHostInterfaceQuerierType variable in the mgmdHostInterface table."

::= { mgmdHostInterfaceEntry 3 }

mgmdHostInterfaceStatus OBJECT-TYPE

SYNTAX RowStatus

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The activation of a row enables the host side of IGMP or MLD on the interface. The destruction of a row disables the host side of IGMP or MLD on the interface."

::= { mgmdHostInterfaceEntry 4 }

mgmdHostInterfaceVersion OBJECT-TYPE

SYNTAX Unsigned32 (1..3)

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The maximum version of MGMD which the host can run on this interface. A value of 1 is only applicable for IPv4, and indicates that the host only supports IGMPv1 on the

interface. A value of 2 indicates that the host also

supports IGMPv2 (for IPv4) or MLDv1 (for IPv6). A value of 3 indicates that the host also supports IGMPv3 (for IPv4) or MLDv2 (for IPv6)."

DEFVAL { 3 }

::= { mgmdHostInterfaceEntry 5 }

mgmdHostInterfaceVersion1QuerierTimer OBJECT-TYPE

SYNTAX TimeTicks

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The time remaining until the host assumes that there are no IGMPv1 routers present on the interface. While this is non-zero, the host will reply to all queries with version 1 membership reports. This variable applies to IGMPv2 or 3 hosts that are forced to run in v1 for compatibility with v1 routers present on the interface. This object may only be present when the corresponding value of mgmdHostInterfaceQuerierType is ipv4."

REFERENCE "[RFC 2236 section 4](#) and [RFC 3376 section 7.2.1](#)"

DEFVAL { 0 }

::= { mgmdHostInterfaceEntry 6 }

mgmdHostInterfaceVersion2QuerierTimer OBJECT-TYPE

SYNTAX TimeTicks

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The time remaining until the host assumes that there are no MGDv2 routers present on the interface. While this is non-zero, the host will reply to all queries with version 1 or 2 membership reports. This variable applies to MGDv3 hosts that are forced to run in v2 for compatibility with v2 hosts or routers present on the interface."

REFERENCE "[RFC 3376 section 7.2.1](#) and [RFC 3810 section 8.2.1](#)"

DEFVAL { 0 }

::= { mgmdHostInterfaceEntry 7 }

mgmdHostInterfaceVersion3Robustness OBJECT-TYPE

SYNTAX Unsigned32

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The robustness variable utilised by an MGDv3 host in

sending state-change reports for multicast routers. To ensure the state-change report is not missed, the host retransmits the state-change report [mgmdHostInterfaceVersion3Robustness - 1] times. The variable must be a non-zero value."

REFERENCE "[RFC 3376 section 8.1](#) and [RFC 3810 section 9.14.1](#)"

DEFVAL { 2 }

::= { mgmdHostInterfaceEntry 8 }

--

-- The MGMD Router Interface Table

--

mgmdRouterInterfaceTable OBJECT-TYPE

SYNTAX SEQUENCE OF MgmdRouterInterfaceEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The (conceptual) table listing the interfaces on which IGMP or MLD is enabled."

::= { mgmdMIBObjects 2 }

mgmdRouterInterfaceEntry OBJECT-TYPE

SYNTAX MgmdRouterInterfaceEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"An entry (conceptual row) representing an interface on which IGMP or MLD is enabled."

INDEX { mgmdRouterInterfaceIfIndex,
mgmdRouterInterfaceQuerierType }

::= { mgmdRouterInterfaceTable 1 }

MgmdRouterInterfaceEntry ::= SEQUENCE {

mgmdRouterInterfaceIfIndex	InterfaceIndex,
mgmdRouterInterfaceQuerierType	InetAddressType,
mgmdRouterInterfaceQuerier	InetAddress,
mgmdRouterInterfaceQueryInterval	Unsigned32,
mgmdRouterInterfaceStatus	RowStatus,
mgmdRouterInterfaceVersion	Unsigned32,
mgmdRouterInterfaceQueryMaxResponseTime	Unsigned32,
mgmdRouterInterfaceQuerierUpTime	TimeTicks,

mgmdRouterInterfaceQuerierExpiryTime	TimeTicks,
mgmdRouterInterfaceWrongVersionQueries	Counter32,

Internet-Draft

MGMD MIB

February 2009

mgmdRouterInterfaceJoins	Counter32,
mgmdRouterInterfaceProxyIfIndex	InterfaceIndexOrZero,
mgmdRouterInterfaceGroups	Gauge32,
mgmdRouterInterfaceRobustness	Unsigned32,
mgmdRouterInterfaceLastMemberQueryInterval	Unsigned32,
mgmdRouterInterfaceLastMemberQueryCount	Unsigned32,
mgmdRouterInterfaceStartupQueryCount	Unsigned32,
mgmdRouterInterfaceStartupQueryInterval	Unsigned32

}

mgmdRouterInterfaceIfIndex OBJECT-TYPE

SYNTAX InterfaceIndex

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The ifIndex value of the interface for which IGMP or MLD is enabled. The table is indexed by the ifIndex value and the InetAddressType to allow for interfaces which may be configured in both IPv4 and IPv6 modes."

::= { mgmdRouterInterfaceEntry 1 }

mgmdRouterInterfaceQuerierType OBJECT-TYPE

SYNTAX InetAddressType { ipv4(1), ipv6(2) }

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The address type of this interface. This entry along with the ifIndex value acts as the index to the mgmdRouterInterface table. A physical interface may be configured in multiple modes concurrently, e.g. in IPv4 and IPv6 modes connected to the same interface, however the traffic is considered to be logically separate."

::= { mgmdRouterInterfaceEntry 2 }

mgmdRouterInterfaceQuerier OBJECT-TYPE

SYNTAX InetAddress (SIZE(4|16))

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The address of the IGMP or MLD Querier on the IP subnet to which this interface is attached. The InetAddressType, e.g. IPv4 or IPv6, is identified by the mgmdRouterInterfaceQuerierType variable in the mgmdRouterInterface table."

::= { mgmdRouterInterfaceEntry 3 }

mgmdRouterInterfaceQueryInterval OBJECT-TYPE

SYNTAX Unsigned32 (1..31744)

UNITS "seconds"

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The frequency at which IGMP or MLD Host-Query packets are transmitted on this interface."

DEFVAL { 125 }

::= { mgmdRouterInterfaceEntry 4 }

mgmdRouterInterfaceStatus OBJECT-TYPE

SYNTAX RowStatus

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The activation of a row enables the router side of IGMP or MLD on the interface. The destruction of a row disables the router side of IGMP or MLD on the interface."

::= { mgmdRouterInterfaceEntry 5 }

mgmdRouterInterfaceVersion OBJECT-TYPE

SYNTAX Unsigned32 (1..3)

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The version of MGMD which is running on this interface. Value 1 applies to IGMPv1 routers only. Value 2 applies

To IGMPv2 and MLDv1 routers, and value 3 applies to IGMPv3 and MLDv2 routers.

This object can be used to configure a router capable of running either version. For IGMP and MLD to function correctly, all routers on a LAN must be configured to run the same version on that LAN."

DEFVAL { 3 }

::= { mgmdRouterInterfaceEntry 6 }

mgmdRouterInterfaceQueryMaxResponseTime OBJECT-TYPE

SYNTAX Unsigned32 (0..31744)

UNITS "tenths of seconds"

MAX-ACCESS read-create

STATUS current

DESCRIPTION

Chesterfield & Haberman Expires August 13, 2009

[Page 11]

Internet-Draft

MGMD MIB

February 2009

"The maximum query response interval advertised in MGMDv2 or IGMPv3 queries on this interface."

REFERENCE "[RFC 3810 section 9.3](#)"

DEFVAL { 100 }

::= { mgmdRouterInterfaceEntry 7 }

mgmdRouterInterfaceQuerierUpTime OBJECT-TYPE

SYNTAX TimeTicks

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The time since mgmdRouterInterfaceQuerier was last changed."

::= { mgmdRouterInterfaceEntry 8 }

mgmdRouterInterfaceQuerierExpiryTime OBJECT-TYPE

SYNTAX TimeTicks

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The amount of time remaining before the Other Querier

Present Timer expires. If the local system is the querier, the value of this object is zero."

::= { mgmdRouterInterfaceEntry 9 }

mgmdRouterInterfaceWrongVersionQueries OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of general queries received whose IGMP or MLD version does not match the equivalent mgmdRouterInterfaceVersion, over the lifetime of the row entry. Both IGMP and MLD require that all routers on a LAN be configured to run the same version. Thus, if any general queries are received with the wrong version, this indicates a configuration error."

::= { mgmdRouterInterfaceEntry 10 }

mgmdRouterInterfaceJoins OBJECT-TYPE

SYNTAX Counter32

Chesterfield & Haberman Expires August 13, 2009

[Page 12]

Internet-Draft

MGMD MIB

February 2009

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of times a group membership has been added on this interface; that is, the number of times an entry for this interface has been added to the Cache Table. This object can give an indication of the amount of activity between samples over time."

::= { mgmdRouterInterfaceEntry 11 }

mgmdRouterInterfaceProxyIfIndex OBJECT-TYPE

SYNTAX InterfaceIndexOrZero

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"Some devices implement a form of IGMP or MLD proxying whereby memberships learned on the interface represented by

this row, cause Host Membership Reports to be sent on the interface whose ifIndex value is given by this object. Such a device would implement the mgmdV2RouterBaseMIBGroup only on its router interfaces (those interfaces with non-zero mgmdRouterInterfaceProxyIfIndex). Typically, the value of this object is 0, indicating that no proxying is being done."

DEFVAL { 0 }

::= { mgmdRouterInterfaceEntry 12 }

mgmdRouterInterfaceGroups OBJECT-TYPE

SYNTAX Gauge32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The current number of entries for this interface in the mgmdRouterCacheTable."

::= { mgmdRouterInterfaceEntry 13 }

mgmdRouterInterfaceRobustness OBJECT-TYPE

SYNTAX Unsigned32 (1..255)

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The Robustness Variable allows tuning for the expected packet loss on a subnet. If a subnet is expected to be lossy, the Robustness Variable may be increased. IGMP and MLD are robust to (Robustness Variable-1) packet losses."

DEFVAL { 2 }

::= { mgmdRouterInterfaceEntry 14 }

mgmdRouterInterfaceLastMemberQueryInterval OBJECT-TYPE

SYNTAX Unsigned32 (0..31744)

UNITS "tenths of seconds"

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The Last Member Query Interval is the Max Query Response

Interval inserted into group-specific queries sent in response to leave group messages, and is also the amount of time between group-specific query messages. This value may be tuned to modify the leave latency of the network. A reduced value results in reduced time to detect the loss of the last member of a group. The value of this object is irrelevant if mgmdRouterInterfaceVersion is 1."

DEFVAL { 10 }

::= { mgmdRouterInterfaceEntry 15 }

mgmdRouterInterfaceLastMemberQueryCount OBJECT-TYPE

SYNTAX Unsigned32 (1..255)

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Represents the number of group-specific and group-and-source-specific queries sent by the router before it assumes there are no local members."

::= { mgmdRouterInterfaceEntry 16 }

mgmdRouterInterfaceStartupQueryCount OBJECT-TYPE

SYNTAX Unsigned32 (1..255)

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Represents the number of Queries sent out on startup separated by the Startup Query Interval."

::= { mgmdRouterInterfaceEntry 17 }

mgmdRouterInterfaceStartupQueryInterval OBJECT-TYPE

SYNTAX Unsigned32 (0..31744)

UNITS "seconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"This variable represents the interval between General Queries sent by a Querier on startup."


```

 ::= { mgmdRouterInterfaceEntry 18 }

--
-- The MGMT Host Cache Table
--

mgmdHostCacheTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF MgmdHostCacheEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The (conceptual) table listing the IP multicast groups for
         which the host is a member on a particular interface."

    ::= { mgmdMIBObjects 3 }

mgmdHostCacheEntry OBJECT-TYPE
    SYNTAX      MgmdHostCacheEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An entry (conceptual row) in the mgmdHostCacheTable."
    INDEX       { mgmdHostCacheAddressType, mgmdHostCacheAddress,
                  mgmdHostCacheIfIndex }

    ::= { mgmdHostCacheTable 1 }

MgmdHostCacheEntry ::= SEQUENCE {
    mgmdHostCacheAddressType      InetAddressType,
    mgmdHostCacheAddress          InetAddress ,
    mgmdHostCacheIfIndex          InterfaceIndex,
    mgmdHostCacheUpTime           TimeTicks,
    mgmdHostCacheLastReporter     InetAddress,
    mgmdHostCacheSourceFilterMode INTEGER
}

mgmdHostCacheAddressType OBJECT-TYPE
    SYNTAX      InetAddressType { ipv4(1), ipv6(2) }
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The address type of the mgmdHostCacheTable entry. This
         value applies to both the mgmdHostCacheAddress and the

```

mgmdHostCacheLastReporter entries."

::= { mgmdHostCacheEntry 1 }

mgmdHostCacheAddress OBJECT-TYPE

SYNTAX InetAddress (SIZE(4|16))

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The IP multicast group address for which this entry contains information. The InetAddressType, e.g. IPv4 or IPv6, is identified by the mgmdHostCacheAddressType variable in the mgmdHostCache table."

::= { mgmdHostCacheEntry 2 }

mgmdHostCacheIfIndex OBJECT-TYPE

SYNTAX InterfaceIndex

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The interface for which this entry contains information for an IP multicast group address."

::= { mgmdHostCacheEntry 3 }

mgmdHostCacheUpTime OBJECT-TYPE

SYNTAX TimeTicks

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The time elapsed since this entry was created."

::= { mgmdHostCacheEntry 4 }

mgmdHostCacheLastReporter OBJECT-TYPE

SYNTAX InetAddress (SIZE(4|16))

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The IP address of the source of the last membership report received for this IP Multicast group address on this interface. If no membership report has been received, this object has a value of 0. The InetAddressType, e.g. IPv4 or IPv6, is identified by the mgmdHostCacheAddressType variable in the mgmdHostCache table."

Internet-Draft

MGMD MIB

February 2009

```
::= { mgmdHostCacheEntry 5 }
```

```
mgmdHostCacheSourceFilterMode OBJECT-TYPE
```

```
SYNTAX      INTEGER {include (1),  
                      exclude (2) }
```

```
MAX-ACCESS  read-only
```

```
STATUS      current
```

```
DESCRIPTION
```

```
    "The state in which the interface is currently set. The  
    value indicates the relevance of the corresponding source  
    list entries in the mgmdHostSecListTable for MGMDv3  
    interfaces."
```

```
::= { mgmdHostCacheEntry 6 }
```

```
--
```

```
-- The MGMD Router Cache Table
```

```
--
```

```
mgmdRouterCacheTable OBJECT-TYPE
```

```
SYNTAX      SEQUENCE OF MgmdRouterCacheEntry
```

```
MAX-ACCESS  not-accessible
```

```
STATUS      current
```

```
DESCRIPTION
```

```
    "The (conceptual) table listing the IP multicast groups for  
    which there are members on a particular router interface."
```

```
::= { mgmdMIBObjects 4 }
```

```
mgmdRouterCacheEntry OBJECT-TYPE
```

```
SYNTAX      MgmdRouterCacheEntry
```

```
MAX-ACCESS  not-accessible
```

```
STATUS      current
```

```
DESCRIPTION
```

```
    "An entry (conceptual row) in the mgmdRouterCacheTable."
```

```
INDEX      { mgmdRouterCacheAddressType, mgmdRouterCacheAddress,  
             mgmdRouterCacheIfIndex }
```

```
::= { mgmdRouterCacheTable 1 }
```

```

MgmdRouterCacheEntry ::= SEQUENCE {
    mgmdRouterCacheAddressType      InetAddressType,
    mgmdRouterCacheAddress          InetAddress,
    mgmdRouterCacheIfIndex          InterfaceIndex,
    mgmdRouterCacheLastReporter     InetAddress,
    mgmdRouterCacheUpTime           TimeTicks,

```

```

    mgmdRouterCacheExpiryTime       TimeTicks,
    mgmdRouterCacheExcludeModeExpiryTimer
                                     TimeTicks,
    mgmdRouterCacheVersion1HostTimer TimeTicks,
    mgmdRouterCacheVersion2HostTimer TimeTicks,
    mgmdRouterCacheSourceFilterMode INTEGER
}

```

mgmdRouterCacheAddressType OBJECT-TYPE

SYNTAX InetAddressType { ipv4(1), ipv6(2) }

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The address type of the mgmdRouterCacheTable entry. This value applies to both the mgmdRouterCacheAddress and the mgmdRouterCacheLastReporter entries."

::= { mgmdRouterCacheEntry 1 }

mgmdRouterCacheAddress OBJECT-TYPE

SYNTAX InetAddress (SIZE(4|16))

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The IP multicast group address for which this entry contains information. The InetAddressType, e.g. IPv4 or IPv6, is identified by the mgmdRouterCacheAddressType variable in the mgmdRouterCache table."

::= { mgmdRouterCacheEntry 2 }

mgmdRouterCacheIfIndex OBJECT-TYPE

SYNTAX InterfaceIndex
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
 "The interface for which this entry contains information
 for an IP multicast group address."

::= { mgmdRouterCacheEntry 3 }

mgmdRouterCacheLastReporter OBJECT-TYPE

SYNTAX InetAddress (SIZE(4|16))
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The IP address of the source of the last membership report

received for this IP Multicast group address on this
interface. If no membership report has been received, this
object has the value 0. The InetAddressType, e.g.
IPv4 or IPv6, is identified by the
mgmdRouterCacheAddressType variable in the mgmdRouterCache
table."

::= { mgmdRouterCacheEntry 4 }

mgmdRouterCacheUpTime OBJECT-TYPE

SYNTAX TimeTicks
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The time elapsed since this entry was created."

::= { mgmdRouterCacheEntry 5 }

mgmdRouterCacheExpiryTime OBJECT-TYPE

SYNTAX TimeTicks
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "This value represents the time remaining
 before the Group Membership Interval state expires. The
 value must always be greater than or equal to 1."

::= { mgmdRouterCacheEntry 6 }

mgmdRouterCacheExcludeModeExpiryTimer OBJECT-TYPE

SYNTAX TimeTicks

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"This value is applicable only to MGMDv3 compatible nodes, and represents the time remaining before the interface EXCLUDE state expires and the interface state transitions to INCLUDE mode. This value can never be greater than mgmdRouterCacheExpiryTime."

::= { mgmdRouterCacheEntry 7 }

mgmdRouterCacheVersion1HostTimer OBJECT-TYPE

SYNTAX TimeTicks

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The time remaining until the local router will assume that

there are no longer any MGMD version 1 members on the IP subnet attached to this interface. This entry only applies to IGMPv1 hosts, and is not implemented for MLD. Upon hearing any MGMDv1 Membership Report (IGMPv1 only), this value is reset to the group membership timer. While this time remaining is non-zero, the local router ignores any MGMDv2 Leave messages (IGMPv2 only) for this group that it receives on this interface."

::= { mgmdRouterCacheEntry 8 }

mgmdRouterCacheVersion2HostTimer OBJECT-TYPE

SYNTAX TimeTicks

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The time remaining until the local router will assume that there are no longer any MGMD version 2 members on the IP subnet attached to this interface. This entry applies to

both IGMP and MLD hosts. Upon hearing any MGMTv2 Membership Report, this value is reset to the group membership timer. Assuming no MGMTv1 hosts have been detected, the local router does not ignore any MGMTv2 Leave messages for this group that it receives on this interface."

::= { mgmdRouterCacheEntry 9 }

mgmdRouterCacheSourceFilterMode OBJECT-TYPE

SYNTAX INTEGER {include (1),
exclude (2) }

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The current cache state, applicable to MGMTv3 compatible nodes. The value indicates whether the state is INCLUDE or EXCLUDE."

::= { mgmdRouterCacheEntry 10 }

--

-- The MGMT Inverse Host interface/cache lookup Table

--

mgmdInverseHostCacheTable OBJECT-TYPE

SYNTAX SEQUENCE OF MgmdInverseHostCacheEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The (conceptual) table listing the interfaces which are members of a particular group. This is an inverse lookup table for entries in the mgmdHostCacheTable."

::= { mgmdMIBObjects 5 }

mgmdInverseHostCacheEntry OBJECT-TYPE

SYNTAX MgmdInverseHostCacheEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

```

        "An entry (conceptual row) in the
        mgmdInverseHostCacheTable."
INDEX      { mgmdInverseHostCacheIfIndex,
              mgmdInverseHostCacheAddressType,
              mgmdInverseHostCacheAddress}

```

```

 ::= { mgmdInverseHostCacheTable 1 }

```

```

MgmdInverseHostCacheEntry ::= SEQUENCE {
    mgmdInverseHostCacheIfIndex      InterfaceIndex,
    mgmdInverseHostCacheAddressType  InetAddressType,
    mgmdInverseHostCacheAddress      InetAddress
}

```

```

mgmdInverseHostCacheIfIndex OBJECT-TYPE
    SYNTAX      InterfaceIndex
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The interface for which this entry contains information."

 ::= { mgmdInverseHostCacheEntry 1 }

```

```

mgmdInverseHostCacheAddressType OBJECT-TYPE
    SYNTAX      InetAddressType { ipv4(1), ipv6(2) }
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The address type of the mgmdInverseHostCacheTable entry."

 ::= { mgmdInverseHostCacheEntry 2 }

```

```

mgmdInverseHostCacheAddress OBJECT-TYPE
    SYNTAX      InetAddress (SIZE(4|16))

```

```

MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The IP multicast group address for which this entry
    contains information about an interface. The

```


InetAddressType, e.g. IPv4 or IPv6, is identified by the mgmdInverseHostCacheAddressType variable in the mgmdInverseHostCache table."

::= { mgmdInverseHostCacheEntry 3 }

--
--
--

The MGMT Inverse Router interface/cache lookup Table

mgmdInverseRouterCacheTable OBJECT-TYPE

SYNTAX SEQUENCE OF MgmdInverseRouterCacheEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The (conceptual) table listing the interfaces which are members of a particular group. This is an inverse lookup table for entries in the mgmdRouterCacheTable."

::= { mgmdMIBObjects 6 }

mgmdInverseRouterCacheEntry OBJECT-TYPE

SYNTAX MgmdInverseRouterCacheEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"An entry (conceptual row) in the mgmdInverseRouterCacheTable."

INDEX { mgmdInverseRouterCacheIfIndex,
mgmdInverseRouterCacheAddressType,
mgmdInverseRouterCacheAddress }

::= { mgmdInverseRouterCacheTable 1 }

MgmdInverseRouterCacheEntry ::= SEQUENCE {

mgmdInverseRouterCacheIfIndex	InterfaceIndex,
mgmdInverseRouterCacheAddressType	InetAddressType,
mgmdInverseRouterCacheAddress	InetAddress

}

mgmdInverseRouterCacheIfIndex OBJECT-TYPE

SYNTAX InterfaceIndex

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The interface for which this entry contains information
for an IP multicast group address."

::= { mgmdInverseRouterCacheEntry 1 }

mgmdInverseRouterCacheAddressType OBJECT-TYPE

SYNTAX InetAddressType { ipv4(1), ipv6(2) }

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The address type of the mgmdInverseRouterCacheTable entry."

::= { mgmdInverseRouterCacheEntry 2 }

mgmdInverseRouterCacheAddress OBJECT-TYPE

SYNTAX InetAddress (SIZE(4|16))

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The IP multicast group address for which this entry
contains information. The InetAddressType, e.g.
IPv4 or IPv6, is identified by the
mgmdInverseRouterCacheAddressType variable in the
mgmdInverseRouterCache table."

::= { mgmdInverseRouterCacheEntry 3 }

--

-- The MGMD Host Source list Table

--

mgmdHostSrcListTable OBJECT-TYPE

SYNTAX SEQUENCE OF MgmdHostSrcListEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The (conceptual) table listing the Source List entries
corresponding to each interface and multicast group pair
on a host."

::= { mgmdMIBObjects 7 }

Internet-Draft

MGMD MIB

February 2009

mgmdHostSrcListEntry OBJECT-TYPE

SYNTAX MgmdHostSrcListEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"An entry (conceptual row) in the mgmdHostSrcListTable."

INDEX { mgmdHostSrcListAddressType, mgmdHostSrcListAddress,
mgmdHostSrcListIfIndex, mgmdHostSrcListHostAddress }

::= { mgmdHostSrcListTable 1 }

MgmdHostSrcListEntry ::= SEQUENCE {

mgmdHostSrcListAddressType InetAddressType,

mgmdHostSrcListAddress InetAddress,

mgmdHostSrcListIfIndex InterfaceIndex,

mgmdHostSrcListHostAddress InetAddress,

mgmdHostSrcListExpire TimeTicks

}

mgmdHostSrcListAddressType OBJECT-TYPE

SYNTAX InetAddressType { ipv4(1), ipv6(2) }

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The address type of the InetAddress variables in this
table. This value applies to the mgmdHostSrcListHostAddress
and mgmdHostSrcListAddress entries."

::= { mgmdHostSrcListEntry 1 }

mgmdHostSrcListAddress OBJECT-TYPE

SYNTAX InetAddress (SIZE(4|16))

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The IP multicast group address for which this entry
contains information."

::= { mgmdHostSrcListEntry 2 }

mgmdHostSrcListIfIndex OBJECT-TYPE

SYNTAX InterfaceIndex
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
 "The interface for which this entry contains information
 for an IP multicast group address."

::= { mgmdHostSrcListEntry 3 }

mgmdHostSrcListHostAddress OBJECT-TYPE

SYNTAX InetAddress (SIZE(4|16))
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
 "The host address to which this entry
 corresponds. The mgmdHostCacheSourceFilterMode value for
 this Group address and interface indicates whether this
 Host address is included or excluded."

::= { mgmdHostSrcListEntry 4 }

mgmdHostSrcListExpire OBJECT-TYPE

SYNTAX TimeTicks
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "This value indicates the relevance of the SrcList entry,
 whereby a non-zero value indicates this is an INCLUDE state
 value, and a zero value indicates this to be an EXCLUDE
 state value."

::= { mgmdHostSrcListEntry 5 }

--
-- The MGMD Router Source list Table
--

mgmdRouterSrcListTable OBJECT-TYPE

SYNTAX SEQUENCE OF MgmdRouterSrcListEntry
MAX-ACCESS not-accessible
STATUS current

DESCRIPTION

"The (conceptual) table listing the Source List entries corresponding to each interface and multicast group pair on a Router."

::= { mgmdMIBObjects 8 }

mgmdRouterSrcListEntry OBJECT-TYPE

SYNTAX MgmdRouterSrcListEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"An entry (conceptual row) in the mgmdRouterSrcListTable."

INDEX { mgmdRouterSrcListAddressType, mgmdRouterSrcListAddress,
mgmdRouterSrcListIfIndex, mgmdRouterSrcListHostAddress }

::= { mgmdRouterSrcListTable 1 }

MgmdRouterSrcListEntry ::= SEQUENCE {

mgmdRouterSrcListAddressType InetAddressType,

mgmdRouterSrcListAddress InetAddress,

mgmdRouterSrcListIfIndex InterfaceIndex,

mgmdRouterSrcListHostAddress InetAddress,

mgmdRouterSrcListExpire TimeTicks

}

mgmdRouterSrcListAddressType OBJECT-TYPE

SYNTAX InetAddressType { ipv4(1), ipv6(2) }

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The address type of the InetAddress variables in this table. This value applies to the mgmdRouterSrcListHostAddress and mgmdRouterSrcListAddress entries."

::= { mgmdRouterSrcListEntry 1 }

mgmdRouterSrcListAddress OBJECT-TYPE

SYNTAX InetAddress (SIZE(4|16))

MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
 "The IP multicast group address for which this entry
 contains information."

::= { mgmdRouterSrcListEntry 2 }

mgmdRouterSrcListIfIndex OBJECT-TYPE

SYNTAX InterfaceIndex
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
 "The interface for which this entry contains information
 for an IP multicast group address."

::= { mgmdRouterSrcListEntry 3 }

mgmdRouterSrcListHostAddress OBJECT-TYPE

SYNTAX InetAddress (SIZE(4|16))
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
 "The host address to which this entry
 corresponds. The mgmdRouterCacheSourceFilterMode value for
 this Group address and interface indicates whether this
 Host address is included or excluded."

::= { mgmdRouterSrcListEntry 4 }

mgmdRouterSrcListExpire OBJECT-TYPE

SYNTAX TimeTicks
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "This value indicates the relevance of the SrcList entry,
 whereby a non-zero value indicates this is an INCLUDE state
 value, and a zero value indicates this to be an EXCLUDE
 state value."

```

        ::= { mgmdRouterSrcListEntry 5 }

-- conformance information

mgmdMIBConformance OBJECT IDENTIFIER ::= { mgmdStdMIB 2 }
mgmdMIBCompliance  OBJECT IDENTIFIER ::= { mgmdMIBConformance 1 }
mgmdMIBGroups       OBJECT IDENTIFIER ::= { mgmdMIBConformance 2 }

-- Protocol Version Conformance

-- Read Compliance statement for IGMPv1 Hosts
-- IGMPv1 only supports the IPv4 Address Family

mgmdIgmpV1HostReadMIBCompliance MODULE-COMPLIANCE
    STATUS current
    DESCRIPTION
        "A read-only compliance statement for hosts running IGMPv1
        [RFC 1112] and implementing the MGMT MIB. IGMPv1 hosts must
        support the IPv4 address type."
    MODULE -- this module
    MANDATORY-GROUPS { mgmdHostBaseMIBGroup }

    OBJECT mgmdHostInterfaceStatus
    SYNTAX RowStatus {active(1)}
    MIN-ACCESS read-only

```

```

DESCRIPTION
    "read-write or read-create access is not required and only
    the value 'active(1)' needs to be supported."

OBJECT mgmdHostInterfaceVersion
SYNTAX Unsigned32 (1)
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required. Only version 1 needs to be
    supported."

GROUP mgmdHostExtendedMIBGroup
DESCRIPTION
    "Supporting this group can be especially useful in

```

an environment with a router which does not support the
MGMD MIB."

::= { mgmdMIBCompliance 1 }

-- Read Compliance statement for IGMPv1 Routers
-- IGMPv1 only supports the IPv4 Address Family

mgmdIgmpV1RouterReadMIBCompliance MODULE-COMPLIANCE

STATUS current

DESCRIPTION

"A read-only compliance statement for routers running
IGMPv1 [[RFC 1112](#)] and implementing the MGMD MIB. IGMPv1
routers only support the IPv4 address type.

Non-accessible index objects that only need IPv4
support are:

OBJECT mgmdRouterCacheAddressType
SYNTAX InetAddressType { ipv4(1) }

OBJECT mgmdRouterCacheAddress
SYNTAX InetAddress (SIZE(4))

OBJECT mgmdRouterInterfaceQuerierType
SYNTAX InetAddressType { ipv4(1) }

OBJECT mgmdInverseRouterCacheAddressType
SYNTAX InetAddressType { ipv4(1) }
"

MODULE -- this module

MANDATORY-GROUPS { mgmdRouterBaseMIBGroup }

OBJECT mgmdRouterCacheLastReporter

SYNTAX InetAddress (SIZE(4))

DESCRIPTION

"IGMPv1 routers only support IPv4 addresses."

OBJECT mgmdRouterInterfaceQuerier

SYNTAX InetAddress (SIZE(4))

DESCRIPTION

"IGMPv1 routers only support IPv4 addresses."

OBJECT mgmdInverseRouterCacheAddress

SYNTAX InetAddress (SIZE(4))

DESCRIPTION

"IGMPv1 routers only support IPv4 addresses."

OBJECT mgmdRouterInterfaceVersion

SYNTAX Unsigned32 (1)

MIN-ACCESS read-only

DESCRIPTION

"Write access is not required. Only version 1 needs to be supported."

OBJECT mgmdRouterInterfaceStatus

SYNTAX RowStatus {active(1)}

MIN-ACCESS read-only

DESCRIPTION

"read-write or read-create access is not required and only the value 'active(1)' needs to be supported."

OBJECT mgmdRouterInterfaceQueryInterval

MIN-ACCESS read-only

DESCRIPTION

"Write access is not required."

::= { mgmdMIBCompliance 2 }

-- Write Compliance statement for IGMPv1 Routers

-- IGMPv1 only supports the IPv4 Address Family

mgmdIgmpV1RouterWriteMIBCompliance MODULE-COMPLIANCE

STATUS current

DESCRIPTION

"A read-create compliance statement for routers running IGMPv1 [[RFC 1112](#)] and implementing the MGMD MIB. IGMPv1 routers only support the IPv4 address type.

Non-accessible index objects that only need IPv4 support are:

```

OBJECT mgmdRouterCacheAddressType
SYNTAX InetAddressType { ipv4(1) }

OBJECT mgmdRouterCacheAddress
SYNTAX InetAddress (SIZE(4))

OBJECT mgmdRouterInterfaceQuerierType
SYNTAX InetAddressType { ipv4(1) }

OBJECT mgmdInverseRouterCacheAddressType
SYNTAX InetAddressType { ipv4(1) }
"
MODULE -- this module
MANDATORY-GROUPS { mgmdRouterBaseMIBGroup }

OBJECT mgmdRouterCacheLastReporter
SYNTAX InetAddress (SIZE(4))
DESCRIPTION
    "Only IPv4 addresses needed for IGMPv1 router support."

OBJECT mgmdRouterInterfaceQuerier
SYNTAX InetAddress (SIZE(4))
DESCRIPTION
    "Only IPv4 addresses needed for IGMPv1 router support."

OBJECT mgmdInverseRouterCacheAddress
SYNTAX InetAddress (SIZE(4))
DESCRIPTION
    "Only IPv4 addresses needed for IGMPv1 router support."

OBJECT mgmdRouterInterfaceVersion
SYNTAX Unsigned32 (1)
DESCRIPTION
    "Write access is not required. Only version 1 needs to
    be supported."

 ::= { mgmdMIBCompliance 3 }

-- Read Compliance statement for IGMPv2 and MLDv1 Hosts
-- IGMPv2 only supports the IPv4 Address Family
-- MLDv1 only supports the IPv6 Address Family

mgmdIgmpV2MldV1HostReadMIBCompliance MODULE-COMPLIANCE
STATUS current
DESCRIPTION
    "A read-only compliance statement for hosts running IGMPv2
    [RFC 2236] or MLDv1 [RFC 2710] and implementing the MGMD
    MIB. IGMPv2 hosts only support the IPv4 address type and

```

Internet-Draft

MGMD MIB

February 2009

```
        MLDv1 hosts only support the IPv6 address type."
MODULE  -- this module
MANDATORY-GROUPS { mgmdHostBaseMIBGroup,
                    mgmdV2HostMIBGroup
                  }

OBJECT mgmdHostInterfaceStatus
SYNTAX RowStatus {active(1)}
MIN-ACCESS read-only
DESCRIPTION
    "Read-write or read-create access is not required and only
    the value 'active(1)' needs to be supported."

OBJECT mgmdHostInterfaceVersion
SYNTAX Unsigned32 (1..2)
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required.  Only versions 1 and 2 need
    to be supported."

GROUP   mgmdHostExtendedMIBGroup
DESCRIPTION
    "Supporting this group can be especially useful in
    an environment with a router which does not support the
    MGMD MIB."

 ::= { mgmdMIBCompliance 4 }

-- Write Compliance statement for IGMPv2 and MLDv1 Hosts
-- IGMPv2 only supports the IPv4 Address Family
-- MLDv1 only supports the IPv6 Address Family

mgmdIgmpV2MldV1HostWriteMIBCompliance MODULE-COMPLIANCE
    STATUS current
    DESCRIPTION
        "A read-create compliance statement for hosts running
        IGMPv2 [RFC 2236] or MLDv1 [RFC 2710] and implementing
        the MGMD MIB. IGMPv2 hosts only support the IPv4 address
        type and MLDv1 hosts only support the IPv6 address type."
    MODULE  -- this module
    MANDATORY-GROUPS { mgmdHostBaseMIBGroup,
                      mgmdV2HostMIBGroup }
```

OBJECT mgmdHostInterfaceVersion
SYNTAX Unsigned32 (1..2)
DESCRIPTION
 "Only versions 1 and 2 need to be supported."

::= { mgmdMIBCompliance 5 }

-- Read Compliance statement for IGMPv2 and MLDv1 Routers
-- IGMPv2 only supports the IPv4 Address Family
-- MLDv1 only supports the IPv6 Address Family

mgmdIgmpV2MldV1RouterReadMIBCompliance MODULE-COMPLIANCE

STATUS current

DESCRIPTION

 "A read-only compliance statement for routers running
 IGMPv2 [[RFC 2236](#)] or MLDv1 [[RFC 2710](#)] and implementing
 the MGMD MIB. IGMPv2 routers only support the IPv4
 address type and MLDv1 routers only support the IPv6
 address type."

MODULE -- this module

MANDATORY-GROUPS { mgmdRouterBaseMIBGroup,
 mgmdV2RouterBaseMIBGroup
 }

OBJECT mgmdRouterInterfaceLastMemberQueryInterval

MIN-ACCESS read-only

DESCRIPTION

 "Write access is not required."

OBJECT mgmdRouterInterfaceRobustness

MIN-ACCESS read-only

DESCRIPTION

 "Write access is not required."

OBJECT mgmdRouterInterfaceQueryMaxResponseTime

MIN-ACCESS read-only

DESCRIPTION

 "Write access is not required."

OBJECT mgmdRouterInterfaceVersion

SYNTAX Unsigned32 (1..2)

MIN-ACCESS read-only

DESCRIPTION

"Write access is not required. Only versions 1 and 2 need to be supported."

OBJECT mgmdRouterInterfaceStatus

SYNTAX RowStatus {active(1)}

MIN-ACCESS read-only

DESCRIPTION

"Read-write or read-create access is not required and only the value 'active(1)' needs to be supported."

Internet-Draft

MGMD MIB

February 2009

OBJECT mgmdRouterInterfaceQueryInterval

MIN-ACCESS read-only

DESCRIPTION

"Write access is not required."

GROUP mgmdV2ProxyMIBGroup

DESCRIPTION

"Write access is not required."

::= { mgmdMIBCompliance 6 }

-- Write Compliance statement for IGMPv2, IGMPv3, MLDv1 and MLDv2 Routers
-- IGMPv2 and IGMPv3 only support the IPv4 Address Family
-- MLDv1 and MLDv2 only support the IPv6 Address Family

mgmdIgmpV2V3MldV1V2RouterWriteMIBCompliance MODULE-COMPLIANCE

STATUS current

DESCRIPTION

"A read-create compliance statement for routers running IGMPv2 [[RFC 2236](#)], IGMPv3 [[RFC 3376](#)], MLDv1 [[RFC 2710](#)], or MLDv2 [[RFC 3810](#)] and implementing the MGMD MIB. IGMPv2 and IGMPv3 routers only support the IPv4 address type while MLDv1 and MLDv2 routers only support the IPv6 address type."

MODULE -- this module

MANDATORY-GROUPS { mgmdRouterBaseMIBGroup,
mgmdV2RouterBaseMIBGroup
}

GROUP mgmdV2ProxyMIBGroup

DESCRIPTION

"Read-create access is required."

::= { mgmdMIBCompliance 7 }

- Read Compliance statement for IGMPv2, IGMPv3, MLDv1 and MLDv2 Hosts
- IGMPv2 and IGMPv3 only support the IPv4 Address Family
- MLDv1 and MLDv2 only support the IPv6 Address Family

mgmdIgmpV3MldV2HostReadMIBCompliance MODULE-COMPLIANCE

STATUS current

DESCRIPTION

"The compliance statement for hosts running IGMPv3
[RFC 3376] or MLDv2 [RFC 3810] and implementing the
MGMD MIB. IGMPv3 hosts only support the IPv4 address
type and MLDv2 hosts only support the IPv6 address type."

MODULE -- this module

MANDATORY-GROUPS { mgmdHostBaseMIBGroup,
mgmdV2HostMIBGroup,

mgmdV3HostMIBGroup
}

OBJECT mgmdHostInterfaceVersion

MIN-ACCESS read-only

DESCRIPTION

"Write access is not required."

OBJECT mgmdHostInterfaceStatus

SYNTAX RowStatus {active(1)}

MIN-ACCESS read-only

DESCRIPTION

"Read-write or read-create access is not required and only
the value 'active(1)' needs to be supported."

OBJECT mgmdHostInterfaceVersion3Robustness

MIN-ACCESS read-only

DESCRIPTION

"Write access is not required."

GROUP mgmdHostExtendedMIBGroup

DESCRIPTION

"Supporting this group can be especially useful in an environment with a router which does not support the MGMT MIB."

::= { mgmtMIBCompliance 8 }

-- Write Compliance statement for IGMPv2, IGMPv3, MLDv1 and MLDv2 Hosts
-- IGMPv2 and IGMPv3 only support the IPv4 Address Family
-- MLDv1 and MLDv2 only support the IPv6 Address Family

mgmtIgmpV3MldV2HostWriteMIBCompliance MODULE-COMPLIANCE

STATUS current

DESCRIPTION

"The compliance statement for hosts running IGMPv3 [[RFC 3376](#)] or MLDv2 [[RFC 3810](#)] and implementing the MGMT MIB. IGMPv3 hosts only support the IPv4 address type and MLDv2 hosts only support the IPv6 address type."

MODULE -- this module

MANDATORY-GROUPS { mgmtHostBaseMIBGroup,
mgmtV2HostMIBGroup,
mgmtV3HostMIBGroup
}

GROUP mgmtHostExtendedMIBGroup

DESCRIPTION

"Supporting this group can be especially useful in

an environment with a router which does not support the MGMT MIB."

::= { mgmtMIBCompliance 9 }

-- Read Compliance statement for IGMPv2, IGMPv3, MLDv1 and MLDv2 Routers
-- IGMPv2 and IGMPv3 only support the IPv4 Address Family
-- MLDv1 and MLDv2 only support the IPv6 Address Family

mgmtIgmpV3MldV2RouterReadMIBCompliance MODULE-COMPLIANCE

STATUS current

DESCRIPTION

"A read-only compliance statement for routers running IGMPv3 [[RFC 3376](#)] or MLDv2 [[RFC 3810](#)] and implementing the MGMT MIB. IGMPv3 routers only support the IPv4

```

        address type and MLDv2 routers only support the IPv6
        address type."
MODULE -- this module
MANDATORY-GROUPS { mgmdRouterBaseMIBGroup,
                    mgmdV2RouterBaseMIBGroup,
                    mgmdV3RouterMIBGroup
                    }

OBJECT mgmdRouterInterfaceLastMemberQueryInterval
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT mgmdRouterInterfaceRobustness
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT mgmdRouterInterfaceQueryMaxResponseTime
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT mgmdRouterInterfaceVersion
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT mgmdRouterInterfaceStatus
SYNTAX RowStatus {active(1)}
MIN-ACCESS read-only
DESCRIPTION
    "read-write or read-create access is not required and only

```

```

        the value 'active(1)' needs to be supported."

OBJECT mgmdRouterInterfaceQueryInterval
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

GROUP mgmdV2ProxyMIBGroup

```


DESCRIPTION

"Write access is not required."

::= { mgmdMIBCompliance 10 }

-- units of conformance

mgmdHostBaseMIBGroup OBJECT-GROUP

OBJECTS { mgmdHostInterfaceStatus,
 mgmdHostInterfaceVersion
 }

STATUS current

DESCRIPTION

"The basic collection of objects providing management of
MGMD version 1, 2 or 3 for hosts."

::= { mgmdMIBGroups 1 }

mgmdRouterBaseMIBGroup OBJECT-GROUP

OBJECTS { mgmdRouterInterfaceStatus,
 mgmdRouterInterfaceQueryInterval,
 mgmdRouterCacheUpTime, mgmdRouterCacheExpiryTime,
 mgmdRouterInterfaceVersion,
 mgmdRouterInterfaceJoins, mgmdRouterInterfaceGroups,
 mgmdRouterCacheLastReporter,
 mgmdRouterInterfaceQuerierUpTime,
 mgmdRouterInterfaceQuerierExpiryTime,
 mgmdRouterInterfaceQuerier,
 mgmdInverseRouterCacheAddress
 }

STATUS current

DESCRIPTION

"The base collection of objects providing
management of MGMD version 1, 2 or 3 for routers."

::= { mgmdMIBGroups 2 }

mgmdV2HostMIBGroup OBJECT-GROUP

OBJECTS { mgmdHostInterfaceVersion1QuerierTimer
 }

STATUS current

DESCRIPTION

"A collection of additional read-only objects for management of IGMP version 2 in hosts for MGMD version 2 compliance."

::= { mgmdMIBGroups 3 }

mgmdHostExtendedMIBGroup OBJECT-GROUP

OBJECTS { mgmdHostCacheLastReporter, mgmdHostCacheUpTime,
mgmdHostInterfaceQuerier, mgmdInverseHostCacheAddress }

STATUS current

DESCRIPTION

"A collection of optional objects for MGMD hosts."

::= { mgmdMIBGroups 4 }

mgmdV2RouterBaseMIBGroup OBJECT-GROUP

OBJECTS { mgmdRouterInterfaceWrongVersionQueries,
mgmdRouterInterfaceLastMemberQueryCount,
mgmdRouterInterfaceStartupQueryCount,
mgmdRouterInterfaceStartupQueryInterval,
mgmdRouterCacheVersion1HostTimer,
mgmdRouterInterfaceQueryMaxResponseTime,
mgmdRouterInterfaceRobustness,
mgmdRouterInterfaceLastMemberQueryInterval
}

STATUS current

DESCRIPTION

"A collection of additional read-only objects for management of MGMD version 2 in routers."

::= { mgmdMIBGroups 5 }

mgmdV2ProxyMIBGroup OBJECT-GROUP

OBJECTS { mgmdRouterInterfaceProxyIfIndex }

STATUS current

DESCRIPTION

"A collection of additional read-create objects for management of MGMD proxy devices."

::= { mgmdMIBGroups 6 }

mgmdV3HostMIBGroup OBJECT-GROUP

OBJECTS { mgmdHostInterfaceVersion2QuerierTimer,
mgmdHostCacheSourceFilterMode,
mgmdHostInterfaceVersion3Robustness,
mgmdHostSrcListExpire

```
    }
    STATUS    current
    DESCRIPTION
        "A collection of additional objects for
        management of MGMD version 3 in hosts."

    ::= { mgmdMIBGroups 7 }

mgmdV3RouterMIBGroup OBJECT-GROUP
    OBJECTS { mgmdRouterCacheSourceFilterMode,
              mgmdRouterCacheVersion2HostTimer,
              mgmdRouterCacheExcludeModeExpiryTimer,
              mgmdRouterSrcListExpire
            }
    STATUS    current
    DESCRIPTION
        "A collection of additional read-only objects for
        management of MGMD version 3 in routers."

    ::= { mgmdMIBGroups 8 }

END
```

6. Security Considerations

There are a number of management objects defined in this MIB module with a MAX-ACCESS clause of read-write and/or read-create. Such objects may be considered sensitive or vulnerable in some network environments. The support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations. These are the tables and objects and their sensitivity/vulnerability:

- o The mgmdRouterInterfaceTable provides read-create access to 2 values; the mgmdRouterInterfaceStatus and the mgmdRouterInterfaceQueryInterval. The mgmdRouterInterfaceStatus presents a remote user with the ability to enable or disable multicast support on a given router interface, and therefore presents a significant denial of service vulnerability. The mgmdRouterInterfaceQueryInterval controls the frequency with which host-query packets are sent, providing less of a vulnerability, but still requiring secure access control.
- o The mgmdRouterCacheTable also provides access to read-create objects. The mgmdRouterInterfaceVersion controls the protocol

conformance of an interface, and is therefore a potential denial of service vulnerability. The

Internet-Draft

MGMD MIB

February 2009

mgmdRouterInterfaceQueryMaxResponseTime, the mgmdRouterInterfaceRobustness and the mgmdRouterInterfaceLastMemberQueryInterval are all tuning parameters to control the characteristic of the host-query packets. Compromise of these objects can potentially be disruptive to local multicast communication.

- o The mgmdHostInterfaceTable provides a read-create object, the mgmdHostInterfaceVersion3Robustness, which controls the robustness of the interface to packet loss. Disabling robustness in the face of packet loss could cause denial of service to hosts, however in general this presents a low risk.

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure (for example by using IPsec), even then, there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB module.

It is RECOMMENDED that implementers consider the security features as provided by the SNMPv3 framework (see [\[RFC3410\]](#), section 8), including full support for the SNMPv3 cryptographic mechanisms (for authentication and privacy).

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

[7.](#) IANA Considerations

This MIB introduces a new term to refer to two existing multicast protocols, Multicast Group Membership Discovery. It encompasses both the IPv4 Multicast discovery protocol, IGMP, and the IPv6 Multicast discovery protocol, MLD, as defined in RFCs 2933 [\[RFC2933\]](#) and 3019 [\[RFC3019\]](#) respectively.

Internet-Draft

MGMD MIB

February 2009

The MIB module in this document uses the following IANA-assigned OBJECT IDENTIFIER values recorded in the SMI Numbers registry:

Descriptor	OBJECT IDENTIFIER value
-----	-----
mgmdStdMIB	{ mib-2 XXX }

Editor's Note (to be removed prior to publication): the IANA is requested to assign a value for "XXX" under the 'mib-2' subtree and to record the assignment in the SMI Numbers registry. When the assignment has been made, the RFC Editor is asked to replace "XXX" (here and in the MIB module) with the assigned value and to remove this note.

[8.](#) Contributors

The authors of [RFC 2933](#) [[RFC2933](#)] and [RFC 3019](#) [[RFC3019](#)] from which this document is derived are:

Keith McCloghrie

Dino Farinacci

Dave Thaler

Brian Haberman

Randy Worzella

[9.](#) Acknowledgements

Special thanks to James Lingard, Bill Fenner, and Dave Thaler for

detailed comments on the MIB.

Bert Wijnen deserves special recognition for his exhaustive reviews and constructive feedback on SNMP and SMI issues related to this MIB.

10. References

10.1. Normative References

- [RFC1112] Deering, S., "Host extensions for IP multicasting", STD 5, [RFC 1112](#), August 1989.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2236] Fenner, W., "Internet Group Management Protocol, Version

2", [RFC 2236](#), November 1997.

- [RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIv2)", STD 58, [RFC 2578](#), April 1999.
- [RFC2579] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIv2", STD 58, [RFC 2579](#), April 1999.
- [RFC2580] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Conformance Statements for SMIv2", STD 58, [RFC 2580](#), April 1999.
- [RFC2710] Deering, S., Fenner, W., and B. Haberman, "Multicast Listener Discovery (MLD) for IPv6", [RFC 2710](#), October 1999.
- [RFC2863] McCloghrie, K. and F. Kastenholz, "The Interfaces Group MIB", [RFC 2863](#), June 2000.
- [RFC3376] Cain, B., Deering, S., Kouvelas, I., Fenner, B., and A. Thyagarajan, "Internet Group Management Protocol, Version 3", [RFC 3376](#), October 2002.

- [RFC3810] Vida, R. and L. Costa, "Multicast Listener Discovery Version 2 (MLDv2) for IPv6", [RFC 3810](#), June 2004.
- [RFC4001] Daniele, M., Haberman, B., Routhier, S., and J. Schoenwaelder, "Textual Conventions for Internet Network Addresses", [RFC 4001](#), February 2005.

10.2. Informative References

- [RFC2629] Rose, M., "Writing I-Ds and RFCs using XML", [RFC 2629](#), June 1999.
- [RFC2933] McCloghrie, K., Farinacci, D., and D. Thaler, "Internet Group Management Protocol MIB", [RFC 2933](#), October 2000.
- [RFC3019] Haberman, B. and R. Worzella, "IP Version 6 Management Information Base for The Multicast Listener Discovery Protocol", [RFC 3019](#), January 2001.
- [RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework", [RFC 3410](#), December 2002.

Chesterfield & Haberman Expires August 13, 2009

[Page 41]

Internet-Draft

MGMD MIB

February 2009

- [RFC4605] Fenner, B., He, H., Haberman, B., and H. Sandick, "Internet Group Management Protocol (IGMP) / Multicast Listener Discovery (MLD)-Based Multicast Forwarding ("IGMP/MLD Proxying")", [RFC 4605](#), August 2006.

Authors' Addresses

Julian Chesterfield
University of Cambridge
15 JJ Thompson Avenue
Cambridge CB3 0FD
UK

Brian Haberman (editor)
Johns Hopkins University / Applied Physics Laboratory
11100 Johns Hopkins Road
Laurel, MD 20723

USA

EMail: brian@innovationslab.net