

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: November 27, 2009

S. Chisholm
Nortel
R. Gerhards
Adiscon GmbH
May 26, 2009

Alarms in SYSLOG
draft-ietf-opsawg-syslog-alarm-02.txt

Status of this Memo

This Internet-Draft is submitted to IETF in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/lid-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on November 27, 2009.

Copyright Notice

Copyright (c) 2009 IETFTrust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents in effect on the date of publication of this document (<http://trustee.ietf.org/license-info>). Please review these documents carefully, as they describe your rights and restrictions with respect to this document.

Internet-Draft

Alarms in SYSLOG

May 2009

Abstract

This document describes how to send alarm information in syslog. It includes the mapping of ITU perceived severities onto syslog message fields and a number of alarm-specific SD-PARAM definitions from X.733 and the IETF Alarm MIB.

Table of Contents

1.	Introduction	3
2.	Severity Mapping	4
3.	Alarm STRUCTURED-DATA Elements	5
3.1.	resource	5
3.2.	probableCause	5
3.3.	perceivedSeverity	5
3.4.	eventType	6
3.5.	trendIndication	6
3.6.	resourceURI	6
4.	Examples	8
5.	Security Considerations	9
6.	IANA Considerations	10
7.	Acknowledgments	11
8.	References	12
8.1.	Normative References	12
8.2.	Informative References	12
	Authors' Addresses	13
	Intellectual Property and Copyright Statements	14

1. Introduction

In addition to sending out alarm information asynchronously via protocols such as SNMP or Netconf, many implementations also log alarms via syslog. This memo defines a set of SD-PARAM to support logging and defines a mapping of syslog severity to the severity of the alarm.

The Alarm MIB ([RFC 3877](#)) included mandatory alarm fields from X.733 as well as information from X.736. In addition, the Alarm MIB introduced its own alarm fields. This memo reuses terminology and fields from the Alarm MIB.

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

Alarm related terminology is defined in [[RFC3877](#)].

2. Severity Mapping

The Alarm MIB [[RFC3877](#)] defines ITU perceived severities which are useful to be able to relate to the syslog message fields, particularly in the case where alarms are being logged. This memo describes the representation of ITU perceived severities in appropriate syslog fields described in [[RFC5424](#)]. Syslog offers both a so-called SEVERITY as well as STRUCTURED-DATA. Due to constraints in syslog, there is no one-to-one mapping possible for SEVERITY. A STRUCTURED-DATA element is defined to allow inclusion of the unmodified ITU perceived severity.

Syslog supports severity values different from ITU perceived severities. These are defined in [section 6.2.1 of \[RFC5424\]](#). The mapping shown in table 1 below SHOULD be used to map ITU perceived severities to syslog severities.

ITU Perceived Severity	syslog SEVERITY (Name)
Critical	1 (Alert)
Major	2 (Critical)

Minor	3 (Error)
Warning	4 (Warning)
Indeterminate	5 (Notice)
Cleared	5 (Notice)

Table 1. ITUPerceivedSeverity to syslog SEVERITY mapping.

[3.](#) Alarm STRUCTURED-DATA Elements

STRUCTURED-DATA allows to include any structured information into a syslog message. The following are defined to support structuring alarm information.

- o Resource Under Alarm
- o Probable Cause
- o Event Type
- o Perceived Severity

- o Trend Indication
- o Resource URI

Support of the "alarm" SD-ID is optional, but once supported some of the SD-PARAMS are mandatory.

[3.1.](#) resource

If the "alarm" SD-ID is supported, the "resource" SD-PARAM MUST be supported. This item uniquely identifies the resource under alarm within the scope of a network element.

[3.2.](#) probableCause

If the "alarm" SD-ID is supported, the "probableCause" SD-PARAM MUST be supported. This parameter is the mnemonic associated with the IANAItuProbableCause object defined within [[RFC3877](#)] and any subsequent extensions defined by IANA. For example, IANAItuProbableCause defines a transmission failure to a probable cause of 'transmissionError (10)'. The value of the parameter in this case would be 'transmissionError''

[3.3.](#) perceivedSeverity

If the "alarm" SD-ID is supported, the "perceivedSeverity" SD-PARAM MUST be supported. Similar to the definition of perceived severity in [[X.736](#)] and [[RFC3877](#)], this object can take the following values:

- o cleared
- o indeterminate

- o critical
- o major
- o minor

- o warning

See [section 2](#) for the relationship between this severity and syslog severity.

[3.4.](#) eventType

If the "alarm" SD-ID is supported, the "eventType" SD-PARAM SHOULD be supported. This parameter is the mnemonic associated with the IANAItuEventType object defined within [\[RFC3877\]](#) and any subsequent extensions defined by IANA. For example, IANAItuEventType defines an environmental alarm to an event type of 'environmentalAlarm (6)'. The value of the parameter in this case would be 'environmentalAlarm'

[3.5.](#) trendIndication

If the "alarm" SD-ID is supported, the "trendIndication" SD-PARAM SHOULD be supported. Similar to the definition of perceived severity in [\[X.733\]](#) and [\[RFC3877\]](#), this object can take the following values:

- o moreSevere
- o noChange
- o lessSevere

[3.6.](#) resourceURI

If the "alarm" SD-ID is supported, the "resourceURI" SD-PARAM SHOULD be supported. This item uniquely identifies the resource under alarm.

The value of this field MUST conform to the URI definition in [\[RFC1738\]](#) and its updates. In the case of an SNMP resource, the syntax in [\[RFC4088\]](#) MUST be used and "resourceURI" must point to the same resource as alarmActiveResourceId [\[RFC3877\]](#) for this alarm.

Both the "resource" and the "resourceURI" parameters point at the resource experiencing the alarm, but the "resourceURI" has syntactic constraint requiring it to be a URI. This makes it easy to correlate this syslog alarm with any alarms that are received via other protocols, such as SNMP or to use SNMP or other protocols to get

additional information about this resource.

[4.](#) Examples

Example 1 - Mandatory Alarm Information

```
<165>1 2003-10-11T22:14:15.003Z mymachine.example.com
evntslog - ID47 [exampleSDID@32473 iut="3" eventSource=
"Application" eventID="1011"][alarm resource="su root"
probableCause="unauthorizedAccessAttempt"
perceivedSeverity="major"]
BOMAn application event log entry...
```

In this example, extended from [Syslog], the VERSION is 1 and the Facility has the value of 4. The severity is 2. The message was created on 11 October 2003 at 10:14:15pm UTC, 3 milliseconds into the next second. The message originated from a host that identifies itself as "mymachine.example.com". The APP-NAME is "su" and the PROCID is unknown. The MSGID is "ID47". We have included both the structured data from the original example, a single element with the value "[exampleSDID@0 iut="3" eventSource="Application" eventID="1011"]" and a new one with the alarm information defined in this memo. The alarm SD-ID contains the mandatory SD-PARAMS of resource, probableCause and perceivedSeverity. The MSG itself is "An application event log entry..." The BOM at the beginning of MSG indicates UTF-8 encoding.

Example 2 - Additional Alarm Information

```
<165>1 2004-11-10T20:15:15.003Z mymachine.example.com
evntslog - ID48 [alarm resource="interface 42"
probableCause="unauthorizedAccessAttempt"
perceivedSeverity="major"
eventType="communicationsAlarm"
resourceURI ="snmp://example.com//1.3.6.1.2.1.2.2.1.1.42"]
```

In this example, we include two optional alarm fields - eventType and resourceURI.

5. Security Considerations

In addition to general syslog security considerations discussed in [\[RFC5424\]](#), the information contained with alarms may provide hackers with helpful information about parts of the system currently experiencing stress as well as general information about the system such as inventory.

Users should not have access to information in alarms that their normal access permissions would not permit if the information was accessed in another manner.

There is no standardized access control model for SYSLOG and hence the ability to filter alarms based on a notion of a receiver identity is at best implementation specific.

[6.](#) IANA Considerations

IANA is requested to register the SD-IDs and PARAM-NAMEs shown below:

SD-ID	PARAM-NAME	
alarm		OPTIONAL
	resource	MANDATORY
	probableCause	MANDATORY
	perceivedSeverity	MANDATORY
	eventType	OPTIONAL
	trendIndication	OPTIONAL
	resourceURI	OPTIONAL

[7.](#) Acknowledgments

Thanks to members of the Syslog and OPSAWG work group who contributed to this specification. We'd also like to thank Juergen Schoenwaelder, Dave Harrington, Wes Hardaker and Randy Presuhn for their reviews.

[8.](#) References

[8.1.](#) Normative References

- [RFC1738] Berners-Lee, T., Masinter, L., and M. McCahill, "Uniform Resource Locators (URL)", [RFC 1738](#), December 1994.
- [RFC2119] Bradner, s., "Key words for RFCs to Indicate Requirements Levels", [RFC 2119](#), March 1997.
- [RFC3877] Chisholm, S. and D. Romascanu, "Alarm Management Information Base (MIB)", [RFC 3877](#), September 2004.
- [RFC4088] Black, D., McCloghrie, K., and J. Schoenwaelder, "Uniform Resource Identifier (URI) Scheme for the Simple Network

Management Protocol (SNMP)", [RFC 4088](#), June 2005.

[RFC5424] Gerhards, R., "The syslog Protocol", [RFC 5424](#), March 2009.

[8.2](#). Informative References

- [X.733] ITU-T, ""Information Technology - Open Systems Interconnection - System Management: Alarm Reporting Function"", ITU-T X.733, 1992.
- [X.736] ITU-T, ""Information Technology - Open Systems Interconnection - System Management: Security Alarm Reporting Function"", ITU-T X.736, 1992.

Authors' Addresses

Sharon Chisholm
Nortel
3500 Carling Ave
Nepean, Ontario K2H 8E9
Canada

Email: schishol@nortel.com

Rainer Gerhards
Adiscon GmbH
Mozartstrasse 21
Grossrinderfeld, BW 97950
Germany

Email: rgerhards@adiscon.com