

Internet Engineering Task Force (IETF)  
Request for Comments: 5911  
Category: Informational  
ISSN: 2070-1721

P. Hoffman  
VPN Consortium  
J. Schaad  
Soaring Hawk Consulting  
June 2010

## **New ASN.1 Modules for Cryptographic Message Syntax (CMS) and S/MIME**

### Abstract

The Cryptographic Message Syntax (CMS) format, and many associated formats, are expressed using ASN.1. The current ASN.1 modules conform to the 1988 version of ASN.1. This document updates those ASN.1 modules to conform to the 2002 version of ASN.1. There are no bits-on-the-wire changes to any of the formats; this is simply a change to the syntax.

### Status of This Memo

This document is not an Internet Standards Track specification; it is published for informational purposes.

This document is a product of the Internet Engineering Task Force (IETF). It represents the consensus of the IETF community. It has received public review and has been approved for publication by the Internet Engineering Steering Group (IESG). Not all documents approved by the IESG are a candidate for any level of Internet Standard; see [Section 2 of RFC 5741](#).

Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at <http://www.rfc-editor.org/info/rfc5911>.

Copyright Notice

Copyright (c) 2010 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

This document may contain material from IETF Documents or IETF Contributions published or made publicly available before November 10, 2008. The person(s) controlling the copyright in some of this material may not have granted the IETF Trust the right to allow modifications of such material outside the IETF Standards Process. Without obtaining an adequate license from the person(s) controlling the copyright in such materials, this document may not be modified outside the IETF Standards Process, and derivative works of it may not be created outside the IETF Standards Process, except to format it for publication as an RFC or to translate it into languages other than English.

Table of Contents

- [1.](#) Introduction . . . . . [3](#)
- [1.1.](#) Design Notes . . . . . [4](#)
- [2.](#) ASN.1 Module AlgorithmInformation . . . . . [4](#)
- [3.](#) ASN.1 Module for [RFC 3370](#) . . . . . [14](#)
- [4.](#) ASN.1 Module for [RFC 3565](#) . . . . . [20](#)
- [5.](#) ASN.1 Module for [RFC 3851](#) . . . . . [22](#)
- [6.](#) ASN.1 Module for [RFC 3852](#) . . . . . [24](#)
- [7.](#) ASN.1 Module for [RFC 4108](#) . . . . . [34](#)
- [8.](#) ASN.1 Module for [RFC 4998](#) . . . . . [40](#)
- [9.](#) ASN.1 Module for [RFC 5035](#) . . . . . [41](#)
- [10.](#) ASN.1 Module for [RFC 5083](#) . . . . . [47](#)
- [11.](#) ASN.1 Module for [RFC 5084](#) . . . . . [48](#)
- [12.](#) ASN.1 Module for [RFC 5275](#) . . . . . [50](#)
- [13.](#) Security Considerations . . . . . [57](#)
- [14.](#) Normative References . . . . . [57](#)



## 1. Introduction

Some developers would like the IETF to use the latest version of ASN.1 in its standards. Most of the RFCs that relate to security protocols still use ASN.1 from the 1988 standard, which has been deprecated. This is particularly true for the standards that relate to PKIX, CMS, and S/MIME.

This document updates the following RFCs to use ASN.1 modules that conform to the 2002 version of ASN.1 [[ASN1-2002](#)]. Note that not all the modules are updated; some are included to simply make the set complete.

- o [RFC 3370](#), CMS Algorithms [[RFC3370](#)]
- o [RFC 3565](#), Use of AES in CMS [[RFC3565](#)]
- o [RFC 3851](#), S/MIME Version 3.1 Message Specification [[RFC3851](#)]
- o [RFC 3852](#), CMS main [[RFC3852](#)]
- o [RFC 4108](#), Using CMS to Protect Firmware Packages [[RFC4108](#)]
- o [RFC 4998](#), Evidence Record Syntax (ERS) [[RFC4998](#)]
- o [RFC 5035](#), Enhanced Security Services (ESS) [[RFC5035](#)]
- o [RFC 5083](#), CMS Authenticated-Enveloped-Data Content Type [[RFC5083](#)]
- o [RFC 5084](#), Using AES-CCM and AES-GCM Authenticated Encryption in CMS [[RFC5084](#)]
- o [RFC 5275](#), CMS Symmetric Key Management and Distribution [[RFC5275](#)]

Note that some of the modules in this document get some of their definitions from places different than the modules in the original RFCs. The idea is that these modules, when combined with the modules in [[RFC5912](#)] can stand on their own and do not need to import definitions from anywhere else. Also note that the ASN.1 modules in this document have references in their text comments that need to be looked up in original RFCs, and that some of those references may have already been superseded by later RFCs.

The document also includes a module of common definitions called "AlgorithmInformation". These definitions are used here and in [[RFC5912](#)].



Note that some of the modules here import definitions from the common definitions module, "PKIX-CommonTypes", in [[RFC5912](#)].

### 1.1. Design Notes

The modules in this document use the object model available in the 2002 ASN.1 documents to a great extent. Objects for each of the different algorithm types are defined. Also, all of the places where the 1988 ASN.1 syntax had ANY holes to allow for variable syntax now use objects.

Much like the way that the PKIX and S/MIME working groups use the prefix of id- for object identifiers, this document has also adopted a set of two-, three-, and four-letter prefixes to allow for quick identification of the type of an object based on its name. This allows, for example, the same back half of the name to be used for the different objects. Thus, "id-sha1" is the object identifier, while "mda-sha1" is the message digest object for "sha1".

One or more object sets for the different types of algorithms are defined. A single consistent name for each different algorithm type is used. For example, an object set named PublicKeys contains the public keys defined in that module. If no public keys are defined, then the object set is not created. When importing these object sets into an ASN.1 module, one needs to be able to distinguish between the different object sets with the same name. This is done by using both the module name (as specified in the IMPORT statement) and the object set name. For example, in the module for [RFC 5280](#):

```
PublicKeys FROM PKIXAlgs-2008 { 1 3 6 1 5 5 7 0 995 }
PublicKeys FROM PKIX1-PSS-OAEP-Algorithms { 1 3 6 1 5 5 7 33 }

PublicKeyAlgorithms PUBLIC-KEY ::= { PKIXAlgs-2008.PublicKeys, ...,
    PKIX1-PSS-OAEP-Algorithms.PublicKeys }
```

### 2. ASN.1 Module AlgorithmInformation

This section contains a module that is imported by many other modules in this document. Note that this module is also given in [[RFC5912](#)]. This module does not come from any existing RFC.

```
AlgorithmInformation-2009
  {iso(1) identified-organization(3) dod(6) internet(1) security(5)
  mechanisms(5) pkix(7) id-mod(0)
  id-mod-algorithmInformation-02(58)}
```



```
DEFINITIONS EXPLICIT TAGS ::=
```

```
BEGIN
```

```
EXPORTS ALL;
```

```
IMPORTS
```

```
KeyUsage
```

```
FROM PKIX1Implicit-2009
```

```
  {iso(1) identified-organization(3) dod(6) internet(1)
   security(5) mechanisms(5) pkix(7) id-mod(0)
   id-mod-pkix1-implicit-02(59)} ;
```

```
-- Suggested prefixes for algorithm objects are:
```

```
--
```

```
-- mda-  Message Digest Algorithms
-- sa-   Signature Algorithms
-- kta-  Key Transport Algorithms (Asymmetric)
-- kaa-  Key Agreement Algorithms (Asymmetric)
-- kwa-  Key Wrap Algorithms (Symmetric)
-- kda-  Key Derivation Algorithms
-- maca- Message Authentication Code Algorithms
-- pk-   Public Key
-- cea-  Content (symmetric) Encryption Algorithms
-- cap-  S/MIME Capabilities
```

```
ParamOptions ::= ENUMERATED {
```

```
  required,      -- Parameters MUST be encoded in structure
  preferredPresent, -- Parameters SHOULD be encoded in structure
  preferredAbsent, -- Parameters SHOULD NOT be encoded in structure
  absent,        -- Parameters MUST NOT be encoded in structure
  inheritable,   -- Parameters are inherited if not present
  optional,      -- Parameters MAY be encoded in the structure
  ...
```

```
}
```

```
-- DIGEST-ALGORITHM
```

```
--
```

```
-- Describes the basic information for ASN.1 and a digest
-- algorithm.
```

```
--
```

```
-- &id - contains the OID identifying the digest algorithm
-- &Params - if present, contains the type for the algorithm
--           parameters; if absent, implies no parameters
-- &paramPresence - parameter presence requirement
```

```
--
```

```
-- Additional information such as the length of the hash could have
-- been encoded. Without a clear understanding of what information
-- is needed by applications, such extraneous information was not
-- considered to be of sufficient importance.
```



```

--
-- Example:
-- mda-sha1 DIGEST-ALGORITHM ::= {
--     IDENTIFIER id-sha1
--     PARAMS TYPE NULL ARE preferredAbsent
-- }

DIGEST-ALGORITHM ::= CLASS {
    &id                OBJECT IDENTIFIER UNIQUE,
    &Params            OPTIONAL,
    &paramPresence    ParamOptions DEFAULT absent
} WITH SYNTAX {
    IDENTIFIER &id
    [PARAMS [TYPE &Params] ARE &paramPresence ]
}

-- SIGNATURE-ALGORITHM
--
-- Describes the basic properties of a signature algorithm
--
-- &id - contains the OID identifying the signature algorithm
-- &Value - contains a type definition for the value structure of
--         the signature; if absent, implies that no ASN.1
--         encoding is performed on the value
-- &Params - if present, contains the type for the algorithm
--           parameters; if absent, implies no parameters
-- &paramPresence - parameter presence requirement
-- &HashSet - The set of hash algorithms used with this
--            signature algorithm
-- &PublicKeySet - the set of public key algorithms for this
--                signature algorithm
-- &smimeCaps - contains the object describing how the S/MIME
--              capabilities are presented.
--
-- Example:
-- sig-RSA-PSS SIGNATURE-ALGORITHM ::= {
--     IDENTIFIER id-RSASSA-PSS
--     PARAMS TYPE RSASSA-PSS-params ARE required
--     HASHES { mda-sha1 | mda-md5, ... }
--     PUBLIC-KEYS { pk-rsa | pk-rsa-pss }
-- }

SIGNATURE-ALGORITHM ::= CLASS {
    &id                OBJECT IDENTIFIER UNIQUE,
    &Value            OPTIONAL,
    &Params            OPTIONAL,
    &paramPresence    ParamOptions DEFAULT absent,
    &HashSet          DIGEST-ALGORITHM OPTIONAL,

```



```

    &PublicKeySet    PUBLIC-KEY OPTIONAL,
    &smimeCaps       SMIME-CAPS OPTIONAL
} WITH SYNTAX {
    IDENTIFIER &id
    [VALUE &Value]
    [PARAMS [TYPE &Params] ARE &paramPresence ]
    [HASHES &HashSet]
    [PUBLIC-KEYS &PublicKeySet]
    [SMIME-CAPS &smimeCaps]
}

-- PUBLIC-KEY
--
-- Describes the basic properties of a public key
--
-- &id - contains the OID identifying the public key
-- &KeyValue - contains the type for the key value
-- &Params - if present, contains the type for the algorithm
--           parameters; if absent, implies no parameters
-- &paramPresence - parameter presence requirement
-- &keyUsage - contains the set of bits that are legal for this
--            key type. Note that it does not make any statement
--            about how bits may be paired.
-- &PrivateKey - contains a type structure for encoding the private
--            key information.
--
-- Example:
-- pk-rsa-pss PUBLIC-KEY ::= {
--     IDENTIFIER id-RSASSA-PSS
--     KEY RSAPublicKey
--     PARAMS TYPE RSASSA-PSS-params ARE optional
--     CERT-KEY-USAGE { .... }
-- }

PUBLIC-KEY ::= CLASS {
    &id                OBJECT IDENTIFIER UNIQUE,
    &KeyValue           OPTIONAL,
    &Params             OPTIONAL,
    &paramPresence     ParamOptions DEFAULT absent,
    &keyUsage           KeyUsage OPTIONAL,
    &PrivateKey         OPTIONAL
} WITH SYNTAX {
    IDENTIFIER &id
    [KEY &KeyValue]
    [PARAMS [TYPE &Params] ARE &paramPresence]
    [CERT-KEY-USAGE &keyUsage]
    [PRIVATE-KEY &PrivateKey]
}

```



```

-- KEY-TRANSPORT
--
-- Describes the basic properties of a key transport algorithm
--
-- &id - contains the OID identifying the key transport algorithm
-- &Params - if present, contains the type for the algorithm
--           parameters; if absent, implies no parameters
-- &paramPresence - parameter presence requirement
-- &PublicKeySet - specifies which public keys are used with
--                 this algorithm
-- &smimeCaps - contains the object describing how the S/MIME
--               capabilities are presented.
--
-- Example:
-- kta-rsaTransport KEY-TRANSPORT ::= {
--     IDENTIFIER &id
--     PARAMS TYPE NULL ARE required
--     PUBLIC-KEYS { pk-rsa | pk-rsa-pss }
-- }

```

```

KEY-TRANSPORT ::= CLASS {
    &id                OBJECT IDENTIFIER UNIQUE,
    &Params            OPTIONAL,
    &paramPresence     ParamOptions DEFAULT absent,
    &PublicKeySet      PUBLIC-KEY OPTIONAL,
    &smimeCaps         SMIME-CAPS OPTIONAL
} WITH SYNTAX {
    IDENTIFIER &id
    [PARAMS [TYPE &Params] ARE &paramPresence]
    [PUBLIC-KEYS &PublicKeySet]
    [SMIME-CAPS &smimeCaps]
}

```

```

-- KEY-AGREE
--
-- Describes the basic properties of a key agreement algorithm
--
-- &id - contains the OID identifying the key agreement algorithm
-- &Params - if present, contains the type for the algorithm
--           parameters; if absent, implies no parameters
-- &paramPresence - parameter presence requirement
-- &PublicKeySet - specifies which public keys are used with
--                 this algorithm
-- &Ukm - type of user keying material used
-- &ukmPresence - specifies the requirements to define the UKM field
-- &smimeCaps - contains the object describing how the S/MIME
--               capabilities are presented.
--

```



```
-- Example:
-- kaa-dh-static-ephemeral KEY-AGREE ::= {
--     IDENTIFIER id-alg-ESDH
--     PARAMS TYPE KeyWrapAlgorithm ARE required
--     PUBLIC-KEYS {
--         {IDENTIFIER dh-public-number KEY DHPublicKey
--          PARAMS TYPE DHDomainParameters ARE inheritable }
--     }
--     - - UKM should be present but is not separately ASN.1-encoded
--     UKM ARE preferredPresent
-- }
```

```
KEY-AGREE ::= CLASS {
    &id          OBJECT IDENTIFIER UNIQUE,
    &Params      OPTIONAL,
    &paramPresence ParamOptions DEFAULT absent,
    &PublicKeySet PUBLIC-KEY OPTIONAL,
    &Ukm         OPTIONAL,
    &ukmPresence ParamOptions DEFAULT absent,
    &smimeCaps   SMIME-CAPS OPTIONAL
} WITH SYNTAX {
    IDENTIFIER &id
    [PARAMS [TYPE &Params] ARE &paramPresence]
    [PUBLIC-KEYS &PublicKeySet]
    [UKM [TYPE &Ukm] ARE &ukmPresence]
    [SMIME-CAPS &smimeCaps]
}
```

```
-- KEY-WRAP
--
-- Describes the basic properties of a key wrap algorithm
--
-- &id - contains the OID identifying the key wrap algorithm
-- &Params - if present, contains the type for the algorithm
--           parameters; if absent, implies no parameters
-- &paramPresence - parameter presence requirement
-- &smimeCaps - contains the object describing how the S/MIME
--             capabilities are presented.
```

```
-- Example:
-- kwa-cms3DESwrap KEY-WRAP ::= {
--     IDENTIFIER id-alg-CMS3DESwrap
--     PARAMS TYPE NULL ARE required
-- }
```

```
KEY-WRAP ::= CLASS {
    &id          OBJECT IDENTIFIER UNIQUE,
    &Params      OPTIONAL,
```



```
    &paramPresence      ParamOptions DEFAULT absent,
    &smimeCaps          SMIME-CAPS OPTIONAL
} WITH SYNTAX {
    IDENTIFIER &id
    [PARAMS [TYPE &Params] ARE &paramPresence]
    [SMIME-CAPS &smimeCaps]
}

-- KEY-DERIVATION
--
-- Describes the basic properties of a key derivation algorithm
--
-- &id - contains the OID identifying the key derivation algorithm
-- &Params - if present, contains the type for the algorithm
--           parameters; if absent, implies no parameters
-- &paramPresence - parameter presence requirement
-- &smimeCaps - contains the object describing how the S/MIME
--             capabilities are presented.
--
-- Example:
-- kda-pbkdf2 KEY-DERIVATION ::= {
--     IDENTIFIER id-PBKDF2
--     PARAMS TYPE PBKDF2-params ARE required
-- }

KEY-DERIVATION ::= CLASS {
    &id                OBJECT IDENTIFIER UNIQUE,
    &Params            OPTIONAL,
    &paramPresence     ParamOptions DEFAULT absent,
    &smimeCaps        SMIME-CAPS OPTIONAL
} WITH SYNTAX {
    IDENTIFIER &id
    [PARAMS [TYPE &Params] ARE &paramPresence]
    [SMIME-CAPS &smimeCaps]
}

-- MAC-ALGORITHM
--
-- Describes the basic properties of a message
-- authentication code (MAC) algorithm
--
-- &id - contains the OID identifying the MAC algorithm
-- &Params - if present, contains the type for the algorithm
--           parameters; if absent, implies no parameters
-- &paramPresence - parameter presence requirement
-- &keyed - MAC algorithm is a keyed MAC algorithm
-- &smimeCaps - contains the object describing how the S/MIME
--             capabilities are presented.
```



```
--
-- Some parameters that perhaps should have been added would be
-- fields with the minimum and maximum MAC lengths for
-- those MAC algorithms that allow truncations.
```

```
-- Example:
-- maca-hmac-sha1 MAC-ALGORITHM ::= {
--     IDENTIFIER HMAC-SHA1
--     PARAMS TYPE NULL ARE preferredAbsent
--     IS KEYED MAC TRUE
--     SMIME-CAPS {IDENTIFIED BY HMAC-SHA1}
-- }
```

```
MAC-ALGORITHM ::= CLASS {
    &id                OBJECT IDENTIFIER UNIQUE,
    &Params             OPTIONAL,
    &paramPresence     ParamOptions DEFAULT absent,
    &keyed              BOOLEAN,
    &smimeCaps         SMIME-CAPS OPTIONAL
} WITH SYNTAX {
    IDENTIFIER &id
    [PARAMS [TYPE &Params] ARE &paramPresence]
    IS-KEYED-MAC &keyed
    [SMIME-CAPS &smimeCaps]
}
```

```
-- CONTENT-ENCRYPTION
--
-- Describes the basic properties of a content encryption
-- algorithm
--
-- &id - contains the OID identifying the content
-- encryption algorithm
-- &Params - if present, contains the type for the algorithm
-- parameters; if absent, implies no parameters
-- &paramPresence - parameter presence requirement
-- &smimeCaps - contains the object describing how the S/MIME
-- capabilities are presented.
```

```
-- Example:
-- cea-3DES-cbc CONTENT-ENCRYPTION ::= {
--     IDENTIFIER des-ede3-cbc
--     PARAMS TYPE IV ARE required
--     SMIME-CAPS { IDENTIFIED BY des-ede3-cbc }
-- }
```

```
CONTENT-ENCRYPTION ::= CLASS {
    &id                OBJECT IDENTIFIER UNIQUE,
```



```

    &Params          OPTIONAL,
    &paramPresence   ParamOptions DEFAULT absent,
    &smimeCaps       SMIME-CAPS OPTIONAL
} WITH SYNTAX {
    IDENTIFIER &id
    [PARAMS [TYPE &Params] ARE &paramPresence]
    [SMIME-CAPS &smimeCaps]
}

-- ALGORITHM
--
-- Describes a generic algorithm identifier
--
-- &id - contains the OID identifying the algorithm
-- &Params - if present, contains the type for the algorithm
--           parameters; if absent, implies no parameters
-- &paramPresence - parameter presence requirement
-- &smimeCaps - contains the object describing how the S/MIME
--              capabilities are presented.
--
-- This would be used for cases where an algorithm of an unknown
-- type is used. In general however, one should either define
-- a more complete algorithm structure (such as the one above)
-- or use the TYPE-IDENTIFIER class.

ALGORITHM ::= CLASS {
    &id OBJECT IDENTIFIER UNIQUE,
    &Params          OPTIONAL,
    &paramPresence ParamOptions DEFAULT absent,
    &smimeCaps       SMIME-CAPS OPTIONAL
} WITH SYNTAX {
    IDENTIFIER &id
    [PARAMS [TYPE &Params] ARE &paramPresence]
    [SMIME-CAPS &smimeCaps]
}

-- AlgorithmIdentifier
--
-- Provides the generic structure that is used to encode algorithm
-- identification and the parameters associated with the
-- algorithm.
--
-- The first parameter represents the type of the algorithm being
-- used.
-- The second parameter represents an object set containing the
-- algorithms that may occur in this situation.
-- The initial list of required algorithms should occur to the
-- left of an extension marker; all other algorithms should

```



```

-- occur to the right of an extension marker.
--
-- The object class ALGORITHM can be used for generic unspecified
-- items.
-- If new ALGORITHM classes are defined, the fields &id and &Params
-- need to be present as fields in the object in order to use
-- this parameterized type.
--
-- Example:
-- SignatureAlgorithmIdentifier ::=
--     AlgorithmIdentifier{SIGNATURE-ALGORITHM, {SignatureAlgSet}}
AlgorithmIdentifier{ALGORITHM-TYPE, ALGORITHM-TYPE:AlgorithmSet} ::=
    SEQUENCE {
        algorithm ALGORITHM-TYPE.&id({AlgorithmSet}),
        parameters ALGORITHM-TYPE.
            &Params({AlgorithmSet}{@algorithm}) OPTIONAL
    }

-- S/MIME Capabilities
--
-- We have moved the SMIME-CAPS from the module for RFC 3851 to here
-- because it is used in RFC 4262 (X.509 Certificate Extension for
-- S/MIME Capabilities)
--
-- This class is used to represent an S/MIME capability. S/MIME
-- capabilities are used to represent what algorithm capabilities
-- an individual has. The classic example was the content encryption
-- algorithm RC2 where the algorithm id and the RC2 key lengths
-- supported needed to be advertised, but the IV used is not fixed.
-- Thus, for RC2 we used
--
-- cap-RC2CBC SMIME-CAPS ::= {
--     TYPE INTEGER ( 40 | 128 ) IDENTIFIED BY rc2-cbc }
--
-- where 40 and 128 represent the RC2 key length in number of bits.
--
-- Another example where information needs to be shown is for
-- RSA-OAEP where only specific hash functions or mask generation
-- functions are supported, but the saltLength is specified by the
-- sender and not the recipient. In this case, one can either
-- generate a number of capability items,
-- or a new S/MIME capability type could be generated where
-- multiple hash functions could be specified.
--
--
-- SMIME-CAP

```



```

--
-- This class is used to associate the type that describes the
-- capabilities with the object identifier.
--

SMIME-CAPS ::= CLASS {
    &id          OBJECT IDENTIFIER UNIQUE,
    &Type        OPTIONAL
}
WITH SYNTAX { [TYPE &Type] IDENTIFIED BY &id }

--
-- Generic type - this is used for defining values.
--

-- Define a single S/MIME capability encoding

SMIMECapability{SMIME-CAPS:CapabilitySet} ::= SEQUENCE {
    capabilityID      SMIME-CAPS.&id({CapabilitySet}),
    parameters        SMIME-CAPS.&Type({CapabilitySet}
                        {@capabilityID}) OPTIONAL
}

-- Define a sequence of S/MIME capability values

SMIMECapabilities { SMIME-CAPS:CapabilitySet } ::=
    SEQUENCE SIZE (1..MAX) OF SMIMECapability{{CapabilitySet} }

END

```

### 3. ASN.1 Module for [RFC 3370](#)

```

CryptographicMessageSyntaxAlgorithms-2009
    { iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)
      smime(16) modules(0) id-mod-cmsalg-2001-02(37) }
DEFINITIONS IMPLICIT TAGS ::=
BEGIN
IMPORTS

ParamOptions, DIGEST-ALGORITHM, SIGNATURE-ALGORITHM,
    PUBLIC-KEY, KEY-DERIVATION, KEY-WRAP, MAC-ALGORITHM,
    KEY-AGREE, KEY-TRANSPORT, CONTENT-ENCRYPTION, ALGORITHM,
    AlgorithmIdentifier{ }, SMIME-CAPS
FROM AlgorithmInformation-2009
    {iso(1) identified-organization(3) dod(6) internet(1) security(5)
     mechanisms(5) pkix(7) id-mod(0)
     id-mod-algorithmInformation-02(58)}

```



```
pk-rsa, pk-dh, pk-dsa, rsaEncryption, DHPublicKey, dhpnumber
```

```
FROM PKIXAlgs-2009
```

```
  {iso(1) identified-organization(3) dod(6)
   internet(1) security(5) mechanisms(5) pkix(7) id-mod(0)
   id-mod-pkix1-algorithms2008-02(56)}
```

```
cap-RC2CBC
```

```
FROM SecureMimeMessageV3dot1-2009
```

```
  {iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)
   smime(16) modules(0) id-mod-msg-v3dot1-02(39)};
```

```
-- 2. Hash algorithms in this document
```

```
MessageDigestAlgs DIGEST-ALGORITHM ::= {
```

```
--   mda-md5 | mda-sha1,
   ... }
```

```
-- 3. Signature algorithms in this document
```

```
SignatureAlgs SIGNATURE-ALGORITHM ::= {
```

```
--   See RFC 3279
   sa-dsaWithSHA1 | sa-rsaWithMD5 | sa-rsaWithSHA1,
   ... }
```

```
-- 4. Key Management Algorithms
```

```
-- 4.1 Key Agreement Algorithms
```

```
KeyAgreementAlgs KEY-AGREE ::= { kaa-esdh | kaa-ssdh, ... }
```

```
KeyAgreePublicKeys PUBLIC-KEY ::= { pk-dh, ... }
```

```
-- 4.2 Key Transport Algorithms
```

```
KeyTransportAlgs KEY-TRANSPORT ::= { kt-rsa, ... }
```

```
-- 4.3 Symmetric Key-Encryption Key Algorithms
```

```
KeyWrapAlgs KEY-WRAP ::= { kwa-3DESWrap | kwa-RC2Wrap, ... }
```

```
-- 4.4 Key Derivation Algorithms
```

```
KeyDerivationAlgs KEY-DERIVATION ::= { kda-PBKDF2, ... }
```

```
-- 5. Content Encryption Algorithms
```

```
ContentEncryptionAlgs CONTENT-ENCRYPTION ::=
```

```
  { cea-3DES-cbc | cea-RC2-cbc, ... }
```

```
-- 6. Message Authentication Code Algorithms
```



```
MessageAuthAlgs MAC-ALGORITHM ::= { maca-hMAC-SHA1, ... }

-- S/MIME Capabilities for these items

SMimeCaps SMIME-CAPS ::= {
    kaa-esdh.&smimeCaps      |
    kaa-ssdh.&smimeCaps      |
    kt-rsa.&smimeCaps        |
    kwa-3DESWrap.&smimeCaps  |
    kwa-RC2Wrap.&smimeCaps   |
    cea-3DES-cbc.&smimeCaps  |
    cea-RC2-cbc.&smimeCaps   |
    maca-hMAC-SHA1.&smimeCaps,
    ...}

--
--
--

-- Algorithm Identifiers

-- rsaEncryption OBJECT IDENTIFIER ::= { iso(1) member-body(2)
--   us(840) rsadsi(113549) pkcs(1) pkcs-1(1) 1 }

id-alg-ESDH OBJECT IDENTIFIER ::= { iso(1) member-body(2) us(840)
  rsadsi(113549) pkcs(1) pkcs-9(9) smime(16) alg(3) 5 }

id-alg-SSDH OBJECT IDENTIFIER ::= { iso(1) member-body(2) us(840)
  rsadsi(113549) pkcs(1) pkcs-9(9) smime(16) alg(3) 10 }

id-alg-CMS3DESwrap OBJECT IDENTIFIER ::= { iso(1) member-body(2)
  us(840) rsadsi(113549) pkcs(1) pkcs-9(9) smime(16) alg(3) 6 }

id-alg-CMSRC2wrap OBJECT IDENTIFIER ::= { iso(1) member-body(2)
  us(840) rsadsi(113549) pkcs(1) pkcs-9(9) smime(16) alg(3) 7 }

des-ede3-cbc OBJECT IDENTIFIER ::= { iso(1) member-body(2)
  us(840) rsadsi(113549) encryptionAlgorithm(3) 7 }

rc2-cbc OBJECT IDENTIFIER ::= { iso(1) member-body(2) us(840)
  rsadsi(113549) encryptionAlgorithm(3) 2 }

hMAC-SHA1 OBJECT IDENTIFIER ::= { iso(1) identified-organization(3)
  dod(6) internet(1) security(5) mechanisms(5) 8 1 2 }

id-PBKDF2 OBJECT IDENTIFIER ::= { iso(1) member-body(2) us(840)
  rsadsi(113549) pkcs(1) pkcs-5(5) 12 }
```



```
-- Algorithm Identifier Parameter Types

KeyWrapAlgorithm ::=
    AlgorithmIdentifier {KEY-WRAP, {KeyWrapAlgs }}

RC2wrapParameter ::= RC2ParameterVersion
RC2ParameterVersion ::= INTEGER

CBCParameter ::= IV

IV ::= OCTET STRING -- exactly 8 octets

RC2CBCParameter ::= SEQUENCE {
    rc2ParameterVersion INTEGER (1..256),
    iv OCTET STRING } -- exactly 8 octets

maca-hMAC-SHA1 MAC-ALGORITHM ::= {
    IDENTIFIER hMAC-SHA1
    PARAMS TYPE NULL ARE preferredAbsent
    IS-KEYED-MAC TRUE
    SMIME-CAPS {IDENTIFIED BY hMAC-SHA1}
}

PBKDF2-PRFsAlgorithmIdentifier ::= AlgorithmIdentifier{ ALGORITHM,
    {PBKDF2-PRFs} }

alg-hMAC-SHA1 ALGORITHM ::=
    { IDENTIFIER hMAC-SHA1 PARAMS TYPE NULL ARE required }

PBKDF2-PRFs ALGORITHM ::= { alg-hMAC-SHA1, ... }

PBKDF2-SaltSources ALGORITHM ::= { ... }

PBKDF2-SaltSourcesAlgorithmIdentifier ::=
    AlgorithmIdentifier {ALGORITHM, {PBKDF2-SaltSources}}

defaultPBKDF2 PBKDF2-PRFsAlgorithmIdentifier ::=
    { algorithm alg-hMAC-SHA1.&id, parameters NULL:NULL }

PBKDF2-params ::= SEQUENCE {
    salt CHOICE {
        specified OCTET STRING,
        otherSource PBKDF2-SaltSourcesAlgorithmIdentifier },
    iterationCount INTEGER (1..MAX),
    keyLength INTEGER (1..MAX) OPTIONAL,
    prf PBKDF2-PRFsAlgorithmIdentifier DEFAULT
        defaultPBKDF2
    }
}
```



```

--
-- This object is included for completeness. It should not be used
-- for encoding of signatures, but was sometimes used in older
-- versions of CMS for encoding of RSA signatures.
--
--
-- sa-rsa SIGNATURE-ALGORITHM ::= {
--     IDENTIFIER rsaEncryption
--     - - value is not ASN.1 encoded
--     PARAMS TYPE NULL ARE required
--     HASHES {mda-sha1 | mda-md5, ...}
--     PUBLIC-KEYS { pk-rsa}
-- }
--
-- No ASN.1 encoding is applied to the signature value
-- for these items

kaa-esdh KEY-AGREE ::= {
    IDENTIFIER id-alg-ESDH
    PARAMS TYPE KeyWrapAlgorithm ARE required
    PUBLIC-KEYS { pk-dh }
    -- UKM is not ASN.1 encoded
    UKM ARE optional
    SMIME-CAPS {TYPE KeyWrapAlgorithm IDENTIFIED BY id-alg-ESDH}
}

kaa-ssdh KEY-AGREE ::= {
    IDENTIFIER id-alg-SSDH
    PARAMS TYPE KeyWrapAlgorithm ARE required
    PUBLIC-KEYS {pk-dh}
    -- UKM is not ASN.1 encoded
    UKM ARE optional
    SMIME-CAPS {TYPE KeyWrapAlgorithm IDENTIFIED BY id-alg-SSDH}
}

dh-public-number OBJECT IDENTIFIER ::= dhpnumber

pk-originator-dh PUBLIC-KEY ::= {
    IDENTIFIER dh-public-number
    KEY DHPublicKey
    PARAMS ARE absent
    CERT-KEY-USAGE {keyAgreement, encipherOnly, decipherOnly}
}

kwa-3DESwrap KEY-WRAP ::= {
    IDENTIFIER id-alg-CMS3DESwrap
    PARAMS TYPE NULL ARE required
    SMIME-CAPS {IDENTIFIED BY id-alg-CMS3DESwrap}
}

```



```
}

kwa-RC2Wrap KEY-WRAP ::= {
    IDENTIFIER id-alg-CMSRC2wrap
    PARAMS TYPE RC2wrapParameter ARE required
    SMIME-CAPS { IDENTIFIED BY id-alg-CMSRC2wrap }
}

kda-PBKDF2 KEY-DERIVATION ::= {
    IDENTIFIER id-PBKDF2
    PARAMS TYPE PBKDF2-params ARE required
    -- No S/MIME caps defined
}

cea-3DES-cbc CONTENT-ENCRYPTION ::= {
    IDENTIFIER des-ed3-cbc
    PARAMS TYPE IV ARE required
    SMIME-CAPS { IDENTIFIED BY des-ed3-cbc }
}

cea-RC2-cbc CONTENT-ENCRYPTION ::= {
    IDENTIFIER rc2-cbc
    PARAMS TYPE RC2CBCParameter ARE required
    SMIME-CAPS cap-RC2CBC
}

kt-rsa KEY-TRANSPORT ::= {
    IDENTIFIER rsaEncryption
    PARAMS TYPE NULL ARE required
    PUBLIC-KEYS { pk-rsa }
    SMIME-CAPS {IDENTIFIED BY rsaEncryption}
}

-- S/MIME Capabilities - most have no label.

cap-3DESwrap SMIME-CAPS ::= { IDENTIFIED BY id-alg-CMS3DESwrap }

END
```



**4. ASN.1 Module for [RFC 3565](#)**

```

CMSAesRsaesOaep-2009 {iso(1) member-body(2) us(840) rsadsi(113549)
    pkcs(1) pkcs-9(9) smime(16) modules(0) id-mod-cms-aes-02(38)}
DEFINITIONS IMPLICIT TAGS ::=
BEGIN
IMPORTS

CONTENT-ENCRYPTION, KEY-WRAP, SMIME-CAPS
FROM AlgorithmInformation-2009
    {iso(1) identified-organization(3) dod(6) internet(1) security(5)
    mechanisms(5) pkix(7) id-mod(0)
    id-mod-algorithmInformation-02(58)};

AES-ContentEncryption CONTENT-ENCRYPTION ::= {
    cea-aes128-cbc | cea-aes192-cbc | cea-aes256-cbc, ...
}

AES-KeyWrap KEY-WRAP ::= {
    kwa-aes128-wrap | kwa-aes192-wrap | kwa-aes256-wrap, ...
}

SMimeCaps SMIME-CAPS ::= {
    cea-aes128-cbc.&smimeCaps |
    cea-aes192-cbc.&smimeCaps |
    cea-aes256-cbc.&smimeCaps |
    kwa-aes128-wrap.&smimeCaps |
    kwa-aes192-wrap.&smimeCaps |
    kwa-aes256-wrap.&smimeCaps, ...
}

-- AES information object identifiers --

aes OBJECT IDENTIFIER ::=
    { joint-iso-itu-t(2) country(16) us(840) organization(1) gov(101)
    csor(3) nistAlgorithms(4) 1 }

-- AES using CBC mode for key sizes of 128, 192, 256

cea-aes128-cbc CONTENT-ENCRYPTION ::= {
    IDENTIFIER id-aes128-CBC
    PARAMS TYPE AES-IV ARE required
    SMIME-CAPS { IDENTIFIED BY id-aes128-CBC }
}
id-aes128-CBC OBJECT IDENTIFIER ::= { aes 2 }

cea-aes192-cbc CONTENT-ENCRYPTION ::= {
    IDENTIFIER id-aes192-CBC

```



```
    PARAMS TYPE AES-IV ARE required
    SMIME-CAPS { IDENTIFIED BY id-aes192-CBC }
  }
id-aes192-CBC OBJECT IDENTIFIER ::= { aes 22 }

cea-aes256-cbc CONTENT-ENCRYPTION ::= {
  IDENTIFIER id-aes256-CBC
  PARAMS TYPE AES-IV ARE required
  SMIME-CAPS { IDENTIFIED BY id-aes256-CBC }
}
id-aes256-CBC OBJECT IDENTIFIER ::= { aes 42 }

-- AES-IV is the parameter for all the above object identifiers.

AES-IV ::= OCTET STRING (SIZE(16))

-- AES Key Wrap Algorithm Identifiers - Parameter is absent

kwa-aes128-wrap KEY-WRAP ::= {
  IDENTIFIER id-aes128-wrap
  PARAMS ARE absent
  SMIME-CAPS { IDENTIFIED BY id-aes128-wrap }
}
id-aes128-wrap OBJECT IDENTIFIER ::= { aes 5 }

kwa-aes192-wrap KEY-WRAP ::= {
  IDENTIFIER id-aes192-wrap
  PARAMS ARE absent
  SMIME-CAPS { IDENTIFIED BY id-aes192-wrap }
}
id-aes192-wrap OBJECT IDENTIFIER ::= { aes 25 }

kwa-aes256-wrap KEY-WRAP ::= {
  IDENTIFIER id-aes256-wrap
  PARAMS ARE absent
  SMIME-CAPS { IDENTIFIED BY id-aes256-wrap }
}
id-aes256-wrap OBJECT IDENTIFIER ::= { aes 45 }

END
```



**5. ASN.1 Module for [RFC 3851](#)**

```
SecureMimeMessageV3dot1-2009
    {iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)
      smime(16) modules(0) id-mod-msg-v3dot1-02(39)}
DEFINITIONS IMPLICIT TAGS ::=
BEGIN
IMPORTS

SMIME-CAPS, SMIMECapabilities{}
FROM AlgorithmInformation-2009
    {iso(1) identified-organization(3) dod(6) internet(1) security(5)
      mechanisms(5) pkix(7) id-mod(0)
      id-mod-algorithmInformation-02(58)}

ATTRIBUTE
FROM PKIX-CommonTypes-2009
    {iso(1) identified-organization(3) dod(6) internet(1) security(5)
      mechanisms(5) pkix(7) id-mod(0) id-mod-pkixCommon-02(57)}

SubjectKeyIdentifier, IssuerAndSerialNumber, RecipientKeyIdentifier
FROM CryptographicMessageSyntax-2009
    {iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)
      smime(16) modules(0) id-mod-cms-2004-02(41)}

rc2-cbc, SMimeCaps
FROM CryptographicMessageSyntaxAlgorithms-2009
    {iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)
      smime(16) modules(0) id-mod-cmsalg-2001-02(37)}

SMimeCaps
FROM PKIXAlgs-2009
    {iso(1) identified-organization(3) dod(6) internet(1) security(5)
      mechanisms(5) pkix(7) id-mod(0)
      id-mod-pkix1-algorithms2008-02(56)}

SMimeCaps
FROM PKIX1-PSS-OAEP-Algorithms-2009
    {iso(1) identified-organization(3) dod(6) internet(1)
      security(5) mechanisms(5) pkix(7) id-mod(0)
      id-mod-pkix1-rsa-pkalgs-02(54)};

SMimeAttributeSet ATTRIBUTE ::=
    { aa-smimeCapabilities | aa-encrypKeyPref, ... }

-- id-aa is the arc with all new authenticated and unauthenticated
-- attributes produced by the S/MIME Working Group
```



```
id-aa OBJECT IDENTIFIER ::=
  { iso(1) member-body(2) usa(840) rsadsi(113549) pkcs(1) pkcs-9(9)
    smime(16) attributes(2)}

-- The S/MIME Capabilities attribute provides a method of broadcasting
-- the symmetric capabilities understood. Algorithms SHOULD be ordered
-- by preference and grouped by type

aa-smimeCapabilities ATTRIBUTE ::=
  { TYPE SMIMECapabilities{{SMimeCapsSet}} IDENTIFIED BY
    smimeCapabilities }
smimeCapabilities OBJECT IDENTIFIER ::=
  { iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)
    15 }

SMimeCapsSet SMIME-CAPS ::=
  { cap-preferBinaryInside | cap-RC2CBC |
    PKIXAlgs-2009.SMimeCaps |
    CryptographicMessageSyntaxAlgorithms-2009.SMimeCaps |
    PKIX1-PSS-OAEP-Algorithms-2009.SMimeCaps, ... }

-- Encryption Key Preference provides a method of broadcasting the
-- preferred encryption certificate.

aa-encrypKeyPref ATTRIBUTE ::=
  { TYPE SMIMEEncryptionKeyPreference
    IDENTIFIED BY id-aa-encrypKeyPref }

id-aa-encrypKeyPref OBJECT IDENTIFIER ::= {id-aa 11}

SMIMEEncryptionKeyPreference ::= CHOICE {
  issuerAndSerialNumber [0] IssuerAndSerialNumber,
  receiptKeyId [1] RecipientKeyIdentifier,
  subjectAltKeyIdentifier [2] SubjectKeyIdentifier
}

-- receiptKeyId is spelt incorrectly, but kept for historical
-- reasons.

id-smime OBJECT IDENTIFIER ::= { iso(1) member-body(2)
  us(840) rsadsi(113549) pkcs(1) pkcs9(9) 16 }

id-cap OBJECT IDENTIFIER ::= { id-smime 11 }

-- The preferBinaryInside indicates an ability to receive messages
-- with binary encoding inside the CMS wrapper

cap-preferBinaryInside SMIME-CAPS ::=
```



```

    { -- No value -- IDENTIFIED BY id-cap-preferBinaryInside }
id-cap-preferBinaryInside OBJECT IDENTIFIER ::= { id-cap 1 }

-- The following list OIDs to be used with S/MIME V3

-- Signature Algorithms Not Found in [RFC3370]
--
-- md2WithRSAEncryption OBJECT IDENTIFIER ::=
--   {iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-1(1)
--     2}
--
-- Other Signed Attributes
--
-- signingTime OBJECT IDENTIFIER ::=
--   {iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)
--     5}
-- See [RFC5652] for a description of how to encode the attribute
-- value.

cap-RC2CBC SMIME-CAPS ::=
  { TYPE SMIMECapabilitiesParametersForRC2CBC
    IDENTIFIED BY rc2-cbc}

SMIMECapabilitiesParametersForRC2CBC ::= INTEGER (40 | 128, ...)
-- (RC2 Key Length (number of bits))

END

```

## 6. ASN.1 Module for [RFC 3852](#)

This module has an ASN.1 idiom for noting in which version of CMS changes were made from the original PKCS #7; that idiom is "[[v:", where "v" is an integer. For example:

```

RevocationInfoChoice ::= CHOICE {
    crl CertificateList,
    ...,
    [[5: other [1] IMPLICIT OtherRevocationInfoFormat ]] }

```

Similarly, this module adds the ASN.1 idiom for extensibility (the "...") in all places that have been extended in the past. See the example above.

```

CryptographicMessageSyntax-2009
  { iso(1) member-body(2) us(840) rsadsi(113549)
    pkcs(1) pkcs-9(9) smime(16) modules(0) id-mod-cms-2004-02(41) }
DEFINITIONS IMPLICIT TAGS ::=

```



BEGIN

IMPORTS

ParamOptions, DIGEST-ALGORITHM, SIGNATURE-ALGORITHM,  
PUBLIC-KEY, KEY-DERIVATION, KEY-WRAP, MAC-ALGORITHM,  
KEY-AGREE, KEY-TRANSPORT, CONTENT-ENCRYPTION, ALGORITHM,  
AlgorithmIdentifier

FROM AlgorithmInformation-2009

{iso(1) identified-organization(3) dod(6) internet(1) security(5)  
mechanisms(5) pkix(7) id-mod(0)  
id-mod-algorithmInformation-02(58)}

SignatureAlgs, MessageDigestAlgs, KeyAgreementAlgs,  
MessageAuthAlgs, KeyWrapAlgs, ContentEncryptionAlgs,  
KeyTransportAlgs, KeyDerivationAlgs, KeyAgreePublicKeys

FROM CryptographicMessageSyntaxAlgorithms-2009

{ iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)  
smime(16) modules(0) id-mod-cmsalg-2001-02(37) }

Certificate, CertificateList, CertificateSerialNumber,  
Name, ATTRIBUTE

FROM PKIX1Explicit-2009

{ iso(1) identified-organization(3) dod(6) internet(1)  
security(5) mechanisms(5) pkix(7) id-mod(0)  
id-mod-pkix1-explicit-02(51) }

AttributeCertificate

FROM PKIXAttributeCertificate-2009

{ iso(1) identified-organization(3) dod(6) internet(1)  
security(5) mechanisms(5) pkix(7) id-mod(0)  
id-mod-attribute-cert-02(47) }

AttributeCertificateV1

FROM AttributeCertificateVersion1-2009

{ iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)  
smime(16) modules(0) id-mod-v1AttrCert-02(49) } ;

-- Cryptographic Message Syntax

-- The following are used for version numbers using the ASN.1

-- idiom "[[n:"

-- Version 1 = PKCS #7

-- Version 2 = S/MIME V2

-- Version 3 = [RFC 2630](#)

-- Version 4 = [RFC 3369](#)

-- Version 5 = [RFC 3852](#)

CONTENT-TYPE ::= TYPE-IDENTIFIER

ContentType ::= CONTENT-TYPE.&id



```
ContentInfo ::= SEQUENCE {
    contentType      CONTENT-TYPE.
                    &id({ContentSet}),
    content          [0] EXPLICIT CONTENT-TYPE.
                    &Type({ContentSet}{@contentType})}

ContentSet CONTENT-TYPE ::= {
    -- Define the set of content types to be recognized.
    ct-Data | ct-SignedData | ct-EncryptedData | ct-EnvelopedData |
    ct-AuthenticatedData | ct-DigestedData, ... }

SignedData ::= SEQUENCE {
    version CMSVersion,
    digestAlgorithms SET OF DigestAlgorithmIdentifier,
    encapContentInfo EncapsulatedContentInfo,
    certificates [0] IMPLICIT CertificateSet OPTIONAL,
    crls [1] IMPLICIT RevocationInfoChoices OPTIONAL,
    signerInfos SignerInfos }

SignerInfos ::= SET OF SignerInfo

EncapsulatedContentInfo ::= SEQUENCE {
    eContentType      CONTENT-TYPE.&id({ContentSet}),
    eContent          [0] EXPLICIT OCTET STRING
                    ( CONTAINING CONTENT-TYPE.
                      &Type({ContentSet}{@eContentType})) OPTIONAL }

SignerInfo ::= SEQUENCE {
    version CMSVersion,
    sid SignerIdentifier,
    digestAlgorithm DigestAlgorithmIdentifier,
    signedAttrs [0] IMPLICIT SignedAttributes OPTIONAL,
    signatureAlgorithm SignatureAlgorithmIdentifier,
    signature SignatureValue,
    unsignedAttrs [1] IMPLICIT Attributes
                 {{UnsignedAttributes}} OPTIONAL }

SignedAttributes ::= Attributes {{ SignedAttributesSet }}

SignerIdentifier ::= CHOICE {
    issuerAndSerialNumber IssuerAndSerialNumber,
    ...,
    [[3: subjectKeyIdentifier [0] SubjectKeyIdentifier ]] }

SignedAttributesSet ATTRIBUTE ::=
    { aa-signingTime | aa-messageDigest | aa-contentType, ... }

UnsignedAttributes ATTRIBUTE ::= { aa-countersignature, ... }
```



SignatureValue ::= OCTET STRING

```

EnvelopedData ::= SEQUENCE {
    version CMSVersion,
    originatorInfo [0] IMPLICIT OriginatorInfo OPTIONAL,
    recipientInfos RecipientInfos,
    encryptedContentInfo EncryptedContentInfo,
    ...,
    [[2: unprotectedAttrs [1] IMPLICIT Attributes
        {{ UnprotectedAttributes }} OPTIONAL ]] }

```

```

OriginatorInfo ::= SEQUENCE {
    certs [0] IMPLICIT CertificateSet OPTIONAL,
    crls [1] IMPLICIT RevocationInfoChoices OPTIONAL }

```

RecipientInfos ::= SET SIZE (1..MAX) OF RecipientInfo

```

EncryptedContentInfo ::= SEQUENCE {
    contentType          CONTENT-TYPE.&id({ContentSet}),
    contentEncryptionAlgorithm ContentEncryptionAlgorithmIdentifier,
    encryptedContent     [0] IMPLICIT OCTET STRING OPTIONAL }

```

-- If you want to do constraints, you might use:

```

-- EncryptedContentInfo ::= SEQUENCE {
--   contentType          CONTENT-TYPE.&id({ContentSet}),
--   contentEncryptionAlgorithm ContentEncryptionAlgorithmIdentifier,
--   encryptedContent     [0] IMPLICIT ENCRYPTED {CONTENT-TYPE.
--       &Type({ContentSet}@contentType) OPTIONAL }
-- ENCRYPTED {ToBeEncrypted} ::= OCTET STRING ( CONSTRAINED BY
--   { ToBeEncrypted } )

```

UnprotectedAttributes ATTRIBUTE ::= { ... }

```

RecipientInfo ::= CHOICE {
    ktri          KeyTransRecipientInfo,
    ...,
    [[3: kari [1] KeyAgreeRecipientInfo ]],
    [[4: kekri [2] KEKRecipientInfo]],
    [[5: pwri [3] PasswordRecipientInfo,
        ori [4] OtherRecipientInfo ]] }

```

EncryptedKey ::= OCTET STRING

```

KeyTransRecipientInfo ::= SEQUENCE {
    version CMSVersion, -- always set to 0 or 2
    rid RecipientIdentifier,
    keyEncryptionAlgorithm AlgorithmIdentifier
        {KEY-TRANSPORT, {KeyTransportAlgorithmSet}},

```



```
encryptedKey EncryptedKey }

KeyTransportAlgorithmSet KEY-TRANSPORT ::= { KeyTransportAlgs, ... }

RecipientIdentifier ::= CHOICE {
    issuerAndSerialNumber IssuerAndSerialNumber,
    ...,
    [[2: subjectKeyIdentifier [0] SubjectKeyIdentifier ]] }
KeyAgreeRecipientInfo ::= SEQUENCE {
    version CMSVersion, -- always set to 3
    originator [0] EXPLICIT OriginatorIdentifierOrKey,
    ukm [1] EXPLICIT UserKeyingMaterial OPTIONAL,
    keyEncryptionAlgorithm AlgorithmIdentifier
        {KEY-AGREE, {KeyAgreementAlgorithmSet}},
    recipientEncryptedKeys RecipientEncryptedKeys }

KeyAgreementAlgorithmSet KEY-AGREE ::= { KeyAgreementAlgs, ... }

OriginatorIdentifierOrKey ::= CHOICE {
    issuerAndSerialNumber IssuerAndSerialNumber,
    subjectKeyIdentifier [0] SubjectKeyIdentifier,
    originatorKey [1] OriginatorPublicKey }

OriginatorPublicKey ::= SEQUENCE {
    algorithm AlgorithmIdentifier {PUBLIC-KEY, {OriginatorKeySet}},
    publicKey BIT STRING }

OriginatorKeySet PUBLIC-KEY ::= { KeyAgreePublicKeys, ... }

RecipientEncryptedKeys ::= SEQUENCE OF RecipientEncryptedKey

RecipientEncryptedKey ::= SEQUENCE {
    rid KeyAgreeRecipientIdentifier,
    encryptedKey EncryptedKey }

KeyAgreeRecipientIdentifier ::= CHOICE {
    issuerAndSerialNumber IssuerAndSerialNumber,
    rKeyId [0] IMPLICIT RecipientKeyIdentifier }

RecipientKeyIdentifier ::= SEQUENCE {
    subjectKeyIdentifier SubjectKeyIdentifier,
    date GeneralizedTime OPTIONAL,
    other OtherKeyAttribute OPTIONAL }

SubjectKeyIdentifier ::= OCTET STRING

KEKRecipientInfo ::= SEQUENCE {
    version CMSVersion, -- always set to 4
```



```
kekid KEKIdentifier,  
keyEncryptionAlgorithm KeyEncryptionAlgorithmIdentifier,  
encryptedKey EncryptedKey }
```

```
KEKIdentifier ::= SEQUENCE {  
    keyIdentifier OCTET STRING,  
    date GeneralizedTime OPTIONAL,  
    other OtherKeyAttribute OPTIONAL }
```

```
PasswordRecipientInfo ::= SEQUENCE {  
    version CMSVersion,    -- always set to 0  
    keyDerivationAlgorithm [0] KeyDerivationAlgorithmIdentifier  
        OPTIONAL,  
    keyEncryptionAlgorithm KeyEncryptionAlgorithmIdentifier,  
    encryptedKey EncryptedKey }
```

```
OTHER-RECIPIENT ::= TYPE-IDENTIFIER
```

```
OtherRecipientInfo ::= SEQUENCE {  
    oriType    OTHER-RECIPIENT.  
        &id({SupportedOtherRecipInfo}),  
    oriValue   OTHER-RECIPIENT.  
        &Type({SupportedOtherRecipInfo}{@oriType})}
```

```
SupportedOtherRecipInfo OTHER-RECIPIENT ::= { ... }
```

```
DigestedData ::= SEQUENCE {  
    version CMSVersion,  
    digestAlgorithm DigestAlgorithmIdentifier,  
    encapContentInfo EncapsulatedContentInfo,  
    digest Digest, ... }
```

```
Digest ::= OCTET STRING
```

```
EncryptedData ::= SEQUENCE {  
    version CMSVersion,  
    encryptedContentInfo EncryptedContentInfo,  
    ...,  
    [[2: unprotectedAttrs [1] IMPLICIT Attributes  
        {{UnprotectedAttributes}} OPTIONAL ]] }
```

```
AuthenticatedData ::= SEQUENCE {  
    version CMSVersion,  
    originatorInfo [0] IMPLICIT OriginatorInfo OPTIONAL,  
    recipientInfos RecipientInfos,  
    macAlgorithm MessageAuthenticationCodeAlgorithm,  
    digestAlgorithm [1] DigestAlgorithmIdentifier OPTIONAL,  
    encapContentInfo EncapsulatedContentInfo,  
    authAttrs [2] IMPLICIT AuthAttributes OPTIONAL,
```



```
    mac MessageAuthenticationCode,
    unauthAttrs [3] IMPLICIT UnauthAttributes OPTIONAL }

AuthAttributes ::= SET SIZE (1..MAX) OF Attribute
    {{AuthAttributeSet}}

AuthAttributeSet ATTRIBUTE ::= { aa-contentType | aa-messageDigest
    | aa-signingTime, ...}
MessageAuthenticationCode ::= OCTET STRING

UnauthAttributes ::= SET SIZE (1..MAX) OF Attribute
    {{UnauthAttributeSet}}

UnauthAttributeSet ATTRIBUTE ::= {...}

--
-- General algorithm definitions
--

DigestAlgorithmIdentifier ::= AlgorithmIdentifier
    {DIGEST-ALGORITHM, {DigestAlgorithmSet}}

DigestAlgorithmSet DIGEST-ALGORITHM ::= {
    CryptographicMessageSyntaxAlgorithms-2009.MessageDigestAlgs, ... }

SignatureAlgorithmIdentifier ::= AlgorithmIdentifier
    {SIGNATURE-ALGORITHM, {SignatureAlgorithmSet}}

SignatureAlgorithmSet SIGNATURE-ALGORITHM ::=
    { SignatureAlgs, ... }

KeyEncryptionAlgorithmIdentifier ::= AlgorithmIdentifier
    {KEY-WRAP, {KeyEncryptionAlgorithmSet}}

KeyEncryptionAlgorithmSet KEY-WRAP ::= { KeyWrapAlgs, ... }

ContentEncryptionAlgorithmIdentifier ::= AlgorithmIdentifier
    {CONTENT-ENCRYPTION, {ContentEncryptionAlgorithmSet}}

ContentEncryptionAlgorithmSet CONTENT-ENCRYPTION ::=
    { ContentEncryptionAlgs, ... }

MessageAuthenticationCodeAlgorithm ::= AlgorithmIdentifier
    {MAC-ALGORITHM, {MessageAuthenticationCodeAlgorithmSet}}

MessageAuthenticationCodeAlgorithmSet MAC-ALGORITHM ::=
    { MessageAuthAlgs, ... }
```



```
KeyDerivationAlgorithmIdentifier ::= AlgorithmIdentifier
    {KEY-DERIVATION, {KeyDerivationAlgs, ...}}
```

```
RevocationInfoChoices ::= SET OF RevocationInfoChoice
```

```
RevocationInfoChoice ::= CHOICE {
    crl CertificateList,
    ...,
    [[5: other [1] IMPLICIT OtherRevocationInfoFormat ]] }
```

```
OTHER-REVOK-INFO ::= TYPE-IDENTIFIER
```

```
OtherRevocationInfoFormat ::= SEQUENCE {
    otherRevInfoFormat OTHER-REVOK-INFO.
        &id({SupportedOtherRevokInfo}),
    otherRevInfo OTHER-REVOK-INFO.
        &Type({SupportedOtherRevokInfo}@otherRevInfoFormat)}
```

```
SupportedOtherRevokInfo OTHER-REVOK-INFO ::= { ... }
```

```
CertificateChoices ::= CHOICE {
    certificate Certificate,
    extendedCertificate [0] IMPLICIT ExtendedCertificate,
    -- Obsolete
    ...,
    [[3: v1AttrCert [1] IMPLICIT AttributeCertificateV1]],
    -- Obsolete
    [[4: v2AttrCert [2] IMPLICIT AttributeCertificateV2]],
    [[5: other [3] IMPLICIT OtherCertificateFormat]] }
```

```
AttributeCertificateV2 ::= AttributeCertificate
```

```
OTHER-CERT-FMT ::= TYPE-IDENTIFIER
```

```
OtherCertificateFormat ::= SEQUENCE {
    otherCertFormat OTHER-CERT-FMT.
        &id({SupportedCertFormats}),
    otherCert OTHER-CERT-FMT.
        &Type({SupportedCertFormats}@otherCertFormat)}
```

```
SupportedCertFormats OTHER-CERT-FMT ::= { ... }
```

```
CertificateSet ::= SET OF CertificateChoices
```

```
IssuerAndSerialNumber ::= SEQUENCE {
    issuer Name,
    serialNumber CertificateSerialNumber }
```



CMSVersion ::= INTEGER { v0(0), v1(1), v2(2), v3(3), v4(4), v5(5) }

UserKeyingMaterial ::= OCTET STRING

KEY-ATTRIBUTE ::= TYPE-IDENTIFIER

OtherKeyAttribute ::= SEQUENCE {  
    keyAttrId KEY-ATTRIBUTE.  
  
    &id({SupportedKeyAttributes}),  
    keyAttr KEY-ATTRIBUTE.  
    &Type({SupportedKeyAttributes}@keyAttrId)}

SupportedKeyAttributes KEY-ATTRIBUTE ::= { ... }

-- Content Type Object Identifiers

id-ct-contentInfo OBJECT IDENTIFIER ::= { iso(1) member-body(2)  
    us(840) rsadsi(113549) pkcs(1) pkcs9(9) smime(16) ct(1) 6 }

ct-Data CONTENT-TYPE ::= {OCTET STRING IDENTIFIED BY id-data}

id-data OBJECT IDENTIFIER ::= { iso(1) member-body(2)  
    us(840) rsadsi(113549) pkcs(1) pkcs7(7) 1 }

ct-SignedData CONTENT-TYPE ::=  
    { SignedData IDENTIFIED BY id-signedData}

id-signedData OBJECT IDENTIFIER ::= { iso(1) member-body(2)  
    us(840) rsadsi(113549) pkcs(1) pkcs7(7) 2 }

ct-EnvelopedData CONTENT-TYPE ::=  
    { EnvelopedData IDENTIFIED BY id-envelopedData}

id-envelopedData OBJECT IDENTIFIER ::= { iso(1) member-body(2)  
    us(840) rsadsi(113549) pkcs(1) pkcs7(7) 3 }

ct-DigestedData CONTENT-TYPE ::=  
    { DigestedData IDENTIFIED BY id-digestedData}

id-digestedData OBJECT IDENTIFIER ::= { iso(1) member-body(2)  
    us(840) rsadsi(113549) pkcs(1) pkcs7(7) 5 }

ct-EncryptedData CONTENT-TYPE ::=  
    { EncryptedData IDENTIFIED BY id-encryptedData}

id-encryptedData OBJECT IDENTIFIER ::= { iso(1) member-body(2)  
    us(840) rsadsi(113549) pkcs(1) pkcs7(7) 6 }



```
ct-AuthenticatedData CONTENT-TYPE ::=
  { AuthenticatedData IDENTIFIED BY id-ct-authData}

id-ct-authData OBJECT IDENTIFIER ::= { iso(1) member-body(2)
  us(840) rsadsi(113549) pkcs(1) pkcs-9(9) smime(16) ct(1) 2 }

--
-- The CMS Attributes
--

MessageDigest ::= OCTET STRING

SigningTime ::= Time

Time ::= CHOICE {
  utcTime UTCTime,
  generalTime GeneralizedTime }

Countersignature ::= SignerInfo

-- Attribute Object Identifiers

aa-contentType ATTRIBUTE ::=
  { TYPE ContentType IDENTIFIED BY id-contentType }
id-contentType OBJECT IDENTIFIER ::= { iso(1) member-body(2)
  us(840) rsadsi(113549) pkcs(1) pkcs9(9) 3 }

aa-messageDigest ATTRIBUTE ::=
  { TYPE MessageDigest IDENTIFIED BY id-messageDigest}
id-messageDigest OBJECT IDENTIFIER ::= { iso(1) member-body(2)
  us(840) rsadsi(113549) pkcs(1) pkcs9(9) 4 }

aa-signingTime ATTRIBUTE ::=
  { TYPE SigningTime IDENTIFIED BY id-signingTime }
id-signingTime OBJECT IDENTIFIER ::= { iso(1) member-body(2)
  us(840) rsadsi(113549) pkcs(1) pkcs9(9) 5 }

aa-countersignature ATTRIBUTE ::=
  { TYPE Countersignature IDENTIFIED BY id-countersignature }
id-countersignature OBJECT IDENTIFIER ::= { iso(1) member-body(2)
  us(840) rsadsi(113549) pkcs(1) pkcs9(9) 6 }

--
-- Obsolete Extended Certificate syntax from PKCS#6
--

ExtendedCertificateOrCertificate ::= CHOICE {
  certificate Certificate,
```



```

    extendedCertificate [0] IMPLICIT ExtendedCertificate }

ExtendedCertificate ::= SEQUENCE {
    extendedCertificateInfo ExtendedCertificateInfo,
    signatureAlgorithm SignatureAlgorithmIdentifier,
    signature Signature }

ExtendedCertificateInfo ::= SEQUENCE {
    version CMSVersion,
    certificate Certificate,
    attributes UnauthAttributes }

Signature ::= BIT STRING

Attribute{ ATTRIBUTE:AttrList } ::= SEQUENCE {
    attrType          ATTRIBUTE,
    &id({AttrList}),
    attrValues        SET OF ATTRIBUTE.
    &Type({AttrList}{@attrType}) }

Attributes { ATTRIBUTE:AttrList } ::=
    SET SIZE (1..MAX) OF Attribute [{ AttrList }]

```

END

## 7. ASN.1 Module for [RFC 4108](#)

```

CMSFirmwareWrapper-2009
    { iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)
      smime(16) modules(0) id-mod-cms-firmware-wrap-02(40) }
DEFINITIONS IMPLICIT TAGS ::=
BEGIN
IMPORTS

OTHER-NAME
FROM PKIX1Implicit-2009
    { iso(1) identified-organization(3) dod(6) internet(1) security(5)
      mechanisms(5) pkix(7) id-mod(0) id-mod-pkix1-implicit-02(59) }

EnvelopedData, CONTENT-TYPE, ATTRIBUTE
FROM CryptographicMessageSyntax-2009
    { iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)
      smime(16) modules(0) id-mod-cms-2004-02(41) };

FirmwareContentTypes CONTENT-TYPE ::= {
    ct-firmwarePackage | ct-firmwareLoadReceipt |
    ct-firmwareLoadError,... }

```



```
FirmwareSignedAttrs ATTRIBUTE ::= {
    aa-firmwarePackageID | aa-targetHardwareIDs |
    aa-decryptKeyID | aa-implCryptoAlgs | aa-implCompressAlgs |
    aa-communityIdentifiers | aa-firmwarePackageInfo, ... }
FirmwareUnsignedAttrs ATTRIBUTE ::= {
    aa-wrappedFirmwareKey, ... }

FirmwareOtherNames OTHER-NAME ::= {
    on-hardwareModuleName, ... }

-- Firmware Package Content Type and Object Identifier

ct-firmwarePackage CONTENT-TYPE ::=
    { FirmwarePkgData IDENTIFIED BY id-ct-firmwarePackage }

id-ct-firmwarePackage OBJECT IDENTIFIER ::= {
    iso(1) member-body(2) us(840) rsdsi(113549) pkcs(1) pkcs9(9)
    smime(16) ct(1) 16 }

FirmwarePkgData ::= OCTET STRING

-- Firmware Package Signed Attributes and Object Identifiers

aa-firmwarePackageID ATTRIBUTE ::=
    { TYPE FirmwarePackageIdentifier IDENTIFIED BY
      id-aa-firmwarePackageID }

id-aa-firmwarePackageID OBJECT IDENTIFIER ::= {
    iso(1) member-body(2) us(840) rsdsi(113549) pkcs(1) pkcs9(9)
    smime(16) aa(2) 35 }

FirmwarePackageIdentifier ::= SEQUENCE {
    name PreferredOrLegacyPackageIdentifier,
    stale PreferredOrLegacyStalePackageIdentifier OPTIONAL }

PreferredOrLegacyPackageIdentifier ::= CHOICE {
    preferred PreferredPackageIdentifier,
    legacy OCTET STRING }

PreferredPackageIdentifier ::= SEQUENCE {
    fwPkgID OBJECT IDENTIFIER,
    verNum INTEGER (0..MAX) }

PreferredOrLegacyStalePackageIdentifier ::= CHOICE {
    preferredStaleVerNum INTEGER (0..MAX),
    legacyStaleVersion OCTET STRING }

aa-targetHardwareIDs ATTRIBUTE ::=
```



```
{ TYPE TargetHardwareIdentifiers IDENTIFIED BY
  id-aa-targetHardwareIDs }
```

```
id-aa-targetHardwareIDs OBJECT IDENTIFIER ::= {
  iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs9(9)
  smime(16) aa(2) 36 }
```

```
TargetHardwareIdentifiers ::= SEQUENCE OF OBJECT IDENTIFIER
```

```
aa-decryptKeyID ATTRIBUTE ::=
  { TYPE DecryptKeyIdentifier IDENTIFIED BY id-aa-decryptKeyID}
```

```
id-aa-decryptKeyID OBJECT IDENTIFIER ::= {
  iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs9(9)
  smime(16) aa(2) 37 }
```

```
DecryptKeyIdentifier ::= OCTET STRING
```

```
aa-implCryptoAlgs ATTRIBUTE ::=
  { TYPE ImplementedCryptoAlgorithms IDENTIFIED BY
    id-aa-implCryptoAlgs }
```

```
id-aa-implCryptoAlgs OBJECT IDENTIFIER ::= {
  iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs9(9)
  smime(16) aa(2) 38 }
```

```
ImplementedCryptoAlgorithms ::= SEQUENCE OF OBJECT IDENTIFIER
```

```
aa-implCompressAlgs ATTRIBUTE ::=
  { TYPE ImplementedCompressAlgorithms IDENTIFIED BY
    id-aa-implCompressAlgs }
```

```
id-aa-implCompressAlgs OBJECT IDENTIFIER ::= {
  iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs9(9)
  smime(16) aa(2) 43 }
```

```
ImplementedCompressAlgorithms ::= SEQUENCE OF OBJECT IDENTIFIER
```

```
aa-communityIdentifiers ATTRIBUTE ::=
  { TYPE CommunityIdentifiers IDENTIFIED BY
    id-aa-communityIdentifiers }
```

```
id-aa-communityIdentifiers OBJECT IDENTIFIER ::= {
  iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs9(9)
  smime(16) aa(2) 40 }
```

```
CommunityIdentifiers ::= SEQUENCE OF CommunityIdentifier
```



```
CommunityIdentifier ::= CHOICE {
    communityOID OBJECT IDENTIFIER,
    hwModuleList HardwareModules }
HardwareModules ::= SEQUENCE {
    hwType OBJECT IDENTIFIER,
    hwSerialEntries SEQUENCE OF HardwareSerialEntry }

HardwareSerialEntry ::= CHOICE {
    all NULL,
    single OCTET STRING,
    block SEQUENCE {
        low OCTET STRING,
        high OCTET STRING
    }
}

aa-firmwarePackageInfo ATTRIBUTE ::=
    { TYPE FirmwarePackageInfo IDENTIFIED BY
      id-aa-firmwarePackageInfo }
id-aa-firmwarePackageInfo OBJECT IDENTIFIER ::= {
    iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs9(9)
    smime(16) aa(2) 42 }

FirmwarePackageInfo ::= SEQUENCE {
    fwPkgType INTEGER OPTIONAL,
    dependencies SEQUENCE OF
    PreferredOrLegacyPackageIdentifier OPTIONAL }

-- Firmware Package Unsigned Attributes and Object Identifiers

aa-wrappedFirmwareKey ATTRIBUTE ::=
    { TYPE WrappedFirmwareKey IDENTIFIED BY
      id-aa-wrappedFirmwareKey }
id-aa-wrappedFirmwareKey OBJECT IDENTIFIER ::= {
    iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs9(9)
    smime(16) aa(2) 39 }

WrappedFirmwareKey ::= EnvelopedData

-- Firmware Package Load Receipt Content Type and Object Identifier

ct-firmwareLoadReceipt CONTENT-TYPE ::=
    { FirmwarePackageLoadReceipt IDENTIFIED BY
      id-ct-firmwareLoadReceipt }
id-ct-firmwareLoadReceipt OBJECT IDENTIFIER ::= {
    iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs9(9)
    smime(16) ct(1) 17 }
```



```
FirmwarePackageLoadReceipt ::= SEQUENCE {
    version FWReceiptVersion DEFAULT v1,
    hwType OBJECT IDENTIFIER,
    hwSerialNum OCTET STRING,
    fwPkgName PreferredOrLegacyPackageIdentifier,
    trustAnchorKeyID OCTET STRING OPTIONAL,
    decryptKeyID [1] OCTET STRING OPTIONAL }

FWReceiptVersion ::= INTEGER { v1(1) }

-- Firmware Package Load Error Report Content Type
-- and Object Identifier

ct-firmwareLoadError CONTENT-TYPE ::=
    { FirmwarePackageLoadError
      IDENTIFIED BY id-ct-firmwareLoadError }
id-ct-firmwareLoadError OBJECT IDENTIFIER ::= {
    iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs9(9)
    smime(16) ct(1) 18 }

FirmwarePackageLoadError ::= SEQUENCE {
    version FWErrorVersion DEFAULT v1,
    hwType OBJECT IDENTIFIER,
    hwSerialNum OCTET STRING,
    errorCode FirmwarePackageLoadErrorCode,
    vendorErrorCode VendorLoadErrorCode OPTIONAL,
    fwPkgName PreferredOrLegacyPackageIdentifier OPTIONAL,
    config [1] SEQUENCE OF CurrentFWConfig OPTIONAL }

FWErrorVersion ::= INTEGER { v1(1) }

CurrentFWConfig ::= SEQUENCE {
    fwPkgType INTEGER OPTIONAL,
    fwPkgName PreferredOrLegacyPackageIdentifier }

FirmwarePackageLoadErrorCode ::= ENUMERATED {
    decodeFailure           (1),
    badContentInfo          (2),
    badSignedData           (3),
    badEncapContent         (4),
    badCertificate          (5),
    badSignerInfo           (6),
    badSignedAttrs          (7),
    badUnsignedAttrs        (8),
    missingContent          (9),
    noTrustAnchor           (10),
    notAuthorized           (11),
    badDigestAlgorithm      (12),
```



```
badSignatureAlgorithm      (13),
unsupportedKeySize          (14),
signatureFailure           (15),
contentTypeMismatch        (16),
badEncryptedData           (17),
unprotectedAttrsPresent    (18),
badEncryptContent          (19),
badEncryptAlgorithm        (20),
missingCiphertext          (21),
noDecryptKey               (22),
decryptFailure             (23),
badCompressAlgorithm       (24),
missingCompressedContent   (25),
decompressFailure          (26),
wrongHardware              (27),
stalePackage               (28),
notInCommunity             (29),
unsupportedPackageType      (30),
missingDependency          (31),
wrongDependencyVersion     (32),
insufficientMemory         (33),
badFirmware                (34),
unsupportedParameters       (35),
breaksDependency           (36),
otherError                  (99) }
```

```
VendorLoadErrorCode ::= INTEGER
```

```
-- Other Name syntax for Hardware Module Name
```

```
on-hardwareModuleName OTHER-NAME ::=
    { HardwareModuleName IDENTIFIED BY id-on-hardwareModuleName }
id-on-hardwareModuleName OBJECT IDENTIFIER ::= {
    iso(1) identified-organization(3) dod(6) internet(1) security(5)
    mechanisms(5) pkix(7) on(8) 4 }
```

```
HardwareModuleName ::= SEQUENCE {
    hwType OBJECT IDENTIFIER,
    hwSerialNum OCTET STRING }
```

```
END
```



**8. ASN.1 Module for RFC 4998**

```

ERS {iso(1) identified-organization(3) dod(6) internet(1)
    security(5) mechanisms(5) ltans(11) id-mod(0) id-mod-ers(1)
    id-mod-ers-v1(1) }
DEFINITIONS IMPLICIT TAGS ::=
BEGIN
IMPORTS

AttributeSet{ }, ATTRIBUTE
FROM PKIX-CommonTypes
    {iso(1) identified-organization(3) dod(6) internet(1) security(5)
    mechanisms(5) pkix(7) id-mod(0) id-mod-pkixCommon-02(57) }

AlgorithmIdentifier{ }, ALGORITHM, DIGEST-ALGORITHM
FROM AlgorithmInformation-2009
    {iso(1) identified-organization(3) dod(6) internet(1) security(5)
    mechanisms(5) pkix(7) id-mod(0)
    id-mod-algorithmInformation-02(58)}

ContentInfo
FROM CryptographicMessageSyntax2004
    { iso(1) member-body(2) us(840) rsadsi(113549)
    pkcs(1) pkcs-9(9) smime(16) modules(0) id-mod-cms-2004-02(41) } ;

aa-er-Internal ATTRIBUTE ::=
    { TYPE EvidenceRecord IDENTIFIED BY id-aa-er-internal }
id-aa-er-internal OBJECT IDENTIFIER ::=
    { iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs9(9)
    smime(16) id-aa(2) 49 }

aa-er-External ATTRIBUTE ::=
    { TYPE EvidenceRecord IDENTIFIED BY id-aa-er-external }
id-aa-er-external OBJECT IDENTIFIER ::=
    { iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs9(9)
    smime(16) id-aa(2) 50 }

ltans OBJECT IDENTIFIER ::=
    {iso(1) identified-organization(3) dod(6) internet(1) security(5)
    mechanisms(5) ltans(11) }

EvidenceRecord ::= SEQUENCE {
    version                INTEGER { v1(1) } ,
    digestAlgorithms       SEQUENCE OF AlgorithmIdentifier
                            {DIGEST-ALGORITHM, {...}},
    cryptoInfos            [0] CryptoInfos OPTIONAL,
    encryptionInfo        [1] EncryptionInfo OPTIONAL,
    archiveTimeStampSequence ArchiveTimeStampSequence

```



}

CryptoInfos ::= SEQUENCE SIZE (1..MAX) OF AttributeSet{{...}}

ArchiveTimeStampSequence ::= SEQUENCE OF ArchiveTimeStampChain

ArchiveTimeStampChain ::= SEQUENCE OF ArchiveTimeStamp

```

ArchiveTimeStamp ::= SEQUENCE {
    digestAlgorithm [0] AlgorithmIdentifier{DIGEST-ALGORITHM, {...}}
                        OPTIONAL,
    attributes      [1] Attributes OPTIONAL,
    reducedHashtree [2] SEQUENCE OF PartialHashtree OPTIONAL,
    timeStamp       ContentInfo
}

```

PartialHashtree ::= SEQUENCE OF OCTET STRING

Attributes ::= SET SIZE (1..MAX) OF AttributeSet{{...}}

```

EncryptionInfo ::= SEQUENCE {
    encryptionInfoType  ENCINFO-TYPE.
                        &id({SupportedEncryptionAlgorithms}),
    encryptionInfoValue ENCINFO-TYPE.
                        &Type({SupportedEncryptionAlgorithms}
                        {@encryptionInfoType})
}

```

ENCINFO-TYPE ::= TYPE-IDENTIFIER

SupportedEncryptionAlgorithms ENCINFO-TYPE ::= {...}

END

## 9. ASN.1 Module for [RFC 5035](#)

Section numbers in the module refer to the sections of [RFC 2634](#) as updated by [RFC 5035](#).

```

ExtendedSecurityServices-2009
    { iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)
      smime(16) modules(0) id-mod-ess-2006-02(42) }
DEFINITIONS IMPLICIT TAGS ::=
BEGIN
IMPORTS

AttributeSet{}, ATTRIBUTE, SECURITY-CATEGORY, SecurityCategory{}
FROM PKIX-CommonTypes-2009
    { iso(1) identified-organization(3) dod(6) internet(1) security(5)

```



```
mechanisms(5) pkix(7) id-mod(0) id-mod-pkixCommon-02(57) }
```

```
AlgorithmIdentifier{ }, ALGORITHM, DIGEST-ALGORITHM
FROM AlgorithmInformation-2009
{ iso(1) identified-organization(3) dod(6) internet(1) security(5)
mechanisms(5) pkix(7) id-mod(0)
id-mod-algorithmInformation-02(58) }
```

```
ContentType, IssuerAndSerialNumber, SubjectKeyIdentifier,
CONTENT-TYPE
FROM CryptographicMessageSyntax-2009
{ iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)
smime(16) modules(0) id-mod-cms-2004-02(41) }
```

```
CertificateSerialNumber
FROM PKIX1Explicit-2009
{ iso(1) identified-organization(3) dod(6) internet(1) security(5)
mechanisms(5) pkix(7) id-mod(0) id-mod-pkix1-explicit-02(51) }
```

```
PolicyInformation, GeneralNames
FROM PKIX1Implicit-2009
{ iso(1) identified-organization(3) dod(6) internet(1) security(5)
mechanisms(5) pkix(7) id-mod(0) id-mod-pkix1-implicit-02(59) }
```

```
mda-sha256
FROM PKIX1-PSS-OAEP-Algorithms-2009
{ iso(1) identified-organization(3) dod(6)
internet(1) security(5) mechanisms(5) pkix(7) id-mod(0)
id-mod-pkix1-rsa-pkalgs-02(54) } ;
```

```
EssSignedAttributes ATTRIBUTE ::= {
aa-receiptRequest | aa-contentIdentifier | aa-contentHint |
aa-msgSigDigest | aa-contentReference | aa-securityLabel |
aa-equivalentLabels | aa-mlExpandHistory | aa-signingCertificate |
aa-signingCertificateV2, ... }
```

```
EssContentTypes CONTENT-TYPE ::= { ct-receipt, ... }
```

```
-- Extended Security Services
-- The construct "SEQUENCE SIZE (1..MAX) OF" appears in several ASN.1
-- constructs in this module. A valid ASN.1 SEQUENCE can have zero or
-- more entries. The SIZE (1..MAX) construct constrains the SEQUENCE
-- to have at least one entry. MAX indicates the upper bound is
-- unspecified. Implementations are free to choose an upper bound
-- that suits their environment.
```

```
-- Section 2.7
```



```
aa-receiptRequest ATTRIBUTE ::=
  { TYPE ReceiptRequest IDENTIFIED BY id-aa-receiptRequest}

ReceiptRequest ::= SEQUENCE {
  signedContentIdentifier ContentIdentifier,
  receiptsFrom ReceiptsFrom,
  receiptsTo SEQUENCE SIZE (1..ub-receiptsTo) OF GeneralNames
}

ub-receiptsTo INTEGER ::= 16

aa-contentIdentifier ATTRIBUTE ::=
  { TYPE ContentIdentifier IDENTIFIED BY id-aa-contentIdentifier}
id-aa-receiptRequest OBJECT IDENTIFIER ::=
  { iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)
  smime(16) id-aa(2) 1}

ContentIdentifier ::= OCTET STRING

id-aa-contentIdentifier OBJECT IDENTIFIER ::= { iso(1) member-body(2)
  us(840) rsadsi(113549) pkcs(1) pkcs-9(9) smime(16) id-aa(2) 7}

ct-receipt CONTENT-TYPE ::=
  { Receipt IDENTIFIED BY id-ct-receipt }
id-ct-receipt OBJECT IDENTIFIER ::=
  { iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)
  smime(16) id-ct(1) 1}

ReceiptsFrom ::= CHOICE {
  allOrFirstTier [0] AllOrFirstTier,
  -- formerly "allOrNone [0]AllOrNone"
  receiptList [1] SEQUENCE OF GeneralNames }

AllOrFirstTier ::= INTEGER { -- Formerly AllOrNone
  allReceipts (0),
  firstTierRecipients (1) }

-- Section 2.8

Receipt ::= SEQUENCE {
  version                ESSVersion,
  contentType            ContentType,
  signedContentIdentifier ContentIdentifier,
  originatorSignatureValue OCTET STRING
}

ESSVersion ::= INTEGER { v1(1) }
```



-- [Section 2.9](#)

```
aa-contentHint ATTRIBUTE ::=
  { TYPE ContentHints IDENTIFIED BY id-aa-contentHint }
id-aa-contentHint OBJECT IDENTIFIER ::=
  { iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)
    smime(16) id-aa(2) 4}

ContentHints ::= SEQUENCE {
  contentDescription UTF8String (SIZE (1..MAX)) OPTIONAL,
  contentType ContentType }
```

-- [Section 2.10](#)

```
aa-msgSigDigest ATTRIBUTE ::=
  { TYPE MsgSigDigest IDENTIFIED BY id-aa-msgSigDigest }
id-aa-msgSigDigest OBJECT IDENTIFIER ::= { iso(1) member-body(2)
  us(840) rsadsi(113549) pkcs(1) pkcs-9(9) smime(16) id-aa(2) 5}

MsgSigDigest ::= OCTET STRING
```

-- [Section 2.11](#)

```
aa-contentReference ATTRIBUTE ::=
  { TYPE ContentReference IDENTIFIED BY id-aa-contentReference }
id-aa-contentReference OBJECT IDENTIFIER ::=
  { iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)
    smime(16) id-aa(2) 10 }

ContentReference ::= SEQUENCE {
  contentType ContentType,
  signedContentIdentifier ContentIdentifier,
  originatorSignatureValue OCTET STRING }
```

-- [Section 3.2](#)

```
aa-securityLabel ATTRIBUTE ::=
  { TYPE ESSSecurityLabel IDENTIFIED BY id-aa-securityLabel }
id-aa-securityLabel OBJECT IDENTIFIER ::=
  { iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)
    smime(16) id-aa(2) 2}

ESSSecurityLabel ::= SET {
  security-policy-identifier SecurityPolicyIdentifier,
  security-classification SecurityClassification OPTIONAL,
  privacy-mark ESSPrivacyMark OPTIONAL,
  security-categories SecurityCategories OPTIONAL }
```



```
SecurityPolicyIdentifier ::= OBJECT IDENTIFIER
```

```
SecurityClassification ::= INTEGER {  
    unmarked (0),  
    unclassified (1),  
    restricted (2),  
    confidential (3),  
    secret (4),  
    top-secret (5)  
} (0..ub-integer-options)
```

```
ub-integer-options INTEGER ::= 256
```

```
ESSPrivacyMark ::= CHOICE {  
    pString      PrintableString (SIZE (1..ub-privacy-mark-length)),  
    utf8String   UTF8String (SIZE (1..MAX))  
}
```

```
ub-privacy-mark-length INTEGER ::= 128
```

```
SecurityCategories ::=  
    SET SIZE (1..ub-security-categories) OF SecurityCategory  
    {{SupportedSecurityCategories}}
```

```
ub-security-categories INTEGER ::= 64
```

```
SupportedSecurityCategories SECURITY-CATEGORY ::= { ... }
```

```
-- Section 3.4
```

```
aa-equivalentLabels ATTRIBUTE ::=  
    { TYPE EquivalentLabels IDENTIFIED BY id-aa-equivalentLabels }  
id-aa-equivalentLabels OBJECT IDENTIFIER ::=  
    { iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)  
      smime(16) id-aa(2) 9 }
```

```
EquivalentLabels ::= SEQUENCE OF ESSSecurityLabel
```

```
-- Section 4.4
```

```
aa-mLExpandHistory ATTRIBUTE ::=  
    { TYPE MLExpansionHistory IDENTIFIED BY id-aa-mLExpandHistory }  
id-aa-mLExpandHistory OBJECT IDENTIFIER ::=  
    { iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)  
      smime(16) id-aa(2) 3 }
```

```
MLExpansionHistory ::= SEQUENCE  
    SIZE (1..ub-mLExpansion-history) OF MLData
```



```
ub-ml-expansion-history INTEGER ::= 64
```

```
MLData ::= SEQUENCE {  
    mailListIdentifier EntityIdentifier,  
    expansionTime GeneralizedTime,  
    mlReceiptPolicy MLReceiptPolicy OPTIONAL }
```

```
EntityIdentifier ::= CHOICE {  
    issuerAndSerialNumber IssuerAndSerialNumber,  
    subjectKeyIdentifier SubjectKeyIdentifier }
```

```
MLReceiptPolicy ::= CHOICE {  
    none [0] NULL,  
    insteadOf [1] SEQUENCE SIZE (1..MAX) OF GeneralNames,  
    inAdditionTo [2] SEQUENCE SIZE (1..MAX) OF GeneralNames }
```

```
-- Section 5.4
```

```
aa-signingCertificate ATTRIBUTE ::=  
    { TYPE SigningCertificate IDENTIFIED BY  
      id-aa-signingCertificate }
```

```
id-aa-signingCertificate OBJECT IDENTIFIER ::=  
    { iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs9(9)  
      smime(16) id-aa(2) 12 }
```

```
SigningCertificate ::= SEQUENCE {  
    certs SEQUENCE OF ESSCertID,  
    policies SEQUENCE OF PolicyInformation OPTIONAL  
}
```

```
aa-signingCertificateV2 ATTRIBUTE ::=  
    { TYPE SigningCertificateV2 IDENTIFIED BY  
      id-aa-signingCertificateV2 }
```

```
id-aa-signingCertificateV2 OBJECT IDENTIFIER ::=  
    { iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs9(9)  
      smime(16) id-aa(2) 47 }
```

```
SigningCertificateV2 ::= SEQUENCE {  
    certs SEQUENCE OF ESSCertIDv2,  
    policies SEQUENCE OF PolicyInformation OPTIONAL  
}
```

```
HashAlgorithm ::= AlgorithmIdentifier{DIGEST-ALGORITHM,  
    {mda-sha256, ...}}
```

```
ESSCertIDv2 ::= SEQUENCE {  
    hashAlgorithm HashAlgorithm  
    DEFAULT { algorithm mda-sha256.&id },
```



```

    certHash      Hash,
    issuerSerial  IssuerSerial OPTIONAL
}
ESSCertID ::= SEQUENCE {
    certHash      Hash,
    issuerSerial  IssuerSerial OPTIONAL
}

Hash ::= OCTET STRING

IssuerSerial ::= SEQUENCE {
    issuer        GeneralNames,
    serialNumber  CertificateSerialNumber
}

END

```

#### 10. ASN.1 Module for [RFC 5083](#)

```

CMS-AuthEnvelopedData-2009
    {iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)
    smime(16) modules(0) id-mod-cms-authEnvelopedData-02(43)}
DEFINITIONS IMPLICIT TAGS ::=
BEGIN
IMPORTS

AuthAttributes, CMSVersion, EncryptedContentInfo,
    MessageAuthenticationCode, OriginatorInfo, RecipientInfos,
    UnauthAttributes, CONTENT-TYPE
FROM CryptographicMessageSyntax-2009
    {iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)
    smime(16) modules(0) id-mod-cms-2004-02(41)} ;

ContentTypes CONTENT-TYPE ::= {ct-authEnvelopedData, ... }

ct-authEnvelopedData CONTENT-TYPE ::= {
    AuthEnvelopedData IDENTIFIED BY id-ct-authEnvelopedData
}

id-ct-authEnvelopedData OBJECT IDENTIFIER ::=
    {iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)
    smime(16) ct(1) 23}

AuthEnvelopedData ::= SEQUENCE {
    version CMSVersion,
    originatorInfo [0] IMPLICIT OriginatorInfo OPTIONAL,
    recipientInfos RecipientInfos,
    authEncryptedContentInfo EncryptedContentInfo,

```



```

    authAttrs [1] IMPLICIT AuthAttributes OPTIONAL,
    mac MessageAuthenticationCode,
    unauthAttrs [2] IMPLICIT UnauthAttributes OPTIONAL
}

```

```
END
```

## 11. ASN.1 Module for [RFC 5084](#)

```

CMS-AES-CCM-and-AES-GCM-2009
    { iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1)
      pkcs-9(9) smime(16) modules(0) id-mod-cms-aes-ccm-gcm-02(44) }
DEFINITIONS IMPLICIT TAGS ::=
BEGIN
EXPORTS ALL;
IMPORTS

CONTENT-ENCRYPTION, SMIME-CAPS
FROM AlgorithmInformation-2009
    {iso(1) identified-organization(3) dod(6) internet(1) security(5)
     mechanisms(5) pkix(7) id-mod(0)
     id-mod-algorithmInformation-02(58)};

-- Add this algorithm set to include all of the algorithms defined in
-- this document

ContentEncryptionAlgs CONTENT-ENCRYPTION ::= {
    cea-aes128-CCM | cea-aes192-CCM | cea-aes256-CCM |
    cea-aes128-GCM | cea-aes192-GCM | cea-aes256-GCM, ... }

SMimeCaps SMIME-CAPS ::= {
    cea-aes128-CCM.&smimeCaps |
    cea-aes192-CCM.&smimeCaps |
    cea-aes256-CCM.&smimeCaps |
    cea-aes128-GCM.&smimeCaps |
    cea-aes192-GCM.&smimeCaps |
    cea-aes256-GCM.&smimeCaps,
    ...
}

-- Defining objects

aes OBJECT IDENTIFIER ::= { joint-iso-itu-t(2) country(16) us(840)
    organization(1) gov(101) csor(3) nistAlgorithms(4) 1 }

cea-aes128-CCM CONTENT-ENCRYPTION ::= {
    IDENTIFIER id-aes128-CCM
    PARAMS TYPE CCMPParameters ARE required
}

```



```
        SMIME-CAPS { IDENTIFIED BY id-aes128-CCM }
    }
    id-aes128-CCM OBJECT IDENTIFIER ::= { aes 7 }

    cea-aes192-CCM CONTENT-ENCRYPTION ::= {
        IDENTIFIER id-aes192-CCM
        PARAMS TYPE CCMPParameters ARE required
        SMIME-CAPS { IDENTIFIED BY id-aes192-CCM }
    }
    id-aes192-CCM OBJECT IDENTIFIER ::= { aes 27 }

    cea-aes256-CCM CONTENT-ENCRYPTION ::= {
        IDENTIFIER id-aes256-CCM
        PARAMS TYPE CCMPParameters ARE required
        SMIME-CAPS { IDENTIFIED BY id-aes256-CCM }
    }
    id-aes256-CCM OBJECT IDENTIFIER ::= { aes 47 }

    cea-aes128-GCM CONTENT-ENCRYPTION ::= {
        IDENTIFIER id-aes128-GCM
        PARAMS TYPE GCMPParameters ARE required
        SMIME-CAPS { IDENTIFIED BY id-aes128-GCM }
    }
    id-aes128-GCM OBJECT IDENTIFIER ::= { aes 6 }

    cea-aes192-GCM CONTENT-ENCRYPTION ::= {
        IDENTIFIER id-aes128-GCM
        PARAMS TYPE GCMPParameters ARE required
        SMIME-CAPS { IDENTIFIED BY id-aes192-GCM }
    }
    id-aes192-GCM OBJECT IDENTIFIER ::= { aes 26 }

    cea-aes256-GCM CONTENT-ENCRYPTION ::= {
        IDENTIFIER id-aes128-GCM
        PARAMS TYPE GCMPParameters ARE required
        SMIME-CAPS { IDENTIFIED BY id-aes256-GCM }
    }
    id-aes256-GCM OBJECT IDENTIFIER ::= { aes 46 }

    -- Parameters for AlgorithmIdentifier

    CCMPParameters ::= SEQUENCE {
        aes-nonce          OCTET STRING (SIZE(7..13)),
        aes-ICVlen        AES-CCM-ICVlen DEFAULT 12 }

    AES-CCM-ICVlen ::= INTEGER (4 | 6 | 8 | 10 | 12 | 14 | 16)

    GCMPParameters ::= SEQUENCE {
```



```

aes-nonce      OCTET STRING, -- recommended size is 12 octets
aes-ICVlen     AES-GCM-ICVlen DEFAULT 12 }

```

```
AES-GCM-ICVlen ::= INTEGER (12 | 13 | 14 | 15 | 16)
```

```
END
```

## 12. ASN.1 Module for [RFC 5275](#)

```

SMIMESymmetricKeyDistribution-2009
    {iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)
      smime(16) modules(0) id-mod-symkeydist-02(36)}
DEFINITIONS IMPLICIT TAGS ::=
BEGIN
EXPORTS ALL;
IMPORTS

AlgorithmIdentifier{}, ALGORITHM, DIGEST-ALGORITHM, KEY-WRAP,
    SMIMECapability{}, SMIMECapabilities{}, SMIME-CAPS
FROM AlgorithmInformation-2009
    {iso(1) identified-organization(3) dod(6) internet(1) security(5)
      mechanisms(5) pkix(7) id-mod(0)
      id-mod-algorithmInformation-02(58)}

GeneralName
FROM PKIX1Implicit-2009
    { iso(1) identified-organization(3) dod(6) internet(1) security(5)
      mechanisms(5) pkix(7) id-mod(0) id-mod-pkix1-implicit-02(59) }

Certificate
FROM PKIX1Explicit-2009
    { iso(1) identified-organization(3) dod(6) internet(1) security(5)
      mechanisms(5) pkix(7) id-mod(0) id-mod-pkix1-explicit-02(51) }

RecipientInfos, KEKIdentifier, CertificateSet
FROM CryptographicMessageSyntax-2009
    {iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)
      smime(16) modules(0) id-mod-cms-2004-02(41) }

cap-3DESwrap
FROM CryptographicMessageSyntaxAlgorithms
    { iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)
      smime(16) modules(0) id-mod-cmsalg-2001-02(37) }

AttributeCertificate
FROM PKIXAttributeCertificate-2009
    { iso(1) identified-organization(3) dod(6) internet(1) security(5)
      mechanisms(5) pkix(7) id-mod(0) id-mod-attribute-cert-02(47) }

```



```

CMC-CONTROL, EXTENDED-FAILURE-INFO
FROM EnrollmentMessageSyntax
  { iso(1) identified-organization(3) dod(6) internet(1) security(5)
    mechanisms(5) pkix(7) id-mod(0) id-mod-cmc2002-02(53) }

kwa-aes128-wrap, kwa-aes192-wrap, kwa-aes256-wrap
FROM CMSAesRsaesOaep-2009
  { iso(1) member-body(2) us(840) rsadsi(113549)
    pkcs(1) pkcs-9(9) smime(16) modules(0) id-mod-cms-aes-02(38) } ;

-- This defines the group list (GL symmetric key distribution OID arc
id-skd OBJECT IDENTIFIER ::=
  { iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-9(9)
    smime(16) skd(8) }

SKD-ControlSet CMC-CONTROL ::= {
  skd-glUseKEK | skd-glDelete | skd-glAddMember |
  skd-glDeleteMember | skd-glRekey | skd-glAddOwner |
  skd-glRemoveOwner | skd-glKeyCompromise |
  skd-glRefresh | skd-glaQueryRequest | skd-glProvideCert |
  skd-glManageCert | skd-glKey, ... }

-- This defines the GL Use KEK control attribute

skd-glUseKEK CMC-CONTROL ::=
  { GLUseKEK IDENTIFIED BY id-skd-glUseKEK }

id-skd-glUseKEK OBJECT IDENTIFIER ::= { id-skd 1}

GLUseKEK ::= SEQUENCE {
  glInfo          GLInfo,
  glOwnerInfo     SEQUENCE SIZE (1..MAX) OF GLOwnerInfo,
  glAdministration GLAdministration DEFAULT managed,
  glKeyAttributes GLKeyAttributes OPTIONAL
}

GLInfo ::= SEQUENCE {
  glName      GeneralName,
  glAddress   GeneralName
}

GLOwnerInfo ::= SEQUENCE {
  glOwnerName      GeneralName,
  glOwnerAddress   GeneralName,
  certificates     Certificates OPTIONAL
}

GLAdministration ::= INTEGER {

```



```

    unmanaged (0),
    managed (1),
    closed (2)
}

--
-- The advertised set of algorithm capabilities for the document
--

SKD-Caps SMIME-CAPS ::= {
    cap-3DESwrap | kwa-aes128-wrap.&smimeCaps |
    kwa-aes192-wrap.&smimeCaps | kwa-aes256-wrap.&smimeCaps, ...
}

cap-aes128-cbc KeyWrapAlgorithm ::=
    { capabilityID kwa-aes128-wrap.&smimeCaps.&id }

--
-- The set of key wrap algorithms supported by this specification
--

KeyWrapAlgorithm ::= SMIMECapability{{SKD-Caps}}

GLKeyAttributes ::= SEQUENCE {
    rekeyControlledByGLO [0] BOOLEAN DEFAULT FALSE,
    recipientsNotMutuallyAware [1] BOOLEAN DEFAULT TRUE,
    duration [2] INTEGER DEFAULT 0,
    generationCounter [3] INTEGER DEFAULT 2,
    requestedAlgorithm [4] KeyWrapAlgorithm
    DEFAULT cap-aes128-cbc
}

-- This defines the Delete GL control attribute.
-- It has the simple type GeneralName.

skd-glDelete CMC-CONTROL ::=
    { DeleteGL IDENTIFIED BY id-skd-glDelete }

id-skd-glDelete OBJECT IDENTIFIER ::= { id-skd 2}
DeleteGL ::= GeneralName

-- This defines the Add GL Member control attribute

skd-glAddMember CMC-CONTROL ::=
    { GLAddMember IDENTIFIED BY id-skd-glAddMember }

id-skd-glAddMember OBJECT IDENTIFIER ::= { id-skd 3}
GLAddMember ::= SEQUENCE {

```



```
    glName      GeneralName,
    glMember    GLMember
  }

GLMember ::= SEQUENCE {
    glMemberName      GeneralName,
    glMemberAddress   GeneralName OPTIONAL,
    certificates       Certificates OPTIONAL
  }

Certificates ::= SEQUENCE {
    pKC      [0] Certificate OPTIONAL,
             -- See RFC 5280
    aC      [1] SEQUENCE SIZE (1.. MAX) OF
             AttributeCertificate OPTIONAL,
             -- See RFC 3281
    certPath [2] CertificateSet OPTIONAL
             -- From RFC 3852
  }

-- This defines the Delete GL Member control attribute

skd-glDeleteMember CMC-CONTROL ::=
  { GLDeleteMember IDENTIFIED BY id-skd-glDeleteMember }

id-skd-glDeleteMember OBJECT IDENTIFIER ::= { id-skd 4}

GLDeleteMember ::= SEQUENCE {
    glName          GeneralName,
    glMemberToDelete GeneralName
  }

-- This defines the Delete GL Member control attribute

skd-glRekey CMC-CONTROL ::=
  { GLRekey IDENTIFIED BY id-skd-glRekey }

id-skd-glRekey OBJECT IDENTIFIER ::= { id-skd 5}

GLRekey ::= SEQUENCE {
    glName          GeneralName,
    glAdministration GLAdministration OPTIONAL,
    glNewKeyAttributes GLNewKeyAttributes OPTIONAL,
    glRekeyAllGLKeys  BOOLEAN OPTIONAL
  }

GLNewKeyAttributes ::= SEQUENCE {
    rekeyControlledByGLO [0] BOOLEAN OPTIONAL,
```



```

    recipientsNotMutuallyAware [1] BOOLEAN OPTIONAL,
    duration                    [2] INTEGER OPTIONAL,
    generationCounter          [3] INTEGER OPTIONAL,
    requestedAlgorithm          [4] KeyWrapAlgorithm OPTIONAL
}

-- This defines the Add and Delete GL Owner control attributes

skd-glAddOwner CMC-CONTROL ::=
    { GLOwnerAdministration IDENTIFIED BY id-skd-glAddOwner }
id-skd-glAddOwner OBJECT IDENTIFIER ::= { id-skd 6}

skd-glRemoveOwner CMC-CONTROL ::=
    { GLOwnerAdministration IDENTIFIED BY id-skd-glRemoveOwner }

id-skd-glRemoveOwner OBJECT IDENTIFIER ::= { id-skd 7}

GLOwnerAdministration ::= SEQUENCE {
    glName      GeneralName,
    glOwnerInfo GLOwnerInfo
}

-- This defines the GL Key Compromise control attribute.
-- It has the simple type GeneralName.

skd-glKeyCompromise CMC-CONTROL ::=
    { GLKCompromise IDENTIFIED BY id-skd-glKeyCompromise }

id-skd-glKeyCompromise OBJECT IDENTIFIER ::= { id-skd 8}
GLKCompromise ::= GeneralName

-- This defines the GL Key Refresh control attribute.

skd-glkRefresh CMC-CONTROL ::=
    { GLKRefresh IDENTIFIED BY id-skd-glkRefresh }

id-skd-glkRefresh OBJECT IDENTIFIER ::= { id-skd 9}

GLKRefresh ::= SEQUENCE {
    glName      GeneralName,
    dates      SEQUENCE SIZE (1..MAX) OF Date
}

Date ::= SEQUENCE {
    start GeneralizedTime,
    end   GeneralizedTime OPTIONAL
}

```



-- This defines the GLA Query Request control attribute.

```
skd-glaQueryRequest CMC-CONTROL ::=
  { GLAQueryRequest IDENTIFIED BY id-skd-glaQueryRequest }

id-skd-glaQueryRequest OBJECT IDENTIFIER ::= { id-skd 11}

SKD-QUERY ::= TYPE-IDENTIFIER

SkdQuerySet SKD-QUERY ::= {skd-AlgRequest, ...}
GLAQueryRequest ::= SEQUENCE {
  glaRequestType  SKD-QUERY.&id ({SkdQuerySet}),
  glaRequestValue SKD-QUERY.
                    &Type ({SkdQuerySet}{@glaRequestType})
}
```

-- This defines the GLA Query Response control attribute.

```
skd-glaQueryResponse CMC-CONTROL ::=
  { GLAQueryResponse IDENTIFIED BY id-skd-glaQueryResponse }

id-skd-glaQueryResponse OBJECT IDENTIFIER ::= { id-skd 12}

SKD-RESPONSE ::= TYPE-IDENTIFIER

SkdResponseSet SKD-RESPONSE ::= {skd-AlgResponse, ...}

GLAQueryResponse ::= SEQUENCE {
  glaResponseType  SKD-RESPONSE.
                    &id({SkdResponseSet}),
  glaResponseValue SKD-RESPONSE.
                    &Type({SkdResponseSet}{@glaResponseType})}
}
```

-- This defines the GLA Request/Response (glaRR) arc for  
 -- glaRequestType/glaResponseType.

```
id-cmc-glaRR OBJECT IDENTIFIER ::=
  { iso(1) identified-organization(3) dod(6) internet(1) security(5)
    mechanisms(5) pkix(7) cmc(7) glaRR(99) }
```

-- This defines the Algorithm Request

```
skd-AlgRequest SKD-QUERY ::= {
  SKDAlgRequest IDENTIFIED BY id-cmc-gla-skdAlgRequest
}

id-cmc-gla-skdAlgRequest OBJECT IDENTIFIER ::= { id-cmc-glaRR 1 }
SKDAlgRequest ::= NULL
```



-- This defines the Algorithm Response

```
skd-AlgResponse SKD-RESPONSE ::= {
    SMIMECapability{{SKD-Caps}} IDENTIFIED BY
        id-cmc-gla-skdAlgResponse
}
```

```
id-cmc-gla-skdAlgResponse OBJECT IDENTIFIER ::= { id-cmc-glaARR 2 }
```

-- Note that the response for algorithmSupported request is the  
-- smimeCapabilities attribute as defined in [RFC 3851](#).

-- This defines the control attribute to request an updated  
-- certificate to the GLA.

```
skd-glProvideCert CMC-CONTROL ::=
    { GLManageCert IDENTIFIED BY id-skd-glProvideCert }
```

```
id-skd-glProvideCert OBJECT IDENTIFIER ::= { id-skd 13}
```

```
GLManageCert ::= SEQUENCE {
    glName      GeneralName,
    glMember   GLMember
}
```

-- This defines the control attribute to return an updated  
-- certificate to the GLA. It has the type GLManageCert.

```
skd-glManageCert CMC-CONTROL ::=
    { GLManageCert IDENTIFIED BY id-skd-glManageCert }
```

```
id-skd-glManageCert OBJECT IDENTIFIER ::= { id-skd 14}
```

-- This defines the control attribute to distribute the GL shared  
-- KEK.

```
skd-glKey CMC-CONTROL ::=
    { GLKey IDENTIFIED BY id-skd-glKey }
```

```
id-skd-glKey OBJECT IDENTIFIER ::= { id-skd 15}
```

```
GLKey ::= SEQUENCE {
    glName      GeneralName,
    glIdentifier KEKIdentifier,    -- See RFC 3852
    glkWrapped  RecipientInfos,   -- See RFC 3852
    glkAlgorithm KeyWrapAlgorithm,
    glkNotBefore GeneralizedTime,
    glkNotAfter  GeneralizedTime
}
```



-- This defines the CMC error types

```
skd-ExtendedFailures EXTENDED-FAILURE-INFO ::= {
    SKDFailInfo IDENTIFIED BY id-cet-skdFailInfo
}
```

```
id-cet-skdFailInfo OBJECT IDENTIFIER ::=
    { iso(1) identified-organization(3) dod(6) internet(1) security(5)
      mechanisms(5) pkix(7) cet(15) skdFailInfo(1) }
```

```
SKDFailInfo ::= INTEGER {
    unspecified          (0),
    closedGL             (1),
    unsupportedDuration  (2),
    noGLACertificate     (3),
    invalidCert          (4),
    unsupportedAlgorithm (5),
    noGLONameMatch      (6),
    invalidGLName        (7),
    nameAlreadyInUse    (8),
    noSpam               (9),
    deniedAccess         (10),
    alreadyAMember       (11),
    notAMember           (12),
    alreadyAnOwner       (13),
    notAnOwner           (14) }
```

END

### **13. Security Considerations**

Even though all the RFCs in this document are security-related, the document itself does not have any security considerations. The ASN.1 modules keep the same bits-on-the-wire as the modules that they replace.

### **14. Normative References**

- [ASN1-2002] ITU-T, "ITU-T Recommendation X.680, X.681, X.682, and X.683", ITU-T X.680, X.681, X.682, and X.683, 2002.
- [RFC3370] Housley, R., "Cryptographic Message Syntax (CMS) Algorithms", [RFC 3370](#), August 2002.
- [RFC3565] Schaad, J., "Use of the Advanced Encryption Standard (AES) Encryption Algorithm in Cryptographic Message Syntax (CMS)", [RFC 3565](#), July 2003.



- [RFC3851] Ramsdell, B., "Secure/Multipurpose Internet Mail Extensions (S/MIME) Version 3.1 Message Specification", [RFC 3851](#), July 2004.
- [RFC3852] Housley, R., "Cryptographic Message Syntax (CMS)", [RFC 3852](#), July 2004.
- [RFC4108] Housley, R., "Using Cryptographic Message Syntax (CMS) to Protect Firmware Packages", [RFC 4108](#), August 2005.
- [RFC4998] Gondrom, T., Brandner, R., and U. Pordesch, "Evidence Record Syntax (ERS)", [RFC 4998](#), August 2007.
- [RFC5035] Schaad, J., "Enhanced Security Services (ESS) Update: Adding CertID Algorithm Agility", [RFC 5035](#), August 2007.
- [RFC5083] Housley, R., "Cryptographic Message Syntax (CMS) Authenticated-Enveloped-Data Content Type", [RFC 5083](#), November 2007.
- [RFC5084] Housley, R., "Using AES-CCM and AES-GCM Authenticated Encryption in the Cryptographic Message Syntax (CMS)", [RFC 5084](#), November 2007.
- [RFC5275] Turner, S., "CMS Symmetric Key Management and Distribution", [RFC 5275](#), June 2008.
- [RFC5652] Housley, R., "Cryptographic Message Syntax (CMS)", [RFC 5652](#), September 2009.
- [RFC5912] Hoffman, P. and J. Schaad, "New ASN.1 Modules for the Public Key Infrastructure using X.509 (PKIX)", [RFC 5912](#), June 2010.



Authors' Addresses

Paul Hoffman  
VPN Consortium  
127 Segre Place  
Santa Cruz, CA 95060  
US

Phone: 1-831-426-9827  
EMail: [paul.hoffman@vpnc.org](mailto:paul.hoffman@vpnc.org)

Jim Schaad  
Soaring Hawk Consulting  
  
EMail: [jimsch@exmsft.com](mailto:jimsch@exmsft.com)

