

TCP Maintenance and Minor
Extensions (tcpm)
Internet-Draft
Updates: [793](#), [1011](#), [1122](#)
(if approved)
Intended status: Standards Track
Expires: April 19, 2011

F. Gont
UTN/FRH
A. Yourtchenko
Cisco
October 16, 2010

On the implementation of the TCP urgent mechanism
draft-ietf-tcpm-urgent-data-07.txt

Abstract

This document analyzes how current TCP implementations process TCP urgent indications, and how the behavior of some widely-deployed middle-boxes affect how urgent indications are processed by end systems. This document updates the relevant specifications such that they accommodate current practice in processing TCP urgent indications, raises awareness about the reliability of TCP urgent indications in the Internet and recommends against the use of the urgent indications (but provides advice to applications in case that they do).

Status of this Memo

This Internet-Draft is submitted to IETF in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 19, 2011.

Copyright Notice

Copyright (c) 2010 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents

Internet-Draft

On the TCP urgent mechanism

October 2010

(<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	4
2.	Specification of the TCP urgent mechanism	4
2.1.	Semantics of urgent indications	4
2.2.	Semantics of the Urgent Pointer	5
2.3.	Allowed length of urgent data	5
3.	Current implementation practice of TCP urgent data	6
3.1.	Semantics of urgent indications	6
3.2.	Semantics of the Urgent Pointer	6
3.3.	Allowed length of urgent data	7
3.4.	Interaction of middle-boxes with TCP urgent indications .	7
4.	Updating RFC 793 , RFC 1011 , and RFC 1122	7
5.	Advice to new applications employing TCP	8
6.	Advice to applications that make use of the urgent mechanism	8
7.	Security Considerations	8
8.	IANA Considerations	9
9.	Acknowledgements	9
10.	References	9
10.1.	Normative References	9
10.2.	Informative References	9
Appendix A.	Survey of the processing of TCP urgent indications by some popular TCP implementations . . .	10
A.1.	FreeBSD	10
A.2.	Linux	11
A.3.	NetBSD	11
A.4.	OpenBSD	11
A.5.	Cisco IOS software	12
A.6.	Microsoft Windows 2000, Service Pack 4	12
A.7.	Microsoft Windows 2008	12
A.8.	Microsoft Windows 95	12
Appendix B.	Changes from previous versions of the draft (to be removed by the RFC Editor before publishing	

	this document as an RFC)	12
B.1.	Changes from draft-ietf-tcpm-urgent-data-06	12
B.2.	Changes from draft-ietf-tcpm-urgent-data-05	13
B.3.	Changes from draft-ietf-tcpm-urgent-data-04	13
B.4.	Changes from draft-ietf-tcpm-urgent-data-03	13

B.5.	Changes from draft-ietf-tcpm-urgent-data-02	13
B.6.	Changes from draft-ietf-tcpm-urgent-data-01	13
B.7.	Changes from draft-ietf-tcpm-urgent-data-00	13
B.8.	Changes from draft-gont-tcpm-urgent-data-01	13
Authors' Addresses			13

Internet-Draft

On the TCP urgent mechanism

October 2010

1. Introduction

This document analyzes how some current TCP implementations process TCP urgent indications, and how the behavior of some widely-deployed middle-boxes affect the processing of urgent indications by hosts. This document updates [RFC 793](#) [RFC0793], [RFC 1011](#) [RFC1011], and [RFC 1122](#) [RFC1122] such that they accommodate current practice in processing TCP urgent indications, provides advice to applications using the urgent mechanism, and raises awareness about the reliability of TCP urgent indications in the current Internet.

Given the above issues and potential interoperability issues with respect to the currently common default mode operation, it is strongly recommended that applications do not employ urgent indications. Nevertheless, urgent indications are still retained as a mandatory part of the TCP protocol to support the few legacy applications that employ them. However, it is expected that even these applications will have difficulties in environments with middle-boxes.

[Section 2](#) describes what the current IETF specifications state with respect to TCP urgent indications. [Section 3](#) describes how some current TCP implementations actually process TCP urgent indications. [Section 4](#) updates [RFC 793](#) [RFC0793], [RFC 1011](#) [RFC1011], and [RFC 1122](#) [RFC1122], such that they accommodate current practice in processing TCP urgent indications. [Section 5](#) provides advice to new applications employing TCP, with respect to the TCP urgent mechanism. [Section 6](#) provides advice to existing applications that use or rely on the TCP urgent mechanism.

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

[2.](#) Specification of the TCP urgent mechanism

[2.1.](#) Semantics of urgent indications

TCP incorporates an "urgent mechanism" that allows the sending user to stimulate the receiving user to accept some "urgent data" and to permit the receiving TCP to indicate to the receiving user when all the currently known urgent data have been received by the receiving user.

The TCP urgent mechanism permits a point in the data stream to be designated as the end of urgent information. Whenever this point is in advance of the receive sequence number (RCV.NXT) at the receiving

TCP, that TCP must tell the user to go into "urgent mode"; when the receive sequence number catches up to the urgent pointer, the TCP must tell user to go into "normal mode" [[RFC0793](#)]. This means, for example, that data that was received as "normal data" might become "urgent data" if an urgent indication is received in some successive TCP segment before that data is consumed by the TCP user.

The URG control flag indicates that the "Urgent Pointer" field is meaningful and must be added to the segment sequence number to yield the urgent pointer. The absence of this flag indicates that there is no urgent data outstanding [[RFC0793](#)].

The TCP urgent mechanism is NOT a mechanism for sending "out-of-band" data: the so-called "urgent data" should be delivered "in-line" to the TCP user.

[2.2.](#) Semantics of the Urgent Pointer

There is some ambiguity in [RFC 793](#) [[RFC0793](#)] with respect to the semantics of the Urgent Pointer. [Section 3.1](#) (page 17) of [RFC 793](#) [[RFC0793](#)] states that the Urgent Pointer "communicates the current value of the urgent pointer as a positive offset from the sequence

number in this segment. The urgent pointer points to the sequence number of the octet following the urgent data. This field is only be interpreted in segments with the URG control bit set". However, [Section 3.9](#) (page 56) of [RFC 793](#) [[RFC0793](#)] states, when describing the processing of the SEND call in the ESTABLISHED and CLOSE-WAIT states, that "If the urgent flag is set, then SND.UP <- SND.NXT-1 and set the urgent pointer in the outgoing segments".

[RFC 1011](#) [[RFC1011](#)] clarified this ambiguity in [RFC 793](#) stating that "Page 17 is wrong. The urgent pointer points to the last octet of urgent data (not to the first octet of non-urgent data)". [RFC 1122](#) [[RFC1122](#)] formally updated [RFC 793](#) by stating, in [Section 4.2.2.4](#) (page 84), that "the urgent pointer points to the sequence number of the LAST octet (not LAST+1) in a sequence of urgent data."

[2.3](#). Allowed length of urgent data

[RFC 793](#) [[RFC0793](#)] allows TCP peers to send urgent data of any length, as the TCP urgent mechanism simply provides a pointer to an interesting point in the data stream. In this respect, [Section 4.2.2.4](#) (page 84) of [RFC 1122](#) explicitly states that "A TCP MUST support a sequence of urgent data of any length".

[3](#). Current implementation practice of TCP urgent data

[3.1](#). Semantics of urgent indications

As discussed in [Section 1](#), the TCP urgent mechanism simply permits a point in the data stream to be designated as the end of urgent information, but does NOT provide a mechanism for sending out of band data.

Unfortunately, virtually all TCP implementations process TCP urgent data differently. By default, the last byte of "urgent data" is delivered "out of band" to the application. That is, it is not delivered as part of the normal data stream. For example, the "out of band" byte is read by an application when a `recv(2)` system call with the `MSG_OOB` flag set is issued.

Most implementations provide a socket option (SO_OOBINLINE) that allows an application to override the (broken) default processing of urgent data, so that it is delivered "in band" to the application, thus providing the semantics intended by the IETF specifications.

[3.2.](#) Semantics of the Urgent Pointer

All the popular implementations that the authors of this document have been able to test interpret the semantics of the TCP Urgent Pointer as specified in [Section 3.1 of RFC 793](#). This means that even when [RFC 1122](#) officially updated [RFC 793](#) to clarify the ambiguity in the semantics of the Urgent Pointer, this clarification was never reflected into actual implementations (i.e., virtually all implementations default to the semantics of the urgent pointer specified in [Section 3.1 of RFC 793](#)).

Some operating systems provide a system-wide toggle to override this behavior, and interpret the semantics of the Urgent Pointer as clarified in [RFC 1122](#). However, this system-wide toggle has been found to be inconsistent. For example, Linux provides the sysctl "tcp_stdurg" (i.e., net.ipv4.tcp_stdurg) that, when set, supposedly changes the system behavior to interpret the semantics of the TCP Urgent Pointer as specified in [RFC 1122](#). However, this sysctl changes the semantics of the Urgent Pointer only for incoming segments, but not for outgoing segments. This means that if this sysctl is set, an application might be unable to interoperate with itself if both the TCP sender and the TCP receiver are running on the same host.

[3.3.](#) Allowed length of urgent data

While [Section 4.2.2.4](#) (page 84) of [RFC 1122](#) explicitly states that "A TCP MUST support a sequence of urgent data of any length", in practice all those implementations that interpret TCP urgent indications as a mechanism for sending out-of-band data keep a buffer of a single byte for storing the "last byte of urgent data". Thus, if successive indications of urgent data are received before the

application reads the pending "out of band" byte, that pending byte will be discarded (i.e., overwritten by the new byte of urgent data).

In order to avoid urgent data from being discarded, some implementations queue each of the received "urgent bytes", so that even if another urgent indication is received before the pending urgent data are consumed by the application, those bytes do not need to be discarded. Some of these implementations have been known to fail to enforce any limits on the amount of urgent data that they queue, thus resulting vulnerable to trivial resource exhaustion attacks [[CPNI-TCP](#)].

It should be reinforced that the aforementioned implementations are broken. The TCP urgent mechanism is not a mechanism for delivering out-of-band data.

[3.4.](#) Interaction of middle-boxes with TCP urgent indications

As a result of the publication of Network Intrusion Detection (NIDs) evasion techniques based on TCP urgent indications [[phrack](#)], some middle-boxes clear the urgent indications by clearing the URG flag and setting the Urgent Pointer to zero. This causes the "urgent data" to become "in line" (that is, accessible by the read(2) call or the recv(2) call without the MSG_OOB flag) in the case of those TCP implementations that implement the urgent mechanism as out-of-band data (as described in [Section 3.1](#)). An example of such a middle-box is the Cisco PIX firewall [[Cisco-PIX](#)]. This should discourage applications from depending on urgent indications for their correct operation, as urgent indications may not be reliable in the current Internet.

[4.](#) Updating [RFC 793](#), [RFC 1011](#), and [RFC 1122](#)

Considering that as long as both the TCP sender and the TCP receiver implement the same semantics for the Urgent Pointer there is no functional difference in having the Urgent Pointer point to "the sequence number of the octet following the urgent data" vs. "the last octet of urgent data", and since all known implementations interpret the semantics of the Urgent Pointer as pointing to "the sequence

[793](#) [[RFC0793](#)], [RFC 1011](#) [[RFC1011](#)], and [RFC 1122](#) [[RFC1122](#)], such that "the urgent pointer points to the sequence number of the octet following the urgent data" (in segments with the URG control bit set), thus accommodating virtually all existing TCP implementations.

[5.](#) Advice to new applications employing TCP

As a result of the issues discussed in [Section 3.2](#) and [Section 3.4](#), new applications SHOULD NOT employ the TCP urgent mechanism. However, TCP implementations MUST still include support for the urgent mechanism such that existing applications can still use it.

[6.](#) Advice to applications that make use of the urgent mechanism

Even though applications SHOULD NOT employ the urgent mechanism, applications that still decide to employ it MUST set the SO_OOBINLINE socket option, such that "urgent data" is delivered inline, as intended by the IETF specifications.

Additionally, applications that still decide to use the urgent mechanism need to be designed for correct operation even when the URG flag is cleared by middleboxes.

[7.](#) Security Considerations

Multiple factors can affect the data flow that is actually delivered to an application when the TCP urgent mechanism is employed; namely, the two possible interpretations of the semantics of the Urgent Pointer in current implementations (e.g., depending on the value of the tcp_stdurg sysctl), the possible implementation of the urgent mechanism as an Out-Of-Band (OOB) facility (vs. in-band as intended by the IETF specifications), and middle-boxes (such as packet scrubbers) or the end-systems themselves that could cause the "urgent data" to be processed "in band". This might make it difficult for a Network Intrusion Detection System (NIDS) to track the application-layer data transferred to the destination system, and thus lead to false negatives or false positives in the NIDS [[CPNI-TCP](#)] [[phrack](#)].

Probably the best way to avoid the security implications of TCP urgent data is to avoid having applications use the TCP urgent mechanism altogether. Packet scrubbers could probably be configured to clear the URG bit, and set the Urgent Pointer to zero. This would basically cause the urgent data to be put "in band". However, this might cause interoperability problems or undesired behavior in those

applications that rely on the TCP urgent mechanism, such as Telnet [[RFC0854](#)] and FTP [[RFC0959](#)].

8. IANA Considerations

This document has no actions for IANA.

9. Acknowledgements

The authors of this document would like to thank (in alphabetical order) Jari Arkko, Ron Bonica, David Borman, Dave Cridland, Ralph Droms, Wesley Eddy, John Heffner, Alfred Hoenes, Alexey Melnikov, Keith Moore, Carlos Pignataro, Tim Polk, Anantha Ramaiah, Joe Touch, Michael Welzl, Dan Wing, and Alexander Zimmermann for providing valuable feedback on earlier versions of this document.

Additionally, Fernando would like to thank David Borman and Joe Touch for a fruitful discussion about TCP urgent mode at IETF 73 (Minneapolis).

10. References

10.1. Normative References

- [RFC0793] Postel, J., "Transmission Control Protocol", STD 7, [RFC 793](#), September 1981.
- [RFC1011] Reynolds, J. and J. Postel, "Official Internet protocols", [RFC 1011](#), May 1987.
- [RFC1122] Braden, R., "Requirements for Internet Hosts - Communication Layers", STD 3, [RFC 1122](#), October 1989.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.

10.2. Informative References

- [CPNI-TCP] Gont, F., "Security Assessment of the Transmission Control Protocol (TCP)", <http://www.cpni.gov.uk/Docs/tn-03-09-security-assessment-TCP.pdf>, 2009.

[Cisco-PIX]

Cisco PIX, "<http://www.cisco.com/en/US/docs/security/asa/>

Gont & Yourtchenko

Expires April 19, 2011

[Page 9]

Internet-Draft

On the TCP urgent mechanism

October 2010

[asa70/command/reference/tz.html#wp1288756](http://www.cisco.com/en/US/docs/security/asa/asa70/command/reference/tz.html#wp1288756)".

[FreeBSD] The FreeBSD project, "<http://www.freebsd.org>".

[Linux] The Linux Project, "<http://www.kernel.org>".

[NetBSD] The NetBSD project, "<http://www.netbsd.org>".

[OpenBSD] The OpenBSD project, "<http://www.openbsd.org>".

[RFC0854] Postel, J. and J. Reynolds, "Telnet Protocol Specification", STD 8, [RFC 854](http://www.rfc-base.org/rfc/rfc0854.html), May 1983.

[RFC0959] Postel, J. and J. Reynolds, "File Transfer Protocol", STD 9, [RFC 959](http://www.rfc-base.org/rfc/rfc0959.html), October 1985.

[UNPv1] Stevens, W., "UNIX Network Programming, Volume 1. Networking APIs: Sockets and XTI", Prentice Hall PTR , 1997.

[Windows2000]

Microsoft Windows 2000, "[http://technet.microsoft.com/en-us/library/bb726981\(printer\).aspx](http://technet.microsoft.com/en-us/library/bb726981(printer).aspx)".

[Windows95]

Microsoft Windows 95,
"<ftp://ftp.demon.co.uk/pub/mirrors/win95netfaq/faq-c.html>".

[phrack] Ko, Y., Ko, S., and M. Ko, "NIDS Evasion Method named "SeolMa"", Phrack Magazine, Volume 0x0b, Issue 0x39, Phile #0x03 of 0x12 <http://www.phrack.org/issues.html?issue=57&id=3#article>, 2001.

[Appendix A](#). Survey of the processing of TCP urgent indications by some popular TCP implementations

[A.1](#). FreeBSD

FreeBSD 8.0 [[FreeBSD](#)] interprets the semantics of the urgent pointer as specified in [Section 4](#) of this document. It does not provide any sysctl to override this behavior.

FreeBSD provides the SO_00BINLINE socket option that, when set, causes TCP "urgent data" to remain "in band". That is, it will be accessible by the read(2) call or the recv(2) call without the MSG_00B flag.

FreeBSD supports only one byte of urgent data. That is, only the byte preceding the Urgent Pointer is considered as "urgent data".

[A.2.](#) Linux

Linux 2.6.15-53-386 [[Linux](#)] interprets the semantics of the urgent pointer as specified in [Section 4](#) of this document. It provides the net.ipv4.tcp_stdurg sysctl to override this behavior to interpret the Urgent Pointer as specified in [RFC 1122](#) [[RFC1122](#)]. However, this sysctl only affects the processing of incoming segments (the Urgent Pointer in outgoing segments will still be set as specified in [Section 4](#) of this document).

Linux provides the SO_00BINLINE socket option that, when set, causes TCP "urgent data" to remain "in band". That is, it will be accessible by the read(2) call or the recv(2) call without the MSG_00B flag.

Linux supports only one byte of urgent data. That is, only the byte preceding the Urgent Pointer is considered as "urgent data".

[A.3.](#) NetBSD

NetBSD 5.0.1 [[NetBSD](#)] interprets the semantics of the urgent pointer as specified in [Section 4](#) of this document. It does not provide any sysctl to override this behavior.

NetBSD provides the SO_00BINLINE socket option that, when set, causes TCP "urgent data" to remain "in band". That is, it will be accessible by the read(2) call or the recv(2) call without the MSG_00B flag.

NetBSD supports only one byte of urgent data. That is, only the byte preceding the Urgent Pointer is considered as "urgent data".

[A.4.](#) OpenBSD

OpenBSD 4.2 [[OpenBSD](#)] interprets the semantics of the urgent pointer as specified in [Section 4](#) of this document. It does not provide any sysctl to override this behavior.

OpenBSD provides the SO_OOBINLINE socket option that, when set, causes TCP urgent data to remain "in band". That is, it will be accessible by the read(2) or recv(2) calls without the MSG_OOB flag.

OpenBSD supports only one byte of urgent data. That is, only the byte preceding the Urgent Pointer is considered as "urgent data".

[A.5.](#) Cisco IOS software

Cisco IOS Software Releases 12.2(18)SXF7, 12.4(15)T7 interpret the semantics of the urgent pointer as specified in [Section 4](#) of this document.

The behavior is consistent with having the SO_OOBINLINE socket option turned on, i.e. the data is processed "in band".

[A.6.](#) Microsoft Windows 2000, Service Pack 4

Microsoft Windows 2000 [[Windows2000](#)] interprets the semantics of the urgent pointer as specified in [Section 4](#) of this document. It provides the TcpUseRFC1122UrgentPointer system-wide variable to override this behavior, interpreting the Urgent Pointer as specified in [RFC 1122](#) [[RFC1122](#)].

Tests performed with a sample server application compiled using the cygwin environment has shown that the default behavior is to return the urgent data "in band".

[A.7.](#) Microsoft Windows 2008

Microsoft Windows 2008 interprets the semantics of the urgent pointer as specified in [Section 4](#) of this document.

[A.8.](#) Microsoft Windows 95

Microsoft Windows 95 interprets the semantics of the urgent pointer as specified in [Section 4](#) of this document. It provides the BSDUrgent system-wide variable to override this behavior, interpreting the Urgent Pointer as specified in [RFC 1122](#) [[RFC1122](#)]. Windows 95 supports only one byte of urgent data. That is, only the byte preceding the Urgent Pointer is considered as "urgent data". [[Windows95](#)]

[Appendix B.](#) Changes from previous versions of the draft (to be removed by the RFC Editor before publishing this document as an RFC)

[B.1.](#) Changes from [draft-ietf-tcpm-urgent-data-06](#)

- o Addresses Jari Arkko's and Tim Polk's DISCUSSES, and various COMMENTS by members of the IESG.
- o Addresses IETF LC comments.

Gont & Yourtchenko

Expires April 19, 2011

[Page 12]

Internet-Draft

On the TCP urgent mechanism

October 2010

[B.2.](#) Changes from [draft-ietf-tcpm-urgent-data-05](#)

- o Draft resubmitted (with no changes) because it was close to the expiration day.

[B.3.](#) Changes from [draft-ietf-tcpm-urgent-data-04](#)

- o Fixes grammar errors wrt the term "data" (thanks to David Borman, once again ;-)

[B.4.](#) Changes from [draft-ietf-tcpm-urgent-data-03](#)

- o Addresses feedback sent by David Borman, and nit pointed out by John Heffner.

[B.5.](#) Changes from [draft-ietf-tcpm-urgent-data-02](#)

- o Addresses WGLC feedback submitted by Michael Welzl, Anantha

Ramaiah, and Wesley Eddy.

B.6. Changes from [draft-ietf-tcpm-urgent-data-01](#)

- o Fixes reference to Cisco IOS Software (layer 8+ stuff ;-)).
- o Cleaned-up [Appendix A.5](#).

B.7. Changes from [draft-ietf-tcpm-urgent-data-00](#)

- o Minor editorial changes.
- o Incorporated the specific changes/advice stated in <http://www.ietf.org/mail-archive/web/tcpm/current/msg04548.html> in different sections ([Section 4](#), [Section 5](#), [Section 6](#)).

B.8. Changes from [draft-gont-tcpm-urgent-data-01](#)

- o Draft resubmitted as [draft-ietf](#), as a result of wg consensus on adopting the document as a tcpm wg item.

Authors' Addresses

Fernando Gont
Universidad Tecnologica Nacional / Facultad Regional Haedo
Evaristo Carriego 2644
Haedo, Provincia de Buenos Aires 1706
Argentina

Phone: +54 11 4650 8472
Email: fernando@gont.com.ar
URI: <http://www.gont.com.ar>

Andrew Yourtchenko
Cisco
De Kleetlaan, 7
Diegem B-1831
Belgium

Phone: +32 2 704 5494
Email: ayourtch@cisco.com