

Network Working Group
Internet-Draft
Intended status: Informational
Expires: December 16, 2017

C. Bormann
Universitaet Bremen TZI
B. Gamari
Well-Typed
H. Birkholz
Fraunhofer SIT
June 14, 2017

Concise Binary Object Representation (CBOR) Tags for Time, Duration, and
Period
draft-bormann-cbor-time-tag-01

Abstract

The Concise Binary Object Representation (CBOR, RFC 7049) is a data format whose design goals include the possibility of extremely small code size, fairly small message size, and extensibility without the need for version negotiation.

In CBOR, one point of extensibility is the definition of CBOR tags. RFC 7049 defines two tags for time: CBOR tag 0 (RFC3339 time) and tag 1 (Posix time [TIME_T], int or float). Since then, additional requirements have become known. The present document defines a CBOR tag for time that allows a more elaborate representation of time, and anticipates the definition of related CBOR tags for duration and time period. It is intended as the reference document for the IANA registration of the CBOR tags defined.

Note to Readers

Version -00 of the present draft opened up the possibilities provided by extended representations of time in CBOR. The present version -01 consolidates this draft to non-speculative content, the normative parts of which are believed will stay unchanged during further development of the draft. This version is provided to aid the registration of the CBOR tag immediately needed. Further versions will re-introduce some of the material from -00, but in a more concrete form.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute

working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on December 16, 2017.

Copyright Notice

Copyright (c) 2017 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1. Introduction	3
1.1. Terminology	3
1.2. Background	3
2. Objectives	3
3. Time Format	4
3.1. Key 1	5
3.2. Keys 4 and 5	5
3.3. Keys -3, -6, -9, -12, -15, -18	5
4. CDDL typenames	5
5. IANA Considerations	6
6. Security Considerations	6
7. References	7
7.1. Normative References	7
7.2. Informative References	8
Acknowledgements	8
Authors' Addresses	8

1. Introduction

The Concise Binary Object Representation (CBOR, [RFC7049]) provides for the interchange of structured data without a requirement for a pre-agreed schema. RFC 7049 defines a basic set of data types, as well as a tagging mechanism that enables extending the set of data types supported via an IANA registry.

(TBD: Expand on text from abstract here.)

1.1. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [RFC2119].

The term "byte" is used in its now customary sense as a synonym for "octet". Where bit arithmetic is explained, this document uses the notation familiar from the programming language C (including C++'s 0bnnn binary literals), except that the operator "<<" stands for exponentiation.

1.2. Background

Additional information about the complexities of time representation can be found in [TIME]. This specification uses a number of terms that should be familiar to connoisseurs of precise time; references for these may need to be added.

2. Objectives

For the time tag, the present specification addresses the following objectives that go beyond the original tags 0 and 1:

- o Additional resolution for epoch-based time (as in tag 1). CBOR tag 1 only provides for integer and up to binary64 floating point representation of times, limiting resolution to approximately microseconds at the time of writing (and progressively becoming worse over time).

Not currently addressed, but possibly covered by the definition of additional map keys for the map inside the tag:

- o Indication of time scale. Tags 0 and 1 are for UTC; however, some interchanges are better performed on TAI. Other time scales may be registered once they become relevant (e.g., one of the proposed successors to UTC that might no longer use leap seconds, or a scale based on smeared leap seconds).

- o Direct representation of natural platform time formats. Some platforms use epoch-based time formats that require some computation to convert them into the representations allowed by tag 1; these computations can also lose precision and cause ambiguities. (TBD: The present specification does not take a position on whether tag 1 can be "fixed" to include, e.g., Decimal or BigFloat representations. It does define how to use these with the extended time format.)
- o Additional indication of intents about the interpretation of the time given, in particular for future times. Intents might include information about time zones, daylight savings times, etc.

Additional tags might later be defined for duration and period. The objectives for such duration and period tags are likely similar.

3. Time Format

An extended time is indicated by CBOR tag TBDET, which tags a map data item (CBOR major type 5). The map may contain integer (major types 0 and 1) or text string (major type 3) keys, with the value type determined by each specific key. Implementations MUST ignore key/value types they do not understand for negative integer and text string values of the key. Not understanding key/value for unsigned keys is an error.

The map must contain exactly one unsigned integer key, which specifies the "base time", and may also contain one or more negative integer or text-string keys, which may encode supplementary information such as:

- o a higher precision time offset to be added to the base time,

Future keys may add:

- o a reference time scale and epoch different from the default UTC and 1970-01-01
- o information about clock source and precision, accuracy, and resolution
- o intent information such as timezone and daylight savings time, and/or possibly positioning coordinates, to express information that would indicate a local time.

While this document does not define supplementary text keys, a number of unsigned and negative-integer keys are defined below.

3.1. Key 1

Key 1 indicates a value that is exactly like the data item that would be tagged by CBOR tag 1 (Posix time [TIME_T] as int or float).

3.2. Keys 4 and 5

Keys 4 and 5 are like key 1, except that the data item is an array as defined for CBOR tag 4 or 5, respectively. This can be used to include a Decimal or Bigfloat epoch-based float [TIME_T] in an extended time.

3.3. Keys -3, -6, -9, -12, -15, -18

The keys -3, -6, -9, -12, -15 and -18 indicate additional decimal fractions by giving an unsigned integer (major type 0) and scaling this with the scale factor 1e-3, 1e-6, 1e-9, 1e-12, 1e-15, and 1e-18, respectively (see Table 1). More than one of these keys MUST NOT be present in one extended time data item. These additional fractions are added to a base time in seconds [SI-SECOND] indicated by a Key 1, which then MUST also be present and MUST have an integer value.

Key	meaning	example usage
-3	milliseconds	Java time
-6	microseconds	(old) UNIX time
-9	nanoseconds	(new) UNIX time
-12	picoseconds	Haskell time
-15	femtoseconds	(future)
-18	attoseconds	(future)

Table 1: Key for decimally scaled Fractions

4. CDDL typenames

For the use with the CBOR Data Definition Language, CDDL [I-D.greevenbosch-appsawg-cbor-cddl], the type names defined in Figure 1 are recommended:

```
etime = #6.TBDET({* (int/tstr) => any})
```

Figure 1: Recommended type names for CDDL

5. IANA Considerations

IANA is requested to allocate the tags in Table 2 from the FCFS space, with the present document as the specification reference.

Tag	Data Item	Semantics
TBDET	map	[RFCthis] extended time
TBDED	map	[RFCthis] duration
TBDEP	map	[RFCthis] period

Table 2: Values for Tags

Although duration and period are not yet defined in the present version of this document, the tag values for duration and period are requested at the same time as the value for extended time in order to achieve allocation of all three values as a contiguous set.

RFC editor note: Please replace TBDET, TBDED, and TBDEP by the tag number allocated by IANA throughout the document and delete this note.

6. Security Considerations

The security considerations of RFC 7049 apply; the tags introduced here are not expected to raise security considerations beyond those.

Time, of course, has significant security considerations; these include the exploitation of ambiguities where time is security relevant (e.g., for freshness or in a validity span) or the disclosure of characteristics of the emitting system (e.g., time zone, or clock resolution and wall clock offset).

7. References

7.1. Normative References

- [I-D.greevenbosch-appsawg-cbor-cddl]
Birkholz, H., Vigano, C., and C. Bormann, "CBOR data definition language (CDDL): a notational convention to express CBOR data structures", draft-greevenbosch-appsawg-cbor-cddl-10 (work in progress), March 2017.
- [IEEE1588-2008]
IEEE, "1588-2008 - IEEE Standard for a Precision Clock Synchronization Protocol for Networked Measurement and Control Systems", July 2008,
<<http://standards.ieee.org/findstds/standard/1588-2008.html>>.
- [RESOLUTION]
The Open Group Base Specifications, "Vol. 1: Base Definitions, Issue 7", Section 3.328 '(Time) Resolution', IEEE Std 1003.1-2008, 2016 Edition, 2016,
<http://pubs.opengroup.org/onlinepubs/9699919799/basedefs/V1_chap03.html#tag_03_328>.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997,
<<http://www.rfc-editor.org/info/rfc2119>>.
- [RFC7049] Bormann, C. and P. Hoffman, "Concise Binary Object Representation (CBOR)", RFC 7049, DOI 10.17487/RFC7049, October 2013, <<http://www.rfc-editor.org/info/rfc7049>>.
- [SI-SECOND]
International Organization for Standardization (ISO), "Quantities and units -- Part 3: Space and time", ISO 80000-3, March 2006.
- [TIME_T]
The Open Group Base Specifications, "Vol. 1: Base Definitions, Issue 7", Section 4.15 'Seconds Since the Epoch', IEEE Std 1003.1-2008, 2016 Edition, 2016,
<http://pubs.opengroup.org/onlinepubs/9699919799/basedefs/V1_chap04.html#tag_04_16>.

7.2. Informative References

[TIME] Touch, J., "Resolving Multiple Time Scales in the Internet", draft-touch-time-02 (work in progress), April 2017.

Acknowledgements

Authors' Addresses

Carsten Bormann
Universitaet Bremen TZI
Postfach 330440
Bremen D-28359
Germany

Phone: +49-421-218-63921
Email: cabo@tzi.org

Ben Gamari
Well-Typed
117 Middle Rd.
Portsmouth, NH 03801
United States

Email: ben@well-typed.com

Henk Birkholz
Fraunhofer Institute for Secure Information Technology
Rheinstrasse 75
Darmstadt 64295
Germany

Email: henk.birkholz@sit.fraunhofer.de