

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: April 28, 2018

M. Bjorklund
Tail-f Systems
L. Berger, Ed.
LabN Consulting, L.L.C.
October 25, 2017

YANG Tree Diagrams
draft-ietf-netmod-yang-tree-diagrams-02

Abstract

This document captures the current syntax used in YANG module Tree Diagrams. The purpose of the document is to provide a single location for this definition. This syntax may be updated from time to time based on the evolution of the YANG language.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 28, 2018.

Copyright Notice

Copyright (c) 2017 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1. Introduction	2
2. Tree Diagram Syntax	3
2.1. Submodules	5
2.2. Groupings	5
2.3. yang-data	5
2.4. Collapsed Node Representation	5
2.5. Comments	5
2.6. Node Representation	5
3. Usage Guidelines For RFCs	6
3.1. Wrapping Long Lines	7
3.2. Long Diagrams	7
4. YANG Schema Mount Tree Diagrams	8
4.1. Representation of Instance Data Trees	8
5. IANA Considerations	10
6. Security Considerations	10
7. Informative References	10
Authors' Addresses	11

1. Introduction

YANG Tree Diagrams were first published in [RFC7223]. Such diagrams are commonly used to provide a simplified graphical representation of a data model and can be automatically generated via tools such as "pyang". (See <<https://github.com/mbj4668/pyang>>). This document provides the syntax used in YANG Tree Diagrams. It is expected that this document will be updated or replaced as changes to the YANG language, see [RFC7950], necessitate.

Today's common practice is include the definition of the syntax used to represent a YANG module in every document that provides a tree diagram. This practice has several disadvantages and the purpose of the document is to provide a single location for this definition. It is not the intent of this document to restrict future changes, but rather to ensure such changes are easily identified and suitably agreed upon.

An example tree diagram can be found in [RFC7223] Section 3. A portion of which follows:

```

+--rw interfaces
|   +--rw interface* [name]
|   |   +--rw name                string
|   |   +--rw description?        string
|   |   +--rw type                 identityref
|   |   +--rw enabled?            boolean
|   |   +--rw link-up-down-trap-enable? enumeration

```

2. Tree Diagram Syntax

This section provides the meaning of the symbols used in YANG Tree diagrams.

A full tree diagram of a module represents all elements. It includes the name of the module and sections for top level module statements (typically containers), augmentations, rpcs and notifications all identified under a module statement. Module trees may be included in a document as a whole, by one or more sections, or even subsets of nodes.

A module is identified by "module:" followed the module-name. This is followed by one or more sections, in order:

1. The top-level data nodes defined in the module, offset by 4 spaces.
2. Augmentations, offset by 2 spaces and identified by the keyword "augment" followed by the augment target node and a colon (":") character.
3. RPCs, offset by 2 spaces and identified by "rpcs:".
4. Notifications, offset by 2 spaces and identified by "notifications:".
5. Groupings, offset by 2 spaces, and identified by the keyword "grouping" followed by the name of the grouping and a colon (":") character.
6. yang-data, offset by 2 spaces, and identified by the keyword "yang-data" followed by the name of the yang-data structure and a colon (":") character.

The relative organization of each section is provided using a text-based format that is typical of a file system directory tree display command. Each node in the tree is prefaced with "+--". Schema nodes that are children of another node are offset from the parent by 3 spaces. Schema peer nodes separated are listed with the same space offset and, when separated by lines, linked via a vertical bar ("|") character.

The full format, including spacing conventions is:

```
module: <module-name>
```

```
    +---<node>
    |   +---<node>
    |       +---<node>
    +---<node>
        +---<node>
            +---<node>

augment <target-node>:
    +---<node>
        +---<node>
        +---<node>
            +---<node>
augment <target-node>:
    +---<node>

rpcs:
    +---<rpc-node>
    +---<rpc-node>
        +---<node>
        |   +---<node>
        +---<node>

notifications:
    +---<notification-node>
    +---<notification-node>
        +---<node>
        |   +---<node>
        +---<node>

grouping <grouping-name>:
    +---<node>
        +---<node>
        |   +---<node>
        +---<node>
grouping <grouping-name>:
    +---<node>

yang-data <yang-data-name>:
    +---<node>
        +---<node>
        |   +---<node>
        +---<node>
yang-data <yang-data-name>:
    +---<node>
```

2.1. Submodules

Submodules are represented in the same fashion as modules, but are identified by "submodule:" followed the (sub)module-name. For example:

```
submodule: <module-name>
```

```
  +--<node>
  |   +--<node>
  |   +--<node>
```

2.2. Groupings

Nodes within a used grouping are expanded as if the nodes were defined at the location of the uses statement.

Groupings may optionally be present in the "groupings" section.

2.3. yang-data

If the module defines a "yang-data" structure [RFC8040], these structures may optionally be present in the "yang-data" section.

2.4. Collapsed Node Representation

At times when the composition of the nodes within a module schema are not important in the context of the presented tree, peer nodes and their children can be collapsed using the notation "..." in place of the text lines used to represent the summarized nodes. For example:

```
  +--<node>
  |   ...
  +--<node>
      +--<node>
      +--<node>
```

2.5. Comments

Single line comments, starting with "//" and ending at the end of the line, may be used in the tree notation.

2.6. Node Representation

Each node in a YANG module is printed as:

<status> <flags> <name> <opts> <type> <if-features>

<status> is one of:

- + for current

- x for deprecated

- o for obsolete

<flags> is one of:

- rw for configuration data

- ro for non-configuration data

- x for rpcs and actions

- n for notifications

- mp for nodes containing a "mount-point" extension statment

<name> is the name of the node

(<name>) means that the node is a choice node

:(<name>) means that the node is a case node

If the node is augmented into the tree from another module,
its name is printed as <prefix>:<name>.

<opts> is one of:

- ? for an optional leaf, choice, anydata or anyxml

- ! for a presence container

- * for a leaf-list or list

- [<keys>] for a list's keys

- / for a top-level data node in a mounted module

- @ for a top-level data node in a parent referenced module

<type> is the name of the type for leafs and leaf-lists

If the type is a leafref, the type is printed as "-> TARGET",
where TARGET is either the leafref path, with prefixed removed
if possible.

<if-features> is the list of features this node depends on,
printed within curly brackets and a question mark "{...}?"

3. Usage Guidelines For RFCs

This section provides general guidelines related to the use of tree
diagrams in RFCs.

3.1. Wrapping Long Lines

Internet Drafts and RFCs limit the number of characters that may in a line of text to 72 characters. When the tree representation of a node results in line being longer than this limit the line should be broken between <opts> and <type>. The type should be indented so that the new line starts below <name> with a white space offset of at least two characters. For example:

```
notifications:
  +---n yang-library-change
    +---ro module-set-id
      -> /modules-state/module-set-id
```

The previously mentioned "pyang" command can be helpful in producing such output, for example the above example was produced using:

```
pyang -f tree --tree-line-length 50 ietf-yang-library.yang
```

When a tree diagram is included as a figure in an Internet Draft or RFC, "--tree-line-length 69" works well.

3.2. Long Diagrams

As tree diagrams are intended to provide a simplified view of a module, diagrams longer than a page should generally be avoided. If the complete tree diagram for a module becomes too long, the diagram can be split into several smaller diagrams. For example, it might be possible to have one diagram with the data node and another with all notifications. If the data nodes tree is too long, it is also possible to split the diagram into smaller diagrams for different subtrees. When long diagrams are included in a document, authors should consider whether to include the long diagram in the main body of the document or in an appendix.

An example of such a split can be found in [RFC7407], where section 2.4 shows the diagram for "engine configuration":

```
+--rw snmp
  +--rw engine
    // more parameters from the "engine" subtree here
```

Further, section 2.5 shows the diagram for "target configuration":

```
+--rw snmp
  +--rw target* [name]
    // more parameters from the "target" subtree here
```

The previously mentioned "pyang" command can be helpful in producing such output, for example the above example was produced using:

```
pyang -f tree --tree-path /snmp/target ietf-snmp.yang
```

4. YANG Schema Mount Tree Diagrams

YANG Schema Mount is defined in [I-D.ietf-netmod-schema-mount] and warrants some specific discussion. Schema mount is a generic mechanism that allows for mounting of one or more data modules at a specified location of another (parent) schema. The specific location is referred to as a mount point, and any container or list node in a schema may serve as a mount point. Mount points are identified via the inclusion of the "mount-point" extension statement as a substatement under a container or list node. Mount point nodes are thus directly identified in a module schema definition and can be identified in a tree diagram as indicated above using the "mp" flag.

In the following example taken from [I-D.ietf-rtgwg-ni-model], "vrf-root" is a container that includes the "mount-point" extension statement as part of its definition:

```
module: ietf-network-instance
  +--rw network-instances
    +--rw network-instance* [name]
      +--rw name                string
      +--rw enabled?            boolean
      +--rw description?        string
      +--rw (ni-type)?
      +--rw (root-type)
        +--:(vrf-root)
          | +--mp vrf-root
```

4.1. Representation of Instance Data Trees

The actual modules made available under a mount point is controlled by a server and is provided to clients. This information is typically provided via the Schema Mount module defined in [I-D.ietf-netmod-schema-mount]. The Schema Mount module supports exposure of both mounted schema and "parent-references". Parent references are used for XPath evaluation within mounted modules and do not represent client-accessible paths; the referenced information is available to clients via the parent schema. Schema mount also defines an "inline" type mount point where mounted modules are exposed via the YANG library module.

While the modules made available under a mount point are not specified in YANG modules that include mount points, the document

defining the module will describe the intended use of the module and may identify both modules that will be mounted and parent modules that can be referenced by mounted modules. An example of such a description can be found in [I-D.ietf-rtgwg-ni-model]. A specific implementation of a module containing mount points will also support a specific list of mounted and referenced modules. In describing both intended use and actual implementations, it is helpful to show how mounted modules would be instantiated and referenced under a mount point using tree diagrams.

In such diagrams, the mount point should be treated much like a container that uses a grouping. The flags should also be set based on the "config" leaf mentioned above, and the mount related options indicated above should be shown for the top level nodes in a mounted or referenced module. The following example, taken from [I-D.ietf-rtgwg-ni-model], represents the prior example with YANG Routing and OSPF modules mounted, YANG Interface module nodes accessible via a parent-reference, and "config" indicating true:

```

module: ietf-network-instance
  +--rw network-instances
    +--rw network-instance* [name]
      +--rw name                string
      +--rw enabled?            boolean
      +--rw description?       string
      +--rw (ni-type)?
      +--rw (root-type)
        +--:(vrf-root)
          +--mp vrf-root
            +--ro rt:routing-state/
              |   +--ro router-id?
              |   +--ro control-plane-protocols
              |   |   +--ro control-plane-protocol* [type name]
              |   |   |   +--ro ospf:ospf
              |   |   |   |   +--ro instance* [af]
              |   |   |   |   ...
              |   |   |   ...
              |   +--rw rt:routing/
              |   |   +--rw router-id?
              |   |   +--rw control-plane-protocols
              |   |   |   +--rw control-plane-protocol* [type name]
              |   |   |   +--rw ospf:ospf
              |   |   |   |   +--rw instance* [af]
              |   |   |   |   ...
              |   +--ro if:interfaces@
              |   |   ...
              +--ro if:interfaces-state@
              |   ...

```

It is worth highlighting that the OSPF module augments the Routing module, and while it is listed in the Schema Mount module (or inline YANG library) there is no special mount-related notation in the tree diagram.

A mount point definition alone is not sufficient to identify if the mounted modules are used for configuration or for non-configuration data. This is determined by the "ietf-yang-schema-mount" module's "config" leaf associated with the specific mount point and is indicated on the top level mounted nodes. For example in the above tree, when the "config" for the routing module indicates false, the only change would be to the flag on the rt:routing node:

```
+--ro rt:routing/
```

5. IANA Considerations

There are no IANA requests or assignments included in this document.

6. Security Considerations

There is no security impact related to the tree diagrams defined in this document.

7. Informative References

[I-D.ietf-netmod-schema-mount]

Bjorklund, M. and L. Lhotka, "YANG Schema Mount", draft-ietf-netmod-schema-mount-08 (work in progress), October 2017.

[I-D.ietf-rtgwg-ni-model]

Berger, L., Hopps, C., Lindem, A., Bogdanovic, D., and X. Liu, "YANG Network Instances", draft-ietf-rtgwg-ni-model-04 (work in progress), September 2017.

[RFC7223] Bjorklund, M., "A YANG Data Model for Interface Management", RFC 7223, DOI 10.17487/RFC7223, May 2014, <<https://www.rfc-editor.org/info/rfc7223>>.

[RFC7407] Bjorklund, M. and J. Schoenwaelder, "A YANG Data Model for SNMP Configuration", RFC 7407, DOI 10.17487/RFC7407, December 2014, <<https://www.rfc-editor.org/info/rfc7407>>.

[RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", RFC 7950, DOI 10.17487/RFC7950, August 2016, <<https://www.rfc-editor.org/info/rfc7950>>.

[RFC8040] Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Protocol", RFC 8040, DOI 10.17487/RFC8040, January 2017, <<https://www.rfc-editor.org/info/rfc8040>>.

Authors' Addresses

Martin Bjorklund
Tail-f Systems

Email: mbj@tail-f.com

Lou Berger (editor)
LabN Consulting, L.L.C.

Email: lberger@labn.net