

Network Working Group  
Internet-Draft  
Intended status: Informational  
Expires: February 21, 2018

T. Mizrahi  
I. Yerushalmi  
D. Melman  
Marvell  
R. Browne  
Intel  
August 20, 2017

Network Service Header (NSH) Context Header Allocation: Timestamp  
draft-mymb-sfc-nsh-allocation-timestamp-02

Abstract

This memo defines an allocation for the Context Headers of the Network Service Header (NSH), which incorporates the packet's timestamp, a sequence number, and a source interface identifier.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on February 21, 2018.

Copyright Notice

Copyright (c) 2017 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of

the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

1. Introduction . . . . .	2
2. Terminology . . . . .	3
2.1. Requirements Language . . . . .	3
2.2. Abbreviations . . . . .	3
3. NSH Context Header Allocation Allocation . . . . .	3
4. Timestamping Use Cases . . . . .	5
4.1. Network Analytics . . . . .	5
4.2. Alternate Marking . . . . .	6
4.3. Consistent Updates . . . . .	6
5. Synchronization Considerations . . . . .	6
6. IANA Considerations . . . . .	6
7. Security Considerations . . . . .	6
8. References . . . . .	7
8.1. Normative References . . . . .	7
8.2. Informative References . . . . .	7
Authors' Addresses . . . . .	8

## 1. Introduction

The Network Service Header (NSH), defined in [I-D.ietf-sfc-nsh], is an encapsulation header that is used in Service Function Chains (SFC).

The NSH specification [I-D.ietf-sfc-nsh] supports two possible methods of including metadata in the NSH; MD Type 0x1 and MD Type 0x2. When using MD Type 0x1 the NSH includes 16 octets of Context Header fields. The current memo proposes an allocation for the MD Type 0x1 Context Headers, which incorporates the timestamp of the packet, a sequence number, and a source interface identifier.

In a nutshell, packets that enter the SFC-Enabled Domain are timestamped. The timestamp is measured by the Classifier [RFC7665], and incorporated in the NSH. The timestamp may be used for various different purposes, including delay measurement, packet marking for passive performance monitoring, and timestamp-based policies. Notably, the timestamp does not increase the packet length, since it is incorporated in the MD Type 0x1 Mandatory Context Headers.

The source interface identifier indicates the interface through which the packet was received at the classifier. This identifier may specify a physical or a virtual interface. The sequence numbers can be used by Service Functions (SFs) to detect out-of-order delivery or

duplicate transmissions. The sequence number is maintained on a per-source-interface basis.

KPI-stamping [I-D.browne-sfc-nsh-kpi-stamp] defines an NSH timestamping mechanism that uses the MD Type 0x2 format. The current memo defines a compact MD Type 0x1 Context Header that does not require the packet to be extended beyond the NSH header. Furthermore, the two timestamping mechanisms can be used in concert, as further discussed below.

## 2. Terminology

### 2.1. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [RFC2119].

### 2.2. Abbreviations

The following abbreviations are used in this document:

KPI	Key Performance Indicators [I-D.browne-sfc-nsh-kpi-stamp]
NSH	Network Service Header [I-D.ietf-sfc-nsh]
MD	Metadata [I-D.ietf-sfc-nsh]
SF	Service Function [RFC7665]
SFC	Service Function Chaining [RFC7665]

## 3. NSH Context Header Allocation Allocation

This memo defines the following Context Header allocation, as presented in Figure 1.




Figure 1: NSH Timestamp Allocation.

The NSH Timestamp Allocation includes the following fields:

- o Sequence Number - a 32-bit sequence number. The sequence number is maintained on a per-source-interface basis. The sequence numbers can be used by SFs to detect out-of-order delivery, or duplicate transmissions.
- o Source Interface - a 32-bit source interface identifier that is assigned by the Classifier.
- o Timestamp - this field is 8 octets long, and specifies the time at which the packet was received by the Classifier. Two possible timestamp formats can be used for this field: the two 64-bit recommended formats specified in [I-D.mizrahi-intarea-packet-timestamps]. One of the formats is based on the [IEEE1588] timestamp format, and the other is based on the [RFC5905] format. It is assumed that in a given administrative domain only one of the formats will be used, and that the control plane determines which timestamp format is used.

The two timestamp formats that can be used in the timestamp field are:

- o IEEE 1588 Truncated Timestamp Format: the format of this field uses the 64 least significant bits of the IEEE 1588-2008 Precision Time Protocol format [IEEE1588]. This truncated format consists of a 32-bit seconds field followed by a 32-bit nanoseconds field. As defined in [IEEE1588], the timestamp specifies the number of seconds elapsed since 1 January 1970 00:00:00 according to the International Atomic Time (TAI).




Figure 2: IEEE 1588 Truncated Timestamp Format [IEEE1588].

- o NTP 64-bit Timestamp Format: this format consists of a 32-bit seconds field followed by a 32-bit fractional second field. As defined in [RFC5905], the timestamp specifies the number of seconds elapsed since 1 January 1900 00:00:00 according to the Coordinated Universal Time (UTC).




Figure 3: NTP [RFC5905] 64-bit Timestamp Format

#### 4. Timestamping Use Cases

##### 4.1. Network Analytics

Per-packet timestamping enables coarse-grained monitoring of the network delay along the Service Function Chain. Once a potential problem or bottleneck is detected, for example when the delay exceeds a certain policy, a highly-granular hop-by-hop monitoring mechanism, such as [I-D.browne-sfc-nsh-kpi-stamp] or [I-D.brockners-inband-oam-data], can be triggered, allowing to analyze and localize the problem.

Timestamping is also useful for logging and for flow analytics. It is often useful to maintain the timestamp of the first and last packet of the flow. Furthermore, traffic mirroring and sampling often requires a timestamp to be attached to analyzed packets. Attaching the timestamp to the NSH Context Header provides an in-band common time reference that can be used for various network analytics applications.

#### 4.2. Alternate Marking

A possible approach for passive performance monitoring is to use an alternate marking method [I-D.ietf-ippm-alt-mark]. This method requires data packets to carry a field that marks (colors) the traffic, and enables passive measurement of packet loss, delay, and delay variation. The value of this marking field is periodically toggled between two values.

When the timestamp is incorporated in the NSH Context Header, it can natively be used for alternate marking. For example, the least significant bit of the timestamp Seconds field can be used for this purpose, since the value of this bit is inherently toggled every second.

#### 4.3. Consistent Updates

The timestamp can be used for taking policy decisions such as 'Perform action A if timestamp>=T\_0'. This can be used for enforcing time-of-day policies or periodic policies in service functions. Furthermore, timestamp-based policies can be used for enforcing consistent network updates, as discussed in [DPT].

#### 5. Synchronization Considerations

Some of the applications that make use of the timestamp require the Classifier and SFs to be synchronized to a common time reference, for example using the Network Time Protocol [RFC5905], or the Precision Time Protocol [IEEE1588].

#### 6. IANA Considerations

This memo includes no request to IANA.

#### 7. Security Considerations

The security considerations of NSH in general are discussed in [I-D.ietf-sfc-nsh]. The security considerations of in-band timestamping in the context of NSH is discussed in [I-D.browne-sfc-nsh-kpi-stamp], and the current section is based on that discussion.

The use of in-band timestamping, as defined in this document, can be used as a means for network reconnaissance. By passively eavesdropping to timestamped traffic, an attacker can gather information about network delays and performance bottlenecks. A man-in-the-middle attacker can maliciously modify timestamps in order to

attack applications that use the timestamp values, such as performance monitoring applications.

Since the timestamping mechanism relies on an underlying time synchronization protocol, by attacking the time protocol an attack can potentially compromise the integrity of the NSH timestamp. A detailed discussion about the threats against time protocols and how to mitigate them is presented in [RFC7384].

## 8. References

### 8.1. Normative References

- [I-D.ietf-sfc-nsh]  
Quinn, P., Elzur, U., and C. Pignataro, "Network Service Header (NSH)", draft-ietf-sfc-nsh-19 (work in progress), August 2017.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.

### 8.2. Informative References

- [DPT] Mizrahi, T., Moses, Y., "The Case for Data Plane Timestamping in SDN", IEEE INFOCOM Workshop on Software-Driven Flexible and Agile Networking (SWFAN), 2016.
- [I-D.brockners-inband-oam-data]  
Brockners, F., Bhandari, S., Pignataro, C., Gredler, H., Leddy, J., Youell, S., Mizrahi, T., Mozes, D., Lapukhov, P., Chang, R., and d. daniel.bernier@bell.ca, "Data Fields for In-situ OAM", draft-brockners-inband-oam-data-07 (work in progress), July 2017.
- [I-D.browne-sfc-nsh-kpi-stamp]  
Browne, R., Chilikin, A., and T. Mizrahi, "Network Service Header KPI Stamping", draft-browne-sfc-nsh-kpi-stamp-01 (work in progress), April 2017.
- [I-D.ietf-ippm-alt-mark]  
Fioccola, G., Capello, A., Cociglio, M., Castaldelli, L., Chen, M., Zheng, L., Mirsky, G., and T. Mizrahi, "Alternate Marking method for passive and hybrid performance monitoring", draft-ietf-ippm-alt-mark-06 (work in progress), July 2017.

- [I-D.mizrahi-intarea-packet-timestamps]  
Mizrahi, T., Fabini, J., and A. Morton, "Guidelines for Defining Packet Timestamps", draft-mizrahi-intarea-packet-timestamps-00 (work in progress), June 2017.
- [IEEE1588]  
IEEE, "IEEE 1588 Standard for a Precision Clock Synchronization Protocol for Networked Measurement and Control Systems Version 2", 2008.
- [RFC5905] Mills, D., Martin, J., Ed., Burbank, J., and W. Kasch, "Network Time Protocol Version 4: Protocol and Algorithms Specification", RFC 5905, DOI 10.17487/RFC5905, June 2010, <<https://www.rfc-editor.org/info/rfc5905>>.
- [RFC7384] Mizrahi, T., "Security Requirements of Time Protocols in Packet Switched Networks", RFC 7384, DOI 10.17487/RFC7384, October 2014, <<https://www.rfc-editor.org/info/rfc7384>>.
- [RFC7665] Halpern, J., Ed. and C. Pignataro, Ed., "Service Function Chaining (SFC) Architecture", RFC 7665, DOI 10.17487/RFC7665, October 2015, <<https://www.rfc-editor.org/info/rfc7665>>.

## Authors' Addresses

Tal Mizrahi  
Marvell  
6 Hamada  
Yokneam 2066721  
Israel

Email: [talmi@marvell.com](mailto:talmi@marvell.com)

Ilan Yerushalmi  
Marvell  
6 Hamada  
Yokneam 2066721  
Israel

Email: [yilan@marvell.com](mailto:yilan@marvell.com)



David Melman  
Marvell  
6 Hamada  
Yokneam 2066721  
Israel

Email: davidme@marvell.com

Rory Browne  
Intel  
Dromore House  
Shannon, Co.Clare  
Ireland

Email: rory.browne@intel.com