

SFC WG
Internet-Draft
Intended status: Standards Track
Expires: April 30, 2018

T. Ao
ZTE Corporation
G. Mirsky
ZTE Corp.
Z. Chen
China Telecom
October 27, 2017

Controlled Return Path for Service Function Chain (SFC) OAM
draft-ao-sfc-oam-return-path-specified-01

Abstract

This document defines extensions to the Service Function Chain (SFC) Operation, Administration and Maintenance (OAM) that enable control of the Echo Reply return path by specifying it as Reverse Service Function Path. Enforcing the specific return path can be used to verify bidirectional connectivity of SFC and increase robustness of SFC OAM.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 30, 2018.

Copyright Notice

Copyright (c) 2017 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect

to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1. Introduction	2
2. Conventions used in this document	3
2.1. Terminology	3
2.2. Requirements Language	3
3. Extension	3
4. SFC Reply Path TLV	4
5. Theory of Operation	5
5.1. Case of Bi-directional SFC	5
6. Security Considerations	5
7. IANA Considerations	6
7.1. SFC Return Path Type	6
7.2. New Return Codes	6
8. References	6
8.1. Normative References	6
8.2. Informative References	7
Authors' Addresses	7

1. Introduction

While Service Function Chain (SFC) Echo Request, defined in [I-D.wang-sfc-multi-layer-oam], always traverses the SFC it directed to, the corresponding Echo Reply is sent over IP network [I-D.wang-sfc-multi-layer-oam]. There are scenarios when it is beneficial to direct the responder to use path other than the IP network. This document defines extensions to the Service Function Chain (SFC) Operation, Administration and Maintenance (OAM) that enable control of the Echo Reply return path by specifying it as Reply Service Function Path. This document defines a new Type-Length-Value (TLV), Reply Service Function Path TLV, for Reply via Specified Path mode of SFC Echo Reply (Section 4).

The Reply Service Function Path TLV provides efficient mechanism to test bidirectional and hybrid SFCs, as these were defined in Section 2.2 [RFC7665], that allows an operator to test both directions of the bidirectional or hybrid SFP with a single SFC Echo Request/Echo Reply operation.

2. Conventions used in this document

2.1. Terminology

SF - Service Function

SFF - Service Function Forwarder

SFC - Service Function Chain, an ordered set of some abstract SFs.

SFP - Service Function Path

SPI - Service Path Index

OAM - Operation, Administration, and Maintenance

2.2. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

3. Extension

Following reply modes had been defined in [I-D.wang-sfc-multi-layer-oam]:

- o Do Not Reply
- o Reply via an IPv4/IPv6 UDP Packet
- o Reply via Application Level Control Channel
- o Reply via Specified Path

The Reply via Specified Path mode is intended to enforce use of the particular return path specified in the included TLV. This mode may help to verify bidirectional continuity or increase robustness of the monitoring of the SFC by selecting more stable path. In case of SFC, the sender of Echo Request instructs the egress SFF to send Echo Reply message along the SFP specified in the SFC Reply Path TLV Section 4.

5. Theory of Operation

[RFC7110] defined mechanism to control return path for MPLS LSP Echo Reply. In case of SFC, the return path is a SFP along which SFC Echo Reply message MUST be transmitted. Hence, the SFC Reply Path TLV included in the SFC Echo Request message MUST sufficiently identify the SFP that the sender of the Echo Request message expects the receiver to use for the corresponding SFC Echo Reply.

When sending an Echo Request the sender MUST set the value of Reply Mode field to "Reply via Specified Path", defined in [I-D.wang-sfc-multi-layer-oam], and MUST include SFC Reply Path TLV. The SFC Reply Path TLV includes identifier of the reverse SFP and an appropriate Service Index.

Echo Reply is expected to be sent by the egress SFF of the SFP being tested or by the SFF at which SFC TTL expires as defined [I-D.ietf-sfc-nsh]. Processing described below equally applies in both cases and referred as responding SFF.

If the Echo Request message with SFC Reply Path TLV, received by the responding SFF, has Reply Mode value of "Reply via Specified Path" but no SFC Reply Path TLV is present, then the responding SFF MUST send Echo Reply with Return Code set to "Reply Path TLV is missing" value (TBA2). If the responding SFF cannot find requested SFP it MUST send Echo Reply with Return Code set to "Reply SFP was not found" and include the SFC Reply Path TLV from the Echo Request message.

5.1. Case of Bi-directional SFC

Ability to specify the return path to be used for Echo Reply is very useful in bi-directional SFC. For bi-directional SFC, since the last SFF of the forward SFP may not co-locate with classifier of the reverse SFP, it is assumed that last SFF doesn't know the reply path of a SFC. So even for bi-directional SFC, a reverse SFP also need to be indicated in reply path TLV in echo request message.

6. Security Considerations

Security considerations discussed in [I-D.ietf-sfc-nsh] apply to this document..

In addition, the SFC Return Path extension, defined in this document, may be used for potential "proxying" attacks. For example, an echo request initiator may specify a return path that has a destination different from that of the initiator. But normally, such attacks will not happen in an SFC domain where the initiators and receivers

belong to the same domain, as specified in [RFC7665]. Even if the attack happens, in order to prevent using the SFC Return Path extension for proxying any possible attacks, the return path SFP SHOULD have destination to the sender of the echo request, identified in SFC Source TLV [I-D.wang-sfc-multi-layer-oam]. The receiver may drop the echo request when it cannot determine whether the return path SFP has the destination to the initiator. That means, when sending echo request, the sender SHOULD choose a proper source address according the specified return path SFP to help the receiver to make the decision.

7. IANA Considerations

7.1. SFC Return Path Type

IANA is requested to assign from its SFC Echo Request/Echo Reply TLV registry new type as following:

Value	Description	Reference
TBA1	SFC Reply Path Type	This document

Table 1: SFC Return Path Type

7.2. New Return Codes

IANA is requested to assign new return codes from the SFC Echo Request/Echo Reply Return Codes registry as following:

Value	Description	Reference
TBA2	Reply Path TLV is missing	This document
TBA3	Reply SFP was not found	This document

Table 2: SFC Echo Reply Return Codes

8. References

8.1. Normative References

[I-D.ietf-sfc-nsh]

Quinn, P., Elzur, U., and C. Pignataro, "Network Service Header (NSH)", draft-ietf-sfc-nsh-27 (work in progress), October 2017.

[I-D.wang-sfc-multi-layer-oam]

Mirsky, G., Meng, W., Khasnabish, B., and C. Wang, "Multi-Layer Active OAM for Service Function Chains in Networks", draft-wang-sfc-multi-layer-oam-10 (work in progress), September 2017.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.

[RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.

8.2. Informative References

[RFC7110] Chen, M., Cao, W., Ning, S., Jounay, F., and S. Delord, "Return Path Specified Label Switched Path (LSP) Ping", RFC 7110, DOI 10.17487/RFC7110, January 2014, <<https://www.rfc-editor.org/info/rfc7110>>.

[RFC7665] Halpern, J., Ed. and C. Pignataro, Ed., "Service Function Chaining (SFC) Architecture", RFC 7665, DOI 10.17487/RFC7665, October 2015, <<https://www.rfc-editor.org/info/rfc7665>>.

Authors' Addresses

Ting Ao
ZTE Corporation
No.889, BiBo Road
Shanghai 201203
China

Phone: +86 21 68897642
Email: ao.ting@zte.com.cn

Greg Mirsky
ZTE Corp.
1900 McCarthy Blvd. #205
Milpitas, CA 95035
USA

Email: gregimirsky@gmail.com

Zhonghua Chen
China Telecom
No.1835, South PuDong Road
Shanghai 201203
China

Phone: +86 18918588897
Email: 18918588897@189.cn