

Transport Area Working Group
Internet-Draft
Updates: 3819 (if approved)
Intended status: Best Current Practice
Expires: 7 June 2024

B. Briscoe
Independent
J. Kaippallimalil
Futurewei
5 December 2023

Guidelines for Adding Congestion Notification to Protocols that
Encapsulate IP
draft-ietf-tsvwg-ecn-encap-guidelines-22

Abstract

The purpose of this document is to guide the design of congestion notification in any lower layer or tunnelling protocol that encapsulates IP. The aim is for explicit congestion signals to propagate consistently from lower layer protocols into IP. Then the IP internetwork layer can act as a portability layer to carry congestion notification from non-IP-aware congested nodes up to the transport layer (L4). Following these guidelines should assure interworking among IP layer and lower layer congestion notification mechanisms, whether specified by the IETF or other standards bodies. This document is included in BCP 89 and updates the single paragraph of advice to subnetwork designers about ECN in Section 13 of RFC 3819, by replacing it with a reference to the whole of this document.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 7 June 2024.

Copyright Notice

Copyright (c) 2023 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

This document may contain material from IETF Documents or IETF Contributions published or made publicly available before November 10, 2008. The person(s) controlling the copyright in some of this material may not have granted the IETF Trust the right to allow modifications of such material outside the IETF Standards Process. Without obtaining an adequate license from the person(s) controlling the copyright in such materials, this document may not be modified outside the IETF Standards Process, and derivative works of it may not be created outside the IETF Standards Process, except to format it for publication as an RFC or to translate it into languages other than English.

Table of Contents

1. Introduction	3
1.1. Update to RFC 3819	5
1.2. Scope	6
2. Terminology	8
3. Modes of Operation	9
3.1. Feed-Forward-and-Up Mode	10
3.2. Feed-Up-and-Forward Mode	12
3.3. Feed-Backward Mode	12
3.4. Null Mode	14
4. Feed-Forward-and-Up Mode: Guidelines for Adding Congestion Notification	14
4.1. IP-in-IP Tunnels with Shim Headers	15
4.2. Wire Protocol Design: Indication of ECN Support	16
4.3. Encapsulation Guidelines	19
4.4. Decapsulation Guidelines	21
4.5. Sequences of Similar Tunnels or Subnets	22
4.6. Reframing and Congestion Markings	23
5. Feed-Up-and-Forward Mode: Guidelines for Adding Congestion Notification	25
6. Feed-Backward Mode: Guidelines for Adding Congestion Notification	26
7. IANA Considerations	27
8. Security Considerations	28
9. Conclusions	28
10. References	29

10.1. Normative References	29
10.2. Informative References	30
Comments Solicited	34
Acknowledgements	34
Contributors	35
Authors' Addresses	35

1. Introduction

The benefits of Explicit Congestion Notification (ECN) described in [RFC8087] and summarized below can only be fully realized if support for ECN is added to the relevant subnetwork technology, as well as to IP. When a lower layer buffer drops a packet obviously it does not just drop at that layer; the packet disappears from all layers. In contrast, when active queue management (AQM) at a lower layer marks a packet with ECN, the marking needs to be explicitly propagated up the layers. The same is true if AQM marks the outer header of a packet that encapsulates inner tunnelled headers. Forwarding ECN is not as straightforward as other headers because it has to be assumed ECN may be only partially deployed. If a lower layer header that contains ECN congestion indications is stripped off by a subnet egress that is not ECN-aware, or if the ultimate receiver or sender is not ECN-aware, congestion needs to be indicated by dropping the packet, not marking it.

The purpose of this document is to guide the addition of congestion notification to any subnet technology or tunnelling protocol, so that lower layer AQM algorithms can signal congestion explicitly and it will propagate consistently into encapsulated (higher layer) headers, otherwise the signals will not reach their ultimate destination.

ECN is defined in the IP header (IPv4 and IPv6) [RFC3168] to allow a resource to notify the onset of queue build-up without having to drop packets, by explicitly marking a proportion of packets with the congestion experienced (CE) codepoint.

Given a suitable marking scheme, ECN removes nearly all congestion loss and it cuts delays for two main reasons:

- * It avoids the delay when recovering from congestion losses, which particularly benefits small flows or real-time flows, making their delivery time predictably short [RFC2884];

- * As ECN is used more widely by end-systems, it will gradually remove the need to configure a degree of delay into buffers before they start to notify congestion (the cause of bufferbloat). This is because drop involves a trade-off between sending a timely signal and trying to avoid impairment, whereas ECN is solely a signal not an impairment, so there is no harm triggering it earlier.

Some lower layer technologies (e.g. MPLS, Ethernet) are used to form subnetworks with IP-aware nodes only at the edges. These networks are often sized so that it is rare for interior queues to overflow. However, until recently this was more due to the inability of TCP to saturate the links. For many years, fixes such as window scaling [RFC7323] proved hard to deploy. And the Reno variant of TCP has remained in widespread use despite its inability to scale to high flow rates. However, now that modern operating systems are finally capable of saturating interior links, even the buffers of well-provisioned interior switches will need to signal episodes of queuing.

Propagation of ECN is defined for MPLS [RFC5129], and has been defined for TRILL [RFC7780], [I-D.ietf-trill-ecn-support], but it remains to be defined for a number of other subnetwork technologies.

Similarly, ECN propagation is yet to be defined for many tunnelling protocols. [RFC6040] defines how ECN should be propagated for IP-in-IPv4 [RFC2003], IP-in-IPv6 [RFC2473] and IPsec [RFC4301] tunnels, but there are numerous other tunnelling protocols with a shim and/or a layer 2 header between two IP headers (IPv4 or IPv6). Some address ECN propagation between the IP headers, but many do not. This document gives guidance on how to address ECN propagation for future tunnelling protocols, and a companion standards track specification [I-D.ietf-tsvwg-rfc6040update-shim] updates those existing IP-shim-(L2)-IP protocols that are under IETF change control and still widely used.

Incremental deployment is the most delicate aspect when adding support for ECN. The original ECN protocol in IP [RFC3168] was carefully designed so that a congested buffer would not mark a packet (rather than drop it) unless both source and destination hosts were ECN-capable. Otherwise, its congestion markings would never be detected and congestion would just build up further. However, to support congestion marking below the IP layer or within tunnels, it is not sufficient to only check that the two layer 4 transport endpoints support ECN; correct operation also depends on the decapsulator at each subnet or tunnel egress faithfully propagating congestion notifications to the higher layer. Otherwise, a legacy decapsulator might silently fail to propagate any ECN signals from

the outer to the forwarded header. Then the lost signals would never be detected and again congestion would build up further. The guidelines given later require protocol designers to carefully consider incremental deployment, and suggest various safe approaches for different circumstances.

Of course, the IETF does not have standards authority over every link layer protocol. So this document gives guidelines for designing propagation of congestion notification across the interface between IP and protocols that may encapsulate IP (i.e. that can be layered beneath IP). Each lower layer technology will exhibit different issues and compromises, so the IETF or the relevant standards body must be free to define the specifics of each lower layer congestion notification scheme. Nonetheless, if the guidelines are followed, congestion notification should interwork between different technologies, using IP in its role as a 'portability layer'.

Therefore, the capitalized terms 'SHOULD' or 'SHOULD NOT' are often used in preference to 'MUST' or 'MUST NOT', because it is difficult to know the compromises that will be necessary in each protocol design. If a particular protocol design chooses not to follow a 'SHOULD (NOT)' given in the advice below, it MUST include a sound justification.

It has not been possible to give common guidelines for all lower layer technologies, because they do not all fit a common pattern. Instead, they have been divided into a few distinct modes of operation: feed-forward-and-upward; feed-upward-and-forward; feed-backward; and null mode. These modes are described in Section 3, then in the subsequent sections separate guidelines are given for each mode.

1.1. Update to RFC 3819

This document updates the brief advice to subnetwork designers about ECN in Section 13 of [RFC3819], by replacing the last two paragraphs with the following sentence:

By following the guidelines in [this document], subnetwork designers can enable a layer-2 protocol to participate in congestion control without dropping packets via propagation of explicit congestion notification (ECN [RFC3168]) to receivers.

and adding [this document] as an informative reference. {RFC Editor: Please replace both instances of [this document] above with the number of the present RFC when published.}

1.2. Scope

This document only concerns wire protocol processing of explicit notification of congestion. It makes no changes or recommendations concerning algorithms for congestion marking or for congestion response, because algorithm issues should be independent of the layer the algorithm operates in.

The default ECN semantics are described in [RFC3168] and updated by [RFC8311]. Also, the guidelines for AQM designers [RFC7567] clarify the semantics of both drop and ECN signals from AQM algorithms. [RFC4774] is the appropriate best current practice specification of how algorithms with alternative semantics for the ECN field can be partitioned from Internet traffic that uses the default ECN semantics. There are two main examples for how alternative ECN semantics have been defined in practice:

- * RFC 4774 suggests using the ECN field in combination with a Diffserv codepoint such as in PCN [RFC6660], Voice over 3G [UTRAN] or Voice over LTE (VoLTE) [LTE-RA];
- * RFC 8311 suggests using the ECT(1) codepoint of the ECN field to indicate alternative semantics such as for the experimental Low Latency Low Loss Scalable throughput (L4S) service [RFC9331]).

The aim is that the default rules for encapsulating and decapsulating the ECN field are sufficiently generic that tunnels and subnets will encapsulate and decapsulate packets without regard to how algorithms elsewhere are setting or interpreting the semantics of the ECN field. [RFC6040] updates RFC 4774 to allow alternative encapsulation and decapsulation behaviours to be defined for alternative ECN semantics. However, it reinforces the same point – that it is far preferable to try to fit within the common ECN encapsulation and decapsulation behaviours, because expecting all lower layer technologies and tunnels to be updated is likely to be completely impractical.

Alternative semantics for the ECN field can be defined to depend on the traffic class indicated by the DSCP. Therefore, correct propagation of congestion signals could depend on correct propagation of the DSCP between the layers and along the path. For instance, if the meaning of the ECN field depends on the DSCP (as in PCN or VoLTE) and if the outer DSCP is stripped on decapsulation, as in the pipe model of [RFC2983], the special semantics of the ECN field would be lost. Similarly, if the DSCP is changed at the boundary between Diffserv domains, the special ECN semantics would also be lost. This is an important implication of the localized scope of most Diffserv arrangements. In this document, correct propagation of traffic class information is assumed, while what 'correct' means and how it is achieved is covered elsewhere (e.g. RFC 2983) and is outside the scope of the present document.

The guidelines in this document do ensure that common encapsulation and decapsulation rules are sufficiently generic to cover cases where ECT(1) is used instead of ECT(0) to identify alternative ECN semantics (as in L4S [RFC9331]) and where ECN marking algorithms use ECT(1) to encode 3 severity levels into the ECN field (e.g. PCN [RFC6660]) rather than the default of 2. All these different semantics for the ECN field work because it has been possible to define common default decapsulation rules that allow for all cases.

Note that the guidelines in this document do not necessarily require the subnet wire protocol to be changed to add support for congestion notification. For instance, the Feed-Up-and-Forward Mode (Section 3.2) and the Null Mode (Section 3.4) do not. Another way to add congestion notification without consuming header space in the subnet protocol might be to use a parallel control plane protocol.

This document focuses on the congestion notification interface between IP and lower layer or tunnel protocols that can encapsulate IP, where the term 'IP' includes IPv4 or IPv6, unicast, multicast or anycast. However, it is likely that the guidelines will also be useful when a lower layer protocol or tunnel encapsulates itself, e.g. Ethernet MAC in MAC ([IEEE802.1Q]; previously 802.1ah) or when it encapsulates other protocols. In the feed-backward mode, propagation of congestion signals for multicast and anycast packets is out-of-scope (because the complexity would make it unlikely to be attempted).

2. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

Further terminology used within this document:

Protocol data unit (PDU): Information that is delivered as a unit among peer entities of a layered network consisting of protocol control information (typically a header) and possibly user data (payload) of that layer. The scope of this document includes layer 2 and layer 3 networks, where the PDU is respectively termed a frame or a packet (or a cell in ATM). PDU is a general term for any of these. This definition also includes a payload with a shim header lying somewhere between layer 2 and 3.

Transport: The end-to-end transmission control function, conventionally considered at layer-4 in the OSI reference model. Given the audience for this document will often use the word transport to mean low level bit carriage, whenever the term is used it will be qualified, e.g. 'L4 transport'.

Encapsulator: The link or tunnel endpoint function that adds an outer header to a PDU (also termed the 'link ingress', the 'subnet ingress', the 'ingress tunnel endpoint' or just the 'ingress' where the context is clear).

Decapsulator: The link or tunnel endpoint function that removes an outer header from a PDU (also termed the 'link egress', the 'subnet egress', the 'egress tunnel endpoint' or just the 'egress' where the context is clear).

Incoming header: The header of an arriving PDU before encapsulation.

Outer header: The header added to encapsulate a PDU.

Inner header: The header encapsulated by the outer header.

Outgoing header: The header forwarded by the decapsulator.

CE: Congestion Experienced [RFC3168]

ECT: ECN-Capable (L4) Transport [RFC3168]

Not-ECT: Not ECN-Capable (L4) Transport [RFC3168]

Load Regulator: For each flow of PDUs, the transport function that is capable of controlling the data rate. Typically located at the data source, but in-path nodes can regulate load in some congestion control arrangements (e.g. admission control, policing nodes or transport circuit-breakers [RFC8084]). Note the term "a function capable of controlling the load" deliberately includes a transport that does not actually control the load responsively but ideally it ought to (e.g. a sending application without congestion control that uses UDP).

ECN-PDU: A PDU at the IP layer or below with a capacity to signal congestion that is part of a congestion control feedback loop within which all the nodes necessary to propagate the signal back to the Load Regulator are capable of doing that propagation. An IP packet with a non-zero ECN field implies that the endpoints are ECN-capable, so this would be an ECN-PDU. However, ECN-PDU is intended to be a general term for a PDU at lower layers, as well as at the IP layer.

Not-ECN-PDU: A PDU at the IP layer or below that is part of a congestion control feedback loop that is not capable of propagating explicit congestion notification signals back to the Load Regulator, because at least one of the nodes necessary to propagate the signals is incapable of doing that propagation. Note that this definition is a property of the feedback-loop, not necessarily of the PDU itself, because in some protocols the PDU will self-describe the property, but in others the property might be carried in a separate control-plane context that is somehow bound to the PDU.

3. Modes of Operation

This section sets down the different modes by which congestion information is passed between the lower layer and the higher one. It acts as a reference framework for the following sections, which give normative guidelines for designers of explicit congestion notification protocols, taking each mode in turn:

Feed-Forward-and-Up: Nodes feed forward congestion notification towards the egress within the lower layer then up and along the layers towards the end-to-end destination at the transport layer. The following local optimisation is possible:

Feed-Up-and-Forward: A lower layer switch feeds-up congestion notification directly into the higher layer (e.g. into the ECN field in the IP header), irrespective of whether the node is at the egress of a subnet.

Feed-Backward: Nodes feed back congestion signals towards the ingress of the lower layer and (optionally) attempt to control congestion within their own layer.

Null: Nodes cannot experience congestion at the lower layer except at ingress nodes (which are IP-aware or equivalently higher-layer-aware).

3.1. Feed-Forward-and-Up Mode

Like IP and MPLS, many subnet technologies are based on self-contained protocol data units (PDUs) or frames sent unreliably. They provide no feedback channel at the subnetwork layer, instead relying on higher layers (e.g. TCP) to feed back loss signals.

In these cases, ECN may best be supported by standardising explicit notification of congestion into the lower layer protocol that carries the data forwards. Then a specification is needed for how the egress of the lower layer subnet propagates this explicit signal into the forwarded upper layer (IP) header. This signal continues forwards until it finally reaches the destination transport (at L4). Then typically the destination will feed this congestion notification back to the source transport using an end-to-end protocol (e.g. TCP). This is the arrangement that has already been used to add ECN to IP-in-IP tunnels [RFC6040], IP-in-MPLS and MPLS-in-MPLS [RFC5129].

This mode is illustrated in Figure 1. Along the middle of the figure, layers 2, 3 and 4 of the protocol stack are shown, and one packet is shown along the bottom as it progresses across the network from source to destination, crossing two subnets connected by a router, and crossing two switches on the path across each subnet. Congestion at the output of the first switch (shown as *) leads to a congestion marking in the L2 header (shown as C in the illustration of the packet). The chevrons show the progress of the resulting congestion indication. It is propagated from link to link across the subnet in the L2 header, then when the router removes the marked L2 header, it propagates the marking up into the L3 (IP) header. The router forwards the marked L3 header into subnet B. The L2 protocol used in subnet B does not support ECN, but the signal proceeds across it in the L3 header.

Note that there is no implication that each 'C' marking is encoded the same; a different encoding might be used for the 'C' marking in each protocol.

Finally, for completeness, we show the L3 marking arriving at the destination, where the host transport protocol (e.g. TCP) feeds it back to the source in the L4 acknowledgement (the 'C' at L4 in the packet at the top of the diagram).




Figure 1: Feed-Forward-and-Up Mode

Of course, modern networks are rarely as simple as this text-book example, often involving multiple nested layers. For example, a 3GPP mobile network may have two IP-in-IP (GTP [GTPv1]) tunnels in series and an MPLS backhaul between the base station and the first router. Nonetheless, the example illustrates the general idea of feeding congestion notification forward then upward whenever a header is removed at the egress of a subnet.

Note that the FECN (forward ECN) bit in Frame Relay [Buck00] and the explicit forward congestion indication (EFCI [ITU-T.I.371]) bit in ATM user data cells follow a feed-forward pattern. However, in ATM, this arrangement is only part of a feed-forward-and-backward pattern at the lower layer, not feed-forward-and-up out of the lower layer the intention was never to interface to IP ECN at the subnet egress. To our knowledge, Frame Relay FECN is solely used to detect where more capacity should be provisioned.

3.2. Feed-Up-and-Forward Mode

Ethernet is particularly difficult to extend incrementally to support explicit congestion notification. One way to support ECN in such cases has been to use so called 'layer-3 switches'. These are Ethernet switches that dig into the Ethernet payload to find an IP header and manipulate or act on certain IP fields (specifically Diffserv & ECN). For instance, in Data Center TCP [RFC8257], layer-3 switches are configured to mark the ECN field of the IP header within the Ethernet payload when their output buffer becomes congested. With respect to switching, a layer-3 switch acts solely on the addresses in the Ethernet header; it does not use IP addresses, and it does not decrement the TTL field in the IP header.




Figure 2: Feed-Up-and-Forward Mode

By comparing Figure 2 with Figure 1, it can be seen that subnet E (perhaps a subnet of layer-3 Ethernet switches) works in feed-up-and-forward mode by notifying congestion directly into L3 at the point of congestion, even though the congested switch does not otherwise act at L3. In this example, the technology in subnet F (e.g. MPLS) does support ECN natively, so when the router adds the layer-2 header it copies the ECN marking from L3 to L2 as well, as shown by the 'C's in both layers.

3.3. Feed-Backward Mode

In some layer 2 technologies, explicit congestion notification has been defined for use internally within the subnet with its own feedback and load regulation, but typically the interface with IP for ECN has not been defined.

For instance, for the available bit-rate (ABR) service in ATM, the relative rate mechanism was one of the more popular mechanisms for managing traffic, tending to supersede earlier designs. In this approach ATM switches send special resource management (RM) cells in both the forward and backward directions to control the ingress rate of user data into a virtual circuit. If a switch buffer is approaching congestion or is congested it sends an RM cell back towards the ingress with respectively the No Increase (NI) or Congestion Indication (CI) bit set in its message type field [ATM-TM-ABR]. The ingress then holds or decreases its sending bit-rate accordingly.




Figure 3: Feed-Backward Mode

ATM's feed-backward approach does not fit well when layered beneath IP's feed-forward approach unless the initial data source is the same node as the ATM ingress. Figure 3 shows the feed-backward approach being used in subnet H. If the final switch on the path is congested (*), it does not feed-forward any congestion indications on packet (U). Instead it sends a control cell (V) back to the router at the ATM ingress.

However, the backward feedback does not reach the original data source directly because IP does not support backward feedback (and subnet G is independent of subnet H). Instead, the router in the middle throttles down its sending rate but the original data sources don't reduce their rates. The resulting rate mismatch causes the middle router's buffer at layer 3 to back up until it becomes congested, which it signals forwards on later data packets at layer 3 (e.g. packet W). Note that the forward signal from the middle router is not triggered directly by the backward signal. Rather, it is triggered by congestion resulting from the middle router's mismatched rate response to the backward signal.

In response to this later forward signalling, end-to-end feedback at layer-4 finally completes the tortuous path of congestion indications back to the origin data source, as before.

Quantized congestion notification (QCN [IEEE802.1Q]) would suffer from similar problems if extended to multiple subnets. However, from the start QCN was clearly characterized as solely applicable to a single subnet (see Section 6).

3.4. Null Mode

Often link and physical layer resources are 'non-blocking' by design. In these cases congestion notification may be implemented but it does not need to be deployed at the lower layer; ECN in IP would be sufficient.

A degenerate example is a point-to-point Ethernet link. Excess loading of the link merely causes the queue from the higher layer to back up, while the lower layer remains immune to congestion. Even a whole meshed subnetwork can be made immune to interior congestion by limiting ingress capacity and sufficient sizing of interior links, e.g. a non-blocking fat-tree network [Leiserson85]. An alternative to fat links near the root is numerous thin links with multi-path routing to ensure even worst-case patterns of load cannot congest any link, e.g. a Clos network [Clos53].

4. Feed-Forward-and-Up Mode: Guidelines for Adding Congestion Notification

Feed-forward-and-up is the mode already used for signalling ECN up the layers through MPLS into IP [RFC5129] and through IP-in-IP tunnels [RFC6040], whether encapsulating with IPv4 [RFC2003], IPv6 [RFC2473] or IPsec [RFC4301]. These RFCs take a consistent approach and the following guidelines are designed to ensure this consistency continues as ECN support is added to other protocols that encapsulate IP. The guidelines are also designed to ensure compliance with the

more general best current practice for the design of alternate ECN schemes given in [RFC4774] and extended by [RFC8311].

The rest of this section is structured as follows:

- * Section 4.1 addresses the most straightforward cases, where [RFC6040] can be applied directly to add ECN to tunnels that are effectively IP-in-IP tunnels, but with shim header(s) between the IP headers.
- * The subsequent sections give guidelines for adding ECN to a subnet technology that uses feed-forward-and-up mode like IP, but it is not so similar to IP that [RFC6040] rules can be applied directly. Specifically:
 - Sections 4.2, 4.3 and 4.4 respectively address how to add ECN support to the wire protocol and to the encapsulators and decapsulators at the ingress and egress of the subnet.
 - Section 4.5 deals with the special, but common, case of sequences of tunnels or subnets that all use the same technology
 - Section 4.6 deals with the question of reframing when IP packets do not map 1:1 into lower layer frames.

4.1. IP-in-IP Tunnels with Shim Headers

A common pattern for many tunnelling protocols is to encapsulate an inner IP header with shim header(s) then an outer IP header. A shim header is defined as one that is not sufficient alone to forward the packet as an outer header. Another common pattern is for a shim to encapsulate a layer 2 (L2) header, which in turn encapsulates (or might encapsulate) an IP header. [I-D.ietf-tsvwg-rfc6040update-shim] clarifies that RFC 6040 is just as applicable when there are shim(s) and possibly a L2 header between two IP headers.

However, it is not always feasible or necessary to propagate ECN between IP headers when separated by a shim. For instance, it might be too costly to dig to arbitrary depths to find an inner IP header, there may be little or no congestion within the tunnel by design (see null mode in Section 3.4 above), or a legacy implementation might not support ECN. In cases where a tunnel does not support ECN, it is important that the ingress does not copy the ECN field from an inner IP header to an outer. Therefore Section 4 of [I-D.ietf-tsvwg-rfc6040update-shim] requires network operators to configure the ingress of a tunnel that does not support ECN so that it zeros the ECN field in the outer IP header.

Nonetheless, in many cases it is feasible to propagate the ECN field between IP headers separated by shim header(s) and/or a L2 header. Particularly in the typical case when the outer IP header and the shim(s) are added (or removed) as part of the same procedure. Even if the shim(s) encapsulate a L2 header, it is often possible to find an inner IP header within the L2 PDU and propagate ECN between that and the outer IP header. This can be thought of as a special case of the feed-up-and-forward mode (Section 3.2), so the guidelines for this mode apply (Section 5).

Numerous shim protocols have been defined for IP tunnelling. More recent ones e.g. Geneve [RFC8926] and Generic UDP Encapsulation (GUE) [I-D.ietf-intarea-gue] cite and follow RFC 6040. And some earlier ones, e.g. CAPWAP [RFC5415] and LISP [RFC9300], cite RFC 3168, which is compatible with RFC 6040.

However, as Section 9.3 of [RFC3168] pointed out, ECN support needs to be defined for many earlier shim-based tunnelling protocols, e.g. L2TPv2 [RFC2661], L2TPv3 [RFC3931], GRE [RFC2784], PPTP [RFC2637], GTP [GTPv1], [GTPv1-U], [GTPv2-C] and Teredo [RFC4380] as well as some recent ones, e.g. VXLAN [RFC7348], NVGRE [RFC7637] and NSH [RFC8300].

All these IP-based encapsulations can be updated in one shot by simple reference to RFC 6040. However, it would not be appropriate to update all these protocols from within the present guidance document. Instead a companion specification [I-D.ietf-tsvwg-rfc6040update-shim] has been prepared that has the appropriate standards track status to update standards track protocols. For those that are not under IETF change control [I-D.ietf-tsvwg-rfc6040update-shim] can only recommend that the relevant body updates them.

4.2. Wire Protocol Design: Indication of ECN Support

This section is intended to guide the redesign of any lower layer protocol that encapsulate IP to add native ECN support at the lower layer. It reflects the approaches used in [RFC6040] and in [RFC5129]. Therefore IP-in-IP tunnels or IP-in-MPLS or MPLS-in-MPLS encapsulations that already comply with [RFC6040] or [RFC5129] will already satisfy this guidance.

A lower layer (or subnet) congestion notification system:

1. SHOULD NOT apply explicit congestion notifications to PDUs that are destined for legacy layer-4 transport implementations that will not understand ECN, and

2. SHOULD NOT apply explicit congestion notifications to PDUs if the egress of the subnet might not propagate congestion notifications onward into the higher layer.

We use the term ECN-PDUs for a PDU on a feedback loop that will propagate congestion notification properly because it meets both the above criteria. And a Not-ECN-PDU is a PDU on a feedback loop that does not meet at least one of the criteria, and will therefore not propagate congestion notification properly. A corollary of the above is that a lower layer congestion notification protocol:

3. SHOULD be able to distinguish ECN-PDUs from Not-ECN-PDUs.

Note that there is no need for all interior nodes within a subnet to be able to mark congestion explicitly. A mix of ECN and drop signals from different nodes is fine. However, if any interior nodes might generate ECN markings, guideline 2 above says that all relevant egress node(s) SHOULD be able to propagate those markings up to the higher layer.

In IP, if the ECN field in each PDU is cleared to the Not-ECT (not ECN-capable transport) codepoint, it indicates that the L4 transport will not understand congestion markings. A congested buffer must not mark these Not-ECT PDUs, and therefore has to signal congestion by increasingly applying drop instead.

The mechanism a lower layer uses to distinguish the ECN-capability of PDUs need not mimic that of IP. The above guidelines merely say that the lower layer system, as a whole, should achieve the same outcome. For instance, ECN-capable feedback loops might use PDUs that are identified by a particular set of labels or tags. Alternatively, logical link protocols that use flow state might determine whether a PDU can be congestion marked by checking for ECN-support in the flow state. Other protocols might depend on out-of-band control signals.

The per-domain checking of ECN support in MPLS [RFC5129] is a good example of a way to avoid sending congestion markings to L4 transports that will not understand them, without using any header space in the subnet protocol.

In MPLS, header space is extremely limited, therefore RFC5129 does not provide a field in the MPLS header to indicate whether the PDU is an ECN-PDU or a Not-ECN-PDU. Instead, interior nodes in a domain are allowed to set explicit congestion indications without checking whether the PDU is destined for a L4 transport that will understand them. Nonetheless, this is made safe by requiring that the network operator upgrades all decapsulating edges of a whole domain at once,

as soon as even one switch within the domain is configured to mark rather than drop some PDUs during congestion. Therefore, any edge node that might decapsulate a packet will be capable of checking whether the higher layer transport is ECN-capable. When decapsulating a CE-marked packet, if the decapsulator discovers that the higher layer (inner header) indicates the transport is not ECN-capable, it drops the packet effectively on behalf of the earlier congested node (see Decapsulation Guideline 1 in Section 4.4).

It was only appropriate to define such an incremental deployment strategy because MPLS is targeted solely at professional operators, who can be expected to ensure that a whole subnetwork is consistently configured. This strategy might not be appropriate for other link technologies targeted at zero-configuration deployment or deployment by the general public (e.g. Ethernet). For such 'plug-and-play' environments it will be necessary to invent a failsafe approach that ensures congestion markings will never fall into black holes, no matter how inconsistently a system is put together. Alternatively, congestion notification relying on correct system configuration could be confined to flavours of Ethernet intended only for professional network operators, such as Provider Backbone Bridges (PBB [IEEE802.1Q]; previously 802.1ah).

ECN support in TRILL [I-D.ietf-trill-ecn-support] provides a good example of how to add ECN to a lower layer protocol without relying on careful and consistent operator configuration. TRILL provides an extension header word with space for flags of different categories depending on whether logic to understand the extension is critical. The congestion experienced marking has been defined as a 'critical ingress-to-egress' flag. So if a transit RBridge sets this flag on a frame and an egress RBridge does not have any logic to process it, it will drop it; which is the desired default action anyway. Therefore TRILL RBridges can be updated with support for ECN in no particular order and, at the egress of the TRILL campus, congestion notification will be propagated to IP as ECN whenever ECN logic has been implemented at the egress, or as drop otherwise.

QCN [IEEE802.1Q] is not intended to extend beyond a single subnet, or to interoperate with ECN. Nonetheless, the way QCN indicates to lower layer devices that the end-points will not understand QCN provides another example that a lower layer protocol designer might be able to mimic for their scenario. An operator can define certain Priority Code Points (PCPs [IEEE802.1Q]; previously 802.1p) to indicate non-QCN frames and an ingress bridge is required to map arriving not-QCN-capable IP packets to one of these non-QCN PCPs.

When drop for non-ECN traffic is deferred to the egress of a subnet, it cannot necessarily be assumed that one ECN mark is equivalent to one drop, as was originally required by [RFC3168]. [RFC8311] updated RFC 3168, to allow experimentation with congestion markings that are not equivalent to drop, in particular for L4S [RFC9331]. ECN support in TRILL [I-D.ietf-trill-ecn-support] is a good example of a way to defer drop to the egress of a subnet both when marks are equivalent to drops (as in RFC 3168) and when they are not (as in L4S). The ECN scheme for MPLS [RFC5129] was defined before L4S, so it only currently supports deferred drop that is equivalent to ECN-marking. Nonetheless, in principle, MPLS (and potentially future L2 protocols) could support L4S marking and copy TRILL's approach for determining the drop level of any non-ECN traffic at the subnet egress.

4.3. Encapsulation Guidelines

This section is intended to guide the redesign of any node that encapsulates IP with a lower layer header when adding native ECN support to the lower layer protocol. It reflects the approaches used in [RFC6040] and in [RFC5129]. Therefore IP-in-IP tunnels or IP-in-MPLS or MPLS-in-MPLS encapsulations that already comply with [RFC6040] or [RFC5129] will already satisfy this guidance.

1. Egress Capability Check: A subnet ingress needs to be sure that the corresponding egress of a subnet will propagate any congestion notification added to the outer header across the subnet. This is necessary in addition to checking that an incoming PDU indicates an ECN-capable (L4) transport. Examples of how this guarantee might be provided include:
 - * by configuration (e.g. if any label switches in a domain support ECN marking, [RFC5129] requires all egress nodes to have been configured to propagate ECN)
 - * by the ingress explicitly checking that the egress propagates ECN (e.g. an early attempt to add ECN support to TRILL used IS-IS to check path capabilities before adding ECN extension flags to each frame [RFC7780]).
 - * by inherent design of the protocol (e.g. by encoding ECN marking on the outer header in such a way that a legacy egress that does not understand ECN will consider the PDU corrupt or invalid and discard it, thus at least propagating a form of congestion signal).
2. Egress Fails Capability Check: If the ingress cannot guarantee that the egress will propagate congestion notification, the ingress SHOULD disable ECN at the lower layer when it forwards

the PDU. An example of how the ingress might disable ECN at the lower layer would be by setting the outer header of the PDU to identify it as a Not-ECN-PDU, assuming the subnet technology supports such a concept.

3. Standard Congestion Monitoring Baseline: Once the ingress to a subnet has established that the egress will correctly propagate ECN, on encapsulation it SHOULD encode the same level of congestion in outer headers as is arriving in incoming headers. For example, it might copy any incoming congestion notification into the outer header of the lower layer protocol.

This ensures that bulk congestion monitoring of outer headers (e.g. by a network management node monitoring ECN in passing frames) will measure congestion accumulated along the whole upstream path starting from the Load Regulator not just starting from the ingress of the subnet. A node that is not the Load Regulator SHOULD NOT re-initialize the level of CE markings in the outer to zero.

It would still also be possible to measure congestion introduced across one subnet (or tunnel) by subtracting the level of CE markings on inner headers from that on outer headers (see Appendix C of [RFC6040]). For example:

- * If this guideline has been followed and if the level of CE markings is 0.4% on the outer and 0.1% on the inner, 0.4% congestion has been introduced across all the networks since the load regulator, and 0.3% ($= 0.4\% - 0.1\%$) has been introduced since the ingress to the current subnet (or tunnel);
- * Without this guideline, if the subnet ingress had re-initialized the outer congestion level to zero, the outer and inner would measure 0.1% and 0.3%. It would still be possible to infer that the congestion introduced since the Load Regulator was 0.4% ($= 0.1\% + 0.3\%$). But only if the monitoring system somehow knows whether the subnet ingress re-initialized the congestion level.

As long as subnet and tunnel technologies use the standard congestion monitoring baseline in this guideline, monitoring systems will know to use the former approach, rather than having to "somehow know" which approach to use.

4.4. Decapsulation Guidelines

This section is intended to guide the redesign of any node that decapsulates IP from within a lower layer header when adding native ECN support to the lower layer protocol. It reflects the approaches used in [RFC6040] and in [RFC5129]. Therefore IP-in-IP tunnels or IP-in-MPLS or MPLS-in-MPLS encapsulations that already comply with [RFC6040] or [RFC5129] will already satisfy this guidance.

A subnet egress SHOULD NOT simply copy congestion notification from outer headers to the forwarded header. It SHOULD calculate the outgoing congestion notification field from the inner and outer headers using the following guidelines. If there is any conflict, rules earlier in the list take precedence over rules later in the list:

1. If the arriving inner header is a Not-ECN-PDU it implies the L4 transport will not understand explicit congestion markings.
Then:
 - * If the outer header carries an explicit congestion marking, it is likely that a protocol error has occurred, so drop is the only indication of congestion that the L4 transport will understand. If the congestion marking is the most severe possible, the packet MUST be dropped. However, if congestion can be marked with multiple levels of severity and the packet's marking is not the most severe, this requirement can be relaxed to: the packet SHOULD be dropped.
 - * If the outer is an ECN-PDU that carries no indication of congestion or a Not-ECN-PDU the PDU SHOULD be forwarded, but still as a Not-ECN-PDU.
2. If the outer header does not support explicit congestion notification (a Not-ECN-PDU), but the inner header does (an ECN-PDU), the inner header SHOULD be forwarded unchanged.
3. In some lower layer protocols congestion may be signalled as a numerical level, such as in the control frames of quantized congestion notification (QCN [IEEE802.1Q]). If such a multi-bit encoding encapsulates an ECN-capable IP data packet, a function will be needed to convert the quantized congestion level into the frequency of congestion markings in outgoing IP packets.
4. Congestion indications might be encoded by a severity level. For instance increasing levels of congestion might be encoded by numerically increasing indications, e.g. pre-congestion notification (PCN) can be encoded in each PDU at three severity

levels in IP or MPLS [RFC6660] and the default encapsulation and decapsulation rules [RFC6040] are compatible with this interpretation of the ECN field.

If the arriving inner header is an ECN-PDU, where the inner and outer headers carry indications of congestion of different severity, the more severe indication SHOULD be forwarded in preference to the less severe.

5. The inner and outer headers might carry a combination of congestion notification fields that should not be possible given any currently used protocol transitions. For instance, if Encapsulation Guideline 3 in Section 4.3 had been followed, it should not be possible to have a less severe indication of congestion in the outer than in the inner. It MAY be appropriate to log unexpected combinations of headers and possibly raise an alarm.

If a safe outgoing codepoint can be defined for such a PDU, the PDU SHOULD be forwarded rather than dropped. Some implementers discard PDUs with currently unused combinations of headers just in case they represent an attack. However, an approach using alarms and policy-mediated drop is preferable to hard-coded drop, so that operators can keep track of possible attacks but currently unused combinations are not precluded from future use through new standards actions.

4.5. Sequences of Similar Tunnels or Subnets

In some deployments, particularly in 3GPP networks, an IP packet may traverse two or more IP-in-IP tunnels in sequence that all use identical technology (e.g. GTP).

In such cases, it would be sufficient for every encapsulation and decapsulation in the chain to comply with RFC 6040. Alternatively, as an optimisation, a node that decapsulates a packet and immediately re-encapsulates it for the next tunnel MAY copy the incoming outer ECN field directly to the outgoing outer and the incoming inner ECN field directly to the outgoing inner. Then the overall behavior across the sequence of tunnel segments would still be consistent with RFC 6040.

Appendix C of RFC6040 describes how a tunnel egress can monitor how much congestion has been introduced within a tunnel. A network operator might want to monitor how much congestion had been introduced within a whole sequence of tunnels. Using the technique in Appendix C of RFC6040 at the final egress, the operator could monitor the whole sequence of tunnels, but only if the above

optimisation were used consistently along the sequence of tunnels, in order to make it appear as a single tunnel. Therefore, tunnel endpoint implementations SHOULD allow the operator to configure whether this optimisation is enabled.

When ECN support is added to a subnet technology, consideration SHOULD be given to a similar optimisation between subnets in sequence if they all use the same technology.

4.6. Reframing and Congestion Markings

The guidance in this section is worded in terms of framing boundaries, but it applies equally whether the protocol data units are frames, cells or packets.

Where an AQM marks the ECN field of IP packets as they queue into a layer-2 link, there will be no problem with framing boundaries, because the ECN markings would be applied directly to IP packets. The guidance in this section is only applicable where an ECN capability is being added to a layer-2 protocol so that layer-2 frames can be ECN-marked by an AQM at layer-2. This would only be necessary where AQM will be applied at pure layer-2 nodes (without IP-awareness).

Where ECN marking has had to be applied at non-IP-aware nodes and framing boundaries do not necessarily align with packet boundaries, the decapsulating IP forwarding node SHOULD propagate ECN markings from layer-2 frame headers to IP packets that may have different boundaries as a consequence of reframing.

Two possible design goals for propagating congestion indications, described in Section 5.3 of [RFC3168] and Section 2.4 of [RFC7141], are:

1. approximate preservation of the presence (and therefore timing) of congestion marks on the L2 frames used to construct an IP packet;
 - a. at high frequency of congestion marking, approximate preservation of the proportion of congestion marks arriving and departing;
 - b. at low frequency of congestion marking, approximate preservation of the timing of congestion marks arriving and departing.

In either case, an implementation SHOULD ensure that any new incoming congestion indication is propagated immediately, not held awaiting the possibility of further congestion indications to be sufficient to indicate congestion on an outgoing PDU [RFC7141]. Nonetheless, to facilitate pipelined implementation, it would be acceptable for congestion marks to propagate to a slightly later IP packet.

At decapsulation in either case:

- * ECN marking propagation logically occurs before application of Decapsulation Guideline 1 in Section 4.4. For instance, if ECN marking propagation would cause an ECN congestion indication to be applied to an IP packet that is a Not-ECN-PDU, then that IP packet is dropped in accordance with Guideline 1;
- * where a mix of ECN-PDUs and non-ECN-PDUs arrives to construct the same IP packet, the decapsulation spec SHOULD require that packet to be discarded.
- * where a mix of different types of ECN-PDUs arrives to construct the same IP packet, e.g. a mix of frames that map to ECT(0) and ECT(1) IP packets, the decapsulation spec might consider this a protocol error. But, if the lower layer protocol has defined such a mix of types of ECN-PDU as valid, it SHOULD require the resulting IP packet to be set to either ECT(0) or ECT(1). In this case, it SHOULD take into account that the RFC series has so far allowed ECT(0) and ECT(1) to be considered equivalent [RFC3168], or ECT(1) can provide a less severe congestion marking than CE [RFC6040], or ECT(1) can indicate an unmarked but ECN-capable packet that is subject to a different marking algorithm to ECT(0) packets, for example L4S [RFC8311] [RFC9331].

The following are two ways that goal 1 might be achieved, but they are not intended to be the only ways:

- * Every IP PDU that is constructed, in whole or in part, from an L2 frame that is marked with a congestion signal, has that signal propagated to it;
- * Every L2 frame that is marked with a congestion signal, propagates that signal to one IP PDU which is constructed, in whole or in part, from it. If multiple IP PDUs meet this description, the choice can be made arbitrarily but ought to be consistent.

The following gives one way that goal 2 might be achieved, but it is not intended to be the only way:

- * For each of the streams of frames that encapsulate the IP packets of each IP-ECN codepoint and follow the same path through the subnet, a counter ('in') tracks octets arriving within the payload of marked L2 frames and another ('out') tracks octets departing in marked IP packets. While 'in' exceeds 'out', forwarded IP packets are ECN-marked. If 'out' exceeds 'in' for longer than a timeout, both counters are zeroed, to ensure that the start of the next congestion episode propagates immediately. The 'out' counter includes octets in reconstructed IP packets that would have been marked, but had to be dropped because they were Not-ECN-PDUs (by Decapsulation Guideline 1 in Section 4.4).

Generally, the number of L2 frames may be higher (e.g. ATM), similar to, or lower (e.g. 802.11 aggregation at a L2-only station) than the number of IP PDUs, and this distinction may influence the choice of mechanism.

5. Feed-Up-and-Forward Mode: Guidelines for Adding Congestion Notification

The guidance in this section is applicable, for example, when IP packets:

- * are encapsulated in Ethernet headers, which have no support for ECN;
- * are forwarded by the eNode-B (base station) of a 3GPP radio access network, which is required to apply ECN marking during congestion, [LTE-RA], [UTRAN], but the Packet Data Convergence Protocol (PDCP) that encapsulates the IP header over the radio access has no support for ECN.

This guidance also generalizes to encapsulation by other subnet technologies with no native support for explicit congestion notification at the lower layer, but with support for finding and processing an IP header. It is unlikely to be applicable or necessary for IP-in-IP encapsulation, where feed-forward-and-up mode based on [RFC6040] would be more appropriate.

Marking the IP header while switching at layer-2 (by using a layer-3 switch) or while forwarding in a radio access network seems to represent a layering violation. However, it can be considered as a benign optimisation if the guidelines below are followed. Feed-up-and-forward is certainly not a general alternative to implementing feed-forward congestion notification in the lower layer, because:

- * IPv4 and IPv6 are not the only layer-3 protocols that might be encapsulated by lower layer protocols

- * Link-layer encryption might be in use, making the layer-2 payload inaccessible
- * Many Ethernet switches do not have 'layer-3 switch' capabilities so they cannot read or modify an IP payload
- * It might be costly to find an IP header (IPv4 or IPv6) when it may be encapsulated by more than one lower layer header, e.g. Ethernet MAC in MAC ([IEEE802.1Q]; previously 802.1ah).

Nonetheless, configuring lower layer equipment to look for an ECN field in an encapsulated IP header is a useful optimisation. If the implementation follows the guidelines below, this optimisation does not have to be confined to a controlled environment such as within a data centre; it could usefully be applied on any network even if the operator is not sure whether the above issues will never apply:

1. If a native lower-layer congestion notification mechanism exists for a subnet technology, it is safe to mix feed-up-and-forward with feed-forward-and-up on other switches in the same subnet. However, it will generally be more efficient to use the native mechanism.
 2. The depth of the search for an IP header SHOULD be limited. If an IP header is not found soon enough, or an unrecognized or unreadable header is encountered, the switch SHOULD resort to an alternative means of signalling congestion (e.g. drop, or the native lower layer mechanism if available).
 3. It is sufficient to use the first IP header found in the stack; the egress of the relevant tunnel can propagate congestion notification upwards to any more deeply encapsulated IP headers later.
6. Feed-Backward Mode: Guidelines for Adding Congestion Notification

It can be seen from Section 3.3 that congestion notification in a subnet using feed-backward mode has generally not been designed to be directly coupled with IP layer congestion notification. The subnet attempts to minimize congestion internally, and if the incoming load at the ingress exceeds the capacity somewhere through the subnet, the layer 3 buffer into the ingress backs up. Thus, a feed-backward mode subnet is in some sense similar to a null mode subnet, in that there is no need for any direct interaction between the subnet and higher layer congestion notification. Therefore no detailed protocol design guidelines are appropriate. Nonetheless, a more general guideline is appropriate:

A subnetwork technology intended to eventually interface to IP SHOULD NOT be designed using only the feed-backward mode, which is certainly best for a stand-alone subnet, but would need to be modified to work efficiently as part of the wider Internet, because IP uses feed-forward-and-up mode.

The feed-backward approach at least works beneath IP, where the term 'works' is used only in a narrow functional sense because feed-backward can result in very inefficient and sluggish congestion control except if it is confined to the subnet directly connected to the original data source, when it is faster than feed-forward. It would be valid to design a protocol that could work in feed-backward mode for paths that only cross one subnet, and in feed-forward-and-up mode for paths that cross subnets.

In the early days of TCP/IP, a similar feed-backward approach was tried for explicit congestion signalling, using source-quench (SQ) ICMP control packets. However, SQ fell out of favour and is now formally deprecated [RFC6633]. The main problem was that it is hard for a data source to tell the difference between a spoofed SQ message and a quench request from a genuine buffer on the path. It is also hard for a lower layer buffer to address an SQ message to the original source port number, which may be buried within many layers of headers, and possibly encrypted.

QCN (also known as backward congestion notification, BCN; see Sections 3033 of [IEEE802.1Q]; previously known as 802.1Qau) uses a feed-backward mode structurally similar to ATM's relative rate mechanism. However, QCN confines its applicability to scenarios such as some data centres where all endpoints are directly attached by the same Ethernet technology. If a QCN subnet were later connected into a wider IP-based internetwork (e.g. when attempting to interconnect multiple data centres) it would suffer the inefficiency shown in Figure 3.

7. IANA Considerations

This section is to be removed before publishing as an RFC.

This memo includes no request to IANA.

8. Security Considerations

If a lower layer wire protocol is redesigned to include explicit congestion signalling in-band in the protocol header, care SHOULD be taken to ensure that the field used is specified as mutable during transit. Otherwise interior nodes signalling congestion would invalidate any authentication protocol applied to the lower layer header by altering a header field that had been assumed as immutable.

The redesign of protocols that encapsulate IP in order to propagate congestion signals between layers raises potential signal integrity concerns. Experimental or proposed approaches exist for assuring the end-to-end integrity of in-band congestion signals, e.g.:

- * Congestion exposure (ConEx) for networks to audit that their congestion signals are not being suppressed by other networks or by receivers, and for networks to police that senders are responding sufficiently to the signals, irrespective of the L4 transport protocol used [RFC7713].
- * A test for a sender to detect whether a network or the receiver is suppressing congestion signals (for example see 2nd para of Section 20.2 of [RFC3168]).

Given these end-to-end approaches are already being specified, it would make little sense to attempt to design hop-by-hop congestion signal integrity into a new lower layer protocol, because end-to-end integrity inherently achieves hop-by-hop integrity.

Section 6 gives vulnerability to spoofing as one of the reasons for deprecating feed-backward mode.

9. Conclusions

Following the guidance in this document enables ECN support to be extended consistently to numerous protocols that encapsulate IP (IPv4 and IPv6), so that IP continues to fulfil its role as an end-to-end interoperability layer. This includes:

- * A wide range of tunnelling protocols including those with various forms of shim header between two IP headers, possibly also separated by a L2 header;
- * A wide range of subnet technologies, particularly those that work in the same 'feed-forward-and-up' mode that is used to support ECN in IP and MPLS.

Guidelines have been defined for supporting propagation of ECN between Ethernet and IP on so-called Layer-3 Ethernet switches, using a 'feed-up-and-forward' mode. This approach could enable other subnet technologies to pass ECN signals into the IP layer, even if they do not support ECN natively.

Finally, attempting to add ECN to a subnet technology in feed-backward mode is deprecated except in special cases, due to its likely sluggish response to congestion.

10. References

10.1. Normative References

- [I-D.ietf-trill-ecn-support]
Eastlake, D. E. and B. Briscoe, "TRILL (TRansparent Interconnection of Lots of Links): ECN (Explicit Congestion Notification) Support", Work in Progress, Internet-Draft, draft-ietf-trill-ecn-support-07, 25 February 2018, <<https://datatracker.ietf.org/doc/html/draft-ietf-trill-ecn-support-07>>.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC3168] Ramakrishnan, K., Floyd, S., and D. Black, "The Addition of Explicit Congestion Notification (ECN) to IP", RFC 3168, DOI 10.17487/RFC3168, September 2001, <<https://www.rfc-editor.org/info/rfc3168>>.
- [RFC3819] Karn, P., Ed., Bormann, C., Fairhurst, G., Grossman, D., Ludwig, R., Mahdavi, J., Montenegro, G., Touch, J., and L. Wood, "Advice for Internet Subnetwork Designers", BCP 89, RFC 3819, DOI 10.17487/RFC3819, July 2004, <<https://www.rfc-editor.org/info/rfc3819>>.
- [RFC4774] Floyd, S., "Specifying Alternate Semantics for the Explicit Congestion Notification (ECN) Field", BCP 124, RFC 4774, DOI 10.17487/RFC4774, November 2006, <<https://www.rfc-editor.org/info/rfc4774>>.
- [RFC5129] Davie, B., Briscoe, B., and J. Tay, "Explicit Congestion Marking in MPLS", RFC 5129, DOI 10.17487/RFC5129, January 2008, <<https://www.rfc-editor.org/info/rfc5129>>.

- [RFC6040] Briscoe, B., "Tunnelling of Explicit Congestion Notification", RFC 6040, DOI 10.17487/RFC6040, November 2010, <<https://www.rfc-editor.org/info/rfc6040>>.
- [RFC7141] Briscoe, B. and J. Manner, "Byte and Packet Congestion Notification", BCP 41, RFC 7141, DOI 10.17487/RFC7141, February 2014, <<https://www.rfc-editor.org/info/rfc7141>>.

10.2. Informative References

- [ATM-TM-ABR] Cisco, "Understanding the Available Bit Rate (ABR) Service Category for ATM VCs", Design Technote 10415, 5 June 2005, <<https://www.cisco.com/c/en/us/support/docs/asynchronous-transfer-mode-atm/atm-traffic-management/10415-atmabr.html>>.
- [Buck00] Buckwalter, J.T., "Frame Relay: Technology and Practice", Pub. Addison Wesley ISBN-13: 978-0201485240, 2000.
- [Clos53] Clos, C., "A Study of Non-Blocking Switching Networks", Bell Systems Technical Journal 32(2):406424, March 1953.
- [GTPv1] 3GPP, "GPRS Tunnelling Protocol (GTP) across the Gn and Gp interface", Technical Specification TS 29.060.
- [GTPv1-U] 3GPP, "General Packet Radio System (GPRS) Tunnelling Protocol User Plane (GTPv1-U)", Technical Specification TS 29.281.
- [GTPv2-C] 3GPP, "Evolved General Packet Radio Service (GPRS) Tunnelling Protocol for Control plane (GTPv2-C)", Technical Specification TS 29.274.
- [I-D.ietf-intarea-gue] Herbert, T., Yong, L., and O. Zia, "Generic UDP Encapsulation", Work in Progress, Internet-Draft, draft-ietf-intarea-gue-09, 26 October 2019, <<https://datatracker.ietf.org/doc/html/draft-ietf-intarea-gue-09>>.
- [I-D.ietf-tsvwg-rfc6040update-shim] Briscoe, B., "Propagating Explicit Congestion Notification Across IP Tunnel Headers Separated by a Shim", Work in Progress, Internet-Draft, draft-ietf-tsvwg-rfc6040update-shim-22, 29 October 2023, <<https://datatracker.ietf.org/doc/html/draft-ietf-tsvwg-rfc6040update-shim-22>>.

- [IEEE802.1Q] IEEE, "IEEE Standard for Local and Metropolitan Area Networks Virtual Bridged Local Area Networks Amendment 6: Provider Backbone Bridges", IEEE Std 802.1Q-2018, July 2018, <<https://ieeexplore.ieee.org/document/8403927>>.
- [ITU-T.I.371] ITU-T, "Traffic Control and Congestion Control in B-ISDN", ITU-T Rec. I.371 (03/04), March 2004, <<https://www.itu.int/rec/T-REC-I.371>>.
- [Leiserson85] Leiserson, C.E., "Fat-trees: universal networks for hardware-efficient supercomputing", IEEE Transactions on Computers 34(10):892901, October 1985.
- [LTE-RA] 3GPP, "Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Universal Terrestrial Radio Access Network (E-UTRAN); Overall description; Stage 2", Technical Specification TS 36.300.
- [RFC2003] Perkins, C., "IP Encapsulation within IP", RFC 2003, DOI 10.17487/RFC2003, October 1996, <<https://www.rfc-editor.org/info/rfc2003>>.
- [RFC2473] Conta, A. and S. Deering, "Generic Packet Tunneling in IPv6 Specification", RFC 2473, DOI 10.17487/RFC2473, December 1998, <<https://www.rfc-editor.org/info/rfc2473>>.
- [RFC2637] Hamzeh, K., Pall, G., Verthein, W., Taarud, J., Little, W., and G. Zorn, "Point-to-Point Tunneling Protocol (PPTP)", RFC 2637, DOI 10.17487/RFC2637, July 1999, <<https://www.rfc-editor.org/info/rfc2637>>.
- [RFC2661] Townsley, W., Valencia, A., Rubens, A., Pall, G., Zorn, G., and B. Palter, "Layer Two Tunneling Protocol "L2TP"", RFC 2661, DOI 10.17487/RFC2661, August 1999, <<https://www.rfc-editor.org/info/rfc2661>>.
- [RFC2784] Farinacci, D., Li, T., Hanks, S., Meyer, D., and P. Traina, "Generic Routing Encapsulation (GRE)", RFC 2784, DOI 10.17487/RFC2784, March 2000, <<https://www.rfc-editor.org/info/rfc2784>>.
- [RFC2884] Hadi Salim, J. and U. Ahmed, "Performance Evaluation of Explicit Congestion Notification (ECN) in IP Networks", RFC 2884, DOI 10.17487/RFC2884, July 2000, <<https://www.rfc-editor.org/info/rfc2884>>.

- [RFC2983] Black, D., "Differentiated Services and Tunnels", RFC 2983, DOI 10.17487/RFC2983, October 2000, <<https://www.rfc-editor.org/info/rfc2983>>.
- [RFC3931] Lau, J., Ed., Townsley, M., Ed., and I. Goyret, Ed., "Layer Two Tunneling Protocol - Version 3 (L2TPv3)", RFC 3931, DOI 10.17487/RFC3931, March 2005, <<https://www.rfc-editor.org/info/rfc3931>>.
- [RFC4301] Kent, S. and K. Seo, "Security Architecture for the Internet Protocol", RFC 4301, DOI 10.17487/RFC4301, December 2005, <<https://www.rfc-editor.org/info/rfc4301>>.
- [RFC4380] Huitema, C., "Teredo: Tunneling IPv6 over UDP through Network Address Translations (NATs)", RFC 4380, DOI 10.17487/RFC4380, February 2006, <<https://www.rfc-editor.org/info/rfc4380>>.
- [RFC5415] Calhoun, P., Ed., Montemurro, M., Ed., and D. Stanley, Ed., "Control And Provisioning of Wireless Access Points (CAPWAP) Protocol Specification", RFC 5415, DOI 10.17487/RFC5415, March 2009, <<https://www.rfc-editor.org/info/rfc5415>>.
- [RFC6633] Gont, F., "Deprecation of ICMP Source Quench Messages", RFC 6633, DOI 10.17487/RFC6633, May 2012, <<https://www.rfc-editor.org/info/rfc6633>>.
- [RFC6660] Briscoe, B., Moncaster, T., and M. Menth, "Encoding Three Pre-Congestion Notification (PCN) States in the IP Header Using a Single Diffserv Codepoint (DSCP)", RFC 6660, DOI 10.17487/RFC6660, July 2012, <<https://www.rfc-editor.org/info/rfc6660>>.
- [RFC7323] Borman, D., Braden, B., Jacobson, V., and R. Scheffenegger, Ed., "TCP Extensions for High Performance", RFC 7323, DOI 10.17487/RFC7323, September 2014, <<https://www.rfc-editor.org/info/rfc7323>>.
- [RFC7348] Mahalingam, M., Dutt, D., Duda, K., Agarwal, P., Kreeger, L., Sridhar, T., Bursell, M., and C. Wright, "Virtual eXtensible Local Area Network (VXLAN): A Framework for Overlaying Virtualized Layer 2 Networks over Layer 3 Networks", RFC 7348, DOI 10.17487/RFC7348, August 2014, <<https://www.rfc-editor.org/info/rfc7348>>.

- [RFC7567] Baker, F., Ed. and G. Fairhurst, Ed., "IETF Recommendations Regarding Active Queue Management", BCP 197, RFC 7567, DOI 10.17487/RFC7567, July 2015, <<https://www.rfc-editor.org/info/rfc7567>>.
- [RFC7637] Garg, P., Ed. and Y. Wang, Ed., "NVGRE: Network Virtualization Using Generic Routing Encapsulation", RFC 7637, DOI 10.17487/RFC7637, September 2015, <<https://www.rfc-editor.org/info/rfc7637>>.
- [RFC7713] Mathis, M. and B. Briscoe, "Congestion Exposure (ConEx) Concepts, Abstract Mechanism, and Requirements", RFC 7713, DOI 10.17487/RFC7713, December 2015, <<https://www.rfc-editor.org/info/rfc7713>>.
- [RFC7780] Eastlake 3rd, D., Zhang, M., Perlman, R., Banerjee, A., Ghanwani, A., and S. Gupta, "Transparent Interconnection of Lots of Links (TRILL): Clarifications, Corrections, and Updates", RFC 7780, DOI 10.17487/RFC7780, February 2016, <<https://www.rfc-editor.org/info/rfc7780>>.
- [RFC8084] Fairhurst, G., "Network Transport Circuit Breakers", BCP 208, RFC 8084, DOI 10.17487/RFC8084, March 2017, <<https://www.rfc-editor.org/info/rfc8084>>.
- [RFC8087] Fairhurst, G. and M. Welzl, "The Benefits of Using Explicit Congestion Notification (ECN)", RFC 8087, DOI 10.17487/RFC8087, March 2017, <<https://www.rfc-editor.org/info/rfc8087>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8257] Bensley, S., Thaler, D., Balasubramanian, P., Eggert, L., and G. Judd, "Data Center TCP (DCTCP): TCP Congestion Control for Data Centers", RFC 8257, DOI 10.17487/RFC8257, October 2017, <<https://www.rfc-editor.org/info/rfc8257>>.
- [RFC8300] Quinn, P., Ed., Elzur, U., Ed., and C. Pignataro, Ed., "Network Service Header (NSH)", RFC 8300, DOI 10.17487/RFC8300, January 2018, <<https://www.rfc-editor.org/info/rfc8300>>.
- [RFC8311] Black, D., "Relaxing Restrictions on Explicit Congestion Notification (ECN) Experimentation", RFC 8311, DOI 10.17487/RFC8311, January 2018, <<https://www.rfc-editor.org/info/rfc8311>>.

- [RFC8926] Gross, J., Ed., Ganga, I., Ed., and T. Sridhar, Ed., "Geneve: Generic Network Virtualization Encapsulation", RFC 8926, DOI 10.17487/RFC8926, November 2020, <<https://www.rfc-editor.org/info/rfc8926>>.
- [RFC9300] Farinacci, D., Fuller, V., Meyer, D., Lewis, D., and A. Cabellos, Ed., "The Locator/ID Separation Protocol (LISP)", RFC 9300, DOI 10.17487/RFC9300, October 2022, <<https://www.rfc-editor.org/info/rfc9300>>.
- [RFC9331] De Schepper, K. and B. Briscoe, Ed., "The Explicit Congestion Notification (ECN) Protocol for Low Latency, Low Loss, and Scalable Throughput (L4S)", RFC 9331, DOI 10.17487/RFC9331, January 2023, <<https://www.rfc-editor.org/info/rfc9331>>.
- [UTRAN] 3GPP, "UTRAN Overall Description", Technical Specification TS 25.401.

Comments Solicited

This section is to be removed before publishing as an RFC.

Comments and questions are encouraged and very welcome. They can be addressed to the IETF Transport Area working group mailing list <tswwg@ietf.org>, and/or to the authors.

Acknowledgements

Thanks to Gorry Fairhurst and David Black for extensive reviews. Thanks also to the following reviewers: Joe Touch, Andrew McGregor, Richard Scheffenegger, Ingemar Johansson, Piers O'Hanlon, Donald Eastlake, Jonathan Morton, Markku Kojo, Sebastian Möller, Martin Duke and Michael Welzl, who pointed out that lower layer congestion notification signals may have different semantics to those in IP. Thanks are also due to the tsvwg chairs, TSV ADs and IETF liaison people such as Eric Gray, Dan Romascanu and Gonzalo Camarillo for helping with the liaisons with the IEEE and 3GPP. And thanks to Georg Mayer and particularly to Erik Guttman for the extensive search and categorisation of any 3GPP specifications that cite ECN specifications. Thanks also to the Area Reviewers Dan Harkins, Paul Kyzivat, Sue Hares and Dale Worley.

Bob Briscoe was part-funded by the European Community under its Seventh Framework Programme through the Trilogy project (ICT-216372) for initial drafts then through the Reducing Internet Transport Latency (RITE) project (ICT-317700), and for final drafts (from -18) he was funded by Apple Inc. The views expressed here are solely those of the authors.

Contributors

Pat Thaler
Broadcom Corporation (retired)
CA
USA

Pat was a co-author of this draft, but retired before its publication.

Authors' Addresses

Bob Briscoe
Independent
United Kingdom
Email: ietf@bobbriscoe.net
URI: <https://bobbriscoe.net/>

John Kaippallimalil
Futurewei
5700 Tennyson Parkway, Suite 600
Plano, Texas 75024
United States of America
Email: kjohn@futurewei.com