

BFD in Demand Mode over Point-to-Point MPLS LSP

draft-mirsky-bfd-mpls-demand

Greg Mirsky


IETF-100 November 2017, Singapore

BFD Demand mode

- RFC 5880 defined BFD Demand mode
- BFD node controls mode of its peer, i.e. the BFD node MAY switch its peer into and out of the Demand mode
- To verify bi-directional continuity the node in Demand mode MAY initiate Poll sequence by simply setting Poll (P) bit in BFD control messages sent periodically to its peer
- BFD node

Theory of operation

- Ingress LER A bootstraps the BFD session to LER B using LSP Ping
- BFD session between A and B in Async mode reaches Up state
- BFD node A switches mode to Demand using Poll sequence
- Node B ceases transmission of periodic BFD packets
- Node B detects failure
 - Node B initiates Poll sequence with Diagnostic code set to Control Detection Time Expired
 - Because Node A received failure notification from the node B (RDI) it sends BFD control packet with Final bit set over IP network as following:
 - destination IP address MUST be set to the destination IP address of the LSP Ping Echo request message
 - destination UDP port set to 4784
 - Final (F) flag in BFD control packet MUST be set
 - Demand (D) flag in BFD control packet MUST be cleared
 - Node A moves BFD session state to Down
 - Node A switches the BFD session to Async mode
 - Node A transmits BFD control packets periodically at slow rate



Next steps

- Your comments, suggestions, questions always welcome and greatly appreciated
- WG adoption