IRTF - NFVRG

Rethinking NFV: Supporting Efficient Packet Processing



IETF 100 Singapore November 11-17, 2017 Eduardo Jacob <Eduardo.Jacob@ehu.eus>






CAMPUS OF INTERNATIONAL EXCELLENCE

Agenda

- NFV as we know it.
- Evolution of the technology
- ETSI POC #43
- Limitations
- Some pointers to solution?




- University of the Basque Country
 - Public University of the Basque Country Autonomous Region (Spain) with about 4.500 teachers, 45.000 students and lectures in 112 degree courses in 83 topics.
 - Distributed University: 3 campuses in three provinces.
 - The research group belongs to the Department of Communications Engineering (90 people, 38% full time researchers) and is located in the Faculty of Engineering of Bilbao.
 - The department is running several EU H2020 research projects.



Eduardo Jacob IETF 100 – IRTF – NFVRG




- NFV: Network Function Virtualization
 - Replacing dedicated equipment by commodity computing hardware (originally x86)




- This meant going to cloud technologies
 - Hypervisors
 - Manipulating packets in user space
- Originally network was static
 - Later it could "configured" or defined as needed (SDN, in broad sense)




NFV Management and Orchestration



Eduardo Jacob IETF 100 - IRTF - NFVRG






- Packet processing implies having a compute node
 - Generic packet processing in any point of the network is not possible.



- Can we get a more efficient packet processing?
- In classic NFV approach
 - Compute node treats the packet
 - Network Element (Switch) reroutes packets





- There are two competing approaches targeting a more efficient packet processing.
 - General purpose CPU process
 - Enhanced dataplanes.

With the added complications ofdataplanes implemented in general purpose CPUs...

• Some (old?) ideas

	Price/port	Environmen- tal tolerance	Features Adaptability	Backplane bandwidth	Processing Speed
Computing boxes		1	†††	1	Ť
Switches	1	111	1		***





- Processing on the dataplane (an overview...)
- OF based stateless processing (not considering meters, group ports...)
 - ASIC manufactured for third party switch manufacturers:
 - I.e.: Broadcom Trident II
 - Similar features on switches
 - Vendor specific ASICs
 - I.e.: Aruba Provision
 - Specific features (custom pipelines)
 - NPU based
 - I.e.: Noviflow
 - FPGA based
 - I.e: Corsa
 - X86 based dataplane
 - I.e.: xdpd, Openvswitch, cpqd switch
 - •

- Stateful processing (with different approaches)
 - OpenState[1] mealy finite state machines (FSM)
 - OpenPacket[2] extended finite state machines (XFSM)
 - FAST (Flow-level State Transitions [3]

– P4 [4]

Many of these are in research or experimental status

- [1] https://qmonnet.github.io/whirl-offload/2016/07/17/openstate-stateful-packet-processing/
- [2] https://qmonnet.github.io/whirl-offload/2016/11/09/open-packet-processor/
- [3] M. Moshref, A. Bhargava, A. Gupta, M. Yu, and R. Govindan, "Flow-level state transition as a new switch primitive for SDN," in 3rd workshop on Hot topics in software defined networking,
- [4] https://p4.org






- Packet processing on the computing node (an overview...)
- Processing is done with x86 code.
- Stateful processing.
- Concept of execution environment shrinking to improve processing speed, boot/setup time...
 - Hypervisor + VM
 - I.e.: XEN, VMware
 - Containers
 - Docker, LXC, LXD
 - Unikernels
 - ClicOS[5], Mirage [6]
 - [5] http://cnp.neclab.eu/projects/clickos/
 - [6] https://mirage.io
 - [7] https://www.iovisor.org/technology/xdp
 - [8] https://github.com/luigirizzo/netmap
 - [9] https://github.com/snabbco/snabb


- Low level packet processing improvements
 - Mostly based on bypassing operating system's TCP/IP stack.
 - Many integrate in other tools like
 OpenStack
 - In kernel processing
 - XDP[7] (eXpress Data Path)
 - User space
 - NetMAP[8]
 - DPDK
 - Snabb[9]
 - CPU evolution?
 - Over speed/cores...
 - Hybrid approaches
 - Intel CPU+FPGA
 - Not clear if this usable at packet processing applications: DataCenter.

Eduardo Jacob IETF 100 - IRTF - NFVRG

Rethinking NFV

- Conclusions
 - Boundaries between computer and switch are no longer equivalent to data and packet management ability.
 - A more subtle difference involves "state"
 - Traditional switches are stateless
 - Some new players involve stateful solutions (on both silicon and soft switches)
 - There are champions on each specialty
 - Classical VNF are the kings of stateful processing
 - Full x86 code support and (much) memory.
 - Classical switches are queens of stateless processing.
 - OpenFlow switches could be considered 1st class players in stateless processing..
 - Is there a place for an Hybrid VNF?
 - Combined processing in a general purpose CPU and in the switch?






- Why should we care?
 - There is place for improving current architectures
 - Let's see ETSI POC #43: Towards an efficient Data Plane processing



- This started some years ago...
- SDN-Enabled NFV concept

(now it would have another name)




[10] "Toward an SDN-enabled NFV architecture" IEEE Communications Magazine (April 2015)






 Use case VNF: FlowNAC, a Flow aware Network Access Control





- ETSI PoC#43 Towards an efficient Data Plane processing.
 - Telefonica, HPE, Keynetic, UPV/EHU
 - Demonstrating the improvements this approach can show.
 - FlowNAC demostrated with OSM in
 - Bilbao: ETSI NFV#17/OSM MR#2
 - Paris: MPLS+SDN+NFV World Congress 2017



Eduardo Jacob IETF 100 - IRTF - NFVRG




- ETSI PoC#43 Towards an efficient Data Plane processing.
 - Three scenarios tested and compared:





- ETSI PoC#43 Towards an efficient Data Plane processing.
 - Three scenarios tested and compared:




Classical VM based processing

Mgmt



- ETSI PoC#43 Towards an efficient Data Plane processing.
 - Three scenarios tested and compared:




Classical VM with EPA

Mgmt




- ETSI PoC#43 Towards an efficient Data Plane processing.
 - Three scenarios tested and compared:

Stateless Processing offloaded to OF Switch





 ETSI PoC#43 Towards an efficient Data Plane processing.



The traffic doesn't leave the data plane.

- Enforcing done at full switch speed.
- The control channel is almost no used: less that 5kb per re/ authentication.
- This means that the control function can get topologically decoupled from the enforcing point.
- The policy can be enforced in any switch.
- A core is freed.


POC #43 Report

Comparison of resource usage in the three scenarios





- A "split" VNF (or a VNF with two VNFC)
 - But one of them on a switch)




Eduardo Jacob IETF 100 - IRTF - NFVRG



- Limitations
 - The NFV+SDN equation is usually written as:

NFV + SDN

- SDN was incorporated later.
- The network was not considered to be handled by the Network Service (user)
- Delegating control of part of the network equipment is not easy (not only technically, but also administrative, ie OF instance)



Rethinking NFV

- Limitations (II)
 - Network tends to reorganize: self-healing... supposing packets are not processed: You enter the "placement" game in a delay bounded playground (good luck)
 - VNFD (VNF descriptor) and NSD (NS descriptor) do not contemplate processing outside the computing node.
 - There are too many options/formats/descriptions for packet processing operation (there is no "x86 machine" - like code to describe it, well there could be some): It's not about discussing the format (VM/Container/Unikernel...) in which code is delivered.






- Pointers to a solution? (not a closed list)
 - Rewrite the equation as NFV+SDN.
 - Consider the network really part of the software involved in the NS provisioning
 - You could get tunneling or cyphering as part of the link description and have it provisioned on any network node.
 - You could ease the deployment of advanced slicing mechanisms.
 - A NS should be able to ask for a network connection that could include properties like VLAN translation, tunneling, cyphering or resilience and let the SDN controller take care of it.
 - Network equipment should be able to "virtualize" its resources and delegate control to third parties.
 - Consider recursivity.
 - It's more than an EPA (Enhanced Platform Awareness) issue over a special HW.
 - Get some coffee...



Virtualization and Slicing Security aspects








Virtualization and Slicing Security aspects

To Finish

Research






Virtualization and Slicing Security aspects


To Finish

Research



Let's hope not!!!









CAMPUS OF INTERNATIONAL EXCELLENCE

www.ehu.es