

SIP PUSH

draft-holmberg-sipcore-sip-push
IETF#100 Singapore

Christer Holmberg
christer.holmberg@ericsson.com

WHAT IS THIS?

- NOT A PUSH NOTIFICATION MECHANISM USING SIP MESSAGES
- A MECHANISM FOR TRANSPORTING PUSH NOTIFICATION PARAMETERS BETWEEN A PUSH SUBSCRIBER AND A PUSH NOTIFIER USING SIP, FOR USAGE WITH EXISTING PUSH NOTIFICATION SERVICES
 - Apple Push Notification service, Firebase Cloud Messaging, RFC 8030-based services, etc...


WHAT'S THE PROBLEM?




PROBLEM IN A NUTSHELL

- VoIP apps in iOS have been using background mode (aka legacy VoIP architecture), that allowed them to wake up periodically for receiving events (e.g., SIP INVITE request) from the network
 - This was replaced by the PushKit architecture in iOS 8
 - Apple has deprecated support for legacy VoIP architecture in iOS9 (built with Xcode 7)
 - Apple has removed the support for legacy VoIP architecture in iOS10 (built with Xcode 8)
- Apple forces VoIP apps to take PushKit architecture in to use with Xcode 8
 - VoIP Apps needs to add support for the PushKit
 - Network needs to wake up the client for events via Apple Push Notification Service (APNs)
- Official note from Apple:
 - https://developer.apple.com/library/content/qa/qa1938/_index.html#//apple_ref/doc/uid/DTS40017564
- Android does not currently require, but recommends, usage of push notifications for waking up applications

ARCHITECTURE



SCOPE



THE SIP

- 4 new SIP-URI parameters
 - **pn-prid**
 - Carries the PRID value
 - **pn-type**
 - Carries value (pns-provider) identifying the push notification service
 - Carries service-specific parameters (pns-param)
 - **pn-encode & pn-enckey**
 - Allows usage of draft-ietf-webpush-encryption for push payload e2e (publisher-subscriber) encryption
- **New IANA sub-registry**
 - Registering pns-provider values
 - Draft registers values for APNs and FCM

THE EXAMPLES

SIP REGISTER: UA -> PROXY -> REGISTRAR

REGISTER sip:alice@example.com SIP/2.0
Via: SIP/2.0/UDP alicemobile.example.com:5060;branch=z9hG4bKnashds7
Max-Forwards: 70
To: Alice <sip:alice@example.com>
From: Alice <sip:alice@example.com>;tag=456248
Call-ID: 843817637684230@998sdasdh09
CSeq: 1826 REGISTER
Contact: <sip:alice@alicemobile.example.com;pn-type=acme:acme-param;pn-brid=ZTY4ZDJIMzODE1NmUgKi0K>
Expires: 7200
Content-Length: 0

SIP INVITE: REGISTRAR -> PROXY -> UA

INVITE sip:alice@alicemobile.example.com;pn-type=acme:acme-param;pn-brid=ZTY4ZDJIMzODE1NmUgKi0K SIP/2.0
Via: SIP/2.0/UDP registrar.example.com:5060;branch=z9hG4bKnaxhds8
Max-Forwards: 70
To: Alice <sip:alice@example.com>
From: Bob <sip:bob@example.com>;tag=556859
Call-ID: 5454854854954@998sdaXdh12
CSeq: 101 INVITE
Contact: <sip:bob@bobmobile.example.com>

<SDP>

WHO NEEDS THIS?

- Operators need a solution now, and are looking for solutions as we speak
- Different ideas for proprietary (non-interoperable) solutions floating around
- Preference for a standardized solution if available

SO, WHAT'S NEXT?

- Add SIP PUSH to the SIPCORE charter
- Adopt draft-holmberg-sipcore-sip-push as the base for the charter delivery



THANK YOU!