

Network Working Group  
Internet-Draft  
Intended status: Informational  
Expires: December 30, 2018

C. Li  
C. Xie  
China Telecom  
R. Kumar  
R. Lohiya  
Juniper Networks  
G. Fioccola  
Telecom Italia  
W. Xu  
W. Liu  
Huawei Technologies  
D. Ma  
ZDNS  
J. Bi  
Tsinghua University  
June 28, 2018

Coordinated Address Space Management architecture  
draft-li-opsawg-address-pool-management-arch-01

Abstract

IP addresses work as a basic element for providing broadband network services. However, the increase in number, diversity and complexity of modern network devices and services creates unprecedented challenges for the currently prevailing approach of manual IP address management. Manually maintaining IP addresses could always be sub-optimal for IP resource utilization. Besides, it requires heavy human effort from network operators. To achieve high utilization and flexible scheduling of IP network addresses, it is necessary to automate the address scheduling process. This document describes an architecture for the IP address space management. It includes architectural concepts and components used in the CASM (Coordinated Address Space Management), with a focus on those interfaces to be standardized in the IETF.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on December 30, 2018.

#### Copyright Notice

Copyright (c) 2018 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

#### Table of Contents

1. Introduction . . . . .	3
2. Terminology . . . . .	4
3. CASM Reference architecture . . . . .	4
4. The overall procedure of CASM . . . . .	7
5. CASM Interface and operation . . . . .	8
5.1. CASM App-facing Interface . . . . .	8
5.1.1. Functional requirements . . . . .	8
5.1.2. Interface modeling requirements . . . . .	9
5.2. CASM device-facing Interface . . . . .	9
5.2.1. Functional requirements . . . . .	10
5.2.2. Interface modeling requirements/Initial Address Pool Configuration . . . . .	10
5.2.3. Interface modeling requirements/Address Pool Status Report . . . . .	12
5.2.4. Interface modeling requirements/Address Pool Status Query . . . . .	13
5.2.5. Interface modeling requirements/Address Exhaustion . . . . .	13
5.2.6. Interface modeling requirements / Address Pool Release . . . . .	14
6. Services SDN Management Use Cases . . . . .	15
7. Security Considerations . . . . .	16
8. Acknowledgements . . . . .	16
9. References . . . . .	16
9.1. Normative References . . . . .	16

9.2. Informative References . . . . .	17
Authors' Addresses . . . . .	17

## 1. Introduction

The address space management is an integral part of any network management solution. However, the increase in number, diversity and complexity of modern network devices and services creates unprecedented challenges for the currently prevailing approach of manual IP address management. Manually maintaining IP addresses could always be sub-optimal for IP resource utilization. Besides, it requires heavy human effort from network operators.

Another factor which drive this work is that tThe network architectures are rapidly changing with the migration toward private and public clouds. At the same time, application architectures are also evolving with a shift toward micro-services and multi-tiered approach.

There is a pressing need to define a new address management system which can meet these diverse set of requirements. To achieve high utilization and flexible scheduling of IP network addresses, Such a system should be capable of automating the address scheduling process. Such a system must be built with well-defined interfaces so users can easily migrate from one vendor to another without rewriting their network management systems.

This document defines a reference architecture that should become the basis to develop a new address management system. This system is called Coodinated Address Space Management (CSAM) system.

A series of use cases are defined in "Use Case Draft". For example, Broadband Network Gateway (BNG), which manages a routable IP address on behalf of each subscriber, should be configured with the IP address pools allocated to subscribers. However, currently operators are facing with the address shortage problem, the remaining IPv4 address pools are usually quite scattered, no more than /24 per address pool in many cases. Therefore, it is complicated to manually configure the address pools on lots of Broadband Network Gateway (BNG) for operators. For large scale Metro Area Network (MAN), the number of BNGs can be up to over one hundred. Manual configuration on all the BNGs statically will not only greatly increase the workload, but also decrease the utilization efficiency of the address pools when the number of subscribers changes over time in the future.

Above is one example of use case, there are other devices which may need to configure address pools as well. In this document, we propose a general mechanism to manage the address pools coordinately,

which can be used in multiple use cases. With this approach, operators do not need to configure the address pools one by one manually and it also helps to use the address pools more efficiently.

## 2. Terminology

The following terms are used in this document:

CASM: Coordinated Address Space Management, a newly-defined general architecture which can automate IP address management for wide-variety of use cases

IPAM: IP Address Management, a means of planning, tracking, and managing the Internet Protocol address space used in a network

DA: A device agent within the device, which contacts with CASM Coordinator to manipulate address pool

CASM Coordinator: A management system which has a database manage the overall address pools and allocate address pools to devices.

## 3. CASM Reference architecture

The figure below shows the reference architecture for CASM. This figure covers the various possible scenarios that can exist in future network.




Figure 1: CASM reference architecture

Each component of CASM is introduced as below,

#### 1) CASM Application

The CASM Application is a functional entity which usually has the requirements of centralized address management to realize its specific upper-layer functions. In order to achieve this goal, it needs to manage, operate and maintain the CASM Coordinator. For example, an operator or external user can manage the address pool in

the CASM Coordinator, as well as access log, address allocation records, etc.

## 2) CASM Coordinator

The CASM Coordinator is a coordinated address management coordinator for the CASM Application to maintain overall address pools, addresses, address properties, etc. It maintains an address database including the overall address pools (OAP) and the address pool status (APS). CASM Applications can maintain their remaining address pools in the OAP. They can also reserve some address pools for special purposes. The address pool status is to reflect the current usage of address pools for different devices. The CASM Coordinator also has the capability to maintain the address pools to different devices dynamically.

## 3) CASM Device

A CASM Device is responsible for distributing or allocating addresses from local address pools received from the CASM Coordinator. CASM has two components in devices. The first one is Device Agent (DA), which resides in a CASM Device through which the device can contact with the CASM Coordinator. On behalf of the device, the agent initiates the address pool allocation requests, passes the address pools to local instances, detect the availability of address pools or report the status of local address pool usage and update the address pool requests, etc. For some devices, e.g. IPv6 transition and VPN, additional routing modules are needed to update the routing table accordingly.

The CASM Distributor is another component in a CASM device. The DHCP server is a typical distributor that can assign IP addresses to client hosts, and the DHCP protocol is usually used for this task. The address assignment procedure between the CASM Distributor and the client host is out of the scope of this document.

The device determines whether the usage status of the IP address pool resource within the device satisfies the condition. When the IP address pool resource in the device is insufficient or excessive, the device will obtain IP address pool resource request, and sends the request to the CASM Coordinator. The device receives a resource response with IP address pools allocated for it, then it use these address pools to assign IP addresses to end users. Typical CASM Devices include BNGs, BRASes, CGNs, DHCP Servers, NATs, IPv6 Transitions, DNS Servers, etc.

The form of devices is diverse, it can be physical or virtual, and it can be box-integrated with a control plane and a user plane, or a

separated control plane remote from the box, where one or more devices share the centralized control plane. In the latter case, the control plane will manage multiple user plane devices. A number of devices that are subordinate to the control plane will jointly share the address pools to make address utilization much higher.

#### 4. The overall procedure of CASM

1. Operators configure remaining address pools centrally in the CASM Coordinator. There are multiple address pools that can be configured. The CASM Coordinator server then divides the address pools into addressing units (AUs) which would be allocated to device agents by default.
2. The agent will initiate an AddressPool request to the CASM Coordinator. It can carry its desired size of address pool with the request, or just use a default value. The address pool size in the request is only used as a hint. The actual size of the address pool is totally determined by the CASM Coordinator. It would also carry the DA's identification and the type of the address pool.
3. The CASM Coordinator looks up remaining address pools in its local database, and then allocates a set of address pools to the DA. Each address pool has a lifetime.
4. The DA receives the AddressPool reply and uses it for its purpose.
5. If the lifetime of the address pool is going to expire, the DA should issue an AddressPoolRenew request to extend it, including IPv4, IPv6, port numbers, etc.
6. The AddressPoolReport module keeps monitoring and reports the usage of all current address pools for each transition mechanism. If it is running out of address pools, it can renew the AddressPoolRequest for a newly allocated one. It can also release and recycle an existing address pool if that address pool has not been used for a specific and configurable time.
7. When the connection of the CASM Coordinator is lost or it needs the status information of certain applications, it may pre-actively query the DA for its status information.

Currently, the CASM system focuses on the coordination of IP address resources. This Solution should be extended to handle containers, VLAN assignments, etc. These are subject for future work.

## 5. CASM Interface and operation

### 5.1. CASM App-facing Interface

The CASM architecture consists of three major distinct entities: CASM Application, CASM Coordinator and network device with a device Agent (DA). In order to provide address space and pools resource that CASM Coordinator can centrally maintain, there is an interface between CASM Applications and CASM Coordinator. The CASM Application can manage the address space and pool in the CASM Coordinator, and the get address allocation records, logs from CASM Coordinator.

#### 5.1.1. Functional requirements

The CASM should support following functionality for it to be adopted for wide variety of use cases.

##### 1. Address pools requirements

A CASM system should allow ability to manage different kind of address pools. The following pools should be considered for implementation; this is not mandatory or exhaustive by any means but given here as most commonly used in networks. The CASM system should allow user-defined pools with any address objects.

Unicast address pool:

- o Private IPv4 addresses
- o Public IPv4 addresses
- o IPv6 addresses
- o MAC Addresses

Multicast address pool:

- o IPv4 address
- o IPv6 address

##### 2. Pool management requirements

There should be a rich set of functionality as defined in this section for operation of a given pool.

Address management:



- o Address allocation either as single or block
- o Address reservation
- o Allocation logic such as mapping schemes or algorithm per pool
- o

General management:

- o Pool initializing, resizing, threshold markings for resource monitoring
- o Pool attributes such as used to automatically create DNS record
- o Pool priority for searching across different pools
- o Pool fragmentation rules, such as how pool can be sub-divided
- o Pool lease rules for allocation requests

#### 5.1.2. Interface modeling requirements

There are three broad categories for CASM interface definition:

Pool management interface: Interface to external user or applications such as SDN controller to manage addresses

Log interface: Interface to access log and records such as DHCP, DNS, NAT  
Integration interface: Interface to address services such as DHCP, DNS, NAT

#### 5.2. CASM device-facing Interface

In order to provide address pool manipulations between CASM Coordinator and device, the CASM architecture calls for well-defined protocols for interfacing between them. Protocol such as radius can be used to compatible with legacy network equipment. And in more modern network system, network device acts as NETCONF/RESTCONF server side, device like CASM Coordinator act as client side. The network device sends address pool request message carrying the requested resource information to the CASM Coordinator, the CASM Coordinator send response message to the network device, where the response message includes address pool resource information allocated to the network device, and network device receives the response message and retrieve the allocated address pool resource information carried in the response message.

### 5.2.1. Functional requirements

In order to build a complete address management system, it is important that CASM should be able to integrate with other address services. This will provide a complete solution to network operators without requiring any manual or proprietary workflows.

#### DHCP server:

- o Interface to initialize address pools on DHCP server
- o Notification interface whenever an address lease is modified
- o Interface to access address lease records from DHCP server
- o Ability to store lease records and play back to DHCP server on reboot

#### DNS server:

- o Interface to create DNS records on DNS server based on DHCP server events

#### NAT device:

- o Interface to initialize NAT pools
- o Interface to access NAT records from NAT device
- o Ability to store NAT records and play back to NAT device on reboot

### 5.2.2. Interface modeling requirements/Initial Address Pool Configuration




Figure 2: Initial Address Pool Configuration

As shown in Figure 2, the procedure is as follows:

1. The DA checks whether there is already address pool configured in the local site when it starts up.
2. The DA will initiate Address Pool request to the CASM Coordinator. It can carry its desired size of address pool in the request, or just use a default value. The address pool size in the DA's request is only used as a hint. The actual size of the address pool is totally determined by CASM Coordinator. It will also carry the DA's identification, the type of transition mechanism and the indication of port allocation support.
3. The CASM Coordinator determines the address pool allocated for the DA based on the parameters received.
4. The CASM Coordinator sends the Address Pool Reply to the DA. It will also distribute the routing entry of the address pool automatically. In particular, if the newly received address pool can be aggregated to an existing one, the routing should be aggregated accordingly.

## 5.2.3. Interface modeling requirements/Address Pool Status Report




Figure 3: Address Pool Status Report

Figure 3 illustrates the active address pool status report procedure:

1. The DA will monitor and count the usage status of the local address pool. The DA counts the address usage status in one month, one week and one day, which includes the local address, address usage ratio (peak and average values), and the port usage ratio (peak and average values).
2. The DA reports the address pool usage status to the CASM Coordinator. For example, it will report the address usage status in one day, which contains the IP address, NAT44, address list: 30.14.44.0/28, peak address value 14, average address usage ratio 90%, TCP port usage ratio 20%, UDP port usage ratio 30% and etc.
3. The CASM Coordinator records the status and compares with the existing address information to determine whether additional address pool is needed.
4. The CASM Coordinator will confirm the address pool status report request to the DA. It will keep sending the address pool status

report request to the CASM Coordinator if no confirm message is received.

#### 5.2.4. Interface modeling requirements/Address Pool Status Query

When the status of CASM Coordinator is lost or the CASM Coordinator needs the status information of the DAs, the CASM Coordinator may actively query the TD for the status information, as shown in step 1 of Figure 4. The following steps 2,3,4,5 are the same as the Address Pool Status Report procedure.




Figure 4: Address Pool Status Query

#### 5.2.5. Interface modeling requirements/Address Exhaustion

When the addresses used by the DA reaches a certain usage threshold, the DA will renew the address pool request to the CASM Coordinator for an additional address pool. The procedure is the same as the initial address pool request.

## 5.2.6. Interface modeling requirements / Address Pool Release




Figure 5: Address Pool Release

Figure 5 illustrates the address pool release procedure:

1. The counting module in the DA checks if the usage threshold of address pool reaches a certain condition;
2. The DA sends the address pool release request to the CASM Coordinator to ask the release of those addresses;
3. The CASM Coordinator updates the local address pool information to add the new addressed released;
4. The CASM Coordinator notifies the TD that the addresses have been release successfully;

5. The DA will update the local address pool. If no Address Pool Release Notification is received, the DA will repeat step 2;
6. Optionally, the DA confirms with the CASM Coordinator that the address pool has been released successfully.

## 6. Services SDN Management Use Cases




Figure 6: L3 and L2 Services Orchestration

Network Operators need to manage addressing of undelay network elements in order to build end-to-end services and private or public clouds. So address management of customer equipments, provider edges, but also of virtual machines, virtual functions and overlay networks is a very important task. In general the SDN Orchestrators and other management systems must coordinate addressing schemes to ensure network operation. There is need for one address management system that would meet the requirements of such a network deployment. The SDN Orchestrator manages IPv4, IPv6 addresses and also MAC addresses to assign to network interfaces in order to install end-to-end services, and this task can be achieved by the CASM coordination.

A typical use case is the application to the Service provisioning of L3VPN and L2VPN by the SDN orchestration level. For example the architecture presented in [RFC8309] and, more in general in every SDN architecture, could be integrated with CASM. It is important to mention also the possibility of Multi-Provider services, and in this case the two CASM coordinators of the two involved Providers should synchronize. The following Figure shows how CASM Application can communicate with both the Network Operator Orchestrator and, in case of Multi-Provider Service, with another Network Operator Orchestrator too.

## 7. Security Considerations

## 8. Acknowledgements

N/A.

## 9. References

### 9.1. Normative References

- [RFC2132] Alexander, S. and R. Droms, "DHCP Options and BOOTP Vendor Extensions", RFC 2132, DOI 10.17487/RFC2132, March 1997, <<https://www.rfc-editor.org/info/rfc2132>>.
- [RFC3315] Droms, R., Ed., Bound, J., Volz, B., Lemon, T., Perkins, C., and M. Carney, "Dynamic Host Configuration Protocol for IPv6 (DHCPv6)", RFC 3315, DOI 10.17487/RFC3315, July 2003, <<https://www.rfc-editor.org/info/rfc3315>>.
- [RFC6020] Bjorklund, M., Ed., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", RFC 6020, DOI 10.17487/RFC6020, October 2010, <<https://www.rfc-editor.org/info/rfc6020>>.
- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", RFC 6241, DOI 10.17487/RFC6241, June 2011, <<https://www.rfc-editor.org/info/rfc6241>>.
- [RFC8040] Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Protocol", RFC 8040, DOI 10.17487/RFC8040, January 2017, <<https://www.rfc-editor.org/info/rfc8040>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.



## 9.2. Informative References

[RFC6888] Perreault, S., Ed., Yamagata, I., Miyakawa, S., Nakagawa, A., and H. Ashida, "Common Requirements for Carrier-Grade NATs (CGNs)", BCP 127, RFC 6888, DOI 10.17487/RFC6888, April 2013, <<https://www.rfc-editor.org/info/rfc6888>>.

## Authors' Addresses

Chen Li  
China Telecom  
No.118 Xizhimennei street, Xicheng District  
Beijing 100035  
P.R. China  
  
Email: [lichen@ctbri.com.cn](mailto:lichen@ctbri.com.cn)

Chongfeng Xie  
China Telecom  
No.118 Xizhimennei street, Xicheng District  
Beijing 100035  
P.R. China  
  
Email: [xiechf.bri@chinatelecom.cn](mailto:xiechf.bri@chinatelecom.cn)

Rakesh Kumar  
Juniper Networks  
1133 Innovation Way  
Sunnyvale CA 94089  
US  
  
Email: [rkkumar@juniper.net](mailto:rkkumar@juniper.net)

Anil Lohiya  
Juniper Networks  
1133 Innovation Way  
Sunnyvale CA 94089  
US  
  
Email: [alohiya@juniper.net](mailto:alohiya@juniper.net)

Giuseppe Fioccola  
Telecom Italia  
Via Reiss Romoli, 274  
Torino 10148  
Italy

Email: giuseppe.fioccola@telecomitalia.it

Weiping Xu  
Huawei Technologies  
Bantian, Longgang District  
shenzhen 518129  
P.R. China

Email: xuweiping@huawei.com

Will(Shucheng) Liu  
Huawei Technologies  
Bantian, Longgang District  
shenzhen 518129  
P.R. China

Email: liushucheng@huawei.com

Di Ma  
ZDNS  
4 South 4th St. Zhongguancun  
Beijing 100190  
P.R. China

Email: madi@zdns.cn

Jun Bi  
Tsinghua University  
3-212, FIT Building, Tsinghua University, Haidian District  
Beijing 100084  
P.R. China

Email: junbi@tsinghua.edu.cn