KSK Sentinel

draft-ietf-dnsop-kskroll-sentinel

Geoff Huston
Joao Silva Damas
Warren Kumari

Major changes

ា រា	0 Open	✓ 13 Closed	Author ▼	Labels ▼	Projects ▼	Milestones •	Reviews ▼	Assignee ▼	Sort ▼
□ %		fications regarding caching a pspacek was merged 15 minutes ago	nd SERVFAII	L response	s				□ 1
□ %		ditorial nits pspacek was merged 2 days ago							□ 1
□ %		fy situation with multiple reso paulehoffman was merged 16 minutes a							□ 1
□ %		orial changes to Section 3 paulehoffman was merged 15 days ago							□ 1
□ %		ate Privacy Concerns, depreca w wessels was merged 19 days ago • Appr	-						□ 1
□ %		ed Duane's privacy concerns paulehoffman was merged 20 days ago							□ 1
□ %		es the use cases clearer paulehoffman was merged 20 days ago							□ 1
□ %		d some A/AAAA stuff paulehoffman was merged 20 days ago							□ 2
□ %		nged the example numbers paulehoffman was merged 20 days ago							□ 1
□ %		e it clear that names and addr paulehoffman was merged 20 days ago	esses must	be real					□ 1
□ %		d key-tag and Key Tag consist paulehoffman was merged 20 days ago	enly through	hout					□ 1
□ %		of editorial fixes paulehoffman was merged 20 days ago •	Approved						Д 3
ា រា		e the protocol apply to all zono paulehoffman was closed 20 days ago	es, not just t	the root					□ 1

<u>Major changes</u>

- Conversational description of how this works.
- This is for the active root TA.
- Many many readability fixes (thanks all!)
- Make examples FQDN.
- Some privacy clarifications.
- SERVFAIL vs NXDOMAIN...

<u>Major changes</u> Names!

- _is-ta-<key-tag>
- kskroll-sentinel-is-ta-<hex key-tag>
- kskroll-sentinel-is-ta-<dec key-tag>



Demo: http://www.ksk-test.net:

Sentinel KSK Test

tl;dr: You are using a legacy resolver, we cannot determine your fate!

This page uses the methods described in A Sentinel for Detecting Trusted Keys in DNSSEC to determine if the resolvers that you are using will survive the upcoming KSK roll. You should really read the document, but the 50'000ft view is that it attempts to load resources from 3 names:

- "http://invalid.ksk-test.net/invalid.gif"
- "http://kskroll-sentinel-is-ta-20236.ksk-test.net/is-ta.gif"
- "http://kskroll-sentinel-not-ta-20236.ksk-test.net/not-ta.gif"

It then uses some simple logic to tell what your fate will be after the KSK roll:

- 1. If you are **not** using a validating resolver, you will be able to load the *invalid* record.
- 2. If you are using a validating resolver which **does not** understand this new mechanism you will be able to load both of the sentinel records: kskroll-sentinel-is-ta-20236 and kskroll-sentinel-not-ta-20236.
- 3. If you are using a resolver that supports this mechanism you will only be able to load one of the two sentinel records which one tells you how you will fare in the rollover.

When running the above test, you:

- · were NOT able to fetch the "invalid" record
- · were able to fetch the "kskroll-sentinel-is-ta-20236" record
- · were able to fetch the "kskroll-sentinel-not-ta-20236" record

Questions?



Backup Slides

What's the problem?

- We need want to roll the DNSSEC trust-anchor (KSK)
- Have no way to measure the impact.

RFC8145!

PROPOSED STANDARD

Internet Engineering Task Force (IETF)

Request for Comments: 8145 Category: Standards Track

ISSN: 2070-1721

D. Wessels
Verisign
W. Kumari
Google
P. Hoffman
ICANN
April 2017


Signaling Trust Anchor Knowledge in DNS Security Extensions (DNSSEC)

Abstract


The DNS Security Extensions (DNSSEC) were developed to provide origin authentication and integrity protection for DNS data by using digital signatures. These digital signatures can be verified by building a chain of trust starting from a trust anchor and proceeding down to a

Solved! Nope.

Pretty graphs!



Prettier graphs!



<u>Sentinel</u>

- 1. Requires a (simple) resolver update
- 2. Allows anyone to set up a measurement service
- 3. Exposes the result to the users

The change

Just before sending the **response** (after resolution, validation):

- kskroll-sentinel-is-ta-[key].something?
 - If have the key, reply normally, else SERVFAIL
- kskroll-sentinel-not-ta-[key].something?
 - If do NOT have the key, reply normally, else SERVFAIL

Example

- I'm a validating resolver. I support sentinel.
- I have the new KSK (20326)
- I get a query for invalid.example.com
 - It fails DNSSEC validation SERVFAIL
- I get a query for

kskroll-sentinel-is-ta-20326.example.com

- I resolve it and get 192.0.2.23
 - I have (and am using) KeyID 20326
 - answer with 192.0.2.23
- I get a query for

kskroll-sentinel-not-ta-20326.exam

- I do have (and am using) KeyID 20326
 - send SERVFAIL



Yawn. So what?!

Do you see:

- Fish? Not validating, key-roll doesn't affect you.
- Kitten and Puppy? Legacy, we cannot tell.
- Kitten? You have the new key, you'll be fine.
- Puppy? DANGER! You only have the old key.

Srsly? Kittens?!

Sadly, no...

```
<html>
    <head>
       <script type="text/javascript"</pre>
       src="https://ajax.googleapis.com/ajax/libs/jquery/1.12.4/jquery.min.js"></script>
    </head>
    <body>
       <h1>Sentinel KSK Test</h1>
       <img id="img_invalid" src="http://invalid.ksk-test.net/invalid.gif"/>
        <img id="img_is_ta" src="http://kskroll-sentinel-is-ta-20236.ksk-test.net/is-ta.gif"/>
        <img id="img_not_ta" src="http://kskroll-sentinel-is-ta-20236.ksk-test.net/not-ta.gif"/>
       >
        <span id="sentinel"></span>
17
      <script type="text/javascript">
19
        var invalid=true, is_ta=true, not_ta=true, result="Testing failed...";
20
21
        $('#img_invalid').error(function(){invalid=false});
22
        $('#img is ta').error(function(){is ta=false});
23
        $('#img_not_ta').error(function(){not_ta=false});
24
        window.addEventListener('load', function(){
26
          switch (true) {
27
          case invalid===true:
28
            result='No DNSSEC validation, you will be fine...'; break;
          case (is_ta===true && not_ta===true):
             result='Legacy resolver, cannot determine your fate!'; break;
           case (is_ta===true):
             result='WARNING!: You do not have the new KSK.'; break;
          case (not ta===true):
            result='Congratulations, you have the new key. You will be fine.'; break;
          $('#sentinel').text(result);
        });
       </script>
    </body>
    </html>
```

...but kittens!!!

Sorry, still no...:-(

Demo: http://www.ksk-test.net:

Sentinel KSK Test

tl;dr: You are using a legacy resolver, we cannot determine your fate!

This page uses the methods described in <u>A Sentinel for Detecting Trusted Keys in DNSSEC</u> to determine if the resolvers that you are using will survive the upcoming KSK roll. You should really read the document, but the 50'000ft view is that it attempts to load resources from 3 names:

- "http://invalid.ksk-test.net/invalid.gif"
- "http://kskroll-sentinel-is-ta-20236.ksk-test.net/is-ta.gif"
- "http://kskroll-sentinel-not-ta-20236.ksk-test.net/not-ta.gif"

It then uses some simple logic to tell what your fate will be after the KSK roll:

- 1. If you are not using a validating resolver, you will be able to load the invalid record.
- If you are using a validating resolver which does not understand this new mechanism you will be able to load both of the sentinel records: kskroll-sentinel-is-ta-20236 and kskroll-sentinel-not-ta-20236.
- 3. If you are using a resolver that supports this mechanism you will only be able to load one of the two sentinel records which one tells you how you will fare in the rollover.

When running the above test, you:

- · were NOT able to fetch the "invalid" record
- · were able to fetch the "kskroll-sentinel-is-ta-20236" record
- were able to fetch the "kskroll-sentinel-not-ta-20236" record

Questions?

