

NETCONF Working Group
Internet-Draft
Intended status: Standards Track
Expires: December 6, 2018

K. Watsen
Juniper Networks
G. Wu
Cisco Systems
June 4, 2018

YANG Groupings for SSH Clients and SSH Servers
draft-ietf-netconf-ssh-client-server-06

Abstract

This document defines three YANG modules: the first defines groupings for a generic SSH client, the second defines groupings for a generic SSH server, and the third defines common identities and groupings used by both the client and the server. It is intended that these groupings will be used by applications using the SSH protocol.

Editorial Note (To be removed by RFC Editor)

This draft contains many placeholder values that need to be replaced with finalized values at the time of publication. This note summarizes all of the substitutions that are needed. No other RFC Editor instructions are specified elsewhere in this document.

This document contains references to other drafts in progress, both in the Normative References section, as well as in body text throughout. Please update the following references to reflect their final RFC assignments:

- o I-D.ietf-netconf-trust-anchors
- o I-D.ietf-netconf-keystore

Artwork in this document contains shorthand references to drafts in progress. Please apply the following replacements:

- o "XXXX" --> the assigned RFC value for this draft
- o "YYYY" --> the assigned RFC value for I-D.ietf-netconf-trust-anchors
- o "ZZZZ" --> the assigned RFC value for I-D.ietf-netconf-keystore

Artwork in this document contains placeholder values for the date of publication of this draft. Please apply the following replacement:

- o "2018-06-04" --> the publication date of this draft

The following Appendix section is to be removed prior to publication:

- o Appendix A. Change Log

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on December 6, 2018.

Copyright Notice

Copyright (c) 2018 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1. Introduction	3
2. Terminology	4
3. The SSH Client Model	4
3.1. Tree Diagram	4
3.2. Example Usage	6
3.3. YANG Module	9
4. The SSH Server Model	12
4.1. Tree Diagram	12
4.2. Example Usage	14
4.3. YANG Module	17

5.	The SSH Common Model	20
5.1.	Tree Diagram	21
5.2.	Example Usage	21
5.3.	YANG Module	22
6.	Security Considerations	32
7.	IANA Considerations	33
7.1.	The IETF XML Registry	33
7.2.	The YANG Module Names Registry	33
8.	Acknowledgements	34
9.	References	34
9.1.	Normative References	34
9.2.	Informative References	35
Appendix A.	Change Log	37
A.1.	00 to 01	37
A.2.	01 to 02	37
A.3.	02 to 03	37
A.4.	03 to 04	37
A.5.	04 to 05	38
A.6.	05 to 06	38
	Authors' Addresses	38

1. Introduction

This document defines three YANG 1.1 [RFC7950] modules: the first defines a grouping for a generic SSH client, the second defines a grouping for a generic SSH server, and the third defines identities and groupings common to both the client and the server. It is intended that these groupings will be used by applications using the SSH protocol [RFC4252], [RFC4253], and [RFC4254]. For instance, these groupings could be used to help define the data model for an OpenSSH [OPENSSSH] server or a NETCONF over SSH [RFC6242] based server.

The client and server YANG modules in this document each define one grouping, which is focused on just SSH-specific configuration, and specifically avoids any transport-level configuration, such as what ports to listen on or connect to. This affords applications the opportunity to define their own strategy for how the underlying TCP connection is established. For instance, applications supporting NETCONF Call Home [RFC8071] could use the "ssh-server-grouping" grouping for the SSH parts it provides, while adding data nodes for the TCP-level call-home configuration.

The modules defined in this document uses groupings defined in [I-D.ietf-netconf-keystore] enabling keys to be either locally defined or a reference to globally configured values.

The modules defined in this document optionally support [RFC6187] enabling X.509v3 certificate based host keys and public keys.

2. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

3. The SSH Client Model

3.1. Tree Diagram

This section provides two tree diagrams [RFC8340] for the "ietf-ssh-client" module, the first with used groupings expanded and the second with used groupings not expanded.

The following tree diagram has used groupings expanded:

```

module: ietf-ssh-client

grouping ssh-client-grouping
+-- client-identity
|  +-- username?          string
|  +-- (auth-type)
|  |  +--:(password)
|  |  |  +-- password?    string
|  |  +--:(public-key)
|  |  |  +-- public-key
|  |  |  |  +-- (local-or-keystore)
|  |  |  |  |  +--:(local)
|  |  |  |  |  |  +-- algorithm    ct:key-algorithm-ref
|  |  |  |  |  |  +-- public-key    binary
|  |  |  |  |  |  +-- private-key   union
|  |  |  |  |  +--:(keystore) {keystore-implemented}?
|  |  |  |  +-- reference          ks:asymmetric-key-ref
|  |  +--:(certificate)
|  |  |  +-- certificate {sshcmn:ssh-x509-certs}?
|  |  |  |  +-- (local-or-keystore)
|  |  |  |  |  +--:(local)
|  |  |  |  |  |  +-- algorithm
|  |  |  |  |  |  |  ct:key-algorithm-ref
|  |  |  |  |  |  +-- public-key          binary
|  |  |  |  |  |  +-- private-key        union
|  |  |  |  |  |  +-- cert
|  |  |  |  |  |  |  ct:end-entity-cert-cms
|  |  |  |  |  |  +--n certificate-expiration
|  |  |  |  |  |  |  +-- expiration-date? yang:date-and-time
|  |  |  |  |  +--:(keystore) {keystore-implemented}?
|  |  |  |  +-- reference
|  |  |  |  |  ks:asymmetric-key-certificate-ref
+-- server-auth
|  +-- pinned-ssh-host-keys? ta:pinned-host-keys-ref
|  +-- pinned-ca-certs?     ta:pinned-certificates-ref
|  |  {sshcmn:ssh-x509-certs}?
|  +-- pinned-server-certs? ta:pinned-certificates-ref
|  |  {sshcmn:ssh-x509-certs}?
+-- transport-params {ssh-client-transport-params-config}?
+-- host-key
|  +-- host-key-alg*  identityref
+-- key-exchange
|  +-- key-exchange-alg*  identityref
+-- encryption
|  +-- encryption-alg*  identityref
+-- mac
|  +-- mac-alg*  identityref

```

The following tree diagram does not have the groupings expanded:

[Note: '\' line wrapping for formatting only]

```

module: ietf-ssh-client

  grouping ssh-client-grouping
  +-- client-identity
  |   +-- username?          string
  |   +-- (auth-type)
  |   |   +---:(password)
  |   |   |   +-- password?      string
  |   |   +---:(public-key)
  |   |   |   +-- public-key
  |   |   |   +---u ks:local-or-keystore-asymmetric-key-grouping
  |   |   +---:(certificate)
  |   |   |   +-- certificate {sshcmn:ssh-x509-certs}?
  |   |   |   +---u ks:local-or-keystore-end-entity-certificate-gr\
  |   |   |   ouping
  |   |   |   +-- server-auth
  |   |   |   |   +-- pinned-ssh-host-keys?  ta:pinned-host-keys-ref
  |   |   |   |   +-- pinned-ca-certs?      ta:pinned-certificates-ref
  |   |   |   |   |   {sshcmn:ssh-x509-certs}?
  |   |   |   |   +-- pinned-server-certs?  ta:pinned-certificates-ref
  |   |   |   |   |   {sshcmn:ssh-x509-certs}?
  |   |   +-- transport-params {ssh-client-transport-params-config}?
  |   |   +---u sshcmn:transport-params-grouping

```

3.2. Example Usage

This section presents two examples showing the `ssh-client-grouping` populated with some data. These examples are effectively the same except the first configures the client identity using a local key while the second uses a key configured in a keystore. Both examples are consistent with the examples presented in Section 3 of [I-D.ietf-netconf-trust-anchors] and Section 3.2 of [I-D.ietf-netconf-keystore].

The following example configures the client identity using a local key:

[Note: '\' line wrapping for formatting only]

```
<ssh-client
  xmlns="urn:ietf:params:xml:ns:yang:ietf-ssh-client"
  xmlns:algs="urn:ietf:params:xml:ns:yang:ietf-ssh-common">

  <!-- how this client will authenticate itself to the server -->
  <client-identity>
    <username>foobar</username>
    <public-key>
      <algorithm xmlns:ct="urn:ietf:params:xml:ns:yang:ietf-crypto-t\
types">ct:rsa1024</algorithm>
      <private-key>base64encodedvalue==</private-key>
      <public-key>base64encodedvalue==</public-key>
    </public-key>
  </client-identity>

  <!-- which host-keys will this client trust -->
  <server-auth>
    <pinned-ssh-host-keys>explicitly-trusted-ssh-host-keys</pinned-s\
sh-host-keys>
  </server-auth>

  <transport-params>
    <host-key>
      <host-key-alg>algs:ssh-rsa</host-key-alg>
    </host-key>
    <key-exchange>
      <key-exchange-alg>
        algs:diffie-hellman-group-exchange-sha256
      </key-exchange-alg>
    </key-exchange>
    <encryption>
      <encryption-alg>algs:aes256-ctr</encryption-alg>
      <encryption-alg>algs:aes192-ctr</encryption-alg>
      <encryption-alg>algs:aes128-ctr</encryption-alg>
      <encryption-alg>algs:aes256-cbc</encryption-alg>
      <encryption-alg>algs:aes192-cbc</encryption-alg>
      <encryption-alg>algs:aes128-cbc</encryption-alg>
    </encryption>
    <mac>
      <mac-alg>algs:hmac-sha2-256</mac-alg>
      <mac-alg>algs:hmac-sha2-512</mac-alg>
    </mac>
  </transport-params>

</ssh-client>
```

The following example configures the client identity using a key from the keystore:

[Note: '\' line wrapping for formatting only]

```
<ssh-client
  xmlns="urn:ietf:params:xml:ns:yang:ietf-ssh-client"
  xmlns:algs="urn:ietf:params:xml:ns:yang:ietf-ssh-common">

  <!-- how this client will authenticate itself to the server -->
  <client-identity>
    <username>foobar</username>
    <public-key>
      <reference>ex-rsa-key</reference>
    </public-key>
  </client-identity>

  <!-- which host-keys will this client trust -->
  <server-auth>
    <pinned-ssh-host-keys>explicitly-trusted-ssh-host-keys</pinned-ssh-host-keys>
  </server-auth>

  <transport-params>
    <host-key>
      <host-key-alg>algs:ssh-rsa</host-key-alg>
    </host-key>
    <key-exchange>
      <key-exchange-alg>
        algs:diffie-hellman-group-exchange-sha256
      </key-exchange-alg>
    </key-exchange>
    <encryption>
      <encryption-alg>algs:aes256-ctr</encryption-alg>
      <encryption-alg>algs:aes192-ctr</encryption-alg>
      <encryption-alg>algs:aes128-ctr</encryption-alg>
      <encryption-alg>algs:aes256-cbc</encryption-alg>
      <encryption-alg>algs:aes192-cbc</encryption-alg>
      <encryption-alg>algs:aes128-cbc</encryption-alg>
    </encryption>
    <mac>
      <mac-alg>algs:hmac-sha2-256</mac-alg>
      <mac-alg>algs:hmac-sha2-512</mac-alg>
    </mac>
  </transport-params>

</ssh-client>
```

3.3. YANG Module

This YANG module has normative references to [RFC6536], [I-D.ietf-netconf-trust-anchors], and [I-D.ietf-netconf-keystore].

```
<CODE BEGINS> file "ietf-ssh-client@2018-06-04.yang"
module ietf-ssh-client {
  yang-version 1.1;

  namespace "urn:ietf:params:xml:ns:yang:ietf-ssh-client";
  prefix "sshc";

  import ietf-ssh-common {
    prefix sshcmn;
    revision-date 2018-06-04; // stable grouping definitions
    reference
      "RFC XXXX: YANG Groupings for SSH Clients and SSH Servers";
  }

  import ietf-trust-anchors {
    prefix ta;
    reference
      "RFC YYYY: YANG Data Model for Global Trust Anchors";
  }

  import ietf-keystore {
    prefix ks;
    reference
      "RFC ZZZZ:
      YANG Data Model for a Centralized Keystore Mechanism";
  }

  organization
    "IETF NETCONF (Network Configuration) Working Group";

  contact
    "WG Web: <http://datatracker.ietf.org/wg/netconf/>
    WG List: <mailto:netconf@ietf.org>

    Author: Kent Watsen
            <mailto:kwatsen@juniper.net>

    Author: Gary Wu
            <mailto:garywu@cisco.com>";

  description
    "This module defines a reusable grouping for a SSH client that
```

can be used as a basis for specific SSH client instances.

Copyright (c) 2018 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in Section 4.c of the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC XXXX; see the RFC itself for full legal notices.";

```
revision "2018-06-04" {
  description
    "Initial version";
  reference
    "RFC XXXX: YANG Groupings for SSH Clients and SSH Servers";
}

// features

feature ssh-client-transport-params-config {
  description
    "SSH transport layer parameters are configurable on an SSH
    client.";
}

// groupings

grouping ssh-client-grouping {
  description
    "A reusable grouping for configuring a SSH client without
    any consideration for how an underlying TCP session is
    established.";

  container client-identity {
    description
      "The credentials used by the client to authenticate to
      the SSH server.";

    leaf username {
      type string;
      description
        "The username of this user. This will be the username
        used, for instance, to log into an SSH server.";
    }
  }
}
```

```
    }

    choice auth-type {
      mandatory true;
      description
        "The authentication type.";
      leaf password {
        type string;
        description
          "A password to be used for client authentication.";
      }
      container public-key {
        uses ks:local-or-keystore-asymmetric-key-grouping;
        description
          "A locally-defined or referenced asymmetric key pair
           to be used for client authentication.";
        reference
          "RFC ZZZZ:
           YANG Data Model for a Centralized Keystore Mechanism";
      }
      container certificate {
        if-feature sshcmn:ssh-x509-certs;
        uses ks:local-or-keystore-end-entity-certificate-grouping;
        description
          "A locally-defined or referenced certificate
           to be used for client authentication.";
        reference
          "RFC ZZZZ
           YANG Data Model for a Centralized Keystore Mechanism";
      }
    } // end auth-type
  } // end client-identity

  container server-auth {
    must 'pinned-ssh-host-keys or pinned-ca-certs or '
      + 'pinned-server-certs';
    description
      "Trusted server identities.";
    leaf pinned-ssh-host-keys {
      type ta:pinned-host-keys-ref;
      description
        "A reference to a list of SSH host keys used by the
         SSH client to authenticate SSH server host keys.
         A server host key is authenticated if it is an exact
         match to a configured SSH host key.";
      reference
        "RFC YYYY: YANG Data Model for Global Trust Anchors";
    }
  }
```

```
leaf pinned-ca-certs {
  if-feature sshcmn:ssh-x509-certs;
  type ta:pinned-certificates-ref;
  description
    "A reference to a list of certificate authority (CA)
    certificates used by the SSH client to authenticate
    SSH server certificates. A server certificate is
    authenticated if it has a valid chain of trust to
    a configured CA certificate.";
  reference
    "RFC YYYY: YANG Data Model for Global Trust Anchors";
}

leaf pinned-server-certs {
  if-feature sshcmn:ssh-x509-certs;
  type ta:pinned-certificates-ref;
  description
    "A reference to a list of server certificates used by
    the SSH client to authenticate SSH server certificates.
    A server certificate is authenticated if it is an
    exact match to a configured server certificate.";
  reference
    "RFC YYYY: YANG Data Model for Global Trust Anchors";
}
} // end server-auth

container transport-params {
  if-feature ssh-client-transport-params-config;
  description
    "Configurable parameters of the SSH transport layer.";
  uses sshcmn:transport-params-grouping;
}

} // end ssh-client-grouping

}
<CODE ENDS>
```

4. The SSH Server Model

4.1. Tree Diagram

This section provides two tree diagrams [RFC8340] for the "ietf-ssh-server" module, the first with used groupings expanded and the second with used groupings not expanded.

The following tree diagram has used groupings expanded:

[Note: '\' line wrapping for formatting only]

```

module: ietf-ssh-server

  grouping ssh-server-grouping
    +-- server-identity
      |   +-- host-key* [name]
      |   |   +-- name?                string
      |   |   +-- (host-key-type)
      |   |   |   +--:(public-key)
      |   |   |   |   +-- public-key
      |   |   |   |   +---u ks:local-or-keystore-asymmetric-key-groupin\
  g   |   |   |   |
      |   |   |   +--:(certificate)
      |   |   |   |   +-- certificate {sshcmn:ssh-x509-certs}?
      |   |   |   |   +---u ks:local-or-keystore-end-entity-certificate\
  -grouping
    +-- client-cert-auth {sshcmn:ssh-x509-certs}?
      |   +-- pinned-ca-certs?          ta:pinned-certificates-ref
      |   +-- pinned-client-certs?     ta:pinned-certificates-ref
    +-- transport-params {ssh-server-transport-params-config}?
      +---u sshcmn:transport-params-grouping

```

4.2. Example Usage

This section presents two examples showing the `ssh-server-grouping` populated with some data. These examples are effectively the same except the first configures the server identity using a local key while the second uses a key configured in a keystore. Both examples are consistent with the examples presented in Section 3 of [I-D.ietf-netconf-trust-anchors] and Section 3.2 of [I-D.ietf-netconf-keystore].

The following example configures the server identity using a local key:

[Note: '\' line wrapping for formatting only]

```

<ssh-server xmlns="urn:ietf:params:xml:ns:yang:ietf-ssh-server"
            xmlns:algs="urn:ietf:params:xml:ns:yang:ietf-ssh-common"\
>

  <!-- which host-keys will this SSH server present -->
  <server-identity>
    <host-key>
      <name>deployment-specific-certificate</name>
      <public-key>

```

```
        <algorithm xmlns:ct="urn:ietf:params:xml:ns:yang:ietf-crypto\
-types">ct:rsa1024</algorithm>
        <private-key>base64encodedvalue==</private-key>
        <public-key>base64encodedvalue==</public-key>
        </public-key>
    </host-key>
</server-identity>

<!-- which client-certs will this SSH server trust -->
<client-cert-auth>
    <pinned-ca-certs>explicitly-trusted-client-ca-certs</pinned-ca-c\
erts>
    <pinned-client-certs>explicitly-trusted-client-certs</pinned-cli\
ent-certs>
</client-cert-auth>

<transport-params>
    <host-key>
        <host-key-alg>algs:ssh-rsa</host-key-alg>
    </host-key>
    <key-exchange>
        <key-exchange-alg>
            algs:diffie-hellman-group-exchange-sha256
        </key-exchange-alg>
    </key-exchange>
    <encryption>
        <encryption-alg>algs:aes256-ctr</encryption-alg>
        <encryption-alg>algs:aes192-ctr</encryption-alg>
        <encryption-alg>algs:aes128-ctr</encryption-alg>
        <encryption-alg>algs:aes256-cbc</encryption-alg>
        <encryption-alg>algs:aes192-cbc</encryption-alg>
        <encryption-alg>algs:aes128-cbc</encryption-alg>
    </encryption>
    <mac>
        <mac-alg>algs:hmac-sha2-256</mac-alg>
        <mac-alg>algs:hmac-sha2-512</mac-alg>
    </mac>
</transport-params>

</ssh-server>
```

The following example configures the server identity using a key from the keystore:

[Note: '\' line wrapping for formatting only]

```
<ssh-server xmlns="urn:ietf:params:xml:ns:yang:ietf-ssh-server"
            xmlns:algs="urn:ietf:params:xml:ns:yang:ietf-ssh-common"\
>

  <!-- which host-keys will this SSH server present -->
  <server-identity>
    <host-key>
      <name>deployment-specific-certificate</name>
      <public-key>
        <reference>ex-rsa-key</reference>
      </public-key>
    </host-key>
  </server-identity>

  <!-- which client-certs will this SSH server trust -->
  <client-cert-auth>
    <pinned-ca-certs>explicitly-trusted-client-ca-certs</pinned-ca-c\
erts>
    <pinned-client-certs>explicitly-trusted-client-certs</pinned-cli\
ent-certs>
  </client-cert-auth>

  <transport-params>
    <host-key>
      <host-key-alg>algs:ssh-rsa</host-key-alg>
    </host-key>
    <key-exchange>
      <key-exchange-alg>
        algs:diffie-hellman-group-exchange-sha256
      </key-exchange-alg>
    </key-exchange>
    <encryption>
      <encryption-alg>algs:aes256-ctr</encryption-alg>
      <encryption-alg>algs:aes192-ctr</encryption-alg>
      <encryption-alg>algs:aes128-ctr</encryption-alg>
      <encryption-alg>algs:aes256-cbc</encryption-alg>
      <encryption-alg>algs:aes192-cbc</encryption-alg>
      <encryption-alg>algs:aes128-cbc</encryption-alg>
    </encryption>
    <mac>
      <mac-alg>algs:hmac-sha2-256</mac-alg>
      <mac-alg>algs:hmac-sha2-512</mac-alg>
    </mac>
  </transport-params>

</ssh-server>
```

4.3. YANG Module

This YANG module has normative references to [I-D.ietf-netconf-trust-anchors] and [I-D.ietf-netconf-keystore] and informative references to [RFC4253] and [RFC7317].

```
<CODE BEGINS> file "ietf-ssh-server@2018-06-04.yang"
module ietf-ssh-server {
  yang-version 1.1;

  namespace "urn:ietf:params:xml:ns:yang:ietf-ssh-server";
  prefix "sshs";

  import ietf-ssh-common {
    prefix sshcmn;
    revision-date 2018-06-04; // stable grouping definitions
    reference
      "RFC XXXX: YANG Groupings for SSH Clients and SSH Servers";
  }

  import ietf-trust-anchors {
    prefix ta;
    reference
      "RFC YYYY: YANG Data Model for Global Trust Anchors";
  }

  import ietf-keystore {
    prefix ks;
    reference
      "RFC ZZZZ:
        YANG Data Model for a Centralized Keystore Mechanism";
  }

  organization
    "IETF NETCONF (Network Configuration) Working Group";

  contact
    "WG Web:   <http://datatracker.ietf.org/wg/netconf/>
    WG List:  <mailto:netconf@ietf.org>

    Author:   Kent Watsen
              <mailto:kwatsen@juniper.net>

    Author:   Gary Wu
              <mailto:garywu@cisco.com>";

  description
```

"This module defines a reusable grouping for a SSH server that can be used as a basis for specific SSH server instances.

Copyright (c) 2018 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in Section 4.c of the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC XXXX; see the RFC itself for full legal notices.";

```
revision "2018-06-04" {
  description
    "Initial version";
  reference
    "RFC XXXX: YANG Groupings for SSH Clients and SSH Servers";
}

// features

feature ssh-server-transport-params-config {
  description
    "SSH transport layer parameters are configurable on an SSH
    server.";
}

// groupings

grouping ssh-server-grouping {
  description
    "A reusable grouping for configuring a SSH server without
    any consideration for how underlying TCP sessions are
    established.";

  container server-identity {
    description
      "The list of host-keys the SSH server will present when
      establishing a SSH connection.";
    list host-key {
      key name;
      min-elements 1;
      ordered-by user;
      description
```

```
    "An ordered list of host keys the SSH server will use to
    construct its ordered list of algorithms, when sending
    its SSH_MSG_KEXINIT message, as defined in Section 7.1
    of RFC 4253.";
reference
  "RFC 4253: The Secure Shell (SSH) Transport Layer
  Protocol";
leaf name {
  type string;
  description
    "An arbitrary name for this host-key";
}
choice host-key-type {
  mandatory true;
  description
    "The type of host key being specified";
  container public-key {
    uses ks:local-or-keystore-asymmetric-key-grouping;
    description
      "A locally-defined or referenced asymmetric key pair
      to be used for the SSH server's host key.";
    reference
      "RFC ZZZZ: YANG Data Model for a Centralized
      Keystore Mechanism";
  }
  container certificate {
    if-feature sshcmn:ssh-x509-certs;
    uses
      ks:local-or-keystore-end-entity-certificate-grouping;
    description
      "A locally-defined or referenced end-entity
      certificate to be used for the SSH server's
      host key.";
    reference
      "RFC ZZZZ: YANG Data Model for a Centralized
      Keystore Mechanism";
  }
}
}
}

container client-cert-auth {
  if-feature sshcmn:ssh-x509-certs;
  description
    "A reference to a list of pinned certificate authority (CA)
    certificates and a reference to a list of pinned client
    certificates.
```

Note: password and public-key based client authentication is not configured in this YANG module as they are expected to be configured by the ietf-system module defined in RFC 7317 ";

```

reference
  "RFC 7317: A YANG Data Model for System Management";
leaf pinned-ca-certs {
  type ta:pinned-certificates-ref;
  description
    "A reference to a list of certificate authority (CA)
    certificates used by the SSH server to authenticate
    SSH client certificates. A client certificate is
    authenticated if it has a valid chain of trust to
    a configured pinned CA certificate.";
  reference
    "RFC YYYY: YANG Data Model for Global Trust Anchors";
}
leaf pinned-client-certs {
  type ta:pinned-certificates-ref;
  description
    "A reference to a list of client certificates used by
    the SSH server to authenticate SSH client certificates.
    A clients certificate is authenticated if it is an
    exact match to a configured pinned client certificate.";
  reference
    "RFC YYYY: YANG Data Model for Global Trust Anchors";
}
}

container transport-params {
  if-feature ssh-server-transport-params-config;
  description
    "Configurable parameters of the SSH transport layer.";
  uses sshcmn:transport-params-grouping;
}

} // end ssh-server-grouping

}
<CODE ENDS>

```

5. The SSH Common Model

The SSH common model presented in this section contains identities and groupings common to both SSH clients and SSH servers. The transport-params-grouping can be used to configure the list of SSH transport algorithms permitted by the SSH client or SSH server. The lists of algorithms are ordered such that, if multiple algorithms are

permitted by the client, the algorithm that appears first in its list that is also permitted by the server is used for the SSH transport layer connection. The ability to restrict the the algorithms allowed is provided in this grouping for SSH clients and SSH servers that are capable of doing so and may serve to make SSH clients and SSH servers compliant with security policies.

Features are defined for algorithms that are OPTIONAL or are not widely supported by popular implementations. Note that the list of algorithms is not exhaustive. As well, some algorithms that are REQUIRED by [RFC4253] are missing, notably "ssh-dss" and "diffie-hellman-group1-sha1" due to their weak security and there being alternatives that are widely supported.

5.1. Tree Diagram

The following tree diagram [RFC8340] provides an overview of the data model for the "ietf-ssh-common" module.

```
module: ietf-ssh-common

  grouping transport-params-grouping
    +-- host-key
       | +-- host-key-alg*  identityref
    +-- key-exchange
       | +-- key-exchange-alg*  identityref
    +-- encryption
       | +-- encryption-alg*  identityref
    +-- mac
       +-- mac-alg*  identityref
```

5.2. Example Usage

This following example illustrates how the transport-params-grouping appears when populated with some data.

```
<transport-params
  xmlns="urn:ietf:params:xml:ns:yang:ietf-ssh-common"
  xmlns:algs="urn:ietf:params:xml:ns:yang:ietf-ssh-common">
  <host-key>
    <host-key-alg>algs:x509v3-rsa2048-sha256</host-key-alg>
    <host-key-alg>algs:ssh-rsa</host-key-alg>
  </host-key>
  <key-exchange>
    <key-exchange-alg>
      algs:diffie-hellman-group-exchange-sha256
    </key-exchange-alg>
  </key-exchange>
  <encryption>
    <encryption-alg>algs:aes256-ctr</encryption-alg>
    <encryption-alg>algs:aes192-ctr</encryption-alg>
    <encryption-alg>algs:aes128-ctr</encryption-alg>
    <encryption-alg>algs:aes256-cbc</encryption-alg>
    <encryption-alg>algs:aes192-cbc</encryption-alg>
    <encryption-alg>algs:aes128-cbc</encryption-alg>
  </encryption>
  <mac>
    <mac-alg>algs:hmac-sha2-256</mac-alg>
    <mac-alg>algs:hmac-sha2-512</mac-alg>
  </mac>
</transport-params>
```

5.3. YANG Module

This YANG module has normative references to [RFC4253], [RFC4344], [RFC4419], [RFC5656], [RFC6187], and [RFC6668].

```
<CODE BEGINS> file "ietf-ssh-common@2018-06-04.yang"
module ietf-ssh-common {
  yang-version 1.1;

  namespace "urn:ietf:params:xml:ns:yang:ietf-ssh-common";
  prefix "sshcmn";

  organization
    "IETF NETCONF (Network Configuration) Working Group";

  contact
    "WG Web: <http://datatracker.ietf.org/wg/netconf/>
    WG List: <mailto:netconf@ietf.org>

    Author: Kent Watsen
    <mailto:kwatsen@juniper.net>
```

Author: Gary Wu
<mailto:garywu@cisco.com>;

description

"This module defines a common features, identities, and groupings for Secure Shell (SSH).

Copyright (c) 2018 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in Section 4.c of the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC XXXX; see the RFC itself for full legal notices.";

```
revision "2018-06-04" {
  description
    "Initial version";
  reference
    "RFC XXXX: YANG Groupings for SSH Clients and SSH Servers";
}

// features

feature ssh-ecc {
  description
    "Elliptic Curve Cryptography is supported for SSH.";
  reference
    "RFC 5656: Elliptic Curve Algorithm Integration in the
      Secure Shell Transport Layer";
}

feature ssh-x509-certs {
  description
    "X.509v3 certificates are supported for SSH per RFC 6187.";
  reference
    "RFC 6187: X.509v3 Certificates for Secure Shell
      Authentication";
}

feature ssh-dh-group-exchange {
  description
    "Diffie-Hellman Group Exchange is supported for SSH.";
```

```
reference
  "RFC 4419: Diffie-Hellman Group Exchange for the
    Secure Shell (SSH) Transport Layer Protocol";
}

feature ssh-ctr {
  description
    "SDCTR encryption mode is supported for SSH.";
  reference
    "RFC 4344: The Secure Shell (SSH) Transport Layer
      Encryption Modes";
}

feature ssh-sha2 {
  description
    "The SHA2 family of cryptographic hash functions is
      supported for SSH.";
  reference
    "FIPS PUB 180-4: Secure Hash Standard (SHS)";
}

// identities

identity public-key-arg-base {
  description
    "Base identity used to identify public key algorithms.";
}

identity ssh-dss {
  base public-key-arg-base;
  description
    "Digital Signature Algorithm using SHA-1 as the
      hashing algorithm.";
  reference
    "RFC 4253:
      The Secure Shell (SSH) Transport Layer Protocol";
}

identity ssh-rsa {
  base public-key-arg-base;
  description
    "RSASSA-PKCS1-v1_5 signature scheme using SHA-1 as the
      hashing algorithm.";
  reference
    "RFC 4253:
      The Secure Shell (SSH) Transport Layer Protocol";
}
```

```
identity ecdsa-sha2-nistp256 {
  base public-key-alg-base;
  if-feature "ssh-ecc and ssh-sha2";
  description
    "Elliptic Curve Digital Signature Algorithm (ECDSA) using the
     nistp256 curve and the SHA2 family of hashing algorithms.";
  reference
    "RFC 5656: Elliptic Curve Algorithm Integration in the
     Secure Shell Transport Layer";
}

identity ecdsa-sha2-nistp384 {
  base public-key-alg-base;
  if-feature "ssh-ecc and ssh-sha2";
  description
    "Elliptic Curve Digital Signature Algorithm (ECDSA) using the
     nistp384 curve and the SHA2 family of hashing algorithms.";
  reference
    "RFC 5656: Elliptic Curve Algorithm Integration in the
     Secure Shell Transport Layer";
}

identity ecdsa-sha2-nistp521 {
  base public-key-alg-base;
  if-feature "ssh-ecc and ssh-sha2";
  description
    "Elliptic Curve Digital Signature Algorithm (ECDSA) using the
     nistp521 curve and the SHA2 family of hashing algorithms.";
  reference
    "RFC 5656: Elliptic Curve Algorithm Integration in the
     Secure Shell Transport Layer";
}

identity x509v3-ssh-rsa {
  base public-key-alg-base;
  if-feature ssh-x509-certs;
  description
    "RSASSA-PKCS1-v1_5 signature scheme using a public key stored
     in an X.509v3 certificate and using SHA-1 as the hashing
     algorithm.";
  reference
    "RFC 6187: X.509v3 Certificates for Secure Shell
     Authentication";
}

identity x509v3-rsa2048-sha256 {
  base public-key-alg-base;
  if-feature "ssh-x509-certs and ssh-sha2";
```

```
description
  "RSASSA-PKCS1-v1_5 signature scheme using a public key stored
  in an X.509v3 certificate and using SHA-256 as the hashing
  algorithm. RSA keys conveyed using this format MUST have a
  modulus of at least 2048 bits.";
reference
  "RFC 6187: X.509v3 Certificates for Secure Shell
  Authentication";
}

identity x509v3-ecdsa-sha2-nistp256 {
  base public-key-arg-base;
  if-feature "ssh-ecc and ssh-x509-certs and ssh-sha2";
  description
    "Elliptic Curve Digital Signature Algorithm (ECDSA)
    using the nistp256 curve with a public key stored in
    an X.509v3 certificate and using the SHA2 family of
    hashing algorithms.";
  reference
    "RFC 6187: X.509v3 Certificates for Secure Shell
    Authentication";
}

identity x509v3-ecdsa-sha2-nistp384 {
  base public-key-arg-base;
  if-feature "ssh-ecc and ssh-x509-certs and ssh-sha2";
  description
    "Elliptic Curve Digital Signature Algorithm (ECDSA)
    using the nistp384 curve with a public key stored in
    an X.509v3 certificate and using the SHA2 family of
    hashing algorithms.";
  reference
    "RFC 6187: X.509v3 Certificates for Secure Shell
    Authentication";
}

identity x509v3-ecdsa-sha2-nistp521 {
  base public-key-arg-base;
  if-feature "ssh-ecc and ssh-x509-certs and ssh-sha2";
  description
    "Elliptic Curve Digital Signature Algorithm (ECDSA)
    using the nistp521 curve with a public key stored in
    an X.509v3 certificate and using the SHA2 family of
    hashing algorithms.";
  reference
    "RFC 6187: X.509v3 Certificates for Secure Shell
    Authentication";
}
```

```
identity key-exchange-alg-base {
  description
    "Base identity used to identify key exchange algorithms.";
}

identity diffie-hellman-group14-sha1 {
  base key-exchange-alg-base;
  description
    "Diffie-Hellman key exchange with SHA-1 as HASH and
    Oakley Group 14 (2048-bit MODP Group).";
  reference
    "RFC 4253: The Secure Shell (SSH) Transport Layer Protocol";
}

identity diffie-hellman-group-exchange-sha1 {
  base key-exchange-alg-base;
  if-feature ssh-dh-group-exchange;
  description
    "Diffie-Hellman Group and Key Exchange with SHA-1 as HASH.";
  reference
    "RFC 4419: Diffie-Hellman Group Exchange for the
    Secure Shell (SSH) Transport Layer Protocol";
}

identity diffie-hellman-group-exchange-sha256 {
  base key-exchange-alg-base;
  if-feature "ssh-dh-group-exchange and ssh-sha2";
  description
    "Diffie-Hellman Group and Key Exchange with SHA-256 as HASH.";
  reference
    "RFC 4419: Diffie-Hellman Group Exchange for the
    Secure Shell (SSH) Transport Layer Protocol";
}

identity ecdh-sha2-nistp256 {
  base key-exchange-alg-base;
  if-feature "ssh-ecc and ssh-sha2";
  description
    "Elliptic Curve Diffie-Hellman (ECDH) key exchange using the
    nistp256 curve and the SHA2 family of hashing algorithms.";
  reference
    "RFC 5656: Elliptic Curve Algorithm Integration in the
    Secure Shell Transport Layer";
}

identity ecdh-sha2-nistp384 {
  base key-exchange-alg-base;
  if-feature "ssh-ecc and ssh-sha2";
```

```
description
  "Elliptic Curve Diffie-Hellman (ECDH) key exchange using the
   nistp384 curve and the SHA2 family of hashing algorithms.>";
reference
  "RFC 5656: Elliptic Curve Algorithm Integration in the
   Secure Shell Transport Layer";
}

identity ecdh-sha2-nistp521 {
  base key-exchange-alg-base;
  if-feature "ssh-ecc and ssh-sha2";
  description
    "Elliptic Curve Diffie-Hellman (ECDH) key exchange using the
     nistp521 curve and the SHA2 family of hashing algorithms.>";
  reference
    "RFC 5656: Elliptic Curve Algorithm Integration in the
     Secure Shell Transport Layer";
}

identity encryption-alg-base {
  description
    "Base identity used to identify encryption algorithms.>";
}

identity triple-des-cbc {
  base encryption-alg-base;
  description
    "Three-key 3DES in CBC mode.>";
  reference
    "RFC 4253: The Secure Shell (SSH) Transport Layer Protocol";
}

identity aes128-cbc {
  base encryption-alg-base;
  description
    "AES in CBC mode, with a 128-bit key.>";
  reference
    "RFC 4253: The Secure Shell (SSH) Transport Layer Protocol";
}

identity aes192-cbc {
  base encryption-alg-base;
  description
    "AES in CBC mode, with a 192-bit key.>";
  reference
    "RFC 4253: The Secure Shell (SSH) Transport Layer Protocol";
}
```

```
identity aes256-cbc {
  base encryption-alg-base;
  description
    "AES in CBC mode, with a 256-bit key.";
  reference
    "RFC 4253: The Secure Shell (SSH) Transport Layer Protocol";
}

identity aes128-ctr {
  base encryption-alg-base;
  if-feature ssh-ctr;
  description
    "AES in SDCTR mode, with 128-bit key.";
  reference
    "RFC 4344: The Secure Shell (SSH) Transport Layer Encryption
      Modes";
}

identity aes192-ctr {
  base encryption-alg-base;
  if-feature ssh-ctr;
  description
    "AES in SDCTR mode, with 192-bit key.";
  reference
    "RFC 4344: The Secure Shell (SSH) Transport Layer Encryption
      Modes";
}

identity aes256-ctr {
  base encryption-alg-base;
  if-feature ssh-ctr;
  description
    "AES in SDCTR mode, with 256-bit key.";
  reference
    "RFC 4344: The Secure Shell (SSH) Transport Layer Encryption
      Modes";
}

identity mac-alg-base {
  description
    "Base identity used to identify message authentication
      code (MAC) algorithms.";
}

identity hmac-sh1 {
  base mac-alg-base;
  description
    "HMAC-SHA1";
}
```

```
reference
  "RFC 4253: The Secure Shell (SSH) Transport Layer Protocol";
}

identity hmac-sha2-256 {
  base mac-alg-base;
  if-feature "ssh-sha2";
  description
    "HMAC-SHA2-256";
  reference
    "RFC 6668: SHA-2 Data Integrity Verification for the
      Secure Shell (SSH) Transport Layer Protocol";
}

identity hmac-sha2-512 {
  base mac-alg-base;
  if-feature "ssh-sha2";
  description
    "HMAC-SHA2-512";
  reference
    "RFC 6668: SHA-2 Data Integrity Verification for the
      Secure Shell (SSH) Transport Layer Protocol";
}

// groupings

grouping transport-params-grouping {
  description
    "A reusable grouping for SSH transport parameters.";
  reference
    "RFC 4253: The Secure Shell (SSH) Transport Layer Protocol";
  container host-key {
    description
      "Parameters regarding host key.";
    leaf-list host-key-alg {
      type identityref {
        base public-key-alg-base;
      }
      ordered-by user;
      description
        "Acceptable host key algorithms in order of descending
          preference.

          If this leaf-list is not configured (has zero elements)
          the acceptable host key algorithms are implementation-
          defined.";
    }
  }
}
```

```
container key-exchange {
  description
    "Parameters regarding key exchange.";
  leaf-list key-exchange-alg {
    type identityref {
      base key-exchange-alg-base;
    }
    ordered-by user;
    description
      "Acceptable key exchange algorithms in order of descending
      preference.

      If this leaf-list is not configured (has zero elements)
      the acceptable key exchange algorithms are implementation
      defined.";
  }
}
container encryption {
  description
    "Parameters regarding encryption.";
  leaf-list encryption-alg {
    type identityref {
      base encryption-alg-base;
    }
    ordered-by user;
    description
      "Acceptable encryption algorithms in order of descending
      preference.

      If this leaf-list is not configured (has zero elements)
      the acceptable encryption algorithms are implementation
      defined.";
  }
}
container mac {
  description
    "Parameters regarding message authentication code (MAC).";
  leaf-list mac-alg {
    type identityref {
      base mac-alg-base;
    }
    ordered-by user;
    description
      "Acceptable MAC algorithms in order of descending
      preference.

      If this leaf-list is not configured (has zero elements)
      the acceptable MAC algorithms are implementation-
```

```
        defined." ;
    }
}

} // transport-params-grouping

}
<CODE ENDS>
```

6. Security Considerations

The YANG modules defined in this document are designed to be accessed via YANG based management protocols, such as NETCONF [RFC6241] and RESTCONF [RFC8040]. Both of these protocols have mandatory-to-implement secure transport layers (e.g., SSH, TLS) with mutual authentication.

The NETCONF access control model (NACM) [RFC6536] provides the means to restrict access for particular users to a pre-configured subset of all available protocol operations and content.

Since the modules defined in this document define only groupings, these considerations are primarily for the designers of other modules that use these groupings.

There are a number of data nodes defined in the YANG modules that are writable/creatable/deletable (i.e., config true, which is the default). These data nodes may be considered sensitive or vulnerable in some network environments. Write operations (e.g., edit-config) to these data nodes without proper protection can have a negative effect on network operations. These are the subtrees and data nodes and their sensitivity/vulnerability:

- /: The entire data tree defined by all the modules defined in this draft are sensitive to write operations. For instance, the addition or removal of references to keys, certificates, trusted anchors, etc., can dramatically alter the implemented security policy. However, no NACM annotations are applied as the data SHOULD be editable by users other than a designated 'recovery session'.

Some of the readable data nodes in the YANG modules may be considered sensitive or vulnerable in some network environments. It is thus important to control read access (e.g., via get, get-config, or notification) to these data nodes. These are the subtrees and data nodes and their sensitivity/vulnerability:

/client-auth/password: This node in the 'ietf-ssh-client' module is additionally sensitive to read operations such that, in normal use cases, it should never be returned to a client. The only time this node should be returned is to support backup/restore type workflows. However, no NACM annotations are applied as the data SHOULD be writable by users other than a designated 'recovery session'.

Some of the RPC operations in this YANG module may be considered sensitive or vulnerable in some network environments. It is thus important to control access to these operations. These are the operations and their sensitivity/vulnerability:

NONE

7. IANA Considerations

7.1. The IETF XML Registry

This document registers three URIs in the IETF XML registry [RFC3688]. Following the format in [RFC3688], the following registrations are requested:

URI: urn:ietf:params:xml:ns:yang:ietf-ssh-client
Registrant Contact: The NETCONF WG of the IETF.
XML: N/A, the requested URI is an XML namespace.

URI: urn:ietf:params:xml:ns:yang:ietf-ssh-server
Registrant Contact: The NETCONF WG of the IETF.
XML: N/A, the requested URI is an XML namespace.

URI: urn:ietf:params:xml:ns:yang:ietf-ssh-common
Registrant Contact: The NETCONF WG of the IETF.
XML: N/A, the requested URI is an XML namespace.

7.2. The YANG Module Names Registry

This document registers three YANG modules in the YANG Module Names registry [RFC7950]. Following the format in [RFC7950], the the following registrations are requested:

```
name:          ietf-ssh-client
namespace:     urn:ietf:params:xml:ns:yang:ietf-ssh-client
prefix:        sshc
reference:     RFC XXXX

name:          ietf-ssh-server
namespace:     urn:ietf:params:xml:ns:yang:ietf-ssh-server
prefix:        sshs
reference:     RFC XXXX

name:          ietf-ssh-common
namespace:     urn:ietf:params:xml:ns:yang:ietf-ssh-common
prefix:        sshcmn
reference:     RFC XXXX
```

8. Acknowledgements

The authors would like to thank for following for lively discussions on list and in the halls (ordered by last name): Andy Bierman, Martin Bjorklund, Benoit Claise, Mehmet Ersue, Balazs Kovacs, David Lamparter, Alan Luchuk, Ladislav Lhotka, Radek Krejci, Tom Petch, Juergen Schoenwaelder, Phil Shafer, Sean Turner, Michal Vasko, and Bert Wijnen.

9. References

9.1. Normative References

- [I-D.ietf-netconf-keystore]
Watsen, K., "YANG Data Model for a "Keystore" Mechanism", draft-ietf-netconf-keystore-04 (work in progress), October 2017.
- [I-D.ietf-netconf-trust-anchors]
Watsen, K., "YANG Data Model for Global Trust Anchors", draft-ietf-netconf-trust-anchors-00 (work in progress), June 2018.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC4344] Bellare, M., Kohno, T., and C. Namprempe, "The Secure Shell (SSH) Transport Layer Encryption Modes", RFC 4344, DOI 10.17487/RFC4344, January 2006, <<https://www.rfc-editor.org/info/rfc4344>>.

- [RFC4419] Friedl, M., Provos, N., and W. Simpson, "Diffie-Hellman Group Exchange for the Secure Shell (SSH) Transport Layer Protocol", RFC 4419, DOI 10.17487/RFC4419, March 2006, <<https://www.rfc-editor.org/info/rfc4419>>.
- [RFC5656] Stebila, D. and J. Green, "Elliptic Curve Algorithm Integration in the Secure Shell Transport Layer", RFC 5656, DOI 10.17487/RFC5656, December 2009, <<https://www.rfc-editor.org/info/rfc5656>>.
- [RFC6187] Igoe, K. and D. Stebila, "X.509v3 Certificates for Secure Shell Authentication", RFC 6187, DOI 10.17487/RFC6187, March 2011, <<https://www.rfc-editor.org/info/rfc6187>>.
- [RFC6536] Bierman, A. and M. Bjorklund, "Network Configuration Protocol (NETCONF) Access Control Model", RFC 6536, DOI 10.17487/RFC6536, March 2012, <<https://www.rfc-editor.org/info/rfc6536>>.
- [RFC6668] Bider, D. and M. Baushke, "SHA-2 Data Integrity Verification for the Secure Shell (SSH) Transport Layer Protocol", RFC 6668, DOI 10.17487/RFC6668, July 2012, <<https://www.rfc-editor.org/info/rfc6668>>.
- [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", RFC 7950, DOI 10.17487/RFC7950, August 2016, <<https://www.rfc-editor.org/info/rfc7950>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.

9.2. Informative References

- [OPENSSSH] "OpenSSH", 2016, <<http://www.openssh.com>>.
- [RFC3688] Mealling, M., "The IETF XML Registry", BCP 81, RFC 3688, DOI 10.17487/RFC3688, January 2004, <<https://www.rfc-editor.org/info/rfc3688>>.
- [RFC4252] Ylonen, T. and C. Lonvick, Ed., "The Secure Shell (SSH) Authentication Protocol", RFC 4252, DOI 10.17487/RFC4252, January 2006, <<https://www.rfc-editor.org/info/rfc4252>>.
- [RFC4253] Ylonen, T. and C. Lonvick, Ed., "The Secure Shell (SSH) Transport Layer Protocol", RFC 4253, DOI 10.17487/RFC4253, January 2006, <<https://www.rfc-editor.org/info/rfc4253>>.

- [RFC4254] Ylonen, T. and C. Lonvick, Ed., "The Secure Shell (SSH) Connection Protocol", RFC 4254, DOI 10.17487/RFC4254, January 2006, <<https://www.rfc-editor.org/info/rfc4254>>.
- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", RFC 6241, DOI 10.17487/RFC6241, June 2011, <<https://www.rfc-editor.org/info/rfc6241>>.
- [RFC6242] Wasserman, M., "Using the NETCONF Protocol over Secure Shell (SSH)", RFC 6242, DOI 10.17487/RFC6242, June 2011, <<https://www.rfc-editor.org/info/rfc6242>>.
- [RFC7317] Bierman, A. and M. Bjorklund, "A YANG Data Model for System Management", RFC 7317, DOI 10.17487/RFC7317, August 2014, <<https://www.rfc-editor.org/info/rfc7317>>.
- [RFC8040] Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Protocol", RFC 8040, DOI 10.17487/RFC8040, January 2017, <<https://www.rfc-editor.org/info/rfc8040>>.
- [RFC8071] Watsen, K., "NETCONF Call Home and RESTCONF Call Home", RFC 8071, DOI 10.17487/RFC8071, February 2017, <<https://www.rfc-editor.org/info/rfc8071>>.
- [RFC8340] Bjorklund, M. and L. Berger, Ed., "YANG Tree Diagrams", BCP 215, RFC 8340, DOI 10.17487/RFC8340, March 2018, <<https://www.rfc-editor.org/info/rfc8340>>.

Appendix A. Change Log

A.1. 00 to 01

- o Noted that '0.0.0.0' and ':::' might have special meanings.
- o Renamed "keychain" to "keystore".

A.2. 01 to 02

- o Removed the groupings 'listening-ssh-client-grouping' and 'listening-ssh-server-grouping'. Now modules only contain the transport-independent groupings.
- o Simplified the "client-auth" part in the ietf-ssh-client module. It now inlines what it used to point to keystore for.
- o Added cipher suites for various algorithms into new 'ietf-ssh-common' module.

A.3. 02 to 03

- o Removed 'RESTRICTED' enum from 'password' leaf type.
- o Added a 'must' statement to container 'server-auth' asserting that at least one of the various auth mechanisms must be specified.
- o Fixed description statement for leaf 'trusted-ca-certs'.

A.4. 03 to 04

- o Change title to "YANG Groupings for SSH Clients and SSH Servers"
- o Added reference to RFC 6668
- o Added RFC 8174 to Requirements Language Section.
- o Enhanced description statement for ietf-ssh-server's "trusted-ca-certs" leaf.
- o Added mandatory true to ietf-ssh-client's "client-auth" 'choice' statement.
- o Changed the YANG prefix for module ietf-ssh-common from 'sshcom' to 'sshcmn'.
- o Removed the compression algorithms as they are not commonly configurable in vendors' implementations.

- o Updating descriptions in transport-params-grouping and the servers's usage of it.
- o Now tree diagrams reference ietf-netmod-yang-tree-diagrams
- o Updated YANG to use typedefs around leafrefs to common keystore paths
- o Now inlines key and certificates (no longer a leafref to keystore)

A.5. 04 to 05

- o Merged changes from co-author.

A.6. 05 to 06

- o Updated to use trust anchors from trust-anchors draft (was keystore draft)
- o Now uses new keystore grouping enabling asymmetric key to be either locally defined or a reference to the keystore.

Authors' Addresses

Kent Watsen
Juniper Networks

EEmail: kwatsen@juniper.net

Gary Wu
Cisco Systems

EEmail: garywu@cisco.com