IETF-102

draft-barnes-stir-passport-div-hi-callflows-01 mary.ietf.barnes@gmail.com

July 18, 2018

Background

- Draft-ietf-stir-passport-divert includes an optional "hi" element in the "div" PASSporT:
 - "hi" element contains the index of the related History-Info header field entry
 - Allows correlation of "div" PASSporT with a History-Info header field entry, which
 provides more information as to why the request was retargeted
 - Note: Reason is not captured in the case of TEL URIs
- History-Info header field captures the request URI as requests are retargeted and tags the type of retargeting:
 - "rc": target user remains the same
 - "mp": target user changes to an AOR unassociated with the AOR of the original target user
 - "np": no change in the request URI
- The "div" PASSporT added in the case of an "mp" type of retargeting.

Example

```
PASSporT for initial request:
History-Info: <sip:bob@example.com>;index=1
                                                            { "orig":{"tn":"12155551212"},
History-Info:
                                                              "dest": {"tn":"12155551213"},
<sip: 12155551213@example.com;user=phone?</pre>
                                                              "iat":1443208345 }
            Reason=SIP%3Bcause%3D302>;
            index=1.1;rc=1
                                                     "div" PASSporT
History-Info: <sip:carol@example.com;cause=480>;
                                                          "orig":{"tn":"12155551212"},
            index=1.2;mp=1
                                                          "dest":{"tn":"12155551214"},
History-Info:
                                                          "iat":1443208345,
<sip:12155551214@example.com;user=phone;cause=480>;
                                                          "div":{"tn":"121555551213",
            index=1.2.1;rc=1.2
                                                               "hi":"1.2.1"}}
```

Discussion points

- 1. History-Info captures the new target i.e., when the entry is added it has the same value as the request URI for the request to which it was added.
 - "div" PASSporT added when a request has been retargeted *and* the destination AOR changes to one not associated with the original target
- 2. Is there value in adding more information to the PASSporT related to History-Info?
 - For example, capturing the Reason

Discussion points

- 3. Other use cases to consider?
 - ACD/Contact Center
 - Current scams such as hacking into someone's voicemail, changing greeting that allows the use of acct for collect calls. Latter are typically from international gateways – thus could block calls with GW attestation ("C").

Way Forward

• Is there value in continuing work on the call flows?