

Network Working Group  
Internet-Draft  
Intended status: Informational  
Expires: April 17, 2019

B. Carpenter  
Univ. of Auckland  
B. Liu  
Huawei Technologies  
October 14, 2018

Limited Domains and Internet Protocols  
draft-carpenter-limited-domains-04

Abstract

There is a noticeable trend towards network requirements, behaviours and semantics that are specific to a limited region of the Internet and a particular set of requirements. Policies, default parameters, the options supported, the style of network management and security requirements may vary. This document reviews examples of such limited domains and emerging solutions, and develops a related taxonomy. It then briefly discusses the standardization of protocols for limited domains. Finally, it shows the needs for a precise definition of limited domain membership and for mechanisms to allow nodes to join a domain securely and to find other members, including boundary nodes.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 17, 2019.

Copyright Notice

Copyright (c) 2018 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents

(<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

1. Introduction . . . . .	2
2. Failure Modes in Today's Internet . . . . .	3
3. Examples of Limited Domain Requirements . . . . .	4
4. Examples of Limited Domain Solutions . . . . .	7
5. Taxonomy of Limited Domains . . . . .	9
5.1. The Domain as a Whole . . . . .	10
5.2. Individual Nodes . . . . .	10
5.3. The Domain Boundary . . . . .	10
5.4. Topology . . . . .	11
5.5. Technology . . . . .	11
5.6. Connection to the Internet . . . . .	11
5.7. Security, Trust and Privacy Model . . . . .	12
5.8. Operations . . . . .	12
5.9. Making use of this taxonomy . . . . .	12
6. The Scope of Protocols in Limited Domains . . . . .	12
7. Functional Requirements of Limited Domains . . . . .	14
8. Security Considerations . . . . .	16
9. IANA Considerations . . . . .	16
10. Contributors . . . . .	16
11. Acknowledgements . . . . .	16
12. Informative References . . . . .	16
Appendix A. Change log [RFC Editor: Please remove] . . . . .	21
Authors' Addresses . . . . .	22

## 1. Introduction

As the Internet continues to grow and diversify, with a realistic prospect of tens of billions of nodes being connected directly and indirectly, there is a noticeable trend towards local requirements, behaviours and semantics. The word "local" should be understood in a special sense, however. In some cases it may refer to geographical and physical locality - all the nodes in a single building, on a single campus, or in a given vehicle. In other cases it may refer to a defined set of users or nodes distributed over a much wider area, but drawn together by a single virtual network over the Internet, or a single physical network running partially in parallel with the Internet. We expand on these possibilities below. To capture the topic, this document refers to such networks as "limited domains".

Some people have concerns about splintering of the Internet along political or linguistic boundaries by mechanisms that block the free flow of information across the network. That is not the topic of this document, which does not discuss filtering mechanisms and does not apply to protocols that are designed for use across the whole Internet. It is only concerned with domains that have specific technical requirements.

The word "domain" in this document does not refer to naming domains in the DNS, although in some cases a limited domain might incidentally be congruent with a DNS domain.

The requirements of limited domains will be different in different scenarios. Policies, default parameters, and the options supported may vary. Also, the style of network management may vary, between a completely unmanaged network, one with fully autonomic management, one with traditional central management, and mixtures of the above. Finally, the requirements and solutions for security and privacy may vary.

This document analyses and discusses some of the consequences of this trend, and how it impacts the idea of universal interoperability in the Internet. Firstly we list examples of limited domain scenarios and of technical solutions for limited domains, with the main focus being the Internet layer of the protocol stack. Then we develop a taxonomy of the features to be found in limited domains. With this background, we discuss the resulting challenge to the notion that all Internet standards must be universal in scope and applicability. To the contrary, we assert that some protocols need to be specifically limited in their applicability. This implies that the concepts of a limited domain, and of its membership, need to be formalised and supported by secure mechanisms. While this document does not propose a design for such mechanisms, it does outline some resulting functional requirements.

## 2. Failure Modes in Today's Internet

Today, the Internet does not have a well-defined concept of limited domains. One result of this is that certain protocols and features fail on certain paths. Previously, this has been analysed in terms of transparency [RFC2775], [RFC4924] or of intrusive middleboxes [RFC3234], [RFC7663], [I-D.dolson-plus-middlebox-benefits]. Unfortunately the problems persist, both in application protocols, and even in very fundamental mechanisms. For example, the Internet is not transparent to IPv6 extension headers [RFC7872], and Path MTU Discovery has been unreliable for many years [RFC2923], [RFC4821]. IP fragmentation is also unreliable

[I-D.bonica-intarea-frag-fragile], and problems in TCP MSS negotiation have been reported [I-D.andrews-tcp-and-ipv6-use-minmtu].

On the security side, the widespread insertion of firewalls at domain boundaries that are perceived by humans but unknown to protocols results in arbitrary failure modes as far as the application layer is concerned.

This situation is not acceptable, so it seems that a new approach is needed.

### 3. Examples of Limited Domain Requirements

This section describes various examples where limited domain requirements can easily be identified, either based on an application scenario or on a technical imperative. It is of course not a complete list, and it is presented in an arbitrary order, loosely from smaller to bigger.

1. A home network. It will be unmanaged, constructed by a non-specialist, and will possibly include wiring errors such as physical loops. It must work with devices "out of the box" as shipped by their manufacturers and must create adequate security by default. Remote access may be required. The requirements and applicable principles are summarised in [RFC7368].
2. A small office network. This is sometimes very similar to a home network, if whoever is in charge has little or no specialist knowledge, but may have differing security and privacy requirements. In other cases it may be professionally constructed using recommended products and configurations, but operate unmanaged. Remote access may be required.
3. A vehicle network. This will be designed by the vehicle manufacturer but may include devices added by the vehicle's owner or operator. Parts of the network will have demanding performance and reliability requirements with implications for human safety. Remote access may be required to certain functions, but absolutely forbidden for others. Communication with other vehicles, roadside infrastructure, and external data sources will be required. See [I-D.ietf-ipwave-vehicular-networking] for a survey of use cases.
4. Supervisory Control And Data Acquisition (SCADA) networks, and other hard real time networks. These will exhibit specific technical requirements, including tough real-time performance targets. See for example [I-D.ietf-detnet-use-cases] for

numerous use cases. An example is a building services network. This will be designed specifically for a particular building, but using standard components. Additional devices may need to be added at any time. Parts of the network may have demanding reliability requirements with implications for human safety. Remote access may be required to certain functions, but absolutely forbidden for others.

5. Sensor networks. The two preceding cases will all include sensors, but some networks may be specifically limited to sensors and the collection and processing of sensor data. They may be in remote or technically challenging locations and installed by non-specialists.
6. Internet of Things (IoT) networks. While this term is very flexible and covers many innovative types of network, including ad hoc networks that are formed spontaneously, it seems reasonable to expect that IoT edge networks will have special requirements and protocols that are useful only within a specific domain, and that these protocols cannot, and for security reasons should not, run over the Internet as a whole.
7. An important subclass of IoT networks consists of constrained networks [RFC7228] in which the nodes are limited in power consumption and communications bandwidth, and are therefore limited to using very frugal protocols.
8. Delay tolerant networks may consist of domains that are relatively isolated and constrained in power (e.g. deep space networks) and are connected only intermittently to the outside, with a very long latency on such connections [RFC4838]. Clearly the protocol requirements and possibilities are very specialised in such networks.
9. "Traditional" enterprise and campus networks, which may be spread over many kilometres and over multiple separate sites, with multiple connections to the Internet. Interestingly, the IETF appears never to have analysed this long-established class of networks in a general way, except in connection with IPv6 deployment (e.g. [RFC7381]).
10. Data centres and hosting centres, or distributed services acting as such centres. These will have high performance, security and privacy requirements and will typically include large numbers of independent "tenant" networks overlaid on shared infrastructure.

11. Content Delivery Networks (CDNs), comprising distributed data centres and the paths between them, spanning thousands of kilometres, with numerous connections to the Internet.
12. Massive Web Service Provider Networks. This is a small class of networks with well known trademarked names, combining aspects of distributed enterprise networks, data centres and CDNs. They have their own international networks bypassing the generic carriers. Like CDNs, they have numerous connections to the Internet, typically offering a tailored service in each economy.

Three other aspects, while not tied to specific network types, also strongly depend on the concept of limited domains:

1. Intent Based Networking. In this concept, a network domain is configured and managed in accordance with an abstract policy known as "Intent", to ensure that the network performs as required [I-D.moulchan-nmrg-network-intent-concepts]. Whatever technologies are used to support this, they will be applied within the domain boundary.
2. Many of the above types of network may be extended throughout the Internet by a variety of virtual private network (VPN) techniques. Therefore we may argue that limited domains may overlap each other in an arbitrary fashion by use of virtualization techniques.
3. Network Slicing. A network slice is a virtual network that consists of a managed set of resources carved off from a larger network [I-D.geng-netslices-architecture]. Whatever technologies are used to support slicing, they will require a clear definition of the boundary of a given slice.

While it is clearly desirable to use common solutions, and therefore common standards, wherever possible, it is increasingly difficult to do so while satisfying the widely varying requirements outlined above. However, there is a tendency when new protocols and protocol extensions are proposed to always ask the question "How will this work across the open Internet?" This document suggests that this is not always the right question. There are protocols and extensions that are not intended to work across the open Internet. On the contrary, their requirements and semantics are specifically limited (in the sense defined above).

A common argument is that if a protocol is intended for limited use, the chances are very high that it will in fact be used (or misused) in other scenarios including the so-called open Internet. This is undoubtedly true and means that limited use is not an excuse for bad

design or poor security. In fact, a limited use requirement potentially adds complexity to both the protocol and its security design, as discussed later.

Nevertheless, because of the diversity of limited environments with specific requirements that is now emerging, specific standards will necessarily emerge. There will be attempts to capture each market sector, but the market will demand standardised limited solutions. However, the "open Internet" must remain as the universal method of interconnection. Reconciling these two aspects is a major challenge.

#### 4. Examples of Limited Domain Solutions

This section lists various examples of specific limited domain solutions that have been proposed or defined. It intentionally does not include Layer 2 technology solutions, which by definition apply to limited domains.

1. Differentiated Services. This mechanism [RFC2474] allows a network to assign locally significant values to the 6-bit Differentiated Services Code Point field in any IP packet. Although there are some recommended codepoint values for specific per-hop queue management behaviours, these are specifically intended to be domain-specific codepoints with traffic being classified, conditioned and re-marked at domain boundaries (unless there is an inter-domain agreement that makes re-marking unnecessary).
2. Network function virtualisation. As described in [I-D.irtf-nfvrg-gaps-network-virtualization], this general concept is an open research topic, in which virtual network functions are orchestrated as part of a distributed system. Inevitably such orchestration applies to an administrative domain of some kind, even though cross-domain orchestration is also a research area.
3. Service Function Chaining (SFC). This technique [RFC7665] assumes that services within a network are constructed as sequences of individual functions within a specific SFC-enabled domain. As that RFC states: "Specific features may need to be enforced at the boundaries of an SFC-enabled domain, for example to avoid leaking SFC information". A Network Service Header (NSH) [RFC8300] is used to encapsulate packets flowing through the service function chain: "The intended scope of the NSH is for use within a single provider's operational domain."
4. Firewall and Service Tickets (FAST). Such tickets would accompany a packet to claim the right to traverse a network or

request a specific network service [I-D.herbert-fast]". They would only be valid within a particular domain.

5. Data Centre Network Virtualization Overlays. A common requirement in data centres that host many tenants (clients) is to provide each one with a secure private network, all running over the same physical infrastructure. [RFC8151] describes various use cases for this, and specifications are under development. These include use cases in which the tenant network is physically split over several data centres, but which must appear to the user as a single secure domain.
6. Segment Routing. This is a technique which "steers a packet through an ordered list of instructions, called segments" [I-D.ietf-spring-segment-routing]. The semantics of these instructions are explicitly local to a segment routing domain or even to a single node. Technically, these segments or instructions are represented as an MPLS label or an IPv6 address, which clearly adds a semantic interpretation to them within the domain.
7. Autonomic Networking. As explained in [I-D.ietf-anima-reference-model], an autonomic network is also a security domain within which an autonomic control plane [I-D.ietf-anima-autonomic-control-plane] is used by service agents. These service agents manage technical objectives, which may be locally defined, subject to domain-wide policy. Thus the domain boundary is important for both security and protocol purposes.
8. Homenet. As shown in [RFC7368], a home networking domain has specific protocol needs that differ from those in an enterprise network or the Internet as a whole. These include the Home Network Control Protocol (HNCP) [RFC7788] and a naming and discovery solution [I-D.ietf-homenet-simple-naming].
9. Creative uses of IPv6 features. As IPv6 enters more general use, engineers notice that it has much more flexibility than IPv4. Innovative suggestions have been made for:
  - \* The flow label, e.g. [RFC6294], [I-D.fioccola-v6ops-ipv6-alt-mark].
  - \* Extension headers, e.g. for segment routing [I-D.ietf-6man-segment-routing-header].
  - \* Meaningful address bits, e.g. [I-D.jiang-semantic-prefix]. Also, segment routing uses IPv6 addresses as segment

identifiers with specific local meanings  
[I-D.ietf-spring-segment-routing].

All of these suggestions are only viable within a specified domain. The case of the extension header is particularly interesting, since its existence has been a major "selling point" for IPv6, but it is notorious that new extension headers are virtually impossible to deploy across the whole Internet [RFC7045], [RFC7872]. It is worth noting that extension header filtering is considered as an important security issue [I-D.ietf-opsec-ipv6-eh-filtering]. There is considerable appetite among vendors or operators to have flexibility in defining extension headers for use in limited or specialised domains, e.g. [I-D.voyer-6man-extension-header-insertion] and [BIGIP].

10. Deterministic Networking (DetNet). The Deterministic Networking Architecture [I-D.ietf-detnet-architecture] and encapsulation [I-D.ietf-detnet-dp-sol] aim to support flows with extremely low data loss rates and bounded latency, but only within a part of the network that is "DetNet aware". Thus, as for differentiated services above, the concept of a domain is fundamental.
11. Provisioning Domains (PvDs). An architecture for Multiple Provisioning Domains has been defined [RFC7556] to allow hosts attached to multiple networks to learn explicit details about the services provided by each of those networks.

## 5. Taxonomy of Limited Domains

This section develops a taxonomy for describing limited domains. Several major aspects are considered in this taxonomy:

- o The domain as a whole.
- o The individual nodes.
- o The domain boundary.
- o The domain's topology.
- o The domain's technology.
- o How the domain connects to the Internet.
- o The security, trust and privacy model.
- o Operations.

The following sub-sections analyse each of these aspects.

#### 5.1. The Domain as a Whole

- o Why does the domain exist? (e.g., human choice, administrative policy, orchestration requirements, technical requirements)
- o If there are special requirements, are they at Layer 2, Layer 3 or an upper layer?
- o Is the domain managed by humans or fully autonomic?
- o If managed, what style of management applies? (Manual configuration, automated configuration, orchestration?)
- o Is there a policy model? (Intent, configuration policies?)
- o Does the domain provide controlled or paid service or open access?

#### 5.2. Individual Nodes

- o Is a domain member a complete node, or only one interface of a node?
- o Are nodes permanent members of a given domain, or are join and leave operations possible?
- o Are nodes physical or virtual devices?
- o Are virtual nodes general-purpose, or limited to specific functions, applications or users?
- o Are nodes constrained (by battery etc)?
- o Are devices installed "out of the box" or pre-configured?

#### 5.3. The Domain Boundary

- o How is the domain boundary identified or defined?
- o Is the domain boundary fixed or dynamic?
- o Are boundary nodes special? Or can any node be at the boundary?

#### 5.4. Topology

- o Is the domain a subset of a layer 2 or 3 connectivity domain?
- o In IP addressing terms, is the domain Link-local, Site-local, or Global?
- o Does the domain overlap other domains? (In other words, a node may or may not be allowed to be a member of multiple domains.)
- o Does the domain match physical topology, or does it have a virtual (overlay) topology?
- o Is the domain in a single building, vehicle or campus? Or is it distributed?
- o If distributed, are the interconnections private or over the Internet?
- o In IP addressing terms, is the domain Link-local, Site-local, or Global?

#### 5.5. Technology

- o In routing terms, what routing protocol(s) are used, or even different forwarding mechanisms (MPLS or other non-IP mechanism)?
- o In an overlay domain, what overlay technique is used (L2VPN, L3VPN, ...)?
- o Are there specific QoS requirements?
- o Link latency - normal or long latency links?
- o Mobility - are nodes mobile? Is the whole network mobile?
- o Which specific technologies, such as those in Section 4, are applicable?

#### 5.6. Connection to the Internet

- o Is the Internet connection permanent or intermittent? (Never connected is out of scope.)
- o What traffic is blocked, in and out?
- o What traffic is allowed, in and out?

- o What traffic is transformed, in and out?
- o Is secure and privileged remote access needed?
- o Does the domain allow unprivileged remote sessions?

#### 5.7. Security, Trust and Privacy Model

- o Must domain members be authorized?
- o Are all nodes in the domain at the same trust level?
- o Is traffic authenticated?
- o Is traffic encrypted?
- o What is hidden from the outside?

#### 5.8. Operations

- o Safety level - does the domain have a critical (human) safety role?
- o Reliability requirement - normal or 99.999% ?
- o Environment - hazardous conditions?
- o Installation - are specialists needed?
- o Service visits - easy, difficult, impossible?
- o Software/firmware updates - possible or impossible?

#### 5.9. Making use of this taxonomy

This taxonomy could be used to design or analyse a specific type of limited domain. For the present document, it is intended to form a background to the following two sections, concerning the scope of protocols used in limited domains, and mechanisms required to securely define domain membership and properties.

### 6. The Scope of Protocols in Limited Domains

One consequence of the deployment of limited domains in the Internet is that some protocols will be designed, extended or configured so that they only work correctly between end systems in such domains. This is to some extent encouraged by some existing standards and by the assignment of code points for local or experimental use. In any

case it cannot be prevented. Also, by endorsing efforts such as Service Function Chaining, Segment Routing and Deterministic Networking, the IETF is in effect encouraging such deployments. Furthermore, it seems inevitable, if the "Internet of Things" becomes reality, that millions of edge networks containing completely novel types of node will be connected to the Internet; each one of these edge networks will be a limited domain.

It is therefore appropriate to discuss whether protocols or protocol extensions should sometimes be standardised to interoperate only within a Limited Domain Boundary. Such protocols would not be required to interoperate across the Internet as a whole. Several possibly overlapping scenarios could then arise:

A. If a limited domain is split into two parts connected over the Internet directly at the IP layer (i.e. with no tunnel encapsulating the packets), a limited-domain protocol could be operated between those two parts regardless of its special nature, as long as it respects standard IP formats and is not arbitrarily blocked by firewalls. A simple example is any protocol using a port number assigned to a specific non-IETF protocol.

Such a protocol could reasonably be described as an "inter-domain" protocol because the Internet is transparent to it, even if it is meaningless except in the two parts of the limited domain. This is of course nothing new in the Internet architecture.

B. If a limited-domain protocol does not respect standard IP formats (for example, if it includes a non-standard IPv6 extension header), it could not be operated between two parts of a domain split at the IP layer.

Such a protocol could reasonably be described as an "intra-domain" protocol, and the Internet is opaque to it.

C. If a limited-domain protocol is clearly specified to be invalid outside its domain of origin, neither scenario A nor B applies. The two domains need to be unified as a single virtual domain. For example, an encapsulating tunnel between the parts of the split domain could be used. Also, nodes at the domain boundary must drop all packets using the limited-domain protocol.

D. If a limited-domain protocol has domain-specific variants, such that implementations in different domains could not interoperate if those domains were unified by some mechanism, the protocol is not interoperable in the normal sense. If two domains using it were merged, the protocol might fail unpredictably. A simple example is any protocol using a port number assigned for

experimental use. Such a protocol usually also falls into scenario C.

To provide an existing example, consider Differentiated Services [RFC2474]. A packet containing any value whatever in the 6 bits of the Differentiated Service Code Point (DSCP) is well-formed and falls into scenario A. However, because the semantics of DSCP values are locally significant, the packet also falls into scenario D. In fact, differentiated services are only interoperable across domain boundaries if there is a corresponding agreement between the operators; otherwise a specific gateway function is required for meaningful interoperability. Much more detailed discussion is to be found in [RFC2474] and [RFC8100].

To provide a provocative example, consider the proposal in [I-D.voyer-6man-extension-header-insertion] that the restrictions in [RFC8200] should be relaxed to allow IPv6 extension headers to be inserted on the fly in IPv6 packets. If this is done in such a way that the affected packets can never leave the specific limited domain in which they were modified, scenario C applies. If the semantic content of the inserted headers is locally defined, scenario D also applies. In neither case is the Internet disturbed.

We conclude that it is reasonable to explicitly define limited-domain protocols, either as standards or as proprietary mechanisms, as long as they describe which of the above scenarios apply and they clarify how the domain is defined. As long as all relevant standards are respected outside the domain boundary, a well-specified limited-domain protocol is not harmful to the Internet. However, as described in the next section, mechanisms are needed to support domain membership operations.

## 7. Functional Requirements of Limited Domains

As the preceding taxonomy shows, there are very numerous aspects to a domain, so the common features are not immediately obvious. It would be possible, but tedious, to apply the taxonomy to each of the domain types described in Section 3. However, we can deduce some generally required features and functions without doing so.

Firstly, if we drew a topology map, any domain -- virtual or physical -- will have a well defined boundary between "inside" and "outside". However, that boundary in itself has no technical meaning. What matters in reality is whether a node is a member of the domain, and whether it is at the boundary between the domain and the rest of the Internet. Thus the boundary in itself does not need to be identified. However, a sending node needs to know whether it is sending to an inside or outside destination; a receiving node needs

to know whether a packet originated inside or outside; and a boundary node needs to know which of its interfaces are inward-facing or outward-facing. It is irrelevant whether the interfaces involved are physical or virtual.

With this perspective, we can list some general functional requirements. An underlying assumption here is that domain membership operations should be cryptographically secured; a domain without such security cannot be reliably protected from attack.

1. Domain Identity. A domain must have a unique and verifiable identifier; effectively this should be a public key for the domain. Without this, there is no way to secure domain operations and domain membership. The holder of the corresponding private key becomes the trust anchor for the domain.
2. Node Eligibility. It must be possible for a node to determine which domain(s) it can potentially join, and on which interface(s).
3. Secure Enrolment. A node must be able to enrol in a given domain via secure node identification and to acquire relevant security credentials (authorization) for operations within the domain. If a node has multiple physical or virtual interfaces, they may require to be individually enrolled.
4. Withdrawal. A node must be able to cancel enrolment in a given domain.
5. Dynamic Membership. Optionally, a node should be able temporarily leave or rejoin a domain (i.e. enrolment is persistent but membership is intermittent).
6. Role, implying authorization to perform a certain set of actions. A node must have a verifiable role. In the simplest case, the choices of role are "interior node" and "boundary node". In a boundary node, individual interfaces may have different roles, e.g. "inward facing" and "outward facing".
7. Verify Peer. A node must be able to verify whether another node is a member of the domain.
8. Verify Role. A node must be able to learn the verified role of another node. In particular, it must be possible for a node to find boundary nodes (interfacing to the Internet).

9. Domain Data. In a domain with management requirements, it must be possible for a node to acquire domain policy and/or domain configuration data. This would include, for example, filtering policy to ensure that inappropriate packets do not leave the domain.

These requirements could form the basis for further analysis and solution design.

## 8. Security Considerations

Clearly, the boundary of a limited domain will almost always also act as a security boundary. In particular, it will serve as a trust boundary, and as a boundary of authority for defining capabilities. Within the boundary, limited-domain protocols or protocol features will be useful, but they will be meaningless if they enter or leave the domain.

The security model for a limited-scope protocol must allow for the boundary, and in particular for a trust model that changes at the boundary. Typically, credentials will need to be signed by a domain-specific authority.

## 9. IANA Considerations

This document makes no request of the IANA.

## 10. Contributors

Sheng Jiang made important contributions to this document.

## 11. Acknowledgements

Useful comments were received from Amelia Andersdotter, Edward Birrane, Ron Bonica, Tim Chown, Darren Dukes, Tom Herbert, John Klensin, Michael Richardson, Rick Taylor, Niels ten Oever, and other members of the ANIMA and INTAREA WGs.

## 12. Informative References

[BIGIP] Li, R., "HUAWAI - Big IP Initiative.", 2018, <<https://www.iaria.org/announcements/HuaweiBigIP.pdf>>.

[I-D.andrews-tcp-and-ipv6-use-minmtu] Andrews, M., "TCP Fails To Respect IPV6\_USE\_MIN\_MTU", draft-andrews-tcp-and-ipv6-use-minmtu-04 (work in progress), October 2015.

- [I-D.bonica-intarea-frag-fragile]  
Bonica, R., Baker, F., Huston, G., Hinden, R., Troan, O.,  
and F. Gont, "IP Fragmentation Considered Fragile", draft-  
bonica-intarea-frag-fragile-03 (work in progress), July  
2018.
- [I-D.dolson-plus-middlebox-benefits]  
Dolson, D., Snellman, J., Boucadair, M., and C. Jacquenet,  
"Beneficial Functions of Middleboxes", draft-dolson-plus-  
middlebox-benefits-03 (work in progress), March 2017.
- [I-D.fioccola-v6ops-ipv6-alt-mark]  
Fioccola, G., Velde, G., Cociglio, M., and P. Muley, "IPv6  
Performance Measurement with Alternate Marking Method",  
draft-fioccola-v6ops-ipv6-alt-mark-01 (work in progress),  
June 2018.
- [I-D.geng-netslices-architecture]  
67, 4., Dong, J., Bryant, S., kiran.makhijani@huawei.com,  
k., Galis, A., Foy, X., and S. Kuklinski, "Network Slicing  
Architecture", draft-geng-netslices-architecture-02 (work  
in progress), July 2017.
- [I-D.herbert-fast]  
Herbert, T., "Firewall and Service Tickets", draft-  
herbert-fast-03 (work in progress), September 2018.
- [I-D.ietf-6man-segment-routing-header]  
Filsfils, C., Previdi, S., Leddy, J., Matsushima, S., and  
d. daniel.voyer@bell.ca, "IPv6 Segment Routing Header  
(SRH)", draft-ietf-6man-segment-routing-header-14 (work in  
progress), June 2018.
- [I-D.ietf-anima-autonomic-control-plane]  
Eckert, T., Behringer, M., and S. Bjarnason, "An Autonomic  
Control Plane (ACP)", draft-ietf-anima-autonomic-control-  
plane-18 (work in progress), August 2018.
- [I-D.ietf-anima-reference-model]  
Behringer, M., Carpenter, B., Eckert, T., Ciavaglia, L.,  
and J. Nobre, "A Reference Model for Autonomic  
Networking", draft-ietf-anima-reference-model-08 (work in  
progress), October 2018.
- [I-D.ietf-detnet-architecture]  
Finn, N., Thubert, P., Varga, B., and J. Farkas,  
"Deterministic Networking Architecture", draft-ietf-  
detnet-architecture-08 (work in progress), September 2018.

- [I-D.ietf-detnet-dp-sol]  
Korhonen, J., Andersson, L., Jiang, Y., Finn, N., Varga, B., Farkas, J., Bernardos, C., Mizrahi, T., and L. Berger, "DetNet Data Plane Encapsulation", draft-ietf-detnet-dp-sol-04 (work in progress), March 2018.
- [I-D.ietf-detnet-use-cases]  
Grossman, E., "Deterministic Networking Use Cases", draft-ietf-detnet-use-cases-19 (work in progress), October 2018.
- [I-D.ietf-homenet-simple-naming]  
Lemon, T., Migault, D., and S. Cheshire, "Simple Homenet Naming and Service Discovery Architecture", draft-ietf-homenet-simple-naming-02 (work in progress), July 2018.
- [I-D.ietf-ipwave-vehicular-networking]  
Jeong, J., "IP Wireless Access in Vehicular Environments (IPWAVE): Problem Statement and Use Cases", draft-ietf-ipwave-vehicular-networking-04 (work in progress), July 2018.
- [I-D.ietf-opsec-ipv6-eh-filtering]  
Gont, F. and W. LIU, "Recommendations on the Filtering of IPv6 Packets Containing IPv6 Extension Headers", draft-ietf-opsec-ipv6-eh-filtering-06 (work in progress), July 2018.
- [I-D.ietf-spring-segment-routing]  
Filsfils, C., Previdi, S., Ginsberg, L., Decraene, B., Litkowski, S., and R. Shakir, "Segment Routing Architecture", draft-ietf-spring-segment-routing-15 (work in progress), January 2018.
- [I-D.irtf-nfvrg-gaps-network-virtualization]  
Bernardos, C., Rahman, A., Zuniga, J., Contreras, L., Aranda, P., and P. Lynch, "Network Virtualization Research Challenges", draft-irtf-nfvrg-gaps-network-virtualization-10 (work in progress), September 2018.
- [I-D.jiang-semantic-prefix]  
Jiang, S., Qiong, Q., Farrer, I., Bo, Y., and T. Yang, "Analysis of Semantic Embedded IPv6 Address Schemas", draft-jiang-semantic-prefix-06 (work in progress), July 2013.

- [I-D.moulchan-nmrg-network-intent-concepts]  
Sivakumar, K. and M. Chandramouli, "Concepts of Network Intent", draft-moulchan-nmrg-network-intent-concepts-00 (work in progress), October 2017.
- [I-D.voyer-6man-extension-header-insertion]  
daniel.voyer@bell.ca, d., Leddy, J., Filsfils, C., Dukes, D., Previdi, S., and S. Matsushima, "Insertion of IPv6 Segment Routing Headers in a Controlled Domain", draft-voyer-6man-extension-header-insertion-04 (work in progress), June 2018.
- [RFC2474] Nichols, K., Blake, S., Baker, F., and D. Black, "Definition of the Differentiated Services Field (DS Field) in the IPv4 and IPv6 Headers", RFC 2474, DOI 10.17487/RFC2474, December 1998, <<https://www.rfc-editor.org/info/rfc2474>>.
- [RFC2775] Carpenter, B., "Internet Transparency", RFC 2775, DOI 10.17487/RFC2775, February 2000, <<https://www.rfc-editor.org/info/rfc2775>>.
- [RFC2923] Lahey, K., "TCP Problems with Path MTU Discovery", RFC 2923, DOI 10.17487/RFC2923, September 2000, <<https://www.rfc-editor.org/info/rfc2923>>.
- [RFC3234] Carpenter, B. and S. Brim, "Middleboxes: Taxonomy and Issues", RFC 3234, DOI 10.17487/RFC3234, February 2002, <<https://www.rfc-editor.org/info/rfc3234>>.
- [RFC4821] Mathis, M. and J. Heffner, "Packetization Layer Path MTU Discovery", RFC 4821, DOI 10.17487/RFC4821, March 2007, <<https://www.rfc-editor.org/info/rfc4821>>.
- [RFC4838] Cerf, V., Burleigh, S., Hooke, A., Torgerson, L., Durst, R., Scott, K., Fall, K., and H. Weiss, "Delay-Tolerant Networking Architecture", RFC 4838, DOI 10.17487/RFC4838, April 2007, <<https://www.rfc-editor.org/info/rfc4838>>.
- [RFC4924] Aboba, B., Ed. and E. Davies, "Reflections on Internet Transparency", RFC 4924, DOI 10.17487/RFC4924, July 2007, <<https://www.rfc-editor.org/info/rfc4924>>.
- [RFC6294] Hu, Q. and B. Carpenter, "Survey of Proposed Use Cases for the IPv6 Flow Label", RFC 6294, DOI 10.17487/RFC6294, June 2011, <<https://www.rfc-editor.org/info/rfc6294>>.

- [RFC7045] Carpenter, B. and S. Jiang, "Transmission and Processing of IPv6 Extension Headers", RFC 7045, DOI 10.17487/RFC7045, December 2013, <<https://www.rfc-editor.org/info/rfc7045>>.
- [RFC7228] Bormann, C., Ersue, M., and A. Keranen, "Terminology for Constrained-Node Networks", RFC 7228, DOI 10.17487/RFC7228, May 2014, <<https://www.rfc-editor.org/info/rfc7228>>.
- [RFC7368] Chown, T., Ed., Arkko, J., Brandt, A., Troan, O., and J. Weil, "IPv6 Home Networking Architecture Principles", RFC 7368, DOI 10.17487/RFC7368, October 2014, <<https://www.rfc-editor.org/info/rfc7368>>.
- [RFC7381] Chittimaneni, K., Chown, T., Howard, L., Kuarsingh, V., Pouffary, Y., and E. Vyncke, "Enterprise IPv6 Deployment Guidelines", RFC 7381, DOI 10.17487/RFC7381, October 2014, <<https://www.rfc-editor.org/info/rfc7381>>.
- [RFC7556] Anipko, D., Ed., "Multiple Provisioning Domain Architecture", RFC 7556, DOI 10.17487/RFC7556, June 2015, <<https://www.rfc-editor.org/info/rfc7556>>.
- [RFC7663] Trammell, B., Ed. and M. Kuehlewind, Ed., "Report from the IAB Workshop on Stack Evolution in a Middlebox Internet (SEMI)", RFC 7663, DOI 10.17487/RFC7663, October 2015, <<https://www.rfc-editor.org/info/rfc7663>>.
- [RFC7665] Halpern, J., Ed. and C. Pignataro, Ed., "Service Function Chaining (SFC) Architecture", RFC 7665, DOI 10.17487/RFC7665, October 2015, <<https://www.rfc-editor.org/info/rfc7665>>.
- [RFC7788] Stenberg, M., Barth, S., and P. Pfister, "Home Networking Control Protocol", RFC 7788, DOI 10.17487/RFC7788, April 2016, <<https://www.rfc-editor.org/info/rfc7788>>.
- [RFC7872] Gont, F., Linkova, J., Chown, T., and W. Liu, "Observations on the Dropping of Packets with IPv6 Extension Headers in the Real World", RFC 7872, DOI 10.17487/RFC7872, June 2016, <<https://www.rfc-editor.org/info/rfc7872>>.
- [RFC8100] Geib, R., Ed. and D. Black, "Diffserv-Interconnection Classes and Practice", RFC 8100, DOI 10.17487/RFC8100, March 2017, <<https://www.rfc-editor.org/info/rfc8100>>.

- [RFC8151] Yong, L., Dunbar, L., Toy, M., Isaac, A., and V. Manral, "Use Cases for Data Center Network Virtualization Overlay Networks", RFC 8151, DOI 10.17487/RFC8151, May 2017, <<https://www.rfc-editor.org/info/rfc8151>>.
- [RFC8200] Deering, S. and R. Hinden, "Internet Protocol, Version 6 (IPv6) Specification", STD 86, RFC 8200, DOI 10.17487/RFC8200, July 2017, <<https://www.rfc-editor.org/info/rfc8200>>.
- [RFC8300] Quinn, P., Ed., Elzur, U., Ed., and C. Pignataro, Ed., "Network Service Header (NSH)", RFC 8300, DOI 10.17487/RFC8300, January 2018, <<https://www.rfc-editor.org/info/rfc8300>>.

Appendix A. Change log [RFC Editor: Please remove]

draft-carpenter-limited-domains-00, 2018-06-11:  
Initial version

draft-carpenter-limited-domains-01, 2018-07-01:  
Minor terminology clarifications

draft-carpenter-limited-domains-02, 2018-08-03:  
Additions following IETF102 discussions  
Updated authorship/contributors

draft-carpenter-limited-domains-03, 2018-09-12:  
First draft of taxonomy  
Editorial improvements

draft-carpenter-limited-domains-04, 2018-10-14:  
Reorganized section 3  
Newly written sections 6 and 7  
Editorial improvements

Authors' Addresses

Brian Carpenter  
Department of Computer Science  
University of Auckland  
PB 92019  
Auckland 1142  
New Zealand

Email: [brian.e.carpenter@gmail.com](mailto:brian.e.carpenter@gmail.com)

Bing Liu  
Huawei Technologies  
Q14, Huawei Campus  
No.156 Beiqing Road  
Hai-Dian District, Beijing 100095  
P.R. China

Email: [leo.liubing@huawei.com](mailto:leo.liubing@huawei.com)