

LAMPS WG
Internet-Draft
Updates: 3279 (if approved)
Intended status: Standards Track
Expires: January 22, 2020

P. Kampanakis
Cisco Systems
Q. Dang
NIST
July 21, 2019

Internet X.509 Public Key Infrastructure: Additional Algorithm
Identifiers for RSASSA-PSS and ECDSA using SHAKEs
draft-ietf-lamps-pkix-shake-15

Abstract

Digital signatures are used to sign messages, X.509 certificates and CRLs. This document updates the "Algorithms and Identifiers for the Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List Profile" (RFC3279) and describes the conventions for using the SHAKE function family in Internet X.509 certificates and revocation lists as one-way hash functions with the RSA Probabilistic signature and ECDSA signature algorithms. The conventions for the associated subject public keys are also described.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on January 22, 2020.

Copyright Notice

Copyright (c) 2019 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents

carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1. Change Log	2
2. Introduction	5
3. Terminology	5
4. Identifiers	5
5. Use in PKIX	6
5.1. Signatures	6
5.1.1. RSASSA-PSS Signatures	7
5.1.2. ECDSA Signatures	8
5.2. Public Keys	9
6. IANA Considerations	9
7. Security Considerations	10
8. Acknowledgements	10
9. References	11
9.1. Normative References	11
9.2. Informative References	12
Appendix A. ASN.1 module	13
Authors' Addresses	17

1. Change Log

[EDNOTE: Remove this section before publication.]

- o draft-ietf-lamps-pkix-shake-15:
 - * Minor editorial nits.
- o draft-ietf-lamps-pkix-shake-14:
 - * Fixing error with incorrect preimage resistance bits for SHA128 and SHA256.
- o draft-ietf-lamps-pkix-shake-13:
 - * Addressing one applicable comment from Dan M. about sec levels while in secdir review of draft-ietf-lamps-cms-shakes.
 - * Addressing comment from Scott B.'s opsdirev review about references in the abstract.
- o draft-ietf-lamps-pkix-shake-12:

- * Nits identified by Roman, Eric V. Ben K., Barry L. in ballot position review.
- o draft-ietf-lamps-pkix-shake-11:
 - * Nits identified by Roman in AD Review.
- o draft-ietf-lamps-pkix-shake-10:
 - * Updated IANA considerations section to request for OID assignments.
- o draft-ietf-lamps-pkix-shake-09:
 - * Fixed minor text nits.
 - * Added text name allocation for SHAKEs in IANA considerations.
 - * Updates in Sec Considerations section.
- o draft-ietf-lamps-pkix-shake-08:
 - * Small nits from Russ while in WGLC.
- o draft-ietf-lamps-pkix-shake-07:
 - * Incorporated Eric's suggestion from WGLC.
- o draft-ietf-lamps-pkix-shake-06:
 - * Added informative references.
 - * Updated ASN.1 so it compiles.
 - * Updated IANA considerations.
- o draft-ietf-lamps-pkix-shake-05:
 - * Added RFC8174 reference and text.
 - * Explicitly explained why RSASSA-PSS-params are omitted in section 5.1.1.
 - * Simplified Public Keys section by removing redundant info from RFCs.
- o draft-ietf-lamps-pkix-shake-04:

- * Removed paragraph suggesting KMAC to be used in generating k in Deterministic ECDSA. That should be RFC6979-bis.
- * Removed paragraph from Security Considerations that talks about randomness of k because we are using deterministic ECDSA.
- * Various ASN.1 fixes.
- * Text fixes.
- o draft-ietf-lamps-pkix-shake-03:
 - * Updates based on suggestions and clarifications by Jim.
 - * Added ASN.1.
- o draft-ietf-lamps-pkix-shake-02:
 - * Significant reorganization of the sections to simplify the introduction, the new OIDs and their use in PKIX.
 - * Added new OIDs for RSASSA-PSS that hardcode hash, salt and MGF, according the WG consensus.
 - * Updated Public Key section to use the new RSASSA-PSS OIDs and clarify the algorithm identifier usage.
 - * Removed the no longer used SHAKE OIDs from section 3.1.
 - * Consolidated subsection for message digest algorithms.
 - * Text fixes.
- o draft-ietf-lamps-pkix-shake-01:
 - * Changed titles and section names.
 - * Removed DSA after WG discussions.
 - * Updated shake OID names and parameters, added MGF1 section.
 - * Updated RSASSA-PSS section.
 - * Added Public key algorithm OIDs.
 - * Populated Introduction and IANA sections.
- o draft-ietf-lamps-pkix-shake-00:

* Initial version

2. Introduction

[RFC3279] defines cryptographic algorithm identifiers for the Internet X.509 Certificate and Certificate Revocation Lists (CRL) profile [RFC5280]. This document updates RFC3279 and defines identifiers for several cryptographic algorithms that use variable length output SHAKE functions introduced in [SHA3] which can be used with .

In the SHA-3 family, two extendable-output functions (SHAKEs), SHAKE128 and SHAKE256, are defined. Four other hash function instances, SHA3-224, SHA3-256, SHA3-384, and SHA3-512, are also defined but are out of scope for this document. A SHAKE is a variable length hash function defined as $\text{SHAKE}(M, d)$ where the output is a d -bits-long digest of message M . The corresponding collision and second-preimage-resistance strengths for SHAKE128 are $\min(d/2, 128)$ and $\min(d, 128)$ bits, respectively (Appendix A.1 [SHA3]). And the corresponding collision and second-preimage-resistance strengths for SHAKE256 are $\min(d/2, 256)$ and $\min(d, 256)$ bits, respectively.

A SHAKE can be used as the message digest function (to hash the message to be signed) in RSASSA-PSS [RFC8017] and ECDSA [X9.62] and as the hash in the mask generation function (MGF) in RSASSA-PSS.

3. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

4. Identifiers

This section defines four new object identifiers (OIDs), for RSASSA-PSS and ECDSA with each of SHAKE128 and SHAKE256. The same algorithm identifiers can be used for identifying a public key in RSASSA-PSS.

The new identifiers for RSASSA-PSS signatures using SHAKEs are below.

```
id-RSASSA-PSS-SHAKE128 OBJECT IDENTIFIER ::= { iso(1)
    identified-organization(3) dod(6) internet(1)
    security(5) mechanisms(5) pkix(7) algorithms(6)
    TBD1 }

id-RSASSA-PSS-SHAKE256 OBJECT IDENTIFIER ::= { iso(1)
    identified-organization(3) dod(6) internet(1)
    security(5) mechanisms(5) pkix(7) algorithms(6)
    TBD2 }
```

The new algorithm identifiers of ECDSA signatures using SHAKEs are below.

```
id-ecdsa-with-shake128 OBJECT IDENTIFIER ::= { iso(1)
    identified-organization(3) dod(6) internet(1)
    security(5) mechanisms(5) pkix(7) algorithms(6)
    TBD3 }

id-ecdsa-with-shake256 OBJECT IDENTIFIER ::= { iso(1)
    identified-organization(3) dod(6) internet(1)
    security(5) mechanisms(5) pkix(7) algorithms(6)
    TBD4 }
```

The parameters for the four identifiers above MUST be absent. That is, the identifier SHALL be a SEQUENCE of one component, the OID.

Section 5.1.1 and Section 5.1.2 specify the required output length for each use of SHAKE128 or SHAKE256 in RSASSA-PSS and ECDSA. In summary, when hashing messages to be signed, output lengths of SHAKE128 and SHAKE256 are 256 and 512 bits respectively. When the SHAKEs are used as mask generation functions RSASSA-PSS, their output length is $(8 * \text{ceil}((n-1)/8) - 264)$ or $(8 * \text{ceil}((n-1)/8) - 520)$ bits, respectively, where n is the RSA modulus size in bits.

5. Use in PKIX

5.1. Signatures

Signatures are used in a number of different ASN.1 structures. As shown in the ASN.1 representation from [RFC5280] below, in an X.509 certificate, a signature is encoded with an algorithm identifier in the signatureAlgorithm attribute and a signatureValue attribute that contains the actual signature.

```
Certificate ::= SEQUENCE {  
    tbsCertificate      TBSCertificate,  
    signatureAlgorithm  AlgorithmIdentifier,  
    signatureValue      BIT STRING }
```

The identifiers defined in Section 4 can be used as the AlgorithmIdentifier in the signatureAlgorithm field in the sequence Certificate and the signature field in the sequence TBSCertificate in X.509 [RFC5280]. The parameters of these signature algorithms are absent as explained in Section 4.

Conforming CA implementations MUST specify the algorithms explicitly by using the OIDs specified in Section 4 when encoding RSASSA-PSS or ECDSA with SHAKE signatures in certificates and CRLs. Conforming client implementations that process certificates and CRLs using RSASSA-PSS or ECDSA with SHAKE MUST recognize the corresponding OIDs. Encoding rules for RSASSA-PSS and ECDSA signature values are specified in [RFC4055] and [RFC5480], respectively.

When using RSASSA-PSS or ECDSA with SHAKEs, the RSA modulus and ECDSA curve order SHOULD be chosen in line with the SHAKE output length. Refer to Section 7 for more details.

5.1.1.1. RSASSA-PSS Signatures

The RSASSA-PSS algorithm is defined in [RFC8017]. When id-RSASSA-PSS-SHAKE128 or id-RSASSA-PSS-SHAKE256 specified in Section 4 is used, the encoding MUST omit the parameters field. That is, the AlgorithmIdentifier SHALL be a SEQUENCE of one component, id-RSASSA-PSS-SHAKE128 or id-RSASSA-PSS-SHAKE256. [RFC4055] defines RSASSA-PSS-params that are used to define the algorithms and inputs to the algorithm. This specification does not use parameters because the hash, mask generation algorithm, trailer and salt are embedded in the OID definition.

The hash algorithm to hash a message being signed and the hash algorithm used as the mask generation function in RSASSA-PSS MUST be the same: both SHAKE128 or both SHAKE256. The output length of the hash algorithm which hashes the message SHALL be 32 (for SHAKE128) or 64 bytes (for SHAKE256).

The mask generation function takes an octet string of variable length and a desired output length as input, and outputs an octet string of the desired length. In RSASSA-PSS with SHAKEs, the SHAKEs MUST be used natively as the MGF function, instead of the MGF1 algorithm that uses the hash function in multiple iterations as specified in Section B.2.1 of [RFC8017]. In other words, the MGF is defined as the SHAKE128 or SHAKE256 output of the mgfSeed for id-RSASSA-PSS-

SHAKE128 and id-RSASSA-PSS-SHAKE256, respectively. The mgfSeed is the seed from which mask is generated, an octet string [RFC8017]. As explained in Step 9 of section 9.1.1 of [RFC8017], the output length of the MGF is $\text{emLen} - \text{hLen} - 1$ bytes. emLen is the maximum message length $\text{ceil}((n-1)/8)$, where n is the RSA modulus in bits. hLen is 32 and 64-bytes for id-RSASSA-PSS-SHAKE128 and id-RSASSA-PSS-SHAKE256, respectively. Thus when SHAKE is used as the MGF, the SHAKE output length maskLen is $(8 * \text{emLen} - 264)$ or $(8 * \text{emLen} - 520)$ bits, respectively. For example, when RSA modulus n is 2048, the output length of SHAKE128 or SHAKE256 as the MGF will be 1784 or 1528-bits when id-RSASSA-PSS-SHAKE128 or id-RSASSA-PSS-SHAKE256 is used, respectively.

The RSASSA-PSS saltLength MUST be 32 bytes for id-RSASSA-PSS-SHAKE128 or 64 bytes for id-RSASSA-PSS-SHAKE256. Finally, the trailerField MUST be 1, which represents the trailer field with hexadecimal value 0xBC [RFC8017].

5.1.2. ECDSA Signatures

The Elliptic Curve Digital Signature Algorithm (ECDSA) is defined in [X9.62]. When the id-ecdsa-with-shake128 or id-ecdsa-with-shake256 (specified in Section 4) algorithm identifier appears, the respective SHAKE function (SHAKE128 or SHAKE256) is used as the hash. The encoding MUST omit the parameters field. That is, the AlgorithmIdentifier SHALL be a SEQUENCE of one component, the OID id-ecdsa-with-shake128 or id-ecdsa-with-shake256.

For simplicity and compliance with the ECDSA standard specification, the output length of the hash function must be explicitly determined. The output length, d , for SHAKE128 or SHAKE256 used in ECDSA MUST be 256 or 512 bits, respectively.

Conforming CA implementations that generate ECDSA with SHAKE signatures in certificates or CRLs SHOULD generate such signatures with a deterministically generated, non-random k in accordance with all the requirements specified in [RFC6979]. They MAY also generate such signatures in accordance with all other recommendations in [X9.62] or [SEC1] if they have a stated policy that requires conformance to those standards. Those standards have not specified SHAKE128 and SHAKE256 as hash algorithm options. However, SHAKE128 and SHAKE256 with output length being 32 and 64 octets, respectively, can be used instead of 256 and 512-bit output hash algorithms such as SHA256 and SHA512.

5.2. Public Keys

Certificates conforming to [RFC5280] can convey a public key for any public key algorithm. The certificate indicates the public key algorithm through an algorithm identifier. This algorithm identifier is an OID and optionally associated parameters. The conventions and encoding for RSASSA-PSS and ECDSA public keys algorithm identifiers are as specified in Section 2.3.1 and 2.3.5 of [RFC3279], Section 3.1 of [RFC4055] and Section 2.1 of [RFC5480].

Traditionally, the `rsaEncryption` object identifier is used to identify RSA public keys. The `rsaEncryption` object identifier continues to identify the subject public key when the RSA private key owner does not wish to limit the use of the public key exclusively to RSASSA-PSS with SHAKes. When the RSA private key owner wishes to limit the use of the public key exclusively to RSASSA-PSS with SHAKes, the `AlgorithmIdentifiers` for RSASSA-PSS defined in Section 4 SHOULD be used as the algorithm field in the `SubjectPublicKeyInfo` sequence [RFC5280]. Conforming client implementations that process RSASSA-PSS with SHAKE public keys when processing certificates and CRLs MUST recognize the corresponding OIDs.

Conforming CA implementations MUST specify the X.509 public key algorithm explicitly by using the OIDs specified in Section 4 when encoding ECDSA with SHAKE public keys in certificates and CRLs. Conforming client implementations that process ECDSA with SHAKE public keys when processing certificates and CRLs MUST recognize the corresponding OIDs.

The identifier parameters, as explained in Section 4, MUST be absent.

6. IANA Considerations

One object identifier for the ASN.1 module in Appendix A is requested for the SMI Security for PKIX Module Identifiers (1.3.6.1.5.5.7.0) registry:

Decimal	Description	References
TBD	id-mod-pkix1-shakes-2019	[EDNOTE: THIS RFC]

IANA is requested to update the SMI Security for PKIX Algorithms [SMI-PKIX] (1.3.6.1.5.5.7.6) registry with four additional entries:

Decimal	Description	References
TBD1	id-RSASSA-PSS-SHAKE128	[EDNOTE: THIS RFC]
TBD2	id-RSASSA-PSS-SHAKE256	[EDNOTE: THIS RFC]
TBD3	id-ecdsa-with-shake128	[EDNOTE: THIS RFC]
TBD4	id-ecdsa-with-shake256	[EDNOTE: THIS RFC]

IANA is also requested to update the Hash Function Textual Names Registry [Hash-Texts] with two additional entries for SHAKE128 and SHAKE256:

Hash Function Name	OID	Reference
shake128	2.16.840.1.101.3.4.2.11	[EDNOTE: THIS RFC]
shake256	2.16.840.1.101.3.4.2.12	[EDNOTE: THIS RFC]

7. Security Considerations

This document updates [RFC3279]. The security considerations section of that document applies to this specification as well.

NIST has defined appropriate use of the hash functions in terms of the algorithm strengths and expected time frames for secure use in Special Publications (SPs) [SP800-78-4] and [SP800-107]. These documents can be used as guides to choose appropriate key sizes for various security scenarios.

SHAKE128 with output length of 256-bits offers 128-bits of collision and preimage resistance. Thus, SHAKE128 OIDs in this specification are RECOMMENDED with 2048 (112-bit security) or 3072-bit (128-bit security) RSA modulus or curves with group order of 256-bits (128-bit security). SHAKE256 with 512-bits output length offers 256-bits of collision and preimage resistance. Thus, the SHAKE256 OIDs in this specification are RECOMMENDED with 4096-bit RSA modulus or higher or curves with group order of at least 521-bits (256-bit security). Note that we recommended 4096-bit RSA because we would need 15360-bit modulus for 256-bits of security which is impractical for today's technology.

8. Acknowledgements

We would like to thank Sean Turner, Jim Schaad and Eric Rescorla for their valuable contributions to this document.

The authors would like to thank Russ Housley for his guidance and very valuable contributions with the ASN.1 module.

9. References

9.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC3279] Bassham, L., Polk, W., and R. Housley, "Algorithms and Identifiers for the Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile", RFC 3279, DOI 10.17487/RFC3279, April 2002, <<https://www.rfc-editor.org/info/rfc3279>>.
- [RFC4055] Schaad, J., Kaliski, B., and R. Housley, "Additional Algorithms and Identifiers for RSA Cryptography for use in the Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile", RFC 4055, DOI 10.17487/RFC4055, June 2005, <<https://www.rfc-editor.org/info/rfc4055>>.
- [RFC5280] Cooper, D., Santesson, S., Farrell, S., Boeyen, S., Housley, R., and W. Polk, "Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile", RFC 5280, DOI 10.17487/RFC5280, May 2008, <<https://www.rfc-editor.org/info/rfc5280>>.
- [RFC5480] Turner, S., Brown, D., Yiu, K., Housley, R., and T. Polk, "Elliptic Curve Cryptography Subject Public Key Information", RFC 5480, DOI 10.17487/RFC5480, March 2009, <<https://www.rfc-editor.org/info/rfc5480>>.
- [RFC8017] Moriarty, K., Ed., Kaliski, B., Jonsson, J., and A. Rusch, "PKCS #1: RSA Cryptography Specifications Version 2.2", RFC 8017, DOI 10.17487/RFC8017, November 2016, <<https://www.rfc-editor.org/info/rfc8017>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.

- [SHA3] National Institute of Standards and Technology (NIST), "SHA-3 Standard – Permutation-Based Hash and Extendable-Output Functions FIPS PUB 202", August 2015, <<https://www.nist.gov/publications/sha-3-standard-permutation-based-hash-and-extendable-output-functions>>.

9.2. Informative References

- [Hash-Texts] IANA, "Hash Function Textual Names", July 2017, <<https://www.iana.org/assignments/hash-function-text-names/hash-function-text-names.xhtml>>.
- [RFC5912] Hoffman, P. and J. Schaad, "New ASN.1 Modules for the Public Key Infrastructure Using X.509 (PKIX)", RFC 5912, DOI 10.17487/RFC5912, June 2010, <<https://www.rfc-editor.org/info/rfc5912>>.
- [RFC6979] Pornin, T., "Deterministic Usage of the Digital Signature Algorithm (DSA) and Elliptic Curve Digital Signature Algorithm (ECDSA)", RFC 6979, DOI 10.17487/RFC6979, August 2013, <<https://www.rfc-editor.org/info/rfc6979>>.
- [SEC1] Standards for Efficient Cryptography Group, "SEC 1: Elliptic Curve Cryptography", May 2009, <<http://www.secg.org/sec1-v2.pdf>>.
- [SMI-PKIX] IANA, "SMI Security for PKIX Algorithms", March 2019, <<https://www.iana.org/assignments/smi-numbers/smi-numbers.xhtml#smi-numbers-1.3.6.1.5.5.7.6>>.
- [SP800-107] National Institute of Standards and Technology (NIST), "SP800-107: Recommendation for Applications Using Approved Hash Algorithms", May 2014, <https://csrc.nist.gov/csrc/media/publications/sp/800-107/rev-1/final/documents/draft_revised_sp800-107.pdf>.
- [SP800-78-4] National Institute of Standards and Technology (NIST), "SP800-78-4: Cryptographic Algorithms and Key Sizes for Personal Identity Verification", May 2014, <https://csrc.nist.gov/csrc/media/publications/sp/800-78/4/final/documents/sp800_78-4_revised_draft.pdf>.

[X9.62] American National Standard for Financial Services (ANSI), "X9.62-2005: Public Key Cryptography for the Financial Services Industry: The Elliptic Curve Digital Signature Standard (ECDSA)", November 2005.

Appendix A. ASN.1 module

This appendix includes the ASN.1 module for SHAKEs in X.509. This module does not come from any existing RFC.

```
PKIXAlgsForSHAKE-2019 { iso(1) identified-organization(3) dod(6)
    internet(1) security(5) mechanisms(5) pkix(7) id-mod(0)
    id-mod-pkix1-shakes-2019(TBD) }

DEFINITIONS EXPLICIT TAGS ::=

BEGIN

-- EXPORTS ALL;

IMPORTS

-- FROM [RFC5912]

PUBLIC-KEY, SIGNATURE-ALGORITHM, DIGEST-ALGORITHM, SMIME-CAPS
FROM AlgorithmInformation-2009
    { iso(1) identified-organization(3) dod(6) internet(1) security(5)
      mechanisms(5) pkix(7) id-mod(0)
      id-mod-algorithmInformation-02(58) }

-- FROM [RFC5912]

RSAPublicKey, rsaEncryption, pk-rsa, pk-ec,
CURVE, id-ecPublicKey, ECPPoint, ECParameters, ECDSA-Sig-Value
FROM PKIXAlgs-2009 { iso(1) identified-organization(3) dod(6)
    internet(1) security(5) mechanisms(5) pkix(7) id-mod(0)
    id-mod-pkix1-algorithms2008-02(56) }
;

--
-- Message Digest Algorithms (mda-)
--
DigestAlgorithms DIGEST-ALGORITHM ::= {
    -- This expands DigestAlgorithms from [RFC5912]
    mda-shake128 |
    mda-shake256,
    ...
}
```

```
--
-- One-Way Hash Functions
--

-- SHAKE128
mda-shake128 DIGEST-ALGORITHM ::= {
  IDENTIFIER id-shake128 -- with output length 32 bytes.
}
id-shake128 OBJECT IDENTIFIER ::= { joint-iso-itu-t(2) country(16)
                                     us(840) organization(1) gov(101)
                                     csor(3) nistAlgorithm(4)
                                     hashAlgs(2) 11 }

-- SHAKE256
mda-shake256 DIGEST-ALGORITHM ::= {
  IDENTIFIER id-shake256 -- with output length 64 bytes.
}
id-shake256 OBJECT IDENTIFIER ::= { joint-iso-itu-t(2) country(16)
                                     us(840) organization(1) gov(101)
                                     csor(3) nistAlgorithm(4)
                                     hashAlgs(2) 12 }

--
-- Public Key (pk-) Algorithms
--
PublicKeys PUBLIC-KEY ::= {
  -- This expands PublicKeys from [RFC5912]
  pk-rsaSSA-PSS-SHAKE128 |
  pk-rsaSSA-PSS-SHAKE256,
  ...
}

-- The hashAlgorithm is mda-shake128
-- The maskGenAlgorithm is id-shake128
-- Mask Gen Algorithm is SHAKE128 with output length
--  $(8 * \text{ceil}((n-1)/8) - 264)$  bits, where n is the RSA
-- modulus in bits.
-- The saltLength is 32. The trailerField is 1.
pk-rsaSSA-PSS-SHAKE128 PUBLIC-KEY ::= {
  IDENTIFIER id-RSASSA-PSS-SHAKE128
  KEY RSAPublicKey
  PARAMS ARE absent
  -- Private key format not in this module --
  CERT-KEY-USAGE { nonRepudiation, digitalSignature,
                  keyCertSign, cRLSign }
}

-- The hashAlgorithm is mda-shake256
```

```

-- The maskGenAlgorithm is id-shake256
-- Mask Gen Algorithm is SHAKE256 with output length
-- (8*ceil((n-1)/8) - 520)-bits, where n is the RSA
-- modulus in bits.
-- The saltLength is 64. The trailerField is 1.
pk-rsaSSA-PSS-SHAKE256 PUBLIC-KEY ::= {
  IDENTIFIER id-RSASSA-PSS-SHAKE256
  KEY RSAPublicKey
  PARAMS ARE absent
  -- Private key format not in this module --
  CERT-KEY-USAGE { nonRepudiation, digitalSignature,
                    keyCertSign, cRLSign }
}

--
-- Signature Algorithms (sa-)
--
SignatureAlgs SIGNATURE-ALGORITHM ::= {
  -- This expands SignatureAlgorithms from [RFC5912]
  sa-rsassaPssWithSHAKE128 |
  sa-rsassaPssWithSHAKE256 |
  sa-ecdsaWithSHAKE128 |
  sa-ecdsaWithSHAKE256,
  ...
}

--
-- SMIME Capabilities (sa-)
--
SMimeCaps SMIME-CAPS ::= {
  -- The expands SMimeCaps from [RFC5912]
  sa-rsassaPssWithSHAKE128.&smimeCaps |
  sa-rsassaPssWithSHAKE256.&smimeCaps |
  sa-ecdsaWithSHAKE128.&smimeCaps |
  sa-ecdsaWithSHAKE256.&smimeCaps,
  ...
}

-- RSASSA-PSS with SHAKE128
sa-rsassaPssWithSHAKE128 SIGNATURE-ALGORITHM ::= {
  IDENTIFIER id-RSASSA-PSS-SHAKE128
  PARAMS ARE absent
  -- The hashAlgorithm is mda-shake128
  -- The maskGenAlgorithm is id-shake128
  -- Mask Gen Algorithm is SHAKE128 with output length
  -- (8*ceil((n-1)/8) - 264) bits, where n is the RSA
  -- modulus in bits.
  -- The saltLength is 32. The trailerField is 1

```

```
HASHES { mda-shake128 }
PUBLIC-KEYS { pk-rsa | pk-rsaSSA-PSS-SHAKE128 }
SMIME-CAPS { IDENTIFIED BY id-RSASSA-PSS-SHAKE128 }
}
id-RSASSA-PSS-SHAKE128 OBJECT IDENTIFIER ::= { iso(1)
    identified-organization(3) dod(6) internet(1)
    security(5) mechanisms(5) pkix(7) algorithms(6)
    TBD1 }

-- RSASSA-PSS with SHAKE256
sa-rsassaPssWithSHAKE256 SIGNATURE-ALGORITHM ::= {
    IDENTIFIER id-RSASSA-PSS-SHAKE256
    PARAMS ARE absent
    -- The hashAlgorithm is mda-shake256
    -- The maskGenAlgorithm is id-shake256
    -- Mask Gen Algorithm is SHAKE256 with output length
    -- (8*ceil((n-1)/8) - 520)-bits, where n is the
    -- RSA modulus in bits.
    -- The saltLength is 64. The trailerField is 1.
    HASHES { mda-shake256 }
    PUBLIC-KEYS { pk-rsa | pk-rsaSSA-PSS-SHAKE256 }
    SMIME-CAPS { IDENTIFIED BY id-RSASSA-PSS-SHAKE256 }
}
id-RSASSA-PSS-SHAKE256 OBJECT IDENTIFIER ::= { iso(1)
    identified-organization(3) dod(6) internet(1)
    security(5) mechanisms(5) pkix(7) algorithms(6)
    TBD2 }

-- ECDSA with SHAKE128
sa-ecdsaWithSHAKE128 SIGNATURE-ALGORITHM ::= {
    IDENTIFIER id-ecdsa-with-shake128
    VALUE ECDSA-Sig-Value
    PARAMS ARE absent
    HASHES { mda-shake128 }
    PUBLIC-KEYS { pk-ec }
    SMIME-CAPS { IDENTIFIED BY id-ecdsa-with-shake128 }
}
id-ecdsa-with-shake128 OBJECT IDENTIFIER ::= { iso(1)
    identified-organization(3) dod(6) internet(1)
    security(5) mechanisms(5) pkix(7) algorithms(6)
    TBD3 }

-- ECDSA with SHAKE256
sa-ecdsaWithSHAKE256 SIGNATURE-ALGORITHM ::= {
    IDENTIFIER id-ecdsa-with-shake256
    VALUE ECDSA-Sig-Value
    PARAMS ARE absent
    HASHES { mda-shake256 }
```



```
PUBLIC-KEYS { pk-ec }
  SMIME-CAPS { IDENTIFIED BY id-ecdsa-with-shake256 }
}
id-ecdsa-with-shake256 OBJECT IDENTIFIER ::= { iso(1)
  identified-organization(3) dod(6) internet(1)
  security(5) mechanisms(5) pkix(7) algorithms(6)
  TBD4 }
```

END

Authors' Addresses

Panos Kampanakis
Cisco Systems

Email: pkampana@cisco.com

Quynh Dang
NIST
100 Bureau Drive, Stop 8930
Gaithersburg, MD 20899-8930
USA

Email: quynh.dang@nist.gov