

OAuth Working Group  
Internet-Draft  
Intended status: Standards Track  
Expires: February 2, 2020

D. Hardt  
August 01, 2019

Reciprocal OAuth  
draft-ietf-oauth-reciprocal-04

Abstract

There are times when a user has a pair of protected resources that would like to request access to each other. While OAuth flows typically enable the user to grant a client access to a protected resource, granting the inverse access requires an additional flow. Reciprocal OAuth enables a more seamless experience for the user to grant access to a pair of protected resources.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on February 2, 2020.

Copyright Notice

Copyright (c) 2019 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of

the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## 1. Introduction

In the usual three legged, authorization code grant, the OAuth flow enables a resource owner (user) to enable a client (party A) to be granted authorization to access a protected resource (party B). If party A also has a protected resource that the user would like to let party B access, then a second complete OAuth flow, but in the reverse direction, must be performed. In practice, this is a complicated user experience as the user is at Party A, but the OAuth flow needs to start from Party B. This requires the second flow to send the user back to party B, which then sends the user to Party A as the first step in the flow. At the end, the user is at Party B, even though the original flow started at Party A.

Reciprocal OAuth simplifies the user experience by eliminating the redirections in the second OAuth flow. After the initial OAuth flow, party A obtains consent from the user to grant party B access to a protected resource at party A, and then passes an authorization code to party B using the access token party A obtained from party B to provide party B the context of the user. Party B then exchanges the authorization code for an access token per the usual OAuth flow.

For example, a user would like their voice assistant (party A) and music service (party B) to work together. The voice assistant wants to call the music service to play music, and the music service wants to call the voice assistant with music information to present to the user. The user starts the OAuth flow at the voice assistant, and is redirected to the music service. The music services obtains consent from the user and the redirects back to the voice assistant. At this point the voice assistant is able to obtain an access token for the music service. The voice assistant can then get consent from the user to authorize the music service to access the voice assistant, and then the voice assistant can create an authorization code and send it to the music service, which then exchanges the authorization code for an access token, all without further user interaction. Note that either the voice assistant or the music service can initiate the flow, so that either can prompt the user for the two parties to work together.

### 1.1. Terminology

In this document, the key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" are to be interpreted as described in BCP 14, RFC 2119 [RFC2119].

## 2. reciprocal Protocol Flow




Figure 1: Abstract reciprocal Protocol Flow

The reciprocal authorization between party A and party B are abstractly represented in Figure 1 and includes the following steps:

- o (A - C) are the same as in [RFC6749] 1.2
- o (D) Party B optionally includes the reciprocal scope in the response. See Section 2.1 for details.
- o (E) Party A sends the reciprocal authorization grant to party B. See Section 2.2.2 for details.
- o (F) Party B requests an access token, mirroring step (B)
- o (G) Party A issues an access token, mirroring step (C)

Note that Resource Owner A and Resource Owner B are the respective resource owner interaction systems controlled by the same owner.

## 2.1. Reciprocal Scope Request

When party B is providing an access token response per [RFC6749] 4.1.4, 4.2.1, 4.3.3 or 4.4.3, party B MAY include an additional query component in the redirection URI to indicate the scope requested in the reciprocal grant:

reciprocal OPTIONAL

The scope of party B's reciprocal access request per [RFC6749] 3.3.

If party B does not provide a reciprocal parameter in the access token response, the reciprocal scope will be a value previously preconfigured by party A and party B.

If an authorization code grant access token response per [RFC6749] 4.1.4, an example successful response (with extra line breaks for display purposes only):

```
HTTP/1.1 200 OK
Content-Type: application/json;charset=UTF-8
Cache-Control: no-store
Pragma: no-cache
```

```
{
  "access_token": "2YotnFZFEjrlzCsicMWpAA",
  "token_type": "example",
  "expires_in": 3600,
  "refresh_token": "tGzv3JOkF0XG5Qx2TlKWIA",
  "reciprocal": "example_scope",
  "example_parameter": "example_value"
}
```

If an authorization code grant access token response per [RFC6749] 4.2.2, an example successful response (with extra line breaks for display purposes only):

```
HTTP/1.1 302 Found
Location: http://example.com/cb#
  access_token=2YotnFZFEjrlzCsicMWpAA&
  state=xyz&
  token_type=example&
  expires_in=3600&
  reciprocal="example_scope"
```

When party B is providing an authorization response per [RFC6749] 4.1.2, party B MAY include an additional query component in the redirection URI to indicate the scope requested in the reciprocal grant.

reciprocal OPTIONAL. The scope of party B's reciprocal access request per [RFC6749] 3.3.

If party B does not provide a reciprocal parameter in the authorization response, the reciprocal scope will be a value previously preconfigured by party A and party B.

## 2.2. Reciprocal Authorization Flow

The reciprocal authorization flow starts after the client (party A) has obtained an access token from the authorization server (party B) per [RFC6749] 4.1 Authorization Code Grant.

### 2.2.1. User Consent

Party A obtains consent from the user to grant Party B access to protected resources at party A. The consent represents the scopes requested by party B from party A per Section 2.1.

### 2.2.2. Reciprocal Authorization Code

Party A generates an authorization code representing the access granted to party B by the user. Party A then makes a request to party B's token endpoint authenticating per [RFC6749] 2.3 and sending the following parameters using the "application/x-www-form-urlencoded" format per [RFC6749] Appendix B with a character encoding of UTF-8 in the HTTP request entity-body:

grant\_type REQUIRED

Value MUST be set to "urn:ietf:params:oauth:grant-type:reciprocal".

code REQUIRED

the authorization code generated by party A.

client\_id REQUIRED

party A's client ID.

access\_token REQUIRED the access token obtained from Party B. Used by Party B to identify which user authorization is being requested.

For example, the client makes the following HTTP request using TLS (with extra line breaks for display purposes only):

```
POST /token HTTP/1.1
Host: server.example.com
Authorization: Basic ej4hsyfishwssjdusisdhjkjsdksusdhjkjsdjk
Content-Type: application/x-www-form-urlencoded

grant_type=urn%3Aietf%3Aparams%3Aoauth%3Agrant-type%3Areciprocal
&code=hasdyubasdjahsbdkjbasd
&client_id=example.com
&access_token=sadadojsadlkjasdkljxxlkjdas
```

Party B MUST verify the authentication provided by Party A per [RFC6749] 2.3

Party B MUST then verify the access token was granted to the client identified by the `client_id`.

Party B MUST respond with either an HTTP 200 (OK) response if the request is valid, or an HTTP 400 "Bad Request" if it is not.

Party B then plays the role of the client to make an access token request per [RFC6749] 4.1.3.

### 3. Authorization Update Flow

After the initial authorization, the user may add or remove scopes available to the client at the authorization server. For example, the user may grant additional scopes to the client using a voice interface, or revoke some scopes. The authorization server can update the client with the new authorization by sending a new authorization code per Section 2.2.2.

### 4. IANA Considerations

#### 4.1. Registration of reciprocal

This section registers the value "reciprocal" in the IANA "OAuth Parameters" registry established by "The OAuth 2.0 Authorization Framework" [RFC6749].

- o Parameter Name: reciprocal
- o Parameter usage location: token response
- o Change Controller: IESG
- o Specification Document: Section 2.1 of this document

#### 4.2. Sub-Namespace Registration of urn:ietf:params:oauth:grant-type:reciprocal

This section registers the value "grant-type:reciprocal" in the IANA "OAuth URI" registry established by "An IETF URN Sub-Namespace for OAuth" [RFC6755].

- o URN: urn:ietf:params:oauth:grant-type:reciprocal
- o Common Name: reciprocal grant for OAuth 2.0
- o Change Controller: IESG
- o Specification Document: Section 2.2.2 of this document

#### 5. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC6749] Hardt, D., Ed., "The OAuth 2.0 Authorization Framework", RFC 6749, DOI 10.17487/RFC6749, October 2012, <<https://www.rfc-editor.org/info/rfc6749>>.
- [RFC6750] Jones, M. and D. Hardt, "The OAuth 2.0 Authorization Framework: Bearer Token Usage", RFC 6750, DOI 10.17487/RFC6750, October 2012, <<https://www.rfc-editor.org/info/rfc6750>>.
- [RFC6755] Campbell, B. and H. Tschofenig, "An IETF URN Sub-Namespace for OAuth", RFC 6755, DOI 10.17487/RFC6755, October 2012, <<https://www.rfc-editor.org/info/rfc6755>>.

#### Appendix A. Document History

##### A.1. draft-ietf-oauth-reciprocal-00

- o Initial version.

##### A.2. draft-ietf-oauth-reciprocal-01

- o Changed reciprocal scope request to be in access token response rather than authorization request

A.3. draft-ietf-oauth-reciprocal-02

- o Added in diagram to clarify protocol flow

A.4. draft-ietf-oauth-reciprocal-03

- o fixed spelling of reciprocal
- o added example use case in introduction
- o resource owner is the same in Party A and Party B

A.5. draft-ietf-oauth-reciprocal-04

- o completed IANA section

Author's Address

Dick Hardt

Email: dick.hardt@gmail.com