

Routing area  
Internet-Draft  
Intended status: Standards Track  
Expires: April 19, 2019

S. Hegde  
K. Arora  
Juniper Networks Inc.  
October 16, 2018

Label Switched Path (LSP) Ping/Traceroute for Segment Routing (SR)  
Egress Peer engineering Segment Identifiers (SIDs) with MPLS Data Planes  
draft-hegde-mpls-spring-epe-oam-00

#### Abstract

Egress Peer Engineering is an application of Segment Routing to solve the problem of egress peer selection. The SR-based BGP-EPE solution allows a centralized (Software Defined Network, SDN) controller to program any egress peer. The EPE solution requires a node to program PeerNodeSID, PeerAdjSID, PeerSetSID as described in [I-D.ietf-spring-segment-routing-central-epe]. This document provides Target FEC stack TLV definitions as defined in [RFC8029] for the EPE SIDs.

#### Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [RFC2119].

#### Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 19, 2019.

## Copyright Notice

Copyright (c) 2018 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

|                                       |   |
|---------------------------------------|---|
| 1. Introduction . . . . .             | 2 |
| 2. FEC Definitions . . . . .          | 3 |
| 2.1. PeerNodeSID/PeerAdjSID . . . . . | 3 |
| 2.2. PeerSetSID . . . . .             | 3 |
| 3. Security Considerations . . . . .  | 4 |
| 4. IANA Considerations . . . . .      | 5 |
| 5. Acknowledgments . . . . .          | 5 |
| 6. References . . . . .               | 5 |
| 6.1. Normative References . . . . .   | 5 |
| 6.2. Informative References . . . . . | 5 |
| Authors' Addresses . . . . .          | 5 |

## 1. Introduction

Egress Peer Engineering (EPE) as defined in [I-D.ietf-spring-segment-routing-central-epe] is an effective mechanism to select the egress peer link based on different criteria. The EPE SIDs provide means to represent egress peer links. Many network deployments have built their networks consisting of multiple Autonomous Systems either for ease of operations or as a result of network mergers and acquisitions. The egress links connecting the two Autonomous Systems could be managed using EPE-SIDs in this case as well. It is important to be able to validate the control plane to forwarding plane synchronization for these SIDs so that any anomaly can be detected easily by the operator.

This document provides Target FEC stack TLV definitions for EPE SIDs. Other procedures for mpls ping and traceroute as defined in [RFC8287] are applicable for EPE-SIDs as well.

## 2. FEC Definitions

As described in [RFC8287] sec 5, 3 new type of segment IDs are defined for the Target FEC stack TLV corresponding to each label in the label stack

### 2.1. PeerNodeSID/PeerAdjSID




Figure 1: Peer Node/Adj Segment ID Sub TLV

Type: 37 (TBD)

Length: variable based on ipv4/ipv6 interface address

AS Number: 4 octet unsigned integer representing the Member ASN inside the Confederation.[RFC5065]

Interface Address: BGP session IPv4/IPv6 local/remote address.

BGP Router ID: 4 octet unsigned integer representing the BGP Identifier as defined in [RFC4271] and [RFC6286].

### 2.2. PeerSetSID




Figure 2: Peer set SID Segment ID Sub TLV

Type : 38 (TBD)

Length : variable based on ipv4/ipv6 interface address

No.of elements in set : Number of links in the set.

AS Number : 4 octet unsigned integer representing the Member ASN inside the Confederation.[RFC5065]

Interface Address : BGP session IPv4/IPv6 local/remote address.

BGP Router ID : 4 octet unsigned integer representing the BGP Identifier as defined in [RFC4271] and [RFC6286]

### 3. Security Considerations

TBD

#### 4. IANA Considerations

New Target FEC stack sub-TLV from the "sub-TLVs for TLV types 1,16 and 21" subregistry of the "Multi-Protocol Label switching (MPLS) Label Switched Paths 9LSPs) Ping parameters" registry

PeerNode/PeerAdjSID segment ID Sub-TLV : 37 (suggested)

PeerSetSID segment ID Sub-TLV : 38 (suggested)

#### 5. Acknowledgments

#### 6. References

##### 6.1. Normative References

- [I-D.ietf-spring-segment-routing-central-epe]  
Filsfils, C., Previdi, S., Dawra, G., Aries, E., and D. Afanasiev, "Segment Routing Centralized BGP Egress Peer Engineering", draft-ietf-spring-segment-routing-central-epe-10 (work in progress), December 2017.
- [RFC8287] Kumar, N., Ed., Pignataro, C., Ed., Swallow, G., Akiya, N., Kini, S., and M. Chen, "Label Switched Path (LSP) Ping/Traceroute for Segment Routing (SR) IGP-Prefix and IGP-Adjacency Segment Identifiers (SIDs) with MPLS Data Planes", RFC 8287, DOI 10.17487/RFC8287, December 2017, <<https://www.rfc-editor.org/info/rfc8287>>.

##### 6.2. Informative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC8029] Kompella, K., Swallow, G., Pignataro, C., Ed., Kumar, N., Aldrin, S., and M. Chen, "Detecting Multiprotocol Label Switched (MPLS) Data-Plane Failures", RFC 8029, DOI 10.17487/RFC8029, March 2017, <<https://www.rfc-editor.org/info/rfc8029>>.

#### Authors' Addresses

Shraddha Hegde  
Juniper Networks Inc.  
Exora Business Park  
Bangalore, KA 560103  
India

Email: shraddha@juniper.net

Kapil Arora  
Juniper Networks Inc.

Email: kapilaro@juniper.net