Design Considerations for Applying ICN to IoT "draft-irtf-icnrg-icniot-02.txt"

Ravi Ravindran (ravi.ravindran@huawei.com) IETF/ICNRG, 103, Bangkok November, 2018

https://tools.ietf.org/html/draft-zhang-icnrg-icniot

Reduced Co-Authors

- Yanyong Zhang (Winlab, Rutgers)
- Alfredo Grieco (Politecnico di Bari (DEI))
- Jeff Burke (UCLA)
- Aytac Azgin (Huawei)
- Andres Lindgren(SICS)
- Bengt Ahlgren (SICS)

Table of Content

1. Introduction	3
2. Motivating ICN for IoT	4
2.1. Advantages of using ICN for IoT	5
2.2. Service Scenarios	6
3. IoT Architectural Requirements	11
3.1. Naming	12
3.2. Security and Privacy	12
3.3. Scalability	13
3.4. Resource Constraints	
3.5. Traffic Characteristics	
3.6. Contextual Communication	14
3.7. Handling Mobility	15
3.8. Storage and Caching	15
3.9. Communication Reliability	
3.10. Self-Organization	16
3.11. Ad hoc and Infrastructure Mode	17
3.12. IoT Platform Management	17
4. State of the Art	
4.1. Silo IoT Architecture	18
4.2. Application-Layer Unified IoT Solutions	19
4.2. Application-tayer unified for solutions	19
4.2.1. Weaknesses of the Application-Layer Approach	
4.2.1. Weaknesses of the Application-Layer Approach 4.2.2. Relation to Delay Tolerant Networking (DTN) architecture and its suitability for IoT	20 22
4.2.1. Weaknesses of the Application-Layer Approach 4.2.2. Relation to Delay Tolerant Networking (DTN) architecture and its suitability for IoT 5. ICN Design Considerations for IoT	20 22 22
4.2.1. Weaknesses of the Application-Layer Approach 4.2.2. Relation to Delay Tolerant Networking (DTN) architecture and its suitability for IoT 5. ICN Design Considerations for IoT 5.1. Naming Devices, Data, and Services	20 22 22 22
4.2.1. Weaknesses of the Application-Layer Approach 4.2.2. Relation to Delay Tolerant Networking (DTN) architecture and its suitability for IoT 5. ICN Design Considerations for IoT 5.1. Naming Devices, Data, and Services 5.2. Name Resolution	22 22 22 22 26
4.2.1. Weaknesses of the Application-Layer Approach 4.2.2. Relation to Delay Tolerant Networking (DTN) architecture and its suitability for IoT 5. ICN Design Considerations for IoT 5.1. Naming Devices, Data, and Services	22 22 22 22 26
4.2.1. Weaknesses of the Application-Layer Approach 4.2.2. Relation to Delay Tolerant Networking (DTN) architecture and its suitability for IoT 5. ICN Design Considerations for IoT 5.1. Naming Devices, Data, and Services 5.2. Name Resolution	22 22 22 22 26 27
4.2.1. Weaknesses of the Application-Layer Approach 4.2.2. Relation to Delay Tolerant Networking (DTN) architecture and its suitability for IoT 5. ICN Design Considerations for IoT 5.1. Naming Devices, Data, and Services 5.2. Name Resolution 5.3. Security and Privacy 5.4. Caching 5.5. Storage	22 22 22 26 27 30 31
4.2.1. Weaknesses of the Application-Layer Approach 4.2.2. Relation to Delay Tolerant Networking (DTN) architecture and its suitability for IoT 5. ICN Design Considerations for IoT 5.1. Naming Devices, Data, and Services 5.2. Name Resolution 5.3. Security and Privacy 5.4. Caching 5.5. Storage 5.6. Routing and Forwarding	20 22 22 22 26 27 30 31 32
4.2.1. Weaknesses of the Application-Layer Approach 4.2.2. Relation to Delay Tolerant Networking (DTN) architecture and its suitability for IoT 5. ICN Design Considerations for IoT 5.1. Naming Devices, Data, and Services 5.2. Name Resolution 5.3. Security and Privacy 5.4. Caching 5.5. Storage 5.6. Routing and Forwarding 5.7. Mobility Management	20 22 22 26 27 30 31 32 33
4.2.1. Weaknesses of the Application-Layer Approach 4.2.2. Relation to Delay Tolerant Networking (DTN) architecture and its suitability for IoT 5. ICN Design Considerations for IoT 5.1. Naming Devices, Data, and Services 5.2. Name Resolution 5.3. Security and Privacy 5.4. Caching 5.5. Storage 5.6. Routing and Forwarding 5.7. Mobility Management 5.8. Contextual Communication	20 22 22 26 27 30 31 32 33 34
4.2.1. Weaknesses of the Application-Layer Approach 4.2.2. Relation to Delay Tolerant Networking (DTN) architecture and its suitability for IoT 5. ICN Design Considerations for IoT 5.1. Naming Devices, Data, and Services 5.2. Name Resolution 5.3. Security and Privacy 5.4. Caching 5.5. Storage 5.6. Routing and Forwarding 5.7. Mobility Management	20 22 22 26 27 30 31 32 33 34
4.2.1. Weaknesses of the Application-Layer Approach 4.2.2. Relation to Delay Tolerant Networking (DTN) architecture and its suitability for IoT 5. ICN Design Considerations for IoT 5.1. Naming Devices, Data, and Services 5.2. Name Resolution 5.3. Security and Privacy 5.4. Caching 5.5. Storage 5.6. Routing and Forwarding 5.7. Mobility Management 5.8. Contextual Communication	20 22 22 26 27 30 31 32 33 34 35
4.2.1. Weaknesses of the Application-Layer Approach 4.2.2. Relation to Delay Tolerant Networking (DTN) architecture and its suitability for IoT 5. ICN Design Considerations for IoT 5.1. Naming Devices, Data, and Services 5.2. Name Resolution 5.3. Security and Privacy 5.4. Caching 5.5. Storage 5.6. Routing and Forwarding 5.7. Mobility Management 5.8. Contextual Communication 5.9. In-network Computing	20 22 22 26 27 30 31 32 33 34 35 36
4.2.1. Weaknesses of the Application-Layer Approach 4.2.2. Relation to Delay Tolerant Networking (DTN) architecture and its suitability for IoT 5. ICN Design Considerations for IoT 5.1. Naming Devices, Data, and Services 5.2. Name Resolution 5.3. Security and Privacy 5.4. Caching 5.5. Storage 5.6. Routing and Forwarding 5.7. Mobility Management 5.8. Contextual Communication 5.9. In-network Computing 5.10. Self-Organization 5.11. Communications Reliability 5.12. Resource Constraints and Heterogeneity	20 22 22 26 27 30 31 32 33 34 35 36 36 37
4.2.1. Weaknesses of the Application-Layer Approach 4.2.2. Relation to Delay Tolerant Networking (DTN) architecture and its suitability for IoT 5. ICN Design Considerations for IoT 5.1. Naming Devices, Data, and Services 5.2. Name Resolution 5.3. Security and Privacy 5.4. Caching 5.5. Storage 5.6. Routing and Forwarding 5.7. Mobility Management 5.8. Contextual Communication 5.9. In-network Computing 5.10. Self-Organization 5.11. Communications Reliability 5.12. Resource Constraints and Heterogeneity 6. Differences from T2TRG	20 22 22 26 27 30 31 32 33 34 35 36 36 37 37
4.2.1. Weaknesses of the Application-Layer Approach 4.2.2. Relation to Delay Tolerant Networking (DTN) architecture and its suitability for IoT 5. ICN Design Considerations for IoT 5.1. Naming Devices, Data, and Services 5.2. Name Resolution 5.3. Security and Privacy 5.4. Caching 5.5. Storage 5.6. Routing and Forwarding 5.7. Mobility Management 5.8. Contextual Communication 5.9. In-network Computing 5.10. Self-Organization 5.11. Communications Reliability 5.12. Resource Constraints and Heterogeneity 6. Differences from T2TRG 7. Security Considerations	20 22 22 26 27 30 31 32 33 34 35 36 37 37 38
4.2.1. Weaknesses of the Application-Layer Approach 4.2.2. Relation to Delay Tolerant Networking (DTN) architecture and its suitability for IoT 5. ICN Design Considerations for IoT 5.1. Naming Devices, Data, and Services 5.2. Name Resolution 5.3. Security and Privacy 5.4. Caching 5.5. Storage 5.6. Routing and Forwarding 5.7. Mobility Management 5.8. Contextual Communication 5.9. In-network Computing 5.10. Self-Organization 5.11. Communications Reliability 5.12. Resource Constraints and Heterogeneity 6. Differences from T2TRG	22 22 22 26 27 30 31 32 33 34 35 36 37 37 38

Draft Updates from 01->02

- Significant editorial (please see the diff), removed redundant material and moved discussions around
- Section 2 "Motivation ICN for IoT"
 - Pulled up the section on "Advantages of using ICN for IoT" as Sec. 2.1
 - Section 2.3 now "Service Scenarios"
 - Smart Building use case has new references from recent work relevant to it
- Section 3.1 on Naming
 - Removed discussion where some specific solution was being discussed on name assignment and management
- Section 3.6 on Contextual Communication, merging of discussion on long and short term contexts.
- Section 4.2.2, renamed to "Relation to DTN Architecture and its suitability to Iot"

Next Steps

- Feedback from Thomas on including some recent works
- Request more reviews and reviews to improve it.