

SLAAC's Reaction to Renumbering Events


draft-gont-6man-slaac-renum

**Fernando Gont
Jan Zorz**

IETF 104
Prague, Czech Republic. March 23-29, 2019

Common scenario

- Sample scenario:



Problem statement

- Problem scenario
 - CPE router is hard-rebooted
 - CPE router crashes and reboots
- What happens when the CPE router comes back to life?
 - Quite frequently it has no state of previously-leased prefix
 - It thus request a new prefix via DHCPv6-PD
 - The new prefix is announced on the LAN
- What about the previous prefix?
 - It is still there!
 - Announced lifetimes allow continued use for days to months

Problem statement (II)

- Result:
 - Old addresses are maintained
 - Quite frequently, such addresses are preferred
 - Old routes are maintained
- What does this mean?
 - Connectivity with new owner of prefix not possible
 - IPv6 connectivity may fail
 - In dual-stack scenarios, it may mean more IPv4 traffic
 - Due to Happy Eyeballs

Deployments that avoid the problem

- **Sites that use stable prefixes**
 - Some provisioning systems reportedly don't support this
 - Bad for user privacy – **RFC4941 mostly useless with stable prefixes!**
 - Some ISPs want to charge extra for stable prefixes – ala IPv4
 - There are IPv6 deployments that employ dynamic prefixes
- **CPEs that record leased prefixes on stable storage**
 - They may have to be able to record many prefixes
 - Lease times of days/months, and reboots may be frequent
 - Still cannot invalidate the stale prefix -- as per RFC4861
 - May hit implementation-specific limit of configured addresses on hosts

How we think it should be solved

- **Get rid of stale addresses and routes in a timelier manner**
- If the same router advertises a new prefix (but not the previous one), assume the prefix has become stale
- Count number of consecutive RAs from same router with PIOs that do not include the previous prefix:
 - After two such RAs, unprefer the addresses
 - After two additional ones, remove the addresses and routes

This solves the problem at the hosts themselves

Additional bits that may help

- Allow routers to invalidate prefixes
 - i.e., update RFC4861 to honor PIOs with Valid Lifetime < 2 hours
- Reduce PIOs lifetimes
 - cap to Router Lifetime
- Our draft also suggest more frequent RAs
 - But there seems to be consensus against this

Moving forward

- Adopt document as wg item to work on topic?
 - not necessarily to keep all proposed workarounds