

6man Working Group  
Internet-Draft  
Intended status: Standards Track  
Expires: November 9, 2021

C. Li  
Huawei Technologies  
W. Cheng  
China Mobile  
Y. Zhu  
China Telecom  
Z. Li  
D. Dhody  
Huawei Technologies  
May 8, 2021

Encapsulation of Path Segment in SRv6  
draft-li-6man-srv6-path-segment-encap-06

## Abstract

Segment Routing (SR) allows for a flexible definition of end-to-end paths by encoding an ordered list of instructions, called "segments". The SR architecture can be implemented over an IPv6 data plane, called SRv6. In some use-cases such as end-to-end SR Path Protection and Performance Measurement (PM), an SRv6 path needs to be identified. An SRv6 Path Segment can be used for identifying an SRv6 path. This document defines a P-flag in the Segment Routing Header to indicate the appearance of SRv6 Path Segment.

## Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on November 9, 2021.

## Copyright Notice

Copyright (c) 2021 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

1. Introduction . . . . .	2
1.1. Requirements Language . . . . .	3
1.2. Terminology . . . . .	3
2. Encoding of an SRv6 Path Segment . . . . .	3
2.1. SRH.P-flag . . . . .	4
3. Processing of SRv6 Path Segment . . . . .	5
4. IANA Considerations . . . . .	5
5. Security Considerations . . . . .	5
6. Acknowledgements . . . . .	6
7. References . . . . .	6
7.1. Normative References . . . . .	6
7.2. Informative References . . . . .	7
Authors' Addresses . . . . .	7

## 1. Introduction

Segment routing (SR) [RFC8402] is a source routing paradigm that explicitly indicates the forwarding path for packets at the ingress node by inserting an ordered list of instructions, called segments.

When segment routing is deployed on an IPv6 data plane, it is called SRv6, and it uses a new IPv6 [RFC8200] Routing Header (EH) called the IPv6 Segment Routing Header (SRH) [RFC8754] to construct an SRv6 path. As per [RFC8986], an SRv6 segment identifier is a 128-bit value.

In several use cases, such as binding bidirectional path [I-D.ietf-pce-sr-bidir-path] and end-to-end performance measurement [I-D.gandhi-spring-twamp-srpm], the ability to implement path identification is a pre-requisite.

An SRv6 path MAY be identified by the content of a segment list in the SRH. However, the segment list may not be a good key, since the length of a segment list is flexible according to the number of required SIDs. Also, the length of a segment list may be too long to be a key when it contains many SIDs. For instance, if packet A uses

an SRH with 3 SIDs while Packet B uses an SRH with 10 SIDs, the key to identify these two paths will be a 384-bits value and a 1280-bits value, respectively. Furthermore, an SRv6 path cannot be identified by the information carried by the SRH in reduced mode [RFC8754] as the first SID is not present. Also, different SRv6 policies may use the same segment list for different candidate paths, so the traffic of different SRv6 policies are merged, resulting in the inability to measure the performance of the specific path. Therefore, [I-D.ietf-spring-srv6-path-segment] defines an SRv6 Path Segment to identify an SRv6 path.

This document defines a P-bit in SRH to indicate the appearance of SRv6 Path Segment in SRH.

### 1.1. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

### 1.2. Terminology

PM: Performance Measurement.

SID: Segment ID.

SL: Segment List.

SR: Segment Routing.

SRH: Segment Routing Header.

PSID: Path Segment Identifier.

PSP: Penultimate Segment Popping.

Further, this document makes use of the terms defined in [RFC8402] and [RFC8986].

## 2. Encoding of an SRv6 Path Segment

This section describes the SRH encoding of an SRv6 Path Segment [I-D.ietf-spring-srv6-path-segment].

## 2.1. SRH.P-flag

As per [I-D.ietf-spring-srv6-path-segment], an SRv6 Path Segment is a 128-bits value, and it MUST appear only once in a SID list, and it MUST appear as the last entry.

To indicate the existence of a Path Segment in the SRH, this document defines a P-flag in the SRH flag field. The encapsulation of SRv6 Path Segment is shown below.




Figure 1. SRv6 Path Segment in SID List

- o P-bit: set when SRv6 Path Segment is inserted. It MUST be ignored when a node does not support SRv6 Path Segment processing.

SRH.P-bit processing can be enabled or disabled by configuration on devices, it can be done by CLI, NETCONF YANG or other ways, and this is out of the scope of this document.

The pseudo code of SRH.P-bit processing is described as below.

```
S01.  if SRH.P-flag processing is enabled:
S02.    if SRH.P-flag is set:
S03.      SRv6 Path Segment processing      ;;refl
```

Ref1: The SRv6 Path Segment processing is accosiated with the specific application, such as SRv6 Path Segment based Performance measurement, and this is out of the scope of this document.

In some use cases, only the egress need to process the SRv6 Path Segment, therefore, the P-bit processing can be done at the egress node only while the intermediate nodes do not need to process it. This feature can be enabled by configuration like CLI , NETCONF YANG or other ways. In this case, the pseudo code is described as below.

```
S01.  if SRH.P-flag processing is enabled:
S02.    if intermediate node processing is disabled:
S03.      if SRH.P-flag is set and SRH.SL == 0:
S04.        SRv6 Path Segment processing
S05.    else:
S06.      if SRH.P-flag is set:
S07.        SRv6 Path Segment processing
```

### 3. Processing of SRv6 Path Segment

The processing of SRv6 path segment is out of the scope of this document and is defined in [I-D.ietf-spring-srv6-path-segment].

### 4. IANA Considerations

This document requests IANA to allocate bit position TBA within the "Segment Routing Header Flags" registry defined in [RFC8402].

### 5. Security Considerations

TBA

## 6. Acknowledgements

TBA

## 7. References

### 7.1. Normative References

- [I-D.ietf-spring-srv6-path-segment]  
Li, C., Cheng, W., Chen, M., Dhody, D., and R. Gandhi,  
"Path Segment for SRv6 (Segment Routing in IPv6)", draft-  
ietf-spring-srv6-path-segment-00 (work in progress),  
November 2020.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate  
Requirement Levels", BCP 14, RFC 2119,  
DOI 10.17487/RFC2119, March 1997,  
<<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC  
2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174,  
May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8200] Deering, S. and R. Hinden, "Internet Protocol, Version 6  
(IPv6) Specification", STD 86, RFC 8200,  
DOI 10.17487/RFC8200, July 2017,  
<<https://www.rfc-editor.org/info/rfc8200>>.
- [RFC8402] Filsfils, C., Ed., Previdi, S., Ed., Ginsberg, L.,  
Decraene, B., Litkowski, S., and R. Shakir, "Segment  
Routing Architecture", RFC 8402, DOI 10.17487/RFC8402,  
July 2018, <<https://www.rfc-editor.org/info/rfc8402>>.
- [RFC8754] Filsfils, C., Ed., Dukes, D., Ed., Previdi, S., Leddy, J.,  
Matsushima, S., and D. Voyer, "IPv6 Segment Routing Header  
(SRH)", RFC 8754, DOI 10.17487/RFC8754, March 2020,  
<<https://www.rfc-editor.org/info/rfc8754>>.
- [RFC8986] Filsfils, C., Ed., Camarillo, P., Ed., Leddy, J., Voyer,  
D., Matsushima, S., and Z. Li, "Segment Routing over IPv6  
(SRv6) Network Programming", RFC 8986,  
DOI 10.17487/RFC8986, February 2021,  
<<https://www.rfc-editor.org/info/rfc8986>>.

## 7.2. Informative References

[I-D.gandhi-spring-twamp-srpm]

Gandhi, R., Filsfils, C., Voyer, D., Chen, M., and B. Janssens, "Performance Measurement Using TWAMP Light for Segment Routing Networks", draft-gandhi-spring-twamp-srpm-11 (work in progress), October 2020.

[I-D.ietf-idr-sr-policy-path-segment]

Li, C., Li, Z., Chen, H., Cheng, W., and K. Talaulikar, "SR Policy Extensions for Path Segment and Bidirectional Path", draft-ietf-idr-sr-policy-path-segment-03 (work in progress), March 2021.

[I-D.ietf-pce-sr-bidir-path]

Li, C., Chen, M., Cheng, W., Gandhi, R., and Q. Xiong, "Path Computation Element Communication Protocol (PCEP) Extensions for Associated Bidirectional Segment Routing (SR) Paths", draft-ietf-pce-sr-bidir-path-05 (work in progress), January 2021.

[I-D.ietf-pce-sr-path-segment]

Li, C., Chen, M., Cheng, W., Gandhi, R., and Q. Xiong, "Path Computation Element Communication Protocol (PCEP) Extension for Path Segment in Segment Routing (SR)", draft-ietf-pce-sr-path-segment-03 (work in progress), February 2021.

[I-D.ietf-spring-segment-routing-policy]

Filsfils, C., Talaulikar, K., Voyer, D., Bogdanov, A., and P. Mattes, "Segment Routing Policy Architecture", draft-ietf-spring-segment-routing-policy-11 (work in progress), April 2021.

## Authors' Addresses

Cheng Li  
Huawei Technologies

Email: c.l@huawei.com

Weiqiang Cheng  
China Mobile

Email: chengweiqiang@chinamobile.com

Yongqing Zhu  
China Telecom  
Guangzhou

Email: zhuyq8@chinatelecom.cn

Zhenbin Li  
Huawei Technologies  
Huawei Campus, No. 156 Beiqing Rd.  
Beijing 100095  
China

Email: lizhenbin@huawei.com

Dhruv Dhody  
Huawei Technologies  
Divyashree Techno Park, Whitefield  
Bangalore 560066  
India

Email: dhruv.ietf@gmail.com