

CCAMP Working Group  
Internet-Draft  
Intended status: Standards Track  
Expires: January 9, 2020

H. Zheng  
A. Guo  
I. Busi  
Huawei Technologies  
A. Sharma  
Google  
R. Rao  
Infinera  
S. Belotti  
Nokia  
V. Lopez  
Telefonica  
Y. Li  
China Mobile  
Y. Xu  
CAICT  
July 08, 2019

OTN Tunnel YANG Model  
draft-ietf-ccamp-otn-tunnel-model-07

Abstract

This document describes the YANG data model for OTN Tunnels.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on January 9, 2020.

Copyright Notice

Copyright (c) 2019 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

1. Introduction	2
2. Terminology and Notations	2
3. OTN Tunnel Model Description	3
3.1. Overview of OTN Tunnel Model	3
3.2. OTN-specific Parameters in Tunnel Model	3
3.3. OTN Path Compute RPC	4
4. OTN Tunnel YANG Tree	4
5. OTN Tunnel YANG Code	14
6. Security Considerations	35
7. IANA Considerations	36
8. Acknowledgements	37
9. Contributors	37
10. References	37
10.1. Normative References	37
10.2. Informative References	38
Authors' Addresses	39

## 1. Introduction

OTN transport networks, specified in [ITU-T], can carry various types of client services. In many cases, the client signal is carried over an OTN tunnel across connected domains in a multi-domain network. These OTN services can either be transported or switched in the OTN network. If an OTN tunnel is switched, then additional parameters need to be provided to create a Mux OTN service.

This document provides YANG model for creating OTN tunnel. The model augments the TE Tunnel model.

## 2. Terminology and Notations

A simplified graphical representation of the data model is used in this document. The meaning of the symbols in the YANG data tree presented later in this draft is defined in [RFC8340]. They are provided below for reference.

- o Brackets "[" and "]" enclose list keys.
- o Abbreviations before data node names: "rw" means configuration (read-write) and "ro" state data (read-only).
- o Symbols after data node names: "?" means an optional node, "!" means a presence container, and "\*" denotes a list and leaf-list.
- o Parentheses enclose choice and case nodes, and case nodes are also marked with a colon (":").
- o Ellipsis ("...") stands for contents of subtrees that are not shown.
- o More OTN specific terms can be found in [I-D.ietf-ccamp-otn-topo-yang].

### 3. OTN Tunnel Model Description

#### 3.1. Overview of OTN Tunnel Model

The OTN tunnel model is using TE tunnel [I-D.ietf-teas-yang-te] as a basic model and augment to the TE tunnel with OTN-specific parameters, including the bandwidth information and label information. It is also worth noting that the OTN tunnel provisioning is usually based on the OTN topology. Therefore the OTN tunnel model is usually used together with OTN topology model specified in [I-D.ietf-ccamp-otn-topo-yang]. The OTN tunnel model also imports a few type modules, including ietf-otn-types, ietf-te-types and ietf-inet-types.

More scenarios and model applications can be found in [I-D.ietf-ccamp-transport-nbi-app-statement] and [I-D.ietf-teas-actn-yang]. The current model is following the YANG language specification as [RFC7950], and the corresponding protocol is recommended to be Netconf protocol in [RFC6241] or RESTconf protocol in [RFC8040].

The YANG module ietf-otn-tunnel defined in this document conforms to the Network Management Datastore Architecture (NMDA) defined in [RFC8342].

#### 3.2. OTN-specific Parameters in Tunnel Model

OTN specific parameters have been augmenting to the TE tunnel models. The attributes on both of the source and destination need to be configured when setting up the tunnel. Typical parameters, including client signal, TPN, TSG and corresponding tributary slot information,

are required in the OTN tunnel model. These parameters are consistent with the framework in [RFC7062], and the specification in [RFC7138] and [RFC7139].

The OTN bandwidth information has been augmenting to various sections of TE tunnel models, including tunnel bandwidth, primary path bandwidth and so on. The OTN label information has been augmenting to label hop of a group of routing objects and also LSPs.

### 3.3. OTN Path Compute RPC

Similarly with TE tunnel, a 'compute-only' mode of OTN tunnel model is also supported for stateful path computation. Given the OTN tunnel computed, the client may query and/or subscribe on the tunnel to be notified whenever it changes. In addition, also a stateless Remote Procedural Call (RPC) is specified. On receiving this RPC, the provider is expected to compute the available path subject to the constraints specified in RPC and feedback to the client without any changing of the OTN network or the OTN tunnels.

## 4. OTN Tunnel YANG Tree

```
module: ietf-otn-tunnel
  augment /te:te/te:tunnels/te:tunnel:
    +--rw src-client-signal?  identityref
    +--rw dst-client-signal?  identityref
  augment /te:te/te:globals/te:named-path-constraints
    /te:named-path-constraint/te:te-bandwidth/te:technology:
    +--:(otn)
      +--rw odu-type?  identityref
  augment /te:te/te:tunnels/te:tunnel/te:te-bandwidth/te:technology:
    +--:(otn)
      +--rw odu-type?  identityref
  augment /te:te/te:tunnels/te:tunnel/te:p2p-primary-paths
    /te:p2p-primary-path/te:te-bandwidth/te:technology:
    +--:(otn)
      +--rw odu-type?  identityref
  augment /te:te/te:tunnels/te:tunnel/te:p2p-primary-paths
    /te:p2p-primary-path/te:p2p-primary-reverse-path
      /te:te-bandwidth/te:technology:
    +--:(otn)
      +--rw odu-type?  identityref
  augment /te:te/te:tunnels/te:tunnel/te:p2p-secondary-paths
    /te:p2p-secondary-path/te:te-bandwidth/te:technology:
    +--:(otn)
      +--rw odu-type?  identityref
  augment /te:te/te:globals/te:named-path-constraints
```

```

        /te:named-path-constraint/te:explicit-route-objects-always
        /te:route-object-exclude-always/te:type/te:label
        /te:label-hop/te:te-label/te:technology:
+--:(otn)
  +--rw tpn?          uint16
  +--rw tsg?          identityref
  +--rw ts-list?      string
augment /te:te/te:globals/te:named-path-constraints
  /te:named-path-constraint/te:explicit-route-objects-always
  /te:route-object-include-exclude/te:type/te:label
  /te:label-hop/te:te-label/te:technology:
+--:(otn)
  +--rw tpn?          uint16
  +--rw tsg?          identityref
  +--rw ts-list?      string
augment /te:te/te:globals/te:named-path-constraints
  /te:named-path-constraint/te:path-in-segment
  /te:label-restrictions/te:label-restriction:
  +--rw range-type?   identityref
  +--rw tsg?          identityref
  +--rw priority?     uint8
augment /te:te/te:globals/te:named-path-constraints
  /te:named-path-constraint/te:path-in-segment
  /te:label-restrictions/te:label-restriction
  /te:label-start/te:te-label/te:technology:
+--:(otn)
  +--rw (otn-label-type)?
    +--:(tributary-port)
    |   +--rw tpn?     uint16
    +--:(tributary-slot)
    |   +--rw ts?      uint16
augment /te:te/te:globals/te:named-path-constraints
  /te:named-path-constraint/te:path-in-segment
  /te:label-restrictions/te:label-restriction
  /te:label-end/te:te-label/te:technology:
+--:(otn)
  +--rw (otn-label-type)?
    +--:(tributary-port)
    |   +--rw tpn?     uint16
    +--:(tributary-slot)
    |   +--rw ts?      uint16
augment /te:te/te:globals/te:named-path-constraints
  /te:named-path-constraint/te:path-out-segment
  /te:label-restrictions/te:label-restriction:
  +--rw range-type?   identityref
  +--rw tsg?          identityref
  +--rw priority?     uint8
augment /te:te/te:globals/te:named-path-constraints

```

```

        /te:named-path-constraint/te:path-out-segment
        /te:label-restrictions/te:label-restriction
        /te:label-start/te:te-label/te:technology:
+--:(otn)
  +--rw (otn-label-type)?
    +--:(tributary-port)
      | +--rw tpn?      uint16
    +--:(tributary-slot)
      +--rw ts?        uint16
augment /te:te/te:globals/te:named-path-constraints
        /te:named-path-constraint/te:path-out-segment
        /te:label-restrictions/te:label-restriction
        /te:label-end/te:te-label/te:technology:
+--:(otn)
  +--rw (otn-label-type)?
    +--:(tributary-port)
      | +--rw tpn?      uint16
    +--:(tributary-slot)
      +--rw ts?        uint16
augment /te:te/te:tunnels/te:tunnel/te:p2p-primary-paths
        /te:p2p-primary-path/te:optimizations/te:algorithm
        /te:metric/te:optimization-metric
        /te:explicit-route-exclude-objects
        /te:route-object-exclude-object/te:type/te:label
        /te:label-hop/te:te-label/te:technology:
+--:(otn)
  +--rw tpn?            uint16
  +--rw tsg?            identityref
  +--rw ts-list?       string
augment /te:te/te:tunnels/te:tunnel/te:p2p-primary-paths
        /te:p2p-primary-path/te:optimizations/te:algorithm
        /te:metric/te:optimization-metric
        /te:explicit-route-include-objects
        /te:route-object-include-object/te:type/te:label
        /te:label-hop/te:te-label/te:technology:
+--:(otn)
  +--rw tpn?            uint16
  +--rw tsg?            identityref
  +--rw ts-list?       string
augment /te:te/te:tunnels/te:tunnel/te:p2p-primary-paths
        /te:p2p-primary-path/te:explicit-route-objects-always
        /te:route-object-exclude-always/te:type/te:label
        /te:label-hop/te:te-label/te:technology:
+--:(otn)
  +--rw tpn?            uint16
  +--rw tsg?            identityref
  +--rw ts-list?       string
augment /te:te/te:tunnels/te:tunnel/te:p2p-primary-paths

```

```

        /te:p2p-primary-path/te:explicit-route-objects-always
        /te:route-object-include-exclude/te:type/te:label
        /te:label-hop/te:te-label/te:technology:
+--:(otn)
  +--rw tpn?          uint16
  +--rw tsg?          identityref
  +--rw ts-list?      string
augment /te:te/te:tunnels/te:tunnel/te:p2p-primary-paths
  /te:p2p-primary-path/te:path-in-segment
    /te:label-restrictions/te:label-restriction:
  +--rw range-type?   identityref
  +--rw tsg?          identityref
  +--rw priority?     uint8
augment /te:te/te:tunnels/te:tunnel/te:p2p-primary-paths
  /te:p2p-primary-path/te:path-in-segment
    /te:label-restrictions/te:label-restriction
    /te:label-start/te:te-label/te:technology:
+--:(otn)
  +--rw (otn-label-type)?
    +--:(tributary-port)
    | +--rw tpn?      uint16
    +--:(tributary-slot)
    | +--rw ts?       uint16
augment /te:te/te:tunnels/te:tunnel/te:p2p-primary-paths
  /te:p2p-primary-path/te:path-in-segment
    /te:label-restrictions/te:label-restriction
    /te:label-end/te:te-label/te:technology:
+--:(otn)
  +--rw (otn-label-type)?
    +--:(tributary-port)
    | +--rw tpn?      uint16
    +--:(tributary-slot)
    | +--rw ts?       uint16
augment /te:te/te:tunnels/te:tunnel/te:p2p-primary-paths
  /te:p2p-primary-path/te:path-out-segment
    /te:label-restrictions/te:label-restriction:
  +--rw range-type?   identityref
  +--rw tsg?          identityref
  +--rw priority?     uint8
augment /te:te/te:tunnels/te:tunnel/te:p2p-primary-paths
  /te:p2p-primary-path/te:path-out-segment
    /te:label-restrictions/te:label-restriction
    /te:label-start/te:te-label/te:technology:
+--:(otn)
  +--rw (otn-label-type)?
    +--:(tributary-port)
    | +--rw tpn?      uint16
    +--:(tributary-slot)

```

```

        +--rw ts?      uint16
augment /te:te/te:tunnels/te:tunnel/te:p2p-primary-paths
        /te:p2p-primary-path/te:path-out-segment
            /te:label-restrictions/te:label-restriction
            /te:label-end/te:te-label/te:technology:
+--:(otn)
    +--rw (otn-label-type)?
        +--:(tributary-port)
            | +--rw tpn?      uint16
        +--:(tributary-slot)
            +--rw ts?      uint16
augment /te:te/te:tunnels/te:tunnel/te:p2p-primary-paths
        /te:p2p-primary-path/te:computed-paths-properties
            /te:computed-path-properties/te:path-properties
            /te:path-route-objects/te:path-computed-route-object
            /te:type/te:label/te:label-hop/te:te-label
            /te:technology:
+--:(otn)
    +--ro tpn?          uint16
    +--ro tsg?          identityref
    +--ro ts-list?      string
augment /te:te/te:tunnels/te:tunnel/te:p2p-primary-paths
        /te:p2p-primary-path/te:lsps/te:lsp
            /te:lsp-record-route-information
            /te:lsp-record-route-information/te:type/te:label
            /te:label-hop/te:te-label/te:technology:
+--:(otn)
    +--ro tpn?          uint16
    +--ro tsg?          identityref
    +--ro ts-list?      string
augment /te:te/te:tunnels/te:tunnel/te:p2p-primary-paths
        /te:p2p-primary-path/te:lsps/te:lsp/te:path-properties
            /te:path-route-objects/te:path-computed-route-object
            /te:type/te:label/te:label-hop/te:te-label
            /te:technology:
+--:(otn)
    +--ro tpn?          uint16
    +--ro tsg?          identityref
    +--ro ts-list?      string
augment /te:te/te:tunnels/te:tunnel/te:p2p-primary-paths
        /te:p2p-primary-path/te:p2p-primary-reverse-path
            /te:optimizations/te:algorithm/te:metric
            /te:optimization-metric
            /te:explicit-route-exclude-objects
            /te:route-object-exclude-object/te:type/te:label
            /te:label-hop/te:te-label/te:technology:
+--:(otn)
    +--rw tpn?          uint16

```



```

    +--rw tsg?          identityref
    +--rw ts-list?      string
augment /te:te/te:tunnels/te:tunnel/te:p2p-primary-paths
    /te:p2p-primary-path/te:p2p-primary-reverse-path
        /te:optimizations/te:algorithm/te:metric
        /te:optimization-metric
        /te:explicit-route-include-objects
        /te:route-object-include-object/te:type/te:label
        /te:label-hop/te:te-label/te:technology:
+--:(otn)
    +--rw tpn?          uint16
    +--rw tsg?          identityref
    +--rw ts-list?      string
augment /te:te/te:tunnels/te:tunnel/te:p2p-primary-paths
    /te:p2p-primary-path/te:p2p-primary-reverse-path
        /te:explicit-route-objects-always
        /te:route-object-exclude-always/te:type/te:label
        /te:label-hop/te:te-label/te:technology:
+--:(otn)
    +--rw tpn?          uint16
    +--rw tsg?          identityref
    +--rw ts-list?      string
augment /te:te/te:tunnels/te:tunnel/te:p2p-primary-paths
    /te:p2p-primary-path/te:p2p-primary-reverse-path
        /te:explicit-route-objects-always
        /te:route-object-include-exclude/te:type/te:label
        /te:label-hop/te:te-label/te:technology:
+--:(otn)
    +--rw tpn?          uint16
    +--rw tsg?          identityref
    +--rw ts-list?      string
augment /te:te/te:tunnels/te:tunnel/te:p2p-primary-paths
    /te:p2p-primary-path/te:p2p-primary-reverse-path
        /te:path-in-segment/te:label-restrictions
        /te:label-restriction:
    +--rw range-type?   identityref
    +--rw tsg?          identityref
    +--rw priority?     uint8
augment /te:te/te:tunnels/te:tunnel/te:p2p-primary-paths
    /te:p2p-primary-path/te:p2p-primary-reverse-path
        /te:path-in-segment/te:label-restrictions
        /te:label-restriction/te:label-start/te:te-label
        /te:technology:
+--:(otn)
    +--rw (otn-label-type)?
    |   +--:(tributary-port)
    |   |   +--rw tpn?   uint16
    |   +--:(tributary-slot)

```

```

        +--rw ts?      uint16
augment /te:te/te:tunnels/te:tunnel/te:p2p-primary-paths
      /te:p2p-primary-path/te:p2p-primary-reverse-path
        /te:path-in-segment/te:label-restrictions
        /te:label-restriction/te:label-end/te:te-label
        /te:technology:
+--:(otn)
  +--rw (otn-label-type)?
    +--:(tributary-port)
      | +--rw tpn?      uint16
    +--:(tributary-slot)
      +--rw ts?      uint16
augment /te:te/te:tunnels/te:tunnel/te:p2p-primary-paths
      /te:p2p-primary-path/te:p2p-primary-reverse-path
        /te:path-out-segment/te:label-restrictions
        /te:label-restriction:
+--rw range-type?      identityref
+--rw tsg?              identityref
+--rw priority?        uint8
augment /te:te/te:tunnels/te:tunnel/te:p2p-primary-paths
      /te:p2p-primary-path/te:p2p-primary-reverse-path
        /te:path-out-segment/te:label-restrictions
        /te:label-restriction/te:label-start/te:te-label
        /te:technology:
+--:(otn)
  +--rw (otn-label-type)?
    +--:(tributary-port)
      | +--rw tpn?      uint16
    +--:(tributary-slot)
      +--rw ts?      uint16
augment /te:te/te:tunnels/te:tunnel/te:p2p-primary-paths
      /te:p2p-primary-path/te:p2p-primary-reverse-path
        /te:path-out-segment/te:label-restrictions
        /te:label-restriction/te:label-end/te:te-label
        /te:technology:
+--:(otn)
  +--rw (otn-label-type)?
    +--:(tributary-port)
      | +--rw tpn?      uint16
    +--:(tributary-slot)
      +--rw ts?      uint16
augment /te:te/te:tunnels/te:tunnel/te:p2p-primary-paths
      /te:p2p-primary-path/te:p2p-primary-reverse-path
        /te:computed-paths-properties
        /te:computed-path-properties
        /te:path-properties/te:path-route-objects
        /te:path-computed-route-object/te:type/te:label
        /te:label-hop/te:te-label/te:technology:

```

```

+--:(otn)
  +--ro tpn?          uint16
  +--ro tsg?          identityref
  +--ro ts-list?      string
augment /te:te/te:tunnels/te:tunnel/te:p2p-primary-paths
  /te:p2p-primary-path/te:p2p-primary-reverse-path
    /te:lsps/te:lsp/te:lsp-record-route-information
    /te:lsp-record-route-information/te:type/te:label
    /te:label-hop/te:te-label/te:technology:

+--:(otn)
  +--ro tpn?          uint16
  +--ro tsg?          identityref
  +--ro ts-list?      string
augment /te:te/te:tunnels/te:tunnel/te:p2p-primary-paths
  /te:p2p-primary-path/te:p2p-primary-reverse-path
    /te:lsps/te:lsp/te:path-properties/te:path-route-objects
    /te:path-computed-route-object/te:type/te:label
    /te:label-hop/te:te-label/te:technology:

+--:(otn)
  +--ro tpn?          uint16
  +--ro tsg?          identityref
  +--ro ts-list?      string
augment /te:te/te:tunnels/te:tunnel/te:p2p-secondary-paths
  /te:p2p-secondary-path/te:optimizations/te:algorithm
    /te:metric/te:optimization-metric
    /te:explicit-route-exclude-objects
    /te:route-object-exclude-object/te:type/te:label
    /te:label-hop/te:te-label/te:technology:

+--:(otn)
  +--rw tpn?          uint16
  +--rw tsg?          identityref
  +--rw ts-list?      string
augment /te:te/te:tunnels/te:tunnel/te:p2p-secondary-paths
  /te:p2p-secondary-path/te:optimizations/te:algorithm
    /te:metric/te:optimization-metric
    /te:explicit-route-include-objects
    /te:route-object-include-object/te:type/te:label
    /te:label-hop/te:te-label/te:technology:

+--:(otn)
  +--rw tpn?          uint16
  +--rw tsg?          identityref
  +--rw ts-list?      string
augment /te:te/te:tunnels/te:tunnel/te:p2p-secondary-paths
  /te:p2p-secondary-path/te:explicit-route-objects-always
    /te:route-object-exclude-always/te:type/te:label
    /te:label-hop/te:te-label/te:technology:

+--:(otn)
  +--rw tpn?          uint16

```

```

    +--rw tsg?          identityref
    +--rw ts-list?      string
augment /te:te/te:tunnels/te:tunnel/te:p2p-secondary-paths
    /te:p2p-secondary-path/te:explicit-route-objects-always
    /te:route-object-include-exclude/te:type/te:label
    /te:label-hop/te:te-label/te:technology:

+--:(otn)
    +--rw tpn?          uint16
    +--rw tsg?          identityref
    +--rw ts-list?      string
augment /te:te/te:tunnels/te:tunnel/te:p2p-secondary-paths
    /te:p2p-secondary-path/te:path-in-segment
    /te:label-restrictions/te:label-restriction:
    +--rw range-type?   identityref
    +--rw tsg?          identityref
    +--rw priority?     uint8
augment /te:te/te:tunnels/te:tunnel/te:p2p-secondary-paths
    /te:p2p-secondary-path/te:path-in-segment
    /te:label-restrictions/te:label-restriction
    /te:label-start/te:te-label/te:technology:

+--:(otn)
    +--rw (otn-label-type)?
    +--:(tributary-port)
    |   +--rw tpn?      uint16
    +--:(tributary-slot)
    |   +--rw ts?       uint16
augment /te:te/te:tunnels/te:tunnel/te:p2p-secondary-paths
    /te:p2p-secondary-path/te:path-in-segment
    /te:label-restrictions/te:label-restriction
    /te:label-end/te:te-label/te:technology:

+--:(otn)
    +--rw (otn-label-type)?
    +--:(tributary-port)
    |   +--rw tpn?      uint16
    +--:(tributary-slot)
    |   +--rw ts?       uint16
augment /te:te/te:tunnels/te:tunnel/te:p2p-secondary-paths
    /te:p2p-secondary-path/te:path-out-segment
    /te:label-restrictions/te:label-restriction:
    +--rw range-type?   identityref
    +--rw tsg?          identityref
    +--rw priority?     uint8
augment /te:te/te:tunnels/te:tunnel/te:p2p-secondary-paths
    /te:p2p-secondary-path/te:path-out-segment
    /te:label-restrictions/te:label-restriction
    /te:label-start/te:te-label/te:technology:

+--:(otn)
    +--rw (otn-label-type)?

```

```

    +---:(tributary-port)
    |   +---rw tpn?      uint16
    +---:(tributary-slot)
        +---rw ts?      uint16
augment /te:te/te:tunnels/te:tunnel/te:p2p-secondary-paths
    /te:p2p-secondary-path/te:path-out-segment
        /te:label-restrictions/te:label-restriction
        /te:label-end/te:te-label/te:technology:
+---:(otn)
    +---rw (otn-label-type)?
    +---:(tributary-port)
    |   +---rw tpn?      uint16
    +---:(tributary-slot)
        +---rw ts?      uint16
augment /te:te/te:tunnels/te:tunnel/te:p2p-secondary-paths
    /te:p2p-secondary-path/te:computed-paths-properties
        /te:computed-path-properties/te:path-properties
        /te:path-route-objects/te:path-computed-route-object
        /te:type/te:label/te:label-hop/te:te-label/te:technology:
+---:(otn)
    +---ro tpn?          uint16
    +---ro tsg?          identityref
    +---ro ts-list?      string
augment /te:te/te:tunnels/te:tunnel/te:p2p-secondary-paths
    /te:p2p-secondary-path/te:lsps/te:lsp
        /te:lsp-record-route-information
        /te:lsp-record-route-information/te:type/te:label
        /te:label-hop/te:te-label/te:technology:
+---:(otn)
    +---ro tpn?          uint16
    +---ro tsg?          identityref
    +---ro ts-list?      string
augment /te:te/te:tunnels/te:tunnel/te:p2p-secondary-paths
    /te:p2p-secondary-path/te:lsps/te:lsp/te:path-properties
        /te:path-route-objects/te:path-computed-route-object
        /te:type/te:label/te:label-hop/te:te-label/te:technology:
+---:(otn)
    +---ro tpn?          uint16
    +---ro tsg?          identityref
    +---ro ts-list?      string
augment /te:te/te:lsps-state/te:lsp
    /te:lsp-record-route-information
        /te:lsp-record-route-information/te:type/te:label
        /te:label-hop/te:te-label/te:technology:
+---:(otn)
    +---ro tpn?          uint16
    +---ro tsg?          identityref
    +---ro ts-list?      string

```

## 5. OTN Tunnel YANG Code

```
<CODE BEGINS>file "ietf-otn-tunnel@2019-07-08.yang"
module iETF-otn-tunnel {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-otn-tunnel";
  prefix "otn-tunnel";

  import iETF-te {
    prefix "te";
    reference
      "I-D.ietf-teas-yang-te: A YANG Data Model for Traffic Engineering
      Tunnels and Interfaces. ";
  }

  import iETF-layer1-types {
    prefix "layer1-types";
    reference
      "I-D.ietf-ccamp-layer1-types: A YANG Data Model for Layer 1 Types.";
  }

  organization
    "IETF CCAMP Working Group";
  contact
    "WG Web: <http://tools.ietf.org/wg/ccamp/>
    WG List: <mailto:ccamp@ietf.org>

    Editor: Haomian Zheng
           <mailto:zhenghaomian@huawei.com>

    Editor: Aihua Guo
           <mailto:aihuaguo@huawei.com>

    Editor: Italo Busi
           <mailto:italo.busi@huawei.com>

    Editor: Anurag Sharma
           <mailto:ansha@google.com>

    Editor: Rajan Rao
           <mailto:rrao@infinera.com>

    Editor: Sergio Belotti
           <mailto:sergio.belotti@nokia.com>

    Editor: Victor Lopez
           <mailto:victor.lopezalvarez@telefonica.com>
```

Editor: Yunbo Li  
<mailto:liyunbo@chinamobile.com>

Editor: Yunbin Xu  
<mailto:xuyunbin@ritt.cn>;

description

"This module defines a model for OTN Tunnel Services.

Copyright (c) 2018 IETF Trust and the persons  
identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or  
without modification, is permitted pursuant to, and subject  
to the license terms contained in, the Simplified BSD License  
set forth in Section 4.c of the IETF Trust's Legal Provisions  
Relating to IETF Documents  
(<https://trustee.ietf.org/license-info>).";

```
revision "2018-08-23" {  
  description  
    "Initial Revision";  
  reference  
    "RFC XXXX: OTN Tunnel YANG Model";  
  // RFC Ed.: replace XXXX with actual RFC number, update date  
  // information and remove this note  
}  
  
/*  
 * Groupings  
 */
```

```
grouping otn-tunnel-attributes {  
  description "Parameters for OTN tunnel";  
  
  leaf src-client-signal {  
    type identityref {  
      base layer1-types:client-signal;  
    }  
    description  
      "Client signal at the source endpoint of the tunnel. ";  
  }  
  
  leaf dst-client-signal {  
    type identityref {  
      base layer1-types:client-signal;  
    }  
    description
```

```
        "Client signal at the destination endpoint of the tunnel";
    }

}

/*
 * Data nodes
 */

augment "/te:te/te:tunnels/te:tunnel" {
    description
        "Augment with additional parameters required for OTN service";
    uses otn-tunnel-attributes;
}

/*
 * Augment TE bandwidth
 */

    /* Augment bandwidth of named-path-constraints */
    augment "/te:te/te:globals/te:named-path-constraints/"
        + "te:named-path-constraint/"
        + "te:te-bandwidth/te:technology" {
        description "OTN bandwidth.";
        case otn {
            uses layer1-types:otn-path-bandwidth;
        }
    }

/* Augment bandwidth of tunnel */
    augment "/te:te/te:tunnels/te:tunnel/"
        + "te:te-bandwidth/te:technology" {
        description "OTN bandwidth.";
        case otn {
            uses layer1-types:otn-path-bandwidth;
        }
    }

/* Augment bandwidth of primary path */
    augment "/te:te/te:tunnels/te:tunnel/"
        + "te:p2p-primary-paths/te:p2p-primary-path/"
        + "te:te-bandwidth/te:technology" {
        description "OTN bandwidth.";
        case otn {
            uses layer1-types:otn-path-bandwidth;
        }
    }
}
```



```
/* Augment bandwidth of reverse primary path */
augment "/te:te/te:tunnels/te:tunnel/"
  + "te:p2p-primary-paths/te:p2p-primary-path/"
  + "te:p2p-primary-reverse-path/"
  + "te:te-bandwidth/te:technology" {
  description "OTN bandwidth.";
  case otn {
    uses layer1-types:otn-path-bandwidth;
  }
}

/* Augment bandwidth of secondary path */
augment "/te:te/te:tunnels/te:tunnel/"
  + "te:p2p-secondary-paths/te:p2p-secondary-path/"
  + "te:te-bandwidth/te:technology" {
  description "OTN bandwidth.";
  case otn {
    uses layer1-types:otn-path-bandwidth;
  }
}

/*
 * Augment TE label.
 */

/* Augment label hop of route-object-exclude-always of named-path-constraints
 */
augment "/te:te/te:globals/te:named-path-constraints/"
  + "te:named-path-constraint/te:explicit-route-objects-always/"
  + "te:route-object-exclude-always/te:type/te:label/"
  + "te:label-hop/te:te-label/te:technology" {
  description "OTN label.";
  case otn {
    uses layer1-types:otn-path-label;
  }
}

/* Augment label hop of route-object-include-exclude of named-path-constraints
 */
augment "/te:te/te:globals/te:named-path-constraints/"
  + "te:named-path-constraint/te:explicit-route-objects-always/"
  + "te:route-object-include-exclude/te:type/te:label/"
  + "te:label-hop/te:te-label/te:technology" {
  description "OTN label.";
  case otn {
    uses layer1-types:otn-path-label;
  }
}

/* Augment label restrictions for the forwarding direction of path-in-segment
of named-path-constraints */
```

```
augment "/te:te/te:globals/te:named-path-constraints/"
  + "te:named-path-constraint/te:path-in-segment/"
  + "te:label-restrictions/te:label-restriction" {
  description "OTN label.";
  uses layer1-types:otn-label-restriction;
}

/* Augment label restrictions start for the forwarding direction of path-in-segment of named-path-constraints */
augment "/te:te/te:globals/te:named-path-constraints/"
  + "te:named-path-constraint/te:path-in-segment/"
  + "te:label-restrictions/"
  + "te:label-restriction/te:label-start/"
  + "te:te-label/te:technology" {
  description "OTN label.";
  case otn {
    uses layer1-types:otn-link-label;
  }
}

/* Augment label restrictions end for the forwarding direction of path-in-segment of named-path-constraints */
augment "/te:te/te:globals/te:named-path-constraints/"
  + "te:named-path-constraint/te:path-in-segment/"
  + "te:label-restrictions/"
  + "te:label-restriction/te:label-end/"
  + "te:te-label/te:technology" {
  description "OTN label.";
  case otn {
    uses layer1-types:otn-link-label;
  }
}

/* Augment label restrictions for the forwarding direction of path-out-segment of named-path-constraints */
augment "/te:te/te:globals/te:named-path-constraints/"
  + "te:named-path-constraint/te:path-out-segment/"
  + "te:label-restrictions/"
  + "te:label-restriction" {
  description "OTN label.";
  uses layer1-types:otn-label-restriction;
}

/* Augment label restrictions start for the forwarding direction of path-out-segment of named-path-constraints */
augment "/te:te/te:globals/te:named-path-constraints/"
  + "te:named-path-constraint/te:path-out-segment/"
  + "te:label-restrictions/"
  + "te:label-restriction/te:label-start/"
  + "te:te-label/te:technology" {
  description "OTN label.";
  case otn {
    uses layer1-types:otn-link-label;
  }
}
```

```

    }
  }

  /* Augment label restrictions end for the forwarding direction of path-out-seg
  ment of named-path-constraints */
  augment "/te:te/te:globals/te:named-path-constraints/"
    + "te:named-path-constraint/te:path-out-segment/"
    + "te:label-restrictions/"
    + "te:label-restriction/te:label-end/"
    + "te:te-label/te:technology" {
    description "OTN label.";
    case otn {
      uses layer1-types:otn-link-label;
    }
  }

  /* Augment label hop of route-exclude of primary path */
  augment "/te:te/te:tunnels/te:tunnel/"
    + "te:p2p-primary-paths/te:p2p-primary-path/"
    + "te:optimizations/te:algorithm/te:metric/"
    + "te:optimization-metric/te:explicit-route-exclude-objects/"
    + "te:route-object-exclude-object/te:type/te:label/"
    + "te:label-hop/te:te-label/te:technology" {
    description "OTN label.";
    case otn {
      uses layer1-types:otn-path-label;
    }
  }

  /* Augment label hop of route-include of primary path */
  augment "/te:te/te:tunnels/te:tunnel/"
    + "te:p2p-primary-paths/te:p2p-primary-path/"
    + "te:optimizations/te:algorithm/te:metric/"
    + "te:optimization-metric/te:explicit-route-include-objects/"
    + "te:route-object-include-object/te:type/te:label/"
    + "te:label-hop/te:te-label/te:technology" {
    description "OTN label.";
    case otn {
      uses layer1-types:otn-path-label;
    }
  }

  /* Augment label hop of route-object-exclude-always of primary path */
  augment "/te:te/te:tunnels/te:tunnel/"
    + "te:p2p-primary-paths/te:p2p-primary-path/"
    + "te:explicit-route-objects-always/"
    + "te:route-object-exclude-always/te:type/te:label/"
    + "te:label-hop/te:te-label/te:technology" {
    description "OTN label.";
  }

```

```
    case otn {
        uses layer1-types:otn-path-label;
    }
}

/* Augment label hop of route-object-include-exclude of primary path */
augment "/te:te/te:tunnels/te:tunnel/"
    + "te:p2p-primary-paths/te:p2p-primary-path/"
    + "te:explicit-route-objects-always/"
    + "te:route-object-include-exclude/te:type/te:label/"
    + "te:label-hop/te:te-label/te:technology" {
    description "OTN label.";
    case otn {
        uses layer1-types:otn-path-label;
    }
}

/* Augment label restrictions for the forwarding direction of path-in-segment
of primary path */
augment "/te:te/te:tunnels/te:tunnel/"
    + "te:p2p-primary-paths/te:p2p-primary-path/"
    + "te:path-in-segment/te:label-restrictions/"
    + "te:label-restriction" {
    description "OTN label.";
    uses layer1-types:otn-label-restriction;
}

/* Augment label restrictions start for the forwarding direction of path-in-segment
of primary path */
augment "/te:te/te:tunnels/te:tunnel/"
    + "te:p2p-primary-paths/te:p2p-primary-path/"
    + "te:path-in-segment/te:label-restrictions/"
    + "te:label-restriction/te:label-start/"
    + "te:te-label/te:technology" {
    description "OTN label.";
    case otn {
        uses layer1-types:otn-link-label;
    }
}

/* Augment label restrictions end for the forwarding direction of path-in-segment
of primary path */
augment "/te:te/te:tunnels/te:tunnel/"
    + "te:p2p-primary-paths/te:p2p-primary-path/"
    + "te:path-in-segment/te:label-restrictions/"
    + "te:label-restriction/te:label-end/"
    + "te:te-label/te:technology" {
    description "OTN label.";
    case otn {
        uses layer1-types:otn-link-label;
    }
}
```

```

    }
  }

  /* Augment label restrictions for the forwarding direction of path-out-segment
  of primary path */
  augment "/te:te/te:tunnels/te:tunnel/"
    + "te:p2p-primary-paths/te:p2p-primary-path/"
    + "te:path-out-segment/te:label-restrictions/"
    + "te:label-restriction" {
    description "OTN label.";
    uses layer1-types:otn-label-restriction;
  }

  /* Augment label restrictions start for the forwarding direction of path-out-s
  egment of primary path */
  augment "/te:te/te:tunnels/te:tunnel/"
    + "te:p2p-primary-paths/te:p2p-primary-path/"
    + "te:path-out-segment/te:label-restrictions/"
    + "te:label-restriction/te:label-start/"
    + "te:te-label/te:technology" {

    description "OTN label.";
    case otn {
      uses layer1-types:otn-link-label;
    }
  }

  /* Augment label restrictions end for the forwarding direction of path-out-seg
  ment of primary path */
  augment "/te:te/te:tunnels/te:tunnel/"
    + "te:p2p-primary-paths/te:p2p-primary-path/"
    + "te:path-out-segment/te:label-restrictions/"
    + "te:label-restriction/te:label-end/"
    + "te:te-label/te:technology" {
    description "OTN label.";
    case otn {
      uses layer1-types:otn-link-label;
    }
  }

  /* Augment label hop of path-route of primary path */
  augment "/te:te/te:tunnels/te:tunnel/"
    + "te:p2p-primary-paths/te:p2p-primary-path/"
    + "te:computed-paths-properties/"
    + "te:computed-path-properties/te:path-properties/"
    + "te:path-route-objects/te:path-computed-route-object/"
    + "te:type/te:label/"
    + "te:label-hop/te:te-label/te:technology" {
    description "OTN label.";
    case otn {
      uses layer1-types:otn-path-label;
    }
  }

```

```
    }
  }

/* Augment label hop of record-route of primary LSP */
augment "/te:te/te:tunnels/te:tunnel/"
  + "te:p2p-primary-paths/te:p2p-primary-path/"
  + "te:lsps/te:lsp/te:lsp-record-route-information/"
  + "te:lsp-record-route-information/te:type/te:label/"
  + "te:label-hop/te:te-label/te:technology" {
  description "OTN label.";
  case otn {
    uses layer1-types:otn-path-label;
  }
}

/* Augment label hop of path-route of primary LSP */
augment "/te:te/te:tunnels/te:tunnel/"
  + "te:p2p-primary-paths/te:p2p-primary-path/"
  + "te:lsps/te:lsp/te:path-properties/"
  + "te:path-route-objects/te:path-computed-route-object/"
  + "te:type/te:label/"
  + "te:label-hop/te:te-label/te:technology" {
  description "OTN label.";
  case otn {
    uses layer1-types:otn-path-label;
  }
}

/* Augment label hop of route-exclude of reverse primary path */
augment "/te:te/te:tunnels/te:tunnel/"
  + "te:p2p-primary-paths/te:p2p-primary-path/"
  + "te:p2p-primary-reverse-path/"
  + "te:optimizations/te:algorithm/te:metric/"
  + "te:optimization-metric/te:explicit-route-exclude-objects/"
  + "te:route-object-exclude-object/te:type/te:label/"
  + "te:label-hop/te:te-label/te:technology" {
  description "OTN label.";
  case otn {
    uses layer1-types:otn-path-label;
  }
}

/* Augment label hop of route-include of reverse primary path */
augment "/te:te/te:tunnels/te:tunnel/"
  + "te:p2p-primary-paths/te:p2p-primary-path/"
  + "te:p2p-primary-reverse-path/"
  + "te:optimizations/te:algorithm/te:metric/"
  + "te:optimization-metric/te:explicit-route-include-objects/"
```

```

        + "te:route-object-include-object/te:type/te:label/"
        + "te:label-hop/te:te-label/te:technology" {
    description "OTN label.";
    case otn {
        uses layer1-types:otn-path-label;
    }
}

/* Augment label hop of route-object-exclude-always of reverse primary path */
augment "/te:te/te:tunnels/te:tunnel/"
    + "te:p2p-primary-paths/te:p2p-primary-path/"
    + "te:p2p-primary-reverse-path/"
    + "te:explicit-route-objects-always/"
    + "te:route-object-exclude-always/"
    + "te:type/te:label/"
    + "te:label-hop/te:te-label/te:technology" {
    description "OTN label.";
    case otn {
        uses layer1-types:otn-path-label;
    }
}

/* Augment label hop of route-object-include-exclude of reverse primary path */
/
augment "/te:te/te:tunnels/te:tunnel/"
    + "te:p2p-primary-paths/te:p2p-primary-path/"
    + "te:p2p-primary-reverse-path/"
    + "te:explicit-route-objects-always/"
    + "te:route-object-include-exclude/"
    + "te:type/te:label/"
    + "te:label-hop/te:te-label/te:technology" {
    description "OTN label.";
    case otn {
        uses layer1-types:otn-path-label;
    }
}

/* Augment label restrictions for the forwarding direction of path-in-segment
of reverse primary path */
augment "/te:te/te:tunnels/te:tunnel/"
    + "te:p2p-primary-paths/te:p2p-primary-path/"
    + "te:p2p-primary-reverse-path/"
    + "te:path-in-segment/te:label-restrictions/"
    + "te:label-restriction" {
    description "OTN label.";
    uses layer1-types:otn-label-restriction;
}

/* Augment label restrictions start for the forwarding direction of path-in-segment
of reverse primary path */
augment "/te:te/te:tunnels/te:tunnel/"

```

```
    + "te:p2p-primary-paths/te:p2p-primary-path/"
    + "te:p2p-primary-reverse-path/"
    + "te:path-in-segment/te:label-restrictions/"
    + "te:label-restriction/te:label-start/"
    + "te:te-label/te:technology" {
description "OTN label.";
case otn {
    uses layer1-types:otn-link-label;
}
}

/* Augment label restrictions end for the forwarding direction of path-in-segment of reverse primary path */
augment "/te:te/te:tunnels/te:tunnel/"
    + "te:p2p-primary-paths/te:p2p-primary-path/"
    + "te:p2p-primary-reverse-path/"
    + "te:path-in-segment/te:label-restrictions/"
    + "te:label-restriction/te:label-end/"
    + "te:te-label/te:technology" {
description "OTN label.";
case otn {
    uses layer1-types:otn-link-label;
}
}

/* Augment label restrictions for the forwarding direction of path-out-segment of reverse primary path */
augment "/te:te/te:tunnels/te:tunnel/"
    + "te:p2p-primary-paths/te:p2p-primary-path/"
    + "te:p2p-primary-reverse-path/"
    + "te:path-out-segment/te:label-restrictions/"
    + "te:label-restriction" {
description "OTN label.";
uses layer1-types:otn-label-restriction;
}

/* Augment label restrictions start for the forwarding direction of path-out-segment of reverse primary path */
augment "/te:te/te:tunnels/te:tunnel/"
    + "te:p2p-primary-paths/te:p2p-primary-path/"
    + "te:p2p-primary-reverse-path/"
    + "te:path-out-segment/te:label-restrictions/"
    + "te:label-restriction/te:label-start/"
    + "te:te-label/te:technology" {
description "OTN label.";
case otn {
    uses layer1-types:otn-link-label;
}
}

/* Augment label restrictions end for the forwarding direction of path-out-segment of reverse primary path */
```



```
augment "/te:te/te:tunnels/te:tunnel/"
  + "te:p2p-primary-paths/te:p2p-primary-path/"
  + "te:p2p-primary-reverse-path/"
  + "te:path-out-segment/te:label-restrictions/"
  + "te:label-restriction/te:label-end/"
  + "te:te-label/te:technology" {
  description "OTN label.";
  case otn {
    uses layer1-types:otn-link-label;
  }
}

/* Augment label hop of path-route of reverse primary path */
augment "/te:te/te:tunnels/te:tunnel/"
  + "te:p2p-primary-paths/te:p2p-primary-path/"
  + "te:p2p-primary-reverse-path/"
  + "te:computed-paths-properties"
    + "/te:computed-path-properties/te:path-properties/"
  + "te:path-route-objects/te:path-computed-route-object/"
  + "te:type/te:label/"
  + "te:label-hop/te:te-label/te:technology" {
  description "OTN label.";
  case otn {
    uses layer1-types:otn-path-label;
  }
}

/* Augment label hop of record-route of reverse primary LSP */
augment "/te:te/te:tunnels/te:tunnel/"
  + "te:p2p-primary-paths/te:p2p-primary-path/"
  + "te:p2p-primary-reverse-path/"
  + "te:lsps/te:lsp/te:lsp-record-route-information/"
  + "te:lsp-record-route-information/te:type/te:label/"
  + "te:label-hop/te:te-label/te:technology" {
  description "OTN label.";
  case otn {
    uses layer1-types:otn-path-label;
  }
}

/* Augment label hop of path-route of reverse primary LSP */
augment "/te:te/te:tunnels/te:tunnel/"
  + "te:p2p-primary-paths/te:p2p-primary-path/"
  + "te:p2p-primary-reverse-path/"
  + "te:lsps/te:lsp/te:path-properties/"
  + "te:path-route-objects/te:path-computed-route-object/"
  + "te:type/te:label/"
  + "te:label-hop/te:te-label/te:technology" {
```

```
    description "OTN label.";
    case otn {
        uses layer1-types:otn-path-label;
    }
}

/* Augment label hop of route-exclude of secondary path */
augment "/te:te/te:tunnels/te:tunnel/"
    + "te:p2p-secondary-paths/te:p2p-secondary-path/"
    + "te:optimizations/te:algorithm/te:metric/"
    + "te:optimization-metric/te:explicit-route-exclude-objects/"
    + "te:route-object-exclude-object/te:type/te:label/"
    + "te:label-hop/te:te-label/te:technology" {

    description "OTN label.";
    case otn {
        uses layer1-types:otn-path-label;
    }
}

/* Augment label hop of route-include of secondary path */
augment "/te:te/te:tunnels/te:tunnel/"
    + "te:p2p-secondary-paths/te:p2p-secondary-path/"
    + "te:optimizations/te:algorithm/te:metric/"
    + "te:optimization-metric/te:explicit-route-include-objects/"
    + "te:route-object-include-object/te:type/te:label/"
    + "te:label-hop/te:te-label/te:technology" {
    description "OTN label.";
    case otn {
        uses layer1-types:otn-path-label;
    }
}

/* Augment label hop of route-object-exclude-always of secondary path */
augment "/te:te/te:tunnels/te:tunnel/"
    + "te:p2p-secondary-paths/te:p2p-secondary-path/"
    + "te:explicit-route-objects-always/"
    + "te:route-object-exclude-always/te:type/te:label/"
    + "te:label-hop/te:te-label/te:technology" {
    description "OTN label.";
    case otn {
        uses layer1-types:otn-path-label;
    }
}

/* Augment label hop of route-object-include-exclude of secondary path */
augment "/te:te/te:tunnels/te:tunnel/"
    + "te:p2p-secondary-paths/te:p2p-secondary-path/"
```

```

    + "te:explicit-route-objects-always/"
    + "te:route-object-include-exclude/te:type/te:label/"
    + "te:label-hop/te:te-label/te:technology" {
description "OTN label.";
case otn {
    uses layer1-types:otn-path-label;
}
}

/* Augment label restrictions for the forwarding direction of path-in-segment
of secondary path */
augment "/te:te/te:tunnels/te:tunnel/"
    + "te:p2p-secondary-paths/te:p2p-secondary-path/"
    + "te:path-in-segment/te:label-restrictions/"
    + "te:label-restriction" {

description "OTN label.";
uses layer1-types:otn-label-restriction;
}

/* Augment label restrictions start for the forwarding direction of path-in-segment
of secondary path */
augment "/te:te/te:tunnels/te:tunnel/"
    + "te:p2p-secondary-paths/te:p2p-secondary-path/"
    + "te:path-in-segment/te:label-restrictions/"
    + "te:label-restriction/te:label-start/"
    + "te:te-label/te:technology" {
description "OTN label.";
case otn {
    uses layer1-types:otn-link-label;
}
}

/* Augment label restrictions end for the forwarding direction of path-in-segment
of secondary path */
augment "/te:te/te:tunnels/te:tunnel/"
    + "te:p2p-secondary-paths/te:p2p-secondary-path/"
    + "te:path-in-segment/te:label-restrictions/"
    + "te:label-restriction/te:label-end/"
    + "te:te-label/te:technology" {
description "OTN label.";
case otn {
    uses layer1-types:otn-link-label;
}
}

/* Augment label restrictions for the forwarding direction of path-out-segment
of secondary path */
augment "/te:te/te:tunnels/te:tunnel/"
    + "te:p2p-secondary-paths/te:p2p-secondary-path/"
    + "te:path-out-segment/te:label-restrictions/"
    + "te:label-restriction" {

```

```
    description "OTN label.";
    uses layer1-types:otn-label-restriction;
}

/* Augment label restrictions start for the forwarding direction of path-out-segment of secondary path */
augment "/te:te/te:tunnels/te:tunnel/"
    + "te:p2p-secondary-paths/te:p2p-secondary-path/"
    + "te:path-out-segment/te:label-restrictions/"
    + "te:label-restriction/te:label-start/"
    + "te:te-label/te:technology" {
    description "OTN label.";
    case otn {
        uses layer1-types:otn-link-label;
    }
}

/* Augment label restrictions end for the forwarding direction of path-out-segment of secondary path */
augment "/te:te/te:tunnels/te:tunnel/"
    + "te:p2p-secondary-paths/te:p2p-secondary-path/"
    + "te:path-out-segment/te:label-restrictions/"
    + "te:label-restriction/te:label-end/"
    + "te:te-label/te:technology" {
    description "OTN label.";
    case otn {
        uses layer1-types:otn-link-label;
    }
}

/* Augment label hop of path-route of secondary path */
augment "/te:te/te:tunnels/te:tunnel/"
    + "te:p2p-secondary-paths/te:p2p-secondary-path/"
    + "te:computed-paths-properties/"
    + "/te:computed-path-properties/"
    + "te:path-properties/te:path-route-objects/"
    + "te:path-computed-route-object/te:type/te:label/"
    + "te:label-hop/te:te-label/te:technology" {
    description "OTN label.";
    case otn {
        uses layer1-types:otn-path-label;
    }
}

/* Augment label hop of record-route of secondary LSP */
augment "/te:te/te:tunnels/te:tunnel/"
    + "te:p2p-secondary-paths/te:p2p-secondary-path/"
    + "te:lsps/te:lsp/te:lsp-record-route-information/"
    + "te:lsp-record-route-information/te:type/te:label/"
    + "te:label-hop/te:te-label/te:technology" {
```

```
    description "OTN label.";
    case otn {
        uses layer1-types:otn-path-label;
    }
}

/* Augment label hop of path-route of secondary LSP */
augment "/te:te/te:tunnels/te:tunnel/"
    + "te:p2p-secondary-paths/te:p2p-secondary-path/"
    + "te:lsps/te:lsp/te:path-properties/"
    + "te:path-route-objects/"
    + "te:path-computed-route-object/te:type/te:label/"
    + "te:label-hop/te:te-label/te:technology" {
    description "OTN label.";
    case otn {
        uses layer1-types:otn-path-label;
    }
}

/* Augment label hop of record-route of LSP */
augment "/te:te/te:lsps-state/"
    + "te:lsp/te:lsp-record-route-information/"
    + "te:lsp-record-route-information/te:type/te:label/"
    + "te:label-hop/te:te-label/te:technology" {
    description "OTN label.";
    case otn {
        uses layer1-types:otn-path-label;
    }
}
/*
grouping p2p-path-ero {
    description
        "TE tunnel ERO configuration grouping";

    leaf te-default-metric {
        type uint32;
        description
            "Traffic engineering metric.";
    }
    leaf te-delay-metric {
        type uint32;
        description
            "Traffic engineering delay metric.";
    }
    leaf te-hop-metric {
        type uint32;
        description
            "Traffic engineering hop metric.";
    }
}
```

```
    }
    container explicit-route-objects-always {
      description "Explicit route objects container";
      list route-object-include-exclude {
        key "index";
        description
          "List of explicit route objects";
        leaf explicit-route-usage {
          type identityref {
            base te-types:route-usage-type;
          }
          description "An explicit-route hop action.";
        }
        uses te-types:explicit-route-hop {
          augment "type/label/label-hop/te-label/technology" {
            description "OTN label.";
            case otn {
              uses layer1-types:otn-path-label;
            }
          }
        }
      }
    }
  }
}
*/
/*
rpc otn-te-tunnel-path-compute {
  description "OTN TE tunnel path computation";
  input {
    list request {
      key "id";
      description "A list of path computation requests.";

      leaf id {
        type uint8;
        description
          "Request ID.";
      }
      leaf type {
        type identityref {
          base te-types:te-tunnel-type;
        }
        description "TE tunnel type.";
      }
      leaf source {
        type inet:ip-address;
        description
          "TE tunnel source address.";
      }
    }
  }
}
```

```
    }

    leaf destination {
      type inet:ip-address;
      description
        "TE tunnel destination address";
    }
    leaf src-tp-id {
      type binary;
      description
        "TE tunnel source termination point identifier.";
    }
    leaf dst-tp-id {
      type binary;
      description
        "TE tunnel destination termination point identifier.";
    }
    leaf switching-layer {
      type identityref {
        base te-types:switching-capabilities;
      }
      description
        "Switching layer where the requests are computed.";
    }
    leaf encoding {
      type identityref {
        base te-types:lsp-encoding-types;
      }
      description "LSP encoding type";
    }
    leaf protection-type {
      type identityref {
        base te-types:lsp-protection-type;
      }
      description "LSP protection type";
    }
    leaf restoration-type {
      type identityref {
        base te-types:lsp-restoration-type;
      }
      description "LSP restoration type";
    }
    leaf provider-id {
      type te-types:te-global-id;
      description
        "An identifier to uniquely identify a provider.";
    }
    leaf client-id {
```

```
    type te-types:te-global-id;
    description

        "An identifier to uniquely identify a client.";
}
leaf te-topology-id {
    type te-types:te-topology-id;
    description
        "It is presumed that a datastore will contain many
        topologies. To distinguish between topologies it is
        vital to have UNIQUE topology identifiers.";
}
leaf setup-priority {
    type uint8 {
        range "0..7";
    }
    description
        "TE LSP setup priority";
}
leaf hold-priority {
    type uint8 {
        range "0..7";
    }
    description
        "TE LSP hold priority";
}
leaf te-path-metric-type {
    type identityref {
        base te-types:path-metric-type;
    }
    default te-types:path-metric-te;
    description
        "The tunnel path metric type.";
}

leaf odu-type {
    type identityref{
        base layer1-types:odu-type;
    }
    description "Type of ODU";
}
container p2p-primary-paths {
    description "Set of P2P primary paths container";
    list p2p-primary-path {
        key "name";
        description
            "List of primary paths for this tunnel.";
        leaf name {
```



```
        type string;
        description "TE path name";
    }

    uses p2p-path-ero;
}

container p2p-secondary-paths {
    description "Set of P2P secondary paths container";
    list p2p-secondary-path {
        key "name";
        description
            "List of secondary paths for this tunnel.";
        leaf name {
            type string;
            description "TE path name";
        }
        uses p2p-path-ero;
    }
}

uses otn-tunnel-attributes;
}

output {
    leaf return-code {
        type enumeration {
            enum success {
                description "success";
            }
            enum aborted {
                description "aborted";
            }
            enum destination-not-found {
                description "destination-not-found";
            }
            enum invalid-argument {
                description "invalid-argument";
            }
            enum no-memory {
                description "no-memory";
            }
            enum no-path-found {
                description "no-path-found";
            }
            enum other-error {
                description "other-error";
            }
            enum some-path-not-found {
```

```
        description "some-path-not-found";
    }
    enum source-not-found {
        description "source-not-found";

    }
    enum topology-error {
        description "topology-error";
    }
}
description
    "Return code";
}
list result {
    key "id";
    description
        "A list of results for all requests.";

    leaf id {
        type uint8;
        description
            "Request ID";
    }
    container p2p-primary-paths {
        description "Set of P2P primary paths container";
        list p2p-primary-path {
            key "name";
            description
                "List of resultant primary paths for this tunnel.";
            leaf name {
                type string;
                description "TE path name";
            }
            uses p2p-path-ero;
        }
    }
    container p2p-secondary-paths {
        description "Set of P2P secondary paths container";
        list p2p-secondary-path {
            key "name";
            description
                "List of resultant secondary paths for this tunnel.";
            leaf name {
                type string;
                description "TE path name";
            }
            uses p2p-path-ero;
        }
    }
}
```

```

    }
  }
}
}*/
}

<CODE ENDS>

```

## 6. Security Considerations

The YANG module specified in this document defines a schema for data that is designed to be accessed via network management protocols such as NETCONF [RFC6241] or RESTCONF [RFC8040]. The lowest NETCONF layer is the secure transport layer, and the mandatory-to-implement secure transport is Secure Shell (SSH) [RFC6242]. The lowest RESTCONF layer is HTTPS, and the mandatory-to-implement secure transport is TLS [RFC8446].

The NETCONF access control model [RFC8341] provides the means to restrict access for particular NETCONF or RESTCONF users to a preconfigured subset of all available NETCONF or RESTCONF protocol operations and content.

There are a number of data nodes defined in this YANG module that are writable/creatable/deletable (i.e., config true, which is the default). These data nodes may be considered sensitive or vulnerable in some network environments. Write operations (e.g., edit-config) to these data nodes without proper protection can have a negative effect on network operations. These are the subtrees and data nodes and their sensitivity/vulnerability:

```

/te:te/te:tunnels/te:tunnel /te:te/../../te:te-bandwidth/te:technology
/te:te/../../te:type/te:label/te:label-hop/te:te-label/te:technology
/te:te/../../te:label-restrictions/te:label-restriction/te:label-start/
te:te-label/te:technology /te:te/../../te:label-restrictions/te:label-
restriction/te:label-end/te:te-label/te:technology
/te:te/../../te:label-restrictions/te:label-restriction/ Editors note:
we are using simplified description by folding similar branches to
avoid repetition.

```

Some of the readable data nodes in this YANG module may be considered sensitive or vulnerable in some network environments. It is thus important to control read access (e.g., via get, get-config, or notification) to these data nodes. These are the subtrees and data nodes and their sensitivity/vulnerability:

/te:te/../../te:type/te:label/te:label-hop/te:te-label/te:technology  
Editors note: we are using simplified description by folding similar branches to avoid repetition.

Some of the RPC operations in this YANG module may be considered sensitive or vulnerable in some network environments. It is thus important to control access to these operations. These are the operations and their sensitivity/vulnerability:

+---x otn-te-tunnel-path-compute This path compute RPC provides a mechanism to enable the client to query and/or subscribe on the tunnel to be notified whenever it changes. Thus path computation is only for the client reference, with no real deploy or resource reservation.

## 7. IANA Considerations

It is proposed that IANA should assign new URIs from the "IETF XML Registry" [RFC3688] as follows:

URI: urn:ietf:params:xml:ns:yang:ietf-otn-tunnel  
Registrant Contact: The IESG  
XML: N/A; the requested URI is an XML namespace.

URI: urn:ietf:params:xml:ns:yang:ietf-otn-types  
Registrant Contact: The IESG  
XML: N/A; the requested URI is an XML namespace.

This document registers following YANG modules in the YANG Module Names registry [RFC7950].

name:	ietf-otn-tunnel
namespace:	urn:ietf:params:xml:ns:yang:ietf-otn-tunnel
prefix:	otn-tunnel
reference:	RFC XXXX

name:	ietf-otn-types
namespace:	urn:ietf:params:xml:ns:yang:ietf-otn-types
prefix:	otn-types
reference:	RFC XXXX

## 8. Acknowledgements

TBD.

## 9. Contributors

Dieter Beller  
Nokia  
Email: dieter.beller@nokia.com

Yanlei Zheng  
China Unicom  
Email: zhengyl@dimpt.com

Xian Zhang  
Huawei Technologies  
Email: zhang.xian@huawei.com

Lei Wang  
China Mobile  
Email: wangleiyj@chinamobile.com

Oscar Gonzalez de Dios  
Telefonica  
Email: oscar.gonzalezdedios@telefonica.com

## 10. References

### 10.1. Normative References

- [I-D.ietf-ccamp-otn-topo-yang]  
Zheng, H., Guo, A., Busi, I., Sharma, A., Liu, X.,  
Belotti, S., Xu, Y., Wang, L., and O. Dios, "A YANG Data  
Model for Optical Transport Network Topology", draft-ietf-  
ccamp-otn-topo-yang-07 (work in progress), July 2019.
- [I-D.ietf-teas-yang-te]  
Saad, T., Gandhi, R., Liu, X., Beeram, V., and I. Bryskin,  
"A YANG Data Model for Traffic Engineering Tunnels and  
Interfaces", draft-ietf-teas-yang-te-21 (work in  
progress), April 2019.
- [ITU-T]  
ITU-, T., "SERIES G: TRANSMISSION SYSTEMS AND MEDIA,  
DIGITAL SYSTEMS AND NETWORKS; Digital networks; Interfaces  
for the optical transport network", ITU-T Rec. G.709v5 ,  
June 2016.

- [RFC3688] Mealling, M., "The IETF XML Registry", BCP 81, RFC 3688, DOI 10.17487/RFC3688, January 2004, <<https://www.rfc-editor.org/info/rfc3688>>.
- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", RFC 6241, DOI 10.17487/RFC6241, June 2011, <<https://www.rfc-editor.org/info/rfc6241>>.
- [RFC6242] Wasserman, M., "Using the NETCONF Protocol over Secure Shell (SSH)", RFC 6242, DOI 10.17487/RFC6242, June 2011, <<https://www.rfc-editor.org/info/rfc6242>>.
- [RFC7139] Zhang, F., Ed., Zhang, G., Belotti, S., Ceccarelli, D., and K. Pithewan, "GMPLS Signaling Extensions for Control of Evolving G.709 Optical Transport Networks", RFC 7139, DOI 10.17487/RFC7139, March 2014, <<https://www.rfc-editor.org/info/rfc7139>>.
- [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", RFC 7950, DOI 10.17487/RFC7950, August 2016, <<https://www.rfc-editor.org/info/rfc7950>>.
- [RFC8040] Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Protocol", RFC 8040, DOI 10.17487/RFC8040, January 2017, <<https://www.rfc-editor.org/info/rfc8040>>.
- [RFC8341] Bierman, A. and M. Bjorklund, "Network Configuration Access Control Model", STD 91, RFC 8341, DOI 10.17487/RFC8341, March 2018, <<https://www.rfc-editor.org/info/rfc8341>>.
- [RFC8342] Bjorklund, M., Schoenwaelder, J., Shafer, P., Watsen, K., and R. Wilton, "Network Management Datastore Architecture (NMDA)", RFC 8342, DOI 10.17487/RFC8342, March 2018, <<https://www.rfc-editor.org/info/rfc8342>>.
- [RFC8446] Rescorla, E., "The Transport Layer Security (TLS) Protocol Version 1.3", RFC 8446, DOI 10.17487/RFC8446, August 2018, <<https://www.rfc-editor.org/info/rfc8446>>.

## 10.2. Informative References

- [I-D.ietf-ccamp-transport-nbi-app-statement]  
Busi, I., King, D., Zheng, H., and Y. Xu, "Transport Northbound Interface Applicability Statement", draft-ietf-ccamp-transport-nbi-app-statement-05 (work in progress), March 2019.

- [I-D.ietf-teas-actn-yang]  
Lee, Y., Zheng, H., Ceccarelli, D., Yoon, B., Dios, O.,  
Shin, J., and S. Belotti, "Applicability of YANG models  
for Abstraction and Control of Traffic Engineered  
Networks", draft-ietf-teas-actn-yang-03 (work in  
progress), February 2019.
- [RFC7062] Zhang, F., Ed., Li, D., Li, H., Belotti, S., and D.  
Ceccarelli, "Framework for GMPLS and PCE Control of G.709  
Optical Transport Networks", RFC 7062,  
DOI 10.17487/RFC7062, November 2013,  
<<https://www.rfc-editor.org/info/rfc7062>>.
- [RFC7138] Ceccarelli, D., Ed., Zhang, F., Belotti, S., Rao, R., and  
J. Drake, "Traffic Engineering Extensions to OSPF for  
GMPLS Control of Evolving G.709 Optical Transport  
Networks", RFC 7138, DOI 10.17487/RFC7138, March 2014,  
<<https://www.rfc-editor.org/info/rfc7138>>.
- [RFC8340] Bjorklund, M. and L. Berger, Ed., "YANG Tree Diagrams",  
BCP 215, RFC 8340, DOI 10.17487/RFC8340, March 2018,  
<<https://www.rfc-editor.org/info/rfc8340>>.

#### Authors' Addresses

Haomian Zheng  
Huawei Technologies  
H1-1-A043S Huawei Industrial Base, Songshanhu  
Dongguan, Guangdong 523808  
China

Email: [zhenghaomian@huawei.com](mailto:zhenghaomian@huawei.com)

Aihua Guo  
Huawei Technologies  
12007 Sunrise Valley Drive, Suite 325  
Reston, VA 20171  
U.S.A

Email: [aihuaguo@huawei.com](mailto:aihuaguo@huawei.com)

Italo Busi  
Huawei Technologies  
HUAWEI TECHNOLOGIES ITALIA Srl Centro Direzionale Milano 2  
Milan, Milan 20090  
Italy

Email: Italo.Busi@huawei.com

Anurag Sharma  
Google  
1600 Amphitheatre Parkway  
Mountain View, CA 94043  
USA

Email: ansha@google.com

Rajan Rao  
Infinera  
169 Java Drive  
Sunnyvale, CA 94089  
USA

Email: rrao@infinera.com

Sergio Belotti  
Nokia

Email: sergio.belotti@nokia.com

Victor Lopez  
Telefonica

Email: victor.lopezalvarez@telefonica.com

Yunbo Li  
China Mobile

Email: liyunbo@chinamobile.com



Yunbin Xu  
CAICT

Email: xuyunbin@rict.cn