



IETF 105 – Montreal
July 2019

draft-ali-spring-ioam-srv6-01

Segment Routing Header encapsulation for In-situ OAM Data

Zafar Ali - Cisco Systems (zali@cisco.com) – Presenter

Rakesh Gandhi - Cisco Systems (rgandhi@cisco.com)

Clarence Filsfils - Cisco Systems (cfilsfil@cisco.com)

Frank Brockners – Cisco Systems (fbrockne@cisco.com)

Nagendra Kumar - Cisco Systems (naikumar@cisco.com)

Carlos Pignataro – Cisco Systems (cpignata@cisco.com)

Cheng Li – Huawei (chengli13@huawei.com)

Mach(Guoyi) Chen- Huawei (mach.chen@huawei.com)

Gaurav Dawra – LinkedIn (gdawra.ietf@gmail.com)

Summary of the Draft

- Defines how iOAM data fields defined in [[I-D.ietf-ippm-ioam-data](#)] are transported in SRv6 Networks.
- iOAM data field are carried in the SRH, using a single SRH TLV.
- Defines procedure for the Ingress node.
- Defines processing at the Segment Endpoint Node.
- Defines procedure for the Egress node.
- The draft does not introduce any new procedure or iOAM encoding defined in IPPM WG.

Next Steps

- The authors would like to request WG for the review and the feedback.
- The authors would like the WG to adopt the document.