



**I E T F**

Spring WG  
IETF 105 – Montreal

# draft-ali-6man-spring-srv6-oam-03.txt

## SRv6 OAM

*Zafar Ali - Cisco Systems ([zali@cisco.com](mailto:zali@cisco.com)) - Presenter*

*Clarence Filselfil - Cisco Systems ([cfilselfil@cisco.com](mailto:cfilselfil@cisco.com))*

*Nagendra Kumar - Cisco Systems ([naikumar@cisco.com](mailto:naikumar@cisco.com))*

*Carlos Pignataro – Cisco Systems ([cpignata@cisco.com](mailto:cpignata@cisco.com))*

*Rakesh Gandhi - Cisco Systems ([rgandhi@cisco.com](mailto:rgandhi@cisco.com))*

*Frank Brockners – Cisco Systems ([fbrockne@cisco.com](mailto:fbrockne@cisco.com))*

*John Leddy - Individual ([john@leddy.net](mailto:john@leddy.net))*

*Satoru Matsushima – Softbank ([satoru.matsushima@g.softbank.co.jp](mailto:satoru.matsushima@g.softbank.co.jp))*

*Robert Raszuk Bloomberg LP ([robert@raszuk.net](mailto:robert@raszuk.net))*

*Daniel Voyer - Bell Canada ([daniel.voyer@bell.ca](mailto:daniel.voyer@bell.ca))*

*Gaurav Dawra – LinkedIn ([gdawra.ietf@gmail.com](mailto:gdawra.ietf@gmail.com))*

*Bart Peirens – Proximus ([bart.peirens@proximus.com](mailto:bart.peirens@proximus.com))*

*Mach Chen – Huawei ([mach.chen@huawei.com](mailto:mach.chen@huawei.com))*

*Faisal Iqbal – Individual ([faisal.ietf@gmail.com](mailto:faisal.ietf@gmail.com))*

*Georgios Ntoulas – Individual ([georgios@ntoulas.com](mailto:georgios@ntoulas.com))*

# History of the Draft

- draft-ali-6man-srv6-oam-00 was published in July 2017.
  - Main draft describing use-cases including classic ping and traceroute in SRv6 networks.
- draft-ali-6man-srv6-oam-01 was published in October 2017.
  - Revision with editorial changes.
- draft-ali-spring-srv6-oam-00.txt was published in Feb 2018.
  - Added SRv6 ping and traceroute.
  - Added SRv6 segment-by-segment ping and overlay traceroute.
  - Presented in IETF101 (London, March 2018).
- draft-ali-spring-srv6-oam-01.txt was published in July 2018.
  - Moved O-bit from SRH draft to this draft.
  - Presented in 6man at IETF102.
- draft-ali-spring-srv6-oam-02.txt was published in October 2018.
  - Presented at IETF103 (6man and Spring).
- draft-ali-6man-spring-srv6-oam-00.txt
  - Presented at IETF104 (6man) in March 2018
- Addressed all comments received in the latest revision.

# Deployment Status

- Deployed in a nation-wide network at Softbank.
- Deployed in a multi-city network at China Telecom.
- Deployed in a nationwide SRv6 network at Iliad.
- Additional deployments are in preparation.

Source: `draft-matsushima-spring-srv6-deployment-status`

# Implementation and Interoperability Status

- Supported by at least 10 platforms with shipping implementation:
  - Cisco ASR 9000 running IOS XR shipping code
  - Cisco NCS 5500 running IOS XR shipping code
  - Cisco NCS 540 running IOS XR shipping code
  - Cisco ASR 1000 running IOS XE engineering code
  - Huawei ATN with VRPV8 shipping code
  - Huawei CX600 with VRPV8 shipping code
  - Huawei NE40E with VRPV8 shipping code
  - Huawei ME60 with VRPV8 shipping code
  - Huawei NE5000E with VRPV8 shipping code
  - Huawei NE9000 with VRPV8 shipping code
  - Huawei NG-OLT MA5800 with VRPV8 shipping code
- Additional known implementations.

Source: draft-matsushima-spring-srv6-deployment-status

# Implementation and Interoperability Status

- In March 2018, the European Advanced Networking Test Center (EANTC) successfully validated multiple implementations of the drafts.
- Results for Multi-vendor Interoperability Testing was showcased at MPLS World congress in April 2019.
- Authors are aware of additional private interoperability testing between different vendors.

Source: [draft-matsushima-spring-srv6-deployment-status](#)

# Draft Summary

- The document describes how existing ICMP mechanisms can be used in SRv6 Network.
- The document defines SRH.Flags.O-bit
  - The O-bit is used to implement “timestamp, punt and forward” behavior.
  - SRH.Flags.O-bit was originally defined in SRH draft.
- The document defines two OAM SIDs for programmable OAM:
  - END.OP (OAM Endpoint with Punt)
  - END.OTP (OAM Endpoint with Timestamp and Punt)

# Use Cases (I-D illustrations)

- Ping
  - End-to-end
  - Segment-by-segment
- Traceroute
  - Hop-by-hop
  - Segment-by-Segment (Overlay Traceroute)
- SRv6 Paths Monitoring
  - Applicability of RFC8403 to SRv6 Networks

# Next Steps

- Draft has been deployed in multiple production networks.
- Multiple interoperable implementations exist.
- The authors like to request the Spring WG for adoption of this work.