

TSVWG  
Internet-Draft  
Intended status: Standards Track  
Expires: December 19, 2019

M. Saito  
M. Matsumoto  
Hiroshima University  
V. Roca (Ed.)  
E. Baccelli  
INRIA  
June 17, 2019

TinyMT32 Pseudo Random Number Generator (PRNG)  
draft-ietf-tsvwg-tinymt32-06

Abstract

This document describes the TinyMT32 Pseudo Random Number Generator (PRNG) that produces 32-bit pseudo-random unsigned integers and aims at having a simple-to-use and deterministic solution. This PRNG is a small-sized variant of Mersenne Twister (MT) PRNG. The main advantage of TinyMT32 over MT is the use of a small internal state, compatible with most target platforms that include embedded devices, while keeping a reasonably good randomness that represents a significant improvement compared to the Park-Miller Linear Congruential PRNG. However, neither the TinyMT nor MT PRNG are meant to be used for cryptographic applications.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on December 19, 2019.

Copyright Notice

Copyright (c) 2019 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

1. Introduction . . . . .	2
2. Definitions . . . . .	3
3. TinyMT32 PRNG Specification . . . . .	3
3.1. TinyMT32 Source Code . . . . .	3
3.2. TinyMT32 Usage . . . . .	7
3.3. Specific Implementation Validation and Deterministic Behavior . . . . .	8
4. Security Considerations . . . . .	9
5. IANA Considerations . . . . .	9
6. Acknowledgments . . . . .	9
7. References . . . . .	9
7.1. Normative References . . . . .	10
7.2. Informative References . . . . .	10
Authors' Addresses . . . . .	11

## 1. Introduction

This document specifies the TinyMT32 PRNG, as a specialization of the reference implementation version 1.1 (2015/04/24) by Mutsuo Saito and Makoto Matsumoto, from Hiroshima University, that can be found at [TinyMT-web] (TinyMT web site) and [TinyMT-dev] (Github site). This specialisation aims at having a simple-to-use and deterministic PRNG, as explained below. However, the TinyMT32 PRNG is not meant to be used for cryptographic applications.

TinyMT is a new small-sized variant introduced in 2011 of the Mersenne Twister (MT) PRNG [MT98]. This document focusses on the TinyMT32 variant (rather than TinyMT64) of the TinyMT PRNG, which outputs 32-bit unsigned integers.

The purpose of TinyMT is not to replace Mersenne Twister: TinyMT has a far shorter period ( $2^{127} - 1$ ) than MT. The merit of TinyMT is in the small size of the internal state of 127 bits, far smaller than the 19937 bits of MT. The outputs of TinyMT satisfy several statistical tests for non-cryptographic randomness, including BigCrush in TestU01 [TestU01] and AdaptiveCrush [AdaptiveCrush],

leaving it well-placed for non-cryptographic usage, especially given the small size of its internal state (see [TinyMT-web]). From this point of view, TinyMT32 represents a major improvement with respect to the Park-Miller Linear Congruential PRNG (e.g., as specified in [RFC5170]) that suffers several known limitations (see for instance [PTVF92], section 7.1, p. 279, and [RLC-ID], Appendix B).

The TinyMT32 PRNG initialization depends, among other things, on a parameter set, namely (mat1, mat2, tmat). In order to facilitate the use of this PRNG and make the sequence of pseudo-random numbers depend only on the seed value, this specification requires the use of a specific parameter set (see Section 3.1). This is a major difference with respect to the implementation version 1.1 (2015/04/24) that leaves this parameter set unspecified.

Finally, the determinism of this PRNG, for a given seed, has been carefully checked (see Section 3.3). It means that the same sequence of pseudo-random numbers should be generated, no matter the target execution platform and compiler, for a given initial seed value. This determinism can be a key requirement as it the case with [RLC-ID] that normatively depends on this specification.

## 2. Definitions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

## 3. TinyMT32 PRNG Specification

### 3.1. TinyMT32 Source Code

The TinyMT32 PRNG requires to be initialized with a parameter set that needs to be well chosen. In this specification, for the sake of simplicity, the following parameter set MUST be used:

```
o mat1 = 0x8f7011ee = 2406486510
o mat2 = 0xfc78ff1f = 4235788063
o tmat = 0x3793fdff = 932445695
```

This parameter set is the first entry of the precalculated parameter sets in file tinymt32dc/tinymt32dc.0.1048576.txt, by Kenji Rikitake, and available at [TinyMT-params]. This is also the parameter set used in [KR12].

The TinyMT32 PRNG reference implementation is reproduced in Figure 1. This is a C language implementation, written for C99 [C99]. This reference implementation differs from the original source code as follows:

- o the original copyright and license have been removed by the original authors who are now authors of this document, in accordance with BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>);
- o the source code initially spread over the `tinymt32.h` and `tinymt32.c` files has been merged;
- o the unused parts of the original source code have been removed. This is the case of the `tinymt32_init_by_array()` alternative initialisation function. This is also the case of the `period_certification()` function after having checked it is not required with the chosen parameter set;
- o the unused constants `TINYMT32_MEXP` and `TINYMT32_MUL` have been removed;
- o the appropriate parameter set has been added to the initialization function;
- o the function order has been changed;
- o certain internal variables have been renamed for compactness purposes;
- o the `const` qualifier has been added to the constant definitions;
- o the code that was dependant on the representation of negative integers by 2's complements has been replaced by a more portable version;

<CODE BEGINS>

```
/**
 * Tiny Mersenne Twister only 127 bit internal state.
 * Derived from the reference implementation version 1.1 (2015/04/24)
 * by Mutsuo Saito (Hiroshima University) and Makoto Matsumoto
 * (Hiroshima University).
 */
#include <stdint.h>

/**
 * tinymt32 internal state vector and parameters
 */
typedef struct {
    uint32_t status[4];
    uint32_t mat1;
    uint32_t mat2;
    uint32_t tmat;
} tinymt32_t;

static void tinymt32_next_state (tinymt32_t* s);
```

```
static uint32_t tinymt32_temper (tinymt32_t* s);

/**
 * Parameter set to use for this IETF specification. Don't change.
 * This parameter set is the first entry of the precalculated
 * parameter sets in file tinymt32dc/tinymt32dc.0.1048576.txt, by
 * Kenji Rikitake, available at:
 *   https://github.com/jjlbdx/tinymtdc-longbatch/
 * It is also the parameter set used:
 *   Rikitake, K., "TinyMT Pseudo Random Number Generator for
 *   Erlang", ACM 11th SIGPLAN Erlang Workshop (Erlang'12),
 *   September, 2012.
 */
const uint32_t TINYMT32_MAT1_PARAM = UINT32_C(0x8f7011ee);
const uint32_t TINYMT32_MAT2_PARAM = UINT32_C(0xfc78ff1f);
const uint32_t TINYMT32_TMAT_PARAM = UINT32_C(0x3793fdff);

/**
 * This function initializes the internal state array with a
 * 32-bit unsigned integer seed.
 * @param s pointer to tinymt internal state.
 * @param seed a 32-bit unsigned integer used as a seed.
 */
void tinymt32_init (tinymt32_t* s, uint32_t seed)
{
    const uint32_t MIN_LOOP = 8;
    const uint32_t PRE_LOOP = 8;
    s->status[0] = seed;
    s->status[1] = s->mat1 = TINYMT32_MAT1_PARAM;
    s->status[2] = s->mat2 = TINYMT32_MAT2_PARAM;
    s->status[3] = s->tmat = TINYMT32_TMAT_PARAM;
    for (int i = 1; i < MIN_LOOP; i++) {
        s->status[i & 3] ^= i + UINT32_C(1812433253)
            * (s->status[(i - 1) & 3]
               ^ (s->status[(i - 1) & 3] >> 30));
    }
    /**
     * NB: the parameter set of this specification warrants
     * that none of the possible 232 seeds leads to an
     * all-zero 127-bit internal state. Therefore, the
     * period_certification() function of the original
     * TinyMT32 source code has been safely removed. If
     * another parameter set is used, this function will
     * have to be re-introduced here.
     */
    for (int i = 0; i < PRE_LOOP; i++) {
        tinymt32_next_state(s);
    }
}
```

```

}

/**
 * This function outputs a 32-bit unsigned integer from
 * the internal state.
 * @param s      pointer to tinymt internal state.
 * @return       32-bit unsigned integer r ( $0 \leq r < 2^{32}$ ).
 */
uint32_t tinymt32_generate_uint32 (tinymt32_t* s)
{
    tinymt32_next_state(s);
    return tinymt32_temper(s);
}

/**
 * Internal tinymt32 constants and functions.
 * Users should not call these functions directly.
 */
const uint32_t TINYMT32_SH0 = 1;
const uint32_t TINYMT32_SH1 = 10;
const uint32_t TINYMT32_SH8 = 8;
const uint32_t TINYMT32_MASK = UINT32_C(0x7fffffff);

/**
 * This function changes the internal state of tinymt32.
 * @param s      pointer to tinymt internal state.
 */
static void tinymt32_next_state (tinymt32_t* s)
{
    uint32_t x;
    uint32_t y;

    y = s->status[3];
    x = (s->status[0] & TINYMT32_MASK)
        ^ s->status[1]
        ^ s->status[2];
    x ^= (x << TINYMT32_SH0);
    y ^= (y >> TINYMT32_SH0) ^ x;
    s->status[0] = s->status[1];
    s->status[1] = s->status[2];
    s->status[2] = x ^ (y << TINYMT32_SH1);
    s->status[3] = y;
    /*
     * The if (y & 1) {...} block below replaces:
     *     s->status[1] ^= -((int32_t)(y & 1)) & s->mat1;
     *     s->status[2] ^= -((int32_t)(y & 1)) & s->mat2;
     * The adopted code is equivalent to the original code
     * but does not depend on the representation of negative

```

```

    * integers by 2's complements. It is therefore more
    * portable, but includes an if-branch which may slow
    * down the generation speed.
    */
    if (y & 1) {
        s->status[1] ^= s->mat1;
        s->status[2] ^= s->mat2;
    }
}

/**
 * This function outputs a 32-bit unsigned integer from
 * the internal state.
 * @param s      pointer to tinymt internal state.
 * @return       32-bit unsigned pseudo-random number.
 */
static uint32_t tinymt32_temper (tinymt32_t* s)
{
    uint32_t t0, t1;
    t0 = s->status[3];
    t1 = s->status[0] + (s->status[2] >> TINYMT32_SH8);
    t0 ^= t1;
    /*
     * The if (t1 & 1) {...} block below replaces:
     *     t0 ^= -((int32_t)(t1 & 1)) & s->tmat;
     * The adopted code is equivalent to the original code
     * but does not depend on the representation of negative
     * integers by 2's complements. It is therefore more
     * portable, but includes an if-branch which may slow
     * down the generation speed.
     */
    if (t1 & 1) {
        t0 ^= s->tmat;
    }
    return t0;
}
<CODE ENDS>

```

Figure 1: TinyMT32 Reference Implementation

### 3.2. TinyMT32 Usage

This PRNG MUST first be initialized with the following function:

```
void tinymt32_init (tinymt32_t* s, uint32_t seed);
```

It takes as input a 32-bit unsigned integer used as a seed (note that value 0 is permitted by TinyMT32). This function also takes as input

a pointer to an instance of a `tinymt32_t` structure that needs to be allocated by the caller but left uninitialized. This structure will then be updated by the various TinyMT32 functions in order to keep the internal state of the PRNG. The use of this structure admits several instances of this PRNG to be used in parallel, each of them having its own instance of the structure.

Then, each time a new 32-bit pseudo-random unsigned integer between 0 and  $2^{32} - 1$  inclusive is needed, the following function is used:

```
uint32_t tinymt32_generate_uint32 (tinymt32_t * s);
```

Of course, the `tinymt32_t` structure must be left unchanged by the caller between successive calls to this function.

### 3.3. Specific Implementation Validation and Deterministic Behavior

PRNG determinism, for a given seed, can be a requirement (e.g., with [RLC-ID]). Consequently, any implementation of the TinyMT32 PRNG in line with this specification **MUST** have the same output as that provided by the reference implementation of Figure 1. In order to increase the compliancy confidence, this document proposes the following criteria. Using a seed value of 1, the first 50 values returned by `tinymt32_generate_uint32(s)` as 32-bit unsigned integers are equal to values provided in Figure 2, to be read line by line. Note that these values come from the `tinymt/check32.out.txt` file provided by the PRNG authors to validate implementations of TinyMT32, as part of the MersenneTwister-Lab/TinyMT Github repository.

```
2545341989  981918433 3715302833 2387538352 3591001365
3820442102 2114400566 2196103051 2783359912 764534509
 643179475 1822416315 881558334 4207026366 3690273640
3240535687 2921447122 3984931427 4092394160 44209675
2188315343 2908663843 1834519336 3774670961 3019990707
4065554902 1239765502 4035716197 3412127188 552822483
 161364450 353727785 140085994 149132008 2547770827
4064042525 4078297538 2057335507 622384752 2041665899
2193913817 1080849512 33160901 662956935 642999063
3384709977 1723175122 3866752252 521822317 2292524454
```

Figure 2: First 50 decimal values (to be read per line) returned by `tinymt32_generate_uint32(s)` as 32-bit unsigned integers, with a seed value of 1.

In particular, the deterministic behavior of the Figure 1 source code has been checked across several platforms: high-end laptops running 64-bits Mac OSX and Linux/Ubuntu; a board featuring a 32-bits ARM Cortex-A15 and running 32-bit Linux/Ubuntu; several embedded cards



featuring either an ARM Cortex-M0+, a Cortex-M3 or a Cortex-M4 32-bit microcontroller, all of them running RIOT [Baccelli18]; two low-end embedded cards featuring either a 16-bit microcontroller (TI MSP430) or a 8-bit microcontroller (Arduino ATMEGA2560), both of them running RIOT.

This specification only outputs 32-bit unsigned pseudo-random numbers and does not try to map this output to a smaller integer range (e.g., between 10 and 49 inclusive). If a specific use-case needs such a mapping, it will have to provide its own function. In that case, if PRNG determinism is also required, the use of floating point (single or double precision) to perform this mapping should probably be avoided, these calculations leading potentially to different rounding errors across different target platforms. Great care should also be put on not introducing biases in the randomness of the mapped output (it may be the case with some mapping algorithms) incompatible with the use-case requirements. The details of how to perform such a mapping are out-of-scope of this document.

#### 4. Security Considerations

The authors do not believe the present specification generates specific security risks per se. However, neither the TinyMT nor MT PRNG are meant to be used for cryptographic applications.

#### 5. IANA Considerations

This document does not require any IANA action.

#### 6. Acknowledgments

The authors would like to thank Belkacem Teibi with whom we explored TinyMT32 specificities when looking to an alternative to the Park-Miller Linear Congruential PRNG. The authors would like to thank Carl Wallace, Stewart Bryant, Greg Skinner, Mike Heard, the three TSVWG chairs, Wesley Eddy, our shepherd, David Black and Gorry Fairhurst, as well as Spencer Dawkins and Mirja Kuhlewind. Last but not least, the authors are really grateful to the IESG members, in particular Benjamin Kaduk, Eric Rescorla, Adam Roach, Roman Danyliw, Barry Leiba, Martin Vigoureux, Eric Vyncke for their highly valuable feedbacks that greatly contributed to improve this specification.

#### 7. References

## 7.1. Normative References

- [C99] "Programming languages - C: C99, correction 3:2007", International Organization for Standardization, ISO/IEC 9899:1999/Cor 3:2007, November 2007.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.

## 7.2. Informative References

- [AdaptiveCrush] Haramoto, H., "Automation of statistical tests on randomness to obtain clearer conclusion", Monte Carlo and Quasi-Monte Carlo Methods 2008, DOI:10.1007/978-3-642-04107-5\_26, November 2009, <<http://www.math.sci.hiroshima-u.ac.jp/~m-mat/MT/ADAPTIVE/>>.
- [Baccelli18] Baccelli, E., Gundogan, C., Hahm, O., Kietzmann, P., Lenders, M., Petersen, H., Schleiser, K., Schmidt, T., and M. Wahlisch, "RIOT: An Open Source Operating System for Low-End Embedded Devices in the IoT", IEEE Internet of Things Journal (Volume 5, Issue 6), DOI: 10.1109/JIOT.2018.2815038, December 2018.
- [KR12] Rikitake, K., "TinyMT Pseudo Random Number Generator for Erlang", ACM 11th SIGPLAN Erlang Workshop (Erlang'12), September 14, 2012, Copenhagen, Denmark, DOI: <http://dx.doi.org/10.1145/2364489.2364504>, September 2012.
- [MT98] Matsumoto, M. and T. Nishimura, "Mersenne Twister: A 623-dimensionally equidistributed uniform pseudorandom number generator", ACM Transactions on Modeling and Computer Simulation (TOMACS), Volume 8 Issue 1, Jan. 1998, pp.3-30, January 1998, DOI:10.1145/272991.272995, January 1998.
- [PTVF92] Press, W., Teukolsky, S., Vetterling, W., and B. Flannery, "Numerical Recipes in C; Second Edition", Cambridge University Press, ISBN: 0-521-43108-5, 1992.

- [RFC5170] Roca, V., Neumann, C., and D. Furodet, "Low Density Parity Check (LDPC) Staircase and Triangle Forward Error Correction (FEC) Schemes", RFC 5170, DOI 10.17487/RFC5170, June 2008, <<https://www.rfc-editor.org/info/rfc5170>>.
- [RLC-ID] Roca, V. and B. Teibi, "Sliding Window Random Linear Code (RLC) Forward Erasure Correction (FEC) Scheme for FECFRAME", Work in Progress, Transport Area Working Group (TSVWG) draft-ietf-tsvwg-rlc-fec-scheme (Work in Progress), February 2019, <<https://tools.ietf.org/html/draft-ietf-tsvwg-rlc-fec-scheme>>.
- [TestU01] L'Ecuyer, P. and R. Simard, "TestU01: A C Library for Empirical Testing of Random Number Generators", ACM Transactions on Mathematical Software, Vol. 33, article 22, 2007, 2007, <<http://simul.iro.umontreal.ca/testu01/tu01.html>>.
- [TinyMT-dev] Saito, M. and M. Matsumoto, "Tiny Mersenne Twister (TinyMT) github site", <<https://github.com/MersenneTwister-Lab/TinyMT>>.
- [TinyMT-params] Rikitake, K., "TinyMT pre-calculated parameter list github site", <<https://github.com/jj1bdx/tinymtdc-longbatch/>>.
- [TinyMT-web] Saito, M. and M. Matsumoto, "Tiny Mersenne Twister (TinyMT) web site", <<http://www.math.sci.hiroshima-u.ac.jp/~m-mat/MT/TINYMT/>>.

## Authors' Addresses

Mutsuo Saito  
Hiroshima University  
Japan

EMail: [saito@math.sci.hiroshima-u.ac.jp](mailto:saito@math.sci.hiroshima-u.ac.jp)

Makoto Matsumoto  
Hiroshima University  
Japan

EMail: [m-mat@math.sci.hiroshima-u.ac.jp](mailto:m-mat@math.sci.hiroshima-u.ac.jp)

Vincent Roca  
INRIA  
Univ. Grenoble Alpes  
France

EMail: [vincent.roca@inria.fr](mailto:vincent.roca@inria.fr)

Emmanuel Baccelli  
INRIA  
France

EMail: [emmanuel.baccelli@inria.fr](mailto:emmanuel.baccelli@inria.fr)