

draft-brissette-bess-evpn-mh-pa-04 update

- 'Port Mode' flag claimed in RFC8584 capabilities bitmap
 - IANA registry "Port Mode" entry request added
 - Bit 5: P bit or 'Port Mode' bit determines that the DF-Algorithm should be modified to consider the port only and not the Ethernet Tags
- Section 4 expanded to include clarification of applicability to existing DF modes:
 - s. 4.2 Modulo-based (RFC7432)
Change from last byte (10) of ESI to 4-byte aligned with ES:Import RT field for better entropy across ES
 - s. 4.3 HRW (RFC 8584)
 - s. 4.4 Preference-based DF (draft-ietf-bess-evpn-pref-df-04)
- Next steps
 - Draft is now mature, multi-vendor support
 - Ready for WG Adoption

draft-brissette-bess-evpn-l2gw-proto-05 update

- Backwards-compatibility section clarified and expanded:
 - 2-ESI solution & how this draft improves upon that,
 - Route resolution at a strict-RFC7432 Remote PE.
- Convergence and MAC Mobility sections already updated after IETF104 per feedback
- (NRoff -> XML source conversion: apologies for the formatting noise in diff)

- Next steps
 - Several feedback received, all incorporated
 - More comments always welcome
 - Document ready to progress