

NETCONF Working Group
Internet-Draft
Intended status: Standards Track
Expires: 9 January 2021

K. Watsen
Watsen Networks
8 July 2020

RESTCONF Client and Server Models
draft-ietf-netconf-restconf-client-server-20

Abstract

This document defines two YANG modules, one module to configure a RESTCONF client and the other module to configure a RESTCONF server. Both modules support the TLS transport protocol with both standard RESTCONF and RESTCONF Call Home connections.

Editorial Note (To be removed by RFC Editor)

This draft contains placeholder values that need to be replaced with finalized values at the time of publication. This note summarizes all of the substitutions that are needed. No other RFC Editor instructions are specified elsewhere in this document.

Artwork in this document contains shorthand references to drafts in progress. Please apply the following replacements (note: not all may be present):

- * "AAAA" --> the assigned RFC value for draft-ietf-netconf-crypto-types
- * "BBBB" --> the assigned RFC value for draft-ietf-netconf-trust-anchors
- * "CCCC" --> the assigned RFC value for draft-ietf-netconf-keystore
- * "DDDD" --> the assigned RFC value for draft-ietf-netconf-tcp-client-server
- * "EEEE" --> the assigned RFC value for draft-ietf-netconf-ssh-client-server
- * "FFFF" --> the assigned RFC value for draft-ietf-netconf-tls-client-server
- * "GGGG" --> the assigned RFC value for draft-ietf-netconf-http-client-server

* "HHHH" --> the assigned RFC value for draft-ietf-netconf-netconf-client-server

* "IIII" --> the assigned RFC value for this draft

Artwork in this document contains placeholder values for the date of publication of this draft. Please apply the following replacement:

* "2020-07-08" --> the publication date of this draft

The following Appendix section is to be removed prior to publication:

* Appendix B. Change Log

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 9 January 2021.

Copyright Notice

Copyright (c) 2020 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1. Introduction	4
---------------------------	---

1.1.	Relation to other RFCs	4
1.2.	Specification Language	5
1.3.	Adherence to the NMDA	5
2.	The "ietf-restconf-client" Module	5
2.1.	Data Model Overview	6
2.2.	Example Usage	10
2.3.	YANG Module	14
3.	The "ietf-restconf-server" Module	24
3.1.	Data Model Overview	24
3.2.	Example Usage	29
3.3.	YANG Module	33
4.	Security Considerations	45
4.1.	The "ietf-restconf-client" YANG Module	45
4.2.	The "ietf-restconf-server" YANG Module	45
5.	IANA Considerations	46
5.1.	The IETF XML Registry	46
5.2.	The YANG Module Names Registry	46
6.	References	47
6.1.	Normative References	47
6.2.	Informative References	48
Appendix A.	Expanded Tree Diagrams	49
A.1.	Expanded Tree Diagram for 'ietf-restconf-client'	50
A.2.	Expanded Tree Diagram for 'ietf-restconf-server'	50
Appendix B.	Change Log	50
B.1.	00 to 01	50
B.2.	01 to 02	50
B.3.	02 to 03	50
B.4.	03 to 04	51
B.5.	04 to 05	51
B.6.	05 to 06	51
B.7.	06 to 07	51
B.8.	07 to 08	52
B.9.	08 to 09	52
B.10.	09 to 10	52
B.11.	10 to 11	52
B.12.	11 to 12	52
B.13.	12 to 13	53
B.14.	13 to 14	53
B.15.	14 to 15	53
B.16.	15 to 16	54
B.17.	16 to 17	54
B.18.	17 to 18	54
B.19.	18 to 19	54
B.20.	19 to 20	54
Acknowledgements	55
Author's Address	55

Label in Diagram	Originating RFC
crypto-types	[I-D.ietf-netconf-crypto-types]
truststore	[I-D.ietf-netconf-trust-anchors]
keystore	[I-D.ietf-netconf-keystore]
tcp-client-server	[I-D.ietf-netconf-tcp-client-server]
ssh-client-server	[I-D.ietf-netconf-ssh-client-server]
tls-client-server	[I-D.ietf-netconf-tls-client-server]
http-client-server	[I-D.ietf-netconf-http-client-server]
netconf-client-server	[I-D.ietf-netconf-netconf-client-server]
restconf-client-server	[I-D.ietf-netconf-restconf-client-server]

Table 1: Label to RFC Mapping

1.2. Specification Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

1.3. Adherence to the NMDA

This document is compliant with the Network Management Datastore Architecture (NMDA) [RFC8342]. For instance, as described in [I-D.ietf-netconf-trust-anchors] and [I-D.ietf-netconf-keystore], trust anchors and keys installed during manufacturing are expected to appear in <operational>.

2. The "ietf-restconf-client" Module

The RESTCONF client model presented in this section supports both clients initiating connections to servers, as well as clients listening for connections from servers calling home.

YANG feature statements are used to enable implementations to advertise which potentially uncommon parts of the model the RESTCONF client supports.

2.1. Data Model Overview

2.1.1. Features

The following diagram lists all the "feature" statements defined in the "ietf-restconf-client" module:

Features:

- +-- https-initiate
- +-- http-listen
- +-- https-listen

2.1.2. Groupings

The following diagram lists all the "grouping" statements defined in the "ietf-restconf-client" module:

Groupings:

- +-- restconf-client-grouping
- +-- restconf-client-initiate-stack-grouping
- +-- restconf-client-listen-stack-grouping
- +-- restconf-client-app-grouping

Each of these groupings are presented in the following subsections.

2.1.2.1. The "restconf-client-grouping" Grouping

The following tree diagram [RFC8340] illustrates the "restconf-client-grouping" grouping:

```
grouping restconf-client-grouping ---> <empty>
```

Comments:

- * This grouping does not define any nodes, but is maintained so that downstream modules can augment nodes into it if needed.
- * The "restconf-client-grouping" defines, if it can be called that, the configuration for just "RESTCONF" part of a protocol stack. It does not, for instance, define any configuration for the "TCP", "TLS", or "HTTP" protocol layers (for that, see Section 2.1.2.2 and Section 2.1.2.3).

2.1.2.2. The "restconf-client-initiate-stack-grouping" Grouping

The following tree diagram [RFC8340] illustrates the "restconf-client-initiate-stack-grouping" grouping:

```
grouping restconf-client-initiate-stack-grouping
  +-- (transport)
    +--:(https) {https-initiate}?
      +-- https
        +-- tcp-client-parameters
          | +---u tcpc:tcp-client-grouping
        +-- tls-client-parameters
          | +---u tlsc:tls-client-grouping
        +-- http-client-parameters
          | +---u http:http-client-grouping
        +-- restconf-client-parameters
          +---u rcc:restconf-client-grouping
```

Comments:

- * The "restconf-client-initiate-stack-grouping" defines the configuration for a full RESTCONF protocol stack, for RESTCONF clients that initiate connections to RESTCONF servers, as opposed to receiving call-home [RFC8071] connections.
- * The "transport" choice node enables transport options to be configured. This document only defines an "https" option, but other options MAY be augmented in.
- * For the referenced grouping statement(s):
 - The "tcp-client-grouping" grouping is discussed in Section 3.1.2.1 of [I-D.ietf-netconf-tcp-client-server].
 - The "tls-client-grouping" grouping is discussed in Section 3.1.2.1 of [I-D.ietf-netconf-tls-client-server].
 - The "http-client-grouping" grouping is discussed in Section 2.1.2.2 of [I-D.ietf-netconf-http-client-server].
 - The "restconf-client-grouping" grouping is discussed in Section 2.1.2.1 in this document.

2.1.2.3. The "restconf-client-listen-stack-grouping" Grouping

The following tree diagram [RFC8340] illustrates the "restconf-client-listen-stack-grouping" grouping:

```
grouping restconf-client-listen-stack-grouping
+-- (transport)
+--:(http) {http-listen}?
|   +-- http
|   |   +-- tcp-server-parameters
|   |   |   +---u tcps:tcp-server-grouping
|   |   +-- http-client-parameters
|   |   |   +---u httpc:http-client-grouping
|   |   +-- restconf-client-parameters
|   |   |   +---u rcc:restconf-client-grouping
+--:(https) {https-listen}?
|   +-- https
|   |   +-- tcp-server-parameters
|   |   |   +---u tcps:tcp-server-grouping
|   |   +-- tls-client-parameters
|   |   |   +---u tlsc:tls-client-grouping
|   |   +-- http-client-parameters
|   |   |   +---u httpc:http-client-grouping
|   |   +-- restconf-client-parameters
|   |   |   +---u rcc:restconf-client-grouping
```

Comments:

- * The "restconf-client-listen-stack-grouping" defines the configuration for a full RESTCONF protocol stack, for RESTCONF clients that receive call-home [RFC8071] connections from RESTCONF servers.
- * The "transport" choice node enables both the HTTP and HTTPS transports to be configured, with each option enabled by a "feature" statement. Note that RESTCONF requires HTTPS, the HTTP option is provided to support cases where a TLS-terminator is deployed in front of the RESTCONF-client.
- * For the referenced grouping statement(s):
 - The "tcp-server-grouping" grouping is discussed in Section 4.1.2.1 of [I-D.ietf-netconf-tcp-client-server].
 - The "tls-client-grouping" grouping is discussed in Section 3.1.2.1 of [I-D.ietf-netconf-tls-client-server].
 - The "http-client-grouping" grouping is discussed in Section 2.1.2.2 of [I-D.ietf-netconf-http-client-server].
 - The "restconf-client-grouping" grouping is discussed in Section 2.1.2.1 in this document.

2.1.2.4. The "restconf-client-app-grouping" Grouping

The following tree diagram [RFC8340] illustrates the "restconf-client-app-grouping" grouping:

```

grouping restconf-client-app-grouping
+-- initiate! {https-initiate}?
|   +-- restconf-server* [name]
|       +-- name? string
|       +-- endpoints
|           +-- endpoint* [name]
|               +-- name? string
|               +---u restconf-client-initiate-stack-grouping
|   +-- connection-type
|       +-- (connection-type)
|           +--:(persistent-connection)
|               | +-- persistent!
|           +--:(periodic-connection)
|               +-- periodic!
|                   +-- period? uint16
|                   +-- anchor-time? yang:date-and-time
|                   +-- idle-timeout? uint16
|   +-- reconnect-strategy
|       +-- start-with? enumeration
|       +-- max-attempts? uint8
+-- listen! {http-listen or https-listen}?
    +-- idle-timeout? uint16
    +-- endpoint* [name]
        +-- name? string
        +---u restconf-client-listen-stack-grouping
  
```

Comments:

- * The "restconf-client-app-grouping" defines the configuration for a RESTCONF client that supports both initiating connections to RESTCONF servers as well as receiving call-home connections from RESTCONF servers.
- * Both the "initiate" and "listen" subtrees must be enabled by "feature" statements.
- * For the referenced grouping statement(s):
 - The "restconf-client-initiate-stack-grouping" grouping is discussed in Section 2.1.2.2 in this document.
 - The "restconf-client-listen-stack-grouping" grouping is discussed in Section 2.1.2.3 in this document.

2.1.3. Protocol-accessible Nodes

The following diagram lists all the protocol-accessible nodes defined in the "ietf-restconf-client" module:

```
module: ietf-restconf-client
  +--rw restconf-client
    +---u restconf-client-app-grouping
```

Comments:

- * Protocol-accessible nodes are those nodes that are accessible when the module is "implemented", as described in Section 5.6.5 of [RFC7950].
- * For the "ietf-restconf-client" module, the protocol-accessible nodes are an instance of the "restconf-client-app-grouping" discussed in Section 2.1.2.4 grouping.
- * The reason for why "restconf-client-app-grouping" exists separate from the protocol-accessible nodes definition is so as to enable instances of restconf-client-app-grouping to be instantiated in other locations, as may be needed or desired by some modules.

2.2. Example Usage

The following example illustrates configuring a RESTCONF client to initiate connections, as well as to listen for call-home connections.

This example is consistent with the examples presented in Section 2.2 of [I-D.ietf-netconf-trust-anchors] and Section 2.2 of [I-D.ietf-netconf-keystore].

===== NOTE: '\' line wrapping per RFC 8792 =====

```
<restconf-client
  xmlns="urn:ietf:params:xml:ns:yang:ietf-restconf-client"
  xmlns:ct="urn:ietf:params:xml:ns:yang:ietf-crypto-types">

  <!-- RESTCONF servers to initiate connections to -->
  <initiate>
    <restconf-server>
      <name>corp-fw1</name>
      <endpoints>
        <endpoint>
          <name>corp-fw1.example.com</name>
          <https>
            <tcp-client-parameters>
```

```

        <remote-address>corp-fw1.example.com</remote-address>
        <keepalives>
          <idle-time>15</idle-time>
          <max-probes>3</max-probes>
          <probe-interval>30</probe-interval>
        </keepalives>
      </tcp-client-parameters>
      <tls-client-parameters>
        <client-identity>
          <certificate>
            <keystore-reference>
              <asymmetric-key>rsa-asymmetric-key</asymmetric-k\
ey>
              <certificate>ex-rsa-cert</certificate>
            </keystore-reference>
          </certificate>
        </client-identity>
        <server-authentication>
          <ca-certs>
            <truststore-reference>trusted-server-ca-certs</tru\
ststore-reference>
          </ca-certs>
          <ee-certs>
            <truststore-reference>trusted-server-ee-certs</tru\
ststore-reference>
          </ee-certs>
        </server-authentication>
      </keepalives>
      <test-peer-aliveness>
        <max-wait>30</max-wait>
        <max-attempts>3</max-attempts>
      </test-peer-aliveness>
    </keepalives>
  </tls-client-parameters>
  <http-client-parameters>
    <client-identity>
      <basic>
        <user-id>bob</user-id>
        <password>secret</password>
      </basic>
    </client-identity>
  </http-client-parameters>
</https>
</endpoint>
<endpoint>
  <name>corp-fw2.example.com</name>
  <https>
    <tcp-client-parameters>

```

```

        <remote-address>corp-fw2.example.com</remote-address>
        <keepalives>
          <idle-time>15</idle-time>
          <max-probes>3</max-probes>
          <probe-interval>30</probe-interval>
        </keepalives>
      </tcp-client-parameters>
      <tls-client-parameters>
        <client-identity>
          <certificate>
            <keystore-reference>
              <asymmetric-key>rsa-asymmetric-key</asymmetric-k\
ey>
              <certificate>ex-rsa-cert</certificate>
            </keystore-reference>
          </certificate>
        </client-identity>
        <server-authentication>
          <ca-certs>
            <truststore-reference>trusted-server-ca-certs</tru\
ststore-reference>
          </ca-certs>
          <ee-certs>
            <truststore-reference>trusted-server-ee-certs</tru\
ststore-reference>
          </ee-certs>
        </server-authentication>
      </keepalives>
      <test-peer-aliveness>
        <max-wait>30</max-wait>
        <max-attempts>3</max-attempts>
      </test-peer-aliveness>
    </keepalives>
  </tls-client-parameters>
  <http-client-parameters>
    <client-identity>
      <basic>
        <user-id>bob</user-id>
        <password>secret</password>
      </basic>
    </client-identity>
  </http-client-parameters>
</https>
</endpoint>
</endpoints>
<connection-type>
  <persistent/>
</connection-type>

```

```

    </restconf-server>
  </initiate>

  <!-- endpoints to listen for RESTCONF Call Home connections on -->
  <listen>
    <endpoint>
      <name>Intranet-facing listener</name>
      <https>
        <tcp-server-parameters>
          <local-address>11.22.33.44</local-address>
        </tcp-server-parameters>
        <tls-client-parameters>
          <client-identity>
            <certificate>
              <keystore-reference>
                <asymmetric-key>rsa-asymmetric-key</asymmetric-key>
                <certificate>ex-rsa-cert</certificate>
              </keystore-reference>
            </certificate>
          </client-identity>
          <server-authentication>
            <ca-certs>
              <truststore-reference>trusted-server-ca-certs</trustst\
ore-reference>
            </ca-certs>
            <ee-certs>
              <truststore-reference>trusted-server-ee-certs</trustst\
ore-reference>
            </ee-certs>
          </server-authentication>
          <keepalives>
            <peer-allowed-to-send/>
          </keepalives>
        </tls-client-parameters>
        <http-client-parameters>
          <client-identity>
            <basic>
              <user-id>bob</user-id>
              <password>secret</password>
            </basic>
          </client-identity>
        </http-client-parameters>
      </https>
    </endpoint>
  </listen>
</restconf-client>

```

2.3. YANG Module

This YANG module has normative references to [RFC6991], [RFC8040], and [RFC8071], [I-D.ietf-netconf-tcp-client-server], [I-D.ietf-netconf-tls-client-server], and [I-D.ietf-netconf-http-client-server].

<CODE BEGINS> file "ietf-restconf-client@2020-07-08.yang"

```
module ietf-restconf-client {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-restconf-client";
  prefix rcc;

  import ietf-yang-types {
    prefix yang;
    reference
      "RFC 6991: Common YANG Data Types";
  }

  import ietf-tcp-client {
    prefix tcpc;
    reference
      "RFC DDDD: YANG Groupings for TCP Clients and TCP Servers";
  }

  import ietf-tcp-server {
    prefix tcps;
    reference
      "RFC DDDD: YANG Groupings for TCP Clients and TCP Servers";
  }

  import ietf-tls-client {
    prefix tlsc;
    reference
      "RFC FFFF: YANG Groupings for TLS Clients and TLS Servers";
  }

  import ietf-http-client {
    prefix httpc;
    reference
      "RFC GGGG: YANG Groupings for HTTP Clients and HTTP Servers";
  }

  organization
    "IETF NETCONF (Network Configuration) Working Group";

  contact
```

```
"WG Web:    <http://datatracker.ietf.org/wg/netconf/>
WG List:    <mailto:netconf@ietf.org>
Author:     Kent Watsen <mailto:kent+ietf@watsen.net>
Author:     Gary Wu <mailto:garywu@cisco.com>";
```

description

```
"This module contains a collection of YANG definitions
for configuring RESTCONF clients.
```

```
Copyright (c) 2020 IETF Trust and the persons identified
as authors of the code. All rights reserved.
```

```
Redistribution and use in source and binary forms, with
or without modification, is permitted pursuant to, and
subject to the license terms contained in, the Simplified
BSD License set forth in Section 4.c of the IETF Trust's
Legal Provisions Relating to IETF Documents
(https://trustee.ietf.org/license-info).
```

```
This version of this YANG module is part of RFC IIII
(https://www.rfc-editor.org/info/rfcIIII); see the RFC
itself for full legal notices.
```

```
The key words 'MUST', 'MUST NOT', 'REQUIRED', 'SHALL',
'SHALL NOT', 'SHOULD', 'SHOULD NOT', 'RECOMMENDED',
'NOT RECOMMENDED', 'MAY', and 'OPTIONAL' in this document
are to be interpreted as described in BCP 14 (RFC 2119)
(RFC 8174) when, and only when, they appear in all
capitals, as shown here.";
```

```
revision 2020-07-08 {
  description
    "Initial version";
  reference
    "RFC IIII: RESTCONF Client and Server Models";
}
```

// Features

```
feature https-initiate {
  description
    "The 'https-initiate' feature indicates that the RESTCONF
    client supports initiating HTTPS connections to RESTCONF
    servers. This feature exists as HTTPS might not be a
    mandatory to implement transport in the future.";
  reference
    "RFC 8040: RESTCONF Protocol";
}
```

```
feature http-listen {
  description
    "The 'https-listen' feature indicates that the RESTCONF client
    supports opening a port to listen for incoming RESTCONF
    server call-home connections. This feature exists as not
    all RESTCONF clients may support RESTCONF call home.";
  reference
    "RFC 8071: NETCONF Call Home and RESTCONF Call Home";
}

feature https-listen {
  description
    "The 'https-listen' feature indicates that the RESTCONF client
    supports opening a port to listen for incoming RESTCONF
    server call-home connections. This feature exists as not
    all RESTCONF clients may support RESTCONF call home.";
  reference
    "RFC 8071: NETCONF Call Home and RESTCONF Call Home";
}

// Groupings

grouping restconf-client-grouping {
  description
    "A reusable grouping for configuring a RESTCONF client
    without any consideration for how underlying transport
    sessions are established.

    This grouping currently doesn't define any nodes.";
}

grouping restconf-client-initiate-stack-grouping {
  description
    "A reusable grouping for configuring a RESTCONF client
    'initiate' protocol stack for a single connection.";

  choice transport {
    mandatory true;
    description
      "Selects between available transports. This is a
      'choice' statement so as to support additional
      transport options to be augmented in.";
    case https {
      if-feature "https-initiate";
      container https {
        must 'tls-client-parameters/client-identity
        or http-client-parameters/client-identity';
        description

```



```
    "Specifies HTTPS-specific transport
    configuration.";
  container tcp-client-parameters {
    description
      "A wrapper around the TCP client parameters
      to avoid name collisions.";
    uses tcpc:tcp-client-grouping {
      refine "remote-port" {
        default "443";
        description
          "The RESTCONF client will attempt to
          connect to the IANA-assigned well-known
          port value for 'https' (443) if no value
          is specified.";
      }
    }
  }
  container tls-client-parameters {
    description
      "A wrapper around the TLS client parameters
      to avoid name collisions.";
    uses tlsc:tls-client-grouping;
  }
  container http-client-parameters {
    description
      "A wrapper around the HTTP client parameters
      to avoid name collisions.";
    uses httpc:http-client-grouping;
  }
  container restconf-client-parameters {
    description
      "A wrapper around the HTTP client parameters
      to avoid name collisions.";
    uses rcc:restconf-client-grouping;
  }
}
}
} // restconf-client-initiate-stack-grouping

grouping restconf-client-listen-stack-grouping {
  description
    "A reusable grouping for configuring a RESTCONF client
    'listen' protocol stack for a single connection. The
    'listen' stack supports call home connections, as
    described in RFC 8071";
  reference
    "RFC 8071: NETCONF Call Home and RESTCONF Call Home";
}
```

```
choice transport {
  mandatory true;
  description
    "Selects between available transports. This is a
    'choice' statement so as to support additional
    transport options to be augmented in.";
  case http {
    if-feature "http-listen";
    container http {
      description
        "HTTP-specific listening configuration for inbound
        connections.

        This transport option is made available to support
        deployments where the TLS connections are terminated
        by another system (e.g., a load balancer) fronting
        the client.";
      container tcp-server-parameters {
        description
          "A wrapper around the TCP client parameters
          to avoid name collisions.";
        uses tcps:tcp-server-grouping {
          refine "local-port" {
            default "4336";
            description
              "The RESTCONF client will listen on the IANA-
              assigned well-known port for 'restconf-ch-tls'
              (4336) if no value is specified.";
          }
        }
      }
      container http-client-parameters {
        description
          "A wrapper around the HTTP client parameters
          to avoid name collisions.";
        uses httpc:http-client-grouping;
      }
      container restconf-client-parameters {
        description
          "A wrapper around the RESTCONF client parameters
          to avoid name collisions.";
        uses rcc:restconf-client-grouping;
      }
    }
  }
  case https {
    if-feature "https-listen";
    container https {
```

```
    must 'tls-client-parameters/client-identity
        or http-client-parameters/client-identity';
    description
        "HTTPS-specific listening configuration for inbound
        connections.";
    container tcp-server-parameters {
        description
            "A wrapper around the TCP client parameters
            to avoid name collisions.";
        uses tcps:tcp-server-grouping {
            refine "local-port" {
                default "4336";
                description
                    "The RESTCONF client will listen on the IANA-
                    assigned well-known port for 'restconf-ch-tls'
                    (4336) if no value is specified.";
            }
        }
    }
    container tls-client-parameters {
        description
            "A wrapper around the TLS client parameters
            to avoid name collisions.";
        uses tlsc:tls-client-grouping;
    }
    container http-client-parameters {
        description
            "A wrapper around the HTTP client parameters
            to avoid name collisions.";
        uses httpc:http-client-grouping;
    }
    container restconf-client-parameters {
        description
            "A wrapper around the RESTCONF client parameters
            to avoid name collisions.";
        uses rcc:restconf-client-grouping;
    }
}
}
} // restconf-client-listen-stack-grouping

grouping restconf-client-app-grouping {
    description
        "A reusable grouping for configuring a RESTCONF client
        application that supports both 'initiate' and 'listen'
        protocol stacks for a multiplicity of connections.";
    container initiate {
```

```
if-feature "https-initiate";
presence "Enables client to initiate TCP connections";
description
  "Configures client initiating underlying TCP connections.";
list restconf-server {
  key "name";
  min-elements 1;
  description
    "List of RESTCONF servers the RESTCONF client is to
    maintain simultaneous connections with.";
  leaf name {
    type string;
    description
      "An arbitrary name for the RESTCONF server.";
  }
  container endpoints {
    description
      "Container for the list of endpoints.";
    list endpoint {
      key "name";
      min-elements 1;
      ordered-by user;
      description
        "A non-empty user-ordered list of endpoints for this
        RESTCONF client to try to connect to in sequence.
        Defining more than one enables high-availability.";
      leaf name {
        type string;
        description
          "An arbitrary name for this endpoint.";
      }
      uses restconf-client-initiate-stack-grouping;
    }
  }
  container connection-type {
    description
      "Indicates the RESTCONF client's preference for how
      the RESTCONF connection is maintained.";
    choice connection-type {
      mandatory true;
      description
        "Selects between available connection types.";
      case persistent-connection {
        container persistent {
          presence "Indicates that a persistent connection
            is to be maintained.";
          description
            "Maintain a persistent connection to the
```

RESTCONF server. If the connection goes down, immediately start trying to reconnect to the RESTCONF server, using the reconnection strategy.

This connection type minimizes any RESTCONF server to RESTCONF client data-transfer delay, albeit at the expense of holding resources longer.";

```
}
}
case periodic-connection {
  container periodic {
    presence "Indicates that a periodic connection is
              to be maintained.";
    description
      "Periodically connect to the RESTCONF server.

      This connection type increases resource
      utilization, albeit with increased delay
      in RESTCONF server to RESTCONF client
      interactions.

      The RESTCONF client SHOULD gracefully close
      the underlying TLS connection upon completing
      planned activities.

      In the case that the previous connection is
      still active, establishing a new connection
      is NOT RECOMMENDED.";
    leaf period {
      type uint16;
      units "minutes";
      default "60";
      description
        "Duration of time between periodic
         connections.";
    }
    leaf anchor-time {
      type yang:date-and-time {
        // constrained to minute-level granularity
        pattern '\d{4}-\d{2}-\d{2}T\d{2}:\d{2}'
          + '(Z|[\+|-]\d{2}:\d{2})';
      }
      description
        "Designates a timestamp before or after which
         a series of periodic connections are
         determined. The periodic connections occur
         at a whole multiple interval from the anchor
         time. For example, for an anchor time is 15
```

```
        minutes past midnight and a period interval
        of 24 hours, then a periodic connection will
        occur 15 minutes past midnight everyday.";
    }
    leaf idle-timeout {
        type uint16;
        units "seconds";
        default 120; // two minutes
        description
            "Specifies the maximum number of seconds
            that the underlying TCP session may remain
            idle. A TCP session will be dropped if it
            is idle for an interval longer than this
            number of seconds. If set to zero, then the
            RESTCONF client will never drop a session
            because it is idle.";
    }
} // periodic-connection
} // connection-type
} // connection-type
container reconnect-strategy {
    description
        "The reconnection strategy directs how a RESTCONF
        client reconnects to a RESTCONF server, after
        discovering its connection to the server has
        dropped, even if due to a reboot. The RESTCONF
        client starts with the specified endpoint and
        tries to connect to it max-attempts times before
        trying the next endpoint in the list (round
        robin).";
    leaf start-with {
        type enumeration {
            enum first-listed {
                description
                    "Indicates that reconnections should start
                    with the first endpoint listed.";
            }
            enum last-connected {
                description
                    "Indicates that reconnections should start
                    with the endpoint last connected to. If
                    no previous connection has ever been
                    established, then the first endpoint
                    configured is used. RESTCONF clients
                    SHOULD be able to remember the last
                    endpoint connected to across reboots.";
            }
        }
    }
}
```

```
        enum random-selection {
            description
                "Indicates that reconnections should start with
                a random endpoint.";
        }
    }
    default "first-listed";
    description
        "Specifies which of the RESTCONF server's
        endpoints the RESTCONF client should start
        with when trying to connect to the RESTCONF
        server.";
    }
    leaf max-attempts {
        type uint8 {
            range "1..max";
        }
        default "3";
        description
            "Specifies the number times the RESTCONF client
            tries to connect to a specific endpoint before
            moving on to the next endpoint in the list
            (round robin).";
    }
    }
} // initiate
container listen {
    if-feature "http-listen or https-listen";
    presence "Enables client to accept call-home connections";
    description
        "Configures the client to accept call-home TCP connections.";
    leaf idle-timeout {
        type uint16;
        units "seconds";
        default 3600; // one hour
        description
            "Specifies the maximum number of seconds that an
            underlying TCP session may remain idle. A TCP session
            will be dropped if it is idle for an interval longer
            than this number of seconds. If set to zero, then
            the server will never drop a session because it is
            idle. Sessions that have a notification subscription
            active are never dropped.";
    }
}
list endpoint {
    key "name";
    min-elements 1;
```

```
        description
          "List of endpoints to listen for RESTCONF connections.";
        leaf name {
          type string;
          description
            "An arbitrary name for the RESTCONF listen endpoint.";
        }
        uses restconf-client-listen-stack-grouping;
      }
    } // restconf-client-app-grouping

    // Protocol accessible node, for servers that implement
    // this module.
    container restconf-client {
      uses restconf-client-app-grouping;
      description
        "Top-level container for RESTCONF client configuration.";
    }
  }

<CODE ENDS>
```

3. The "ietf-restconf-server" Module

The RESTCONF server model presented in this section supports both listening for connections as well as initiating call-home connections.

YANG feature statements are used to enable implementations to advertise which potentially uncommon parts of the model the RESTCONF server supports.

3.1. Data Model Overview

3.1.1. Features

The following diagram lists all the "feature" statements defined in the "ietf-restconf-server" module:

Features:

- +-- http-listen
- +-- https-listen
- +-- https-call-home

3.1.2. Groupings

The following diagram lists all the "grouping" statements defined in the "ietf-restconf-server" module:

Groupings:

```
+-- restconf-server-grouping
+-- restconf-server-listen-stack-grouping
+-- restconf-server-callhome-stack-grouping
+-- restconf-server-app-grouping
```

Each of these groupings are presented in the following subsections.

3.1.2.1. The "restconf-server-grouping" Grouping

The following tree diagram [RFC8340] illustrates the "restconf-server-grouping" grouping:

```
grouping restconf-server-grouping
  +-- client-identity-mappings
    +---u x509c2n:cert-to-name
```

Comments:

- * The "restconf-server-grouping" defines the configuration for just "RESTCONF" part of a protocol stack. It does not, for instance, define any configuration for the "TCP", "TLS", or "HTTP" protocol layers (for that, see Section 3.1.2.2 and Section 3.1.2.3).
- * The "client-identity-mappings" node, which must be enabled by "feature" statements, defines a mapping from certificate fields to RESTCONF user names.
- * For the referenced grouping statement(s):
 - The "cert-to-name" grouping is discussed in Section 4.1 of [RFC7407].

3.1.2.2. The "restconf-server-listen-stack-grouping" Grouping

The following tree diagram [RFC8340] illustrates the "restconf-server-listen-stack-grouping" grouping:

```
grouping restconf-server-listen-stack-grouping
  +-- (transport)
    +--:(http) {http-listen}?
      +-- http
        +-- external-endpoint!
          +-- address      inet:ip-address
          +-- port?       inet:port-number
        +-- tcp-server-parameters
          +---u tcps:tcp-server-grouping
        +-- http-server-parameters
          +---u https:http-server-grouping
        +-- restconf-server-parameters
          +---u rcs:restconf-server-grouping
    +--:(https) {https-listen}?
      +-- https
        +-- tcp-server-parameters
          +---u tcps:tcp-server-grouping
        +-- tls-server-parameters
          +---u tlss:tls-server-grouping
        +-- http-server-parameters
          +---u https:http-server-grouping
        +-- restconf-server-parameters
          +---u rcs:restconf-server-grouping
```

Comments:

- * The "restconf-server-listen-stack-grouping" defines the configuration for a full RESTCONF protocol stack for RESTCONF servers that listen for standard connections from RESTCONF clients, as opposed to initiating call-home [RFC8071] connections.
- * The "transport" choice node enables both the HTTP and HTTPS transports to be configured, with each option enabled by a "feature" statement. The HTTP option is provided to support cases where a TLS-terminator is deployed in front of the RESTCONF-server.
- * For the referenced grouping statement(s):
 - The "tcp-server-grouping" grouping is discussed in Section 4.1.2.1 of [I-D.ietf-netconf-tcp-client-server].
 - The "tls-server-grouping" grouping is discussed in Section 4.1.2.1 of [I-D.ietf-netconf-tls-client-server].
 - The "http-server-grouping" grouping is discussed in Section 3.1.2.1 of [I-D.ietf-netconf-http-client-server].
 - The "restconf-server-grouping" is discussed in Section 3.1.2.1 of this document.

3.1.2.3. The "restconf-server-callhome-stack-grouping" Grouping

The following tree diagram [RFC8340] illustrates the "restconf-server-callhome-stack-grouping" grouping:

```
grouping restconf-server-callhome-stack-grouping
  +-- (transport)
    +--:(https) {https-listen}?
      +-- https
        +-- tcp-client-parameters
        |   +---u tcpc:tcp-client-grouping
        +-- tls-server-parameters
        |   +---u tlss:tls-server-grouping
        +-- http-server-parameters
        |   +---u https:http-server-grouping
        +-- restconf-server-parameters
        |   +---u rcs:restconf-server-grouping
```

Comments:

- * The "restconf-server-callhome-stack-grouping" defines the configuration for a full RESTCONF protocol stack, for RESTCONF servers that initiate call-home [RFC8071] connections to RESTCONF clients.
- * The "transport" choice node enables transport options to be configured. This document only defines an "https" option, but other options MAY be augmented in.
- * For the referenced grouping statement(s):
 - The "tcp-client-grouping" grouping is discussed in Section 3.1.2.1 of [I-D.ietf-netconf-tcp-client-server].
 - The "tls-server-grouping" grouping is discussed in Section 4.1.2.1 of [I-D.ietf-netconf-tls-client-server].
 - The "http-server-grouping" grouping is discussed in Section 3.1.2.1 of [I-D.ietf-netconf-http-client-server].
 - The "restconf-server-grouping" is discussed in Section 3.1.2.1 of this document.

3.1.2.4. The "restconf-server-app-grouping" Grouping

The following tree diagram [RFC8340] illustrates the "restconf-server-app-grouping" grouping:

```

grouping restconf-server-app-grouping
+-- listen! {http-listen or https-listen}?
|   +-- endpoint* [name]
|       +-- name? string
|       +---u restconf-server-listen-stack-grouping
+-- call-home! {https-call-home}?
    +-- restconf-client* [name]
        +-- name? string
        +-- endpoints
            +-- endpoint* [name]
                +-- name? string
                +---u restconf-server-callhome-stack-grouping
        +-- connection-type
            +-- (connection-type)
                +--:(persistent-connection)
                |   +-- persistent!
                +--:(periodic-connection)
                |   +-- periodic!
                |       +-- period? uint16
                |       +-- anchor-time? yang:date-and-time
                |       +-- idle-timeout? uint16
        +-- reconnect-strategy
            +-- start-with? enumeration
            +-- max-attempts? uint8

```

Comments:

- * The "restconf-server-app-grouping" defines the configuration for a RESTCONF server that supports both listening for connections from RESTCONF clients as well as initiating call-home connections to RESTCONF clients.
- * Both the "listen" and "call-home" subtrees must be enabled by "feature" statements.
- * For the referenced grouping statement(s):
 - The "restconf-server-listen-stack-grouping" grouping is discussed in Section 3.1.2.2 in this document.
 - The "restconf-server-callhome-stack-grouping" grouping is discussed in Section 3.1.2.3 in this document.

3.1.3. Protocol-accessible Nodes

The following diagram lists all the protocol-accessible nodes defined in the "ietf-restconf-server" module:

```

module: ietf-restconf-server
  +--rw restconf-server
    +---u restconf-server-app-grouping

```

Comments:

- * Protocol-accessible nodes are those nodes that are accessible when the module is "implemented", as described in Section 5.6.5 of [RFC7950].
- * For the "ietf-restconf-server" module, the protocol-accessible nodes are an instance of the "restconf-server-app-grouping" discussed in Section 3.1.2.4 grouping.
- * The reason for why "restconf-server-app-grouping" exists separate from the protocol-accessible nodes definition is so as to enable instances of restconf-server-app-grouping to be instantiated in other locations, as may be needed or desired by some modules.

3.2. Example Usage

The following example illustrates configuring a RESTCONF server to listen for RESTCONF client connections, as well as configuring call-home to one RESTCONF client.

This example is consistent with the examples presented in Section 2.2 of [I-D.ietf-netconf-trust-anchors] and Section 2.2 of [I-D.ietf-netconf-keystore].

===== NOTE: '\ ' line wrapping per RFC 8792 =====

```

<restconf-server
  xmlns="urn:ietf:params:xml:ns:yang:ietf-restconf-server"
  xmlns:ct="urn:ietf:params:xml:ns:yang:ietf-crypto-types"
  xmlns:x509c2n="urn:ietf:params:xml:ns:yang:ietf-x509-cert-to-name">

  <!-- endpoints to listen for RESTCONF connections on -->
  <listen>
    <endpoint>
      <name>restconf/https</name>
      <https>
        <tcp-server-parameters>
          <local-address>11.22.33.44</local-address>
        </tcp-server-parameters>
        <tls-server-parameters>
          <server-identity>
            <certificate>
              <keystore-reference>

```

```

        <asymmetric-key>rsa-asymmetric-key</asymmetric-key>
        <certificate>ex-rsa-cert</certificate>
    </keystore-reference>
</certificate>
</server-identity>
<client-authentication>
    <ca-certs>
        <truststore-reference>trusted-client-ca-certs</trustst\
ore-reference>
    </ca-certs>
    <ee-certs>
        <truststore-reference>trusted-client-ee-certs</trustst\
ore-reference>
    </ee-certs>
</client-authentication>
<keepalives>
    <peer-allowed-to-send/>
</keepalives>
</tls-server-parameters>
<http-server-parameters>
    <server-name>foo.example.com</server-name>
</http-server-parameters>
<restconf-server-parameters>
    <client-identity-mappings>
        <cert-to-name>
            <id>1</id>
            <fingerprint>11:0A:05:11:00</fingerprint>
            <map-type>x509c2n:specified</map-type>
            <name>scooby-doo</name>
        </cert-to-name>
        <cert-to-name>
            <id>2</id>
            <map-type>x509c2n:san-any</map-type>
        </cert-to-name>
    </client-identity-mappings>
</restconf-server-parameters>
</https>
</endpoint>
</listen>

<!-- call home to a RESTCONF client with two endpoints -->
<call-home>
    <restconf-client>
        <name>config-manager</name>
        <endpoints>
            <endpoint>
                <name>east-data-center</name>
                <https>

```

```

    <tcp-client-parameters>
      <remote-address>east.example.com</remote-address>
      <keepalives>
        <idle-time>15</idle-time>
        <max-probes>3</max-probes>
        <probe-interval>30</probe-interval>
      </keepalives>
    </tcp-client-parameters>
    <tls-server-parameters>
      <server-identity>
        <certificate>
          <keystore-reference>
            <asymmetric-key>rsa-asymmetric-key</asymmetric-k\
ey>
            <certificate>ex-rsa-cert</certificate>
          </keystore-reference>
        </certificate>
      </server-identity>
      <client-authentication>
        <ca-certs>
          <truststore-reference>trusted-client-ca-certs</tru\
ststore-reference>
        </ca-certs>
        <ee-certs>
          <truststore-reference>trusted-client-ee-certs</tru\
ststore-reference>
        </ee-certs>
      </client-authentication>
      <keepalives>
        <test-peer-aliveness>
          <max-wait>30</max-wait>
          <max-attempts>3</max-attempts>
        </test-peer-aliveness>
      </keepalives>
    </tls-server-parameters>
    <http-server-parameters>
      <server-name>foo.example.com</server-name>
    </http-server-parameters>
    <restconf-server-parameters>
      <client-identity-mappings>
        <cert-to-name>
          <id>1</id>
          <fingerprint>11:0A:05:11:00</fingerprint>
          <map-type>x509c2n:specified</map-type>
          <name>scooby-doo</name>
        </cert-to-name>
        <cert-to-name>
          <id>2</id>

```

```

        <map-type>x509c2n:san-any</map-type>
      </cert-to-name>
    </client-identity-mappings>
  </restconf-server-parameters>
</https>
</endpoint>
<endpoint>
  <name>west-data-center</name>
  <https>
    <tcp-client-parameters>
      <remote-address>west.example.com</remote-address>
      <keepalives>
        <idle-time>15</idle-time>
        <max-probes>3</max-probes>
        <probe-interval>30</probe-interval>
      </keepalives>
    </tcp-client-parameters>
    <tls-server-parameters>
      <server-identity>
        <certificate>
          <keystore-reference>
            <asymmetric-key>rsa-asymmetric-key</asymmetric-k\
ey>
            <certificate>ex-rsa-cert</certificate>
          </keystore-reference>
        </certificate>
      </server-identity>
      <client-authentication>
        <ca-certs>
          <truststore-reference>trusted-client-ca-certs</tru\
ststore-reference>
        </ca-certs>
        <ee-certs>
          <truststore-reference>trusted-client-ee-certs</tru\
ststore-reference>
        </ee-certs>
      </client-authentication>
      <keepalives>
        <test-peer-aliveness>
          <max-wait>30</max-wait>
          <max-attempts>3</max-attempts>
        </test-peer-aliveness>
      </keepalives>
    </tls-server-parameters>
    <http-server-parameters>
      <server-name>foo.example.com</server-name>
    </http-server-parameters>
  </restconf-server-parameters>

```



```

    <client-identity-mappings>
      <cert-to-name>
        <id>1</id>
        <fingerprint>11:0A:05:11:00</fingerprint>
        <map-type>x509c2n:specified</map-type>
        <name>scooby-doo</name>
      </cert-to-name>
      <cert-to-name>
        <id>2</id>
        <map-type>x509c2n:san-any</map-type>
      </cert-to-name>
    </client-identity-mappings>
  </restconf-server-parameters>
</https>
</endpoint>
</endpoints>
<connection-type>
  <periodic>
    <idle-timeout>300</idle-timeout>
    <period>60</period>
  </periodic>
</connection-type>
<reconnect-strategy>
  <start-with>last-connected</start-with>
  <max-attempts>3</max-attempts>
</reconnect-strategy>
</restconf-client>
</call-home>
</restconf-server>

```

3.3. YANG Module

This YANG module has normative references to [RFC6991], [RFC7407], [RFC8040], [RFC8071], [I-D.ietf-netconf-tcp-client-server], [I-D.ietf-netconf-tls-client-server], and [I-D.ietf-netconf-http-client-server].

```

<CODE BEGINS> file "ietf-restconf-server@2020-07-08.yang"

module ietf-restconf-server {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-restconf-server";
  prefix rcs;

  import ietf-yang-types {
    prefix yang;
    reference
      "RFC 6991: Common YANG Data Types";
  }

```

```
}

import ietf-inet-types {
  prefix inet;
  reference
    "RFC 6991: Common YANG Data Types";
}

import ietf-x509-cert-to-name {
  prefix x509c2n;
  reference
    "RFC 7407: A YANG Data Model for SNMP Configuration";
}

import ietf-tcp-client {
  prefix tcpc;
  reference
    "RFC DDDD: YANG Groupings for TCP Clients and TCP Servers";
}

import ietf-tcp-server {
  prefix tcps;
  reference
    "RFC DDDD: YANG Groupings for TCP Clients and TCP Servers";
}

import ietf-tls-server {
  prefix tlss;
  reference
    "RFC FFFF: YANG Groupings for TLS Clients and TLS Servers";
}

import ietf-http-server {
  prefix https;
  reference
    "RFC GGGG: YANG Groupings for HTTP Clients and HTTP Servers";
}

organization
  "IETF NETCONF (Network Configuration) Working Group";

contact
  "WG Web:    <http://datatracker.ietf.org/wg/netconf/>
  WG List:    <mailto:netconf@ietf.org>
  Author:     Kent Watsen <mailto:kent+ietf@watsen.net>
  Author:     Gary Wu <mailto:garywu@cisco.com>
  Author:     Juergen Schoenwaelder
               <mailto:j.schoenwaelder@jacobs-university.de>";
```

description

"This module contains a collection of YANG definitions for configuring RESTCONF servers.

Copyright (c) 2020 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in Section 4.c of the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC IIII (<https://www.rfc-editor.org/info/rfcIIII>); see the RFC itself for full legal notices.

The key words 'MUST', 'MUST NOT', 'REQUIRED', 'SHALL', 'SHALL NOT', 'SHOULD', 'SHOULD NOT', 'RECOMMENDED', 'NOT RECOMMENDED', 'MAY', and 'OPTIONAL' in this document are to be interpreted as described in BCP 14 (RFC 2119) (RFC 8174) when, and only when, they appear in all capitals, as shown here.";

```
revision 2020-07-08 {  
  description  
    "Initial version";  
  reference  
    "RFC IIII: RESTCONF Client and Server Models";  
}
```

// Features

```
feature http-listen {  
  description  
    "The 'http-listen' feature indicates that the RESTCONF server  
    supports opening a port to listen for incoming RESTCONF over  
    TPC client connections, whereby the TLS connections are  
    terminated by an external system.";  
  reference  
    "RFC 8040: RESTCONF Protocol";  
}
```

```
feature https-listen {  
  description  
    "The 'https-listen' feature indicates that the RESTCONF server  
    supports opening a port to listen for incoming RESTCONF over
```

```
        TLS client connections, whereby the TLS connections are
        terminated by the server itself.";
    reference
        "RFC 8040: RESTCONF Protocol";
}

feature https-call-home {
    description
        "The 'https-call-home' feature indicates that the RESTCONF
        server supports initiating connections to RESTCONF clients.";
    reference
        "RFC 8071: NETCONF Call Home and RESTCONF Call Home";
}

// Groupings

grouping restconf-server-grouping {
    description
        "A reusable grouping for configuring a RESTCONF server
        without any consideration for how underlying transport
        sessions are established.

        Note that this grouping uses a fairly typical descendent
        node name such that a stack of 'uses' statements will
        have name conflicts. It is intended that the consuming
        data model will resolve the issue by wrapping the 'uses'
        statement in a container called, e.g.,
        'restconf-server-parameters'. This model purposely does
        not do this itself so as to provide maximum flexibility
        to consuming models.";

    container client-identity-mappings {
        description
            "Specifies mappings through which RESTCONF client X.509
            certificates are used to determine a RESTCONF username.
            If no matching and valid cert-to-name list entry can be
            found, then the RESTCONF server MUST close the connection,
            and MUST NOT accept RESTCONF messages over it.";
        reference
            "RFC 7407: A YANG Data Model for SNMP Configuration.";
        uses x509c2n:cert-to-name {
            refine "cert-to-name/fingerprint" {
                mandatory false;
                description
                    "A 'fingerprint' value does not need to be specified
                    when the 'cert-to-name' mapping is independent of
                    fingerprint matching. A 'cert-to-name' having no
```

```
        fingerprint value will match any client certificate
        and therefore should only be present at the end of
        the user-ordered 'cert-to-name' list.";
    }
}
}

grouping restconf-server-listen-stack-grouping {
  description
    "A reusable grouping for configuring a RESTCONF server
    'listen' protocol stack for a single connection.";
  choice transport {
    mandatory true;
    description
      "Selects between available transports. This is a
      'choice' statement so as to support additional
      transport options to be augmented in.";
    case http {
      if-feature "http-listen";
      container http {
        description
          "Configures RESTCONF server stack assuming that
          TLS-termination is handled externally.";
        container external-endpoint {
          presence
            "Specifies configuration for an external endpoint.";
          description
            "Identifies contact information for the external
            system that terminates connections before passing
            them thru to this server (e.g., a network address
            translator or a load balancer). These values have
            no effect on the local operation of this server, but
            may be used by the application when needing to
            inform other systems how to contact this server.";
          leaf address {
            type inet:ip-address;
            mandatory true;
            description
              "The IP address or hostname of the external system
              that terminates incoming RESTCONF client
              connections before forwarding them to this
              server.";
          }
          leaf port {
            type inet:port-number;
            default "443";
            description
```

```
        "The port number that the external system listens
        on for incoming RESTCONF client connections that
        are forwarded to this server. The default HTTPS
        port (443) is used, as expected for a RESTCONF
        connection.";
    }
}
container tcp-server-parameters {
  description
    "A wrapper around the TCP server parameters
    to avoid name collisions.";
  uses tcps:tcp-server-grouping {
    refine "local-port" {
      default "80";
      description
        "The RESTCONF server will listen on the IANA-
        assigned well-known port value for 'http'
        (80) if no value is specified.";
    }
  }
}
container http-server-parameters {
  description
    "A wrapper around the HTTP server parameters
    to avoid name collisions.";
  uses https:http-server-grouping;
}
container restconf-server-parameters {
  description
    "A wrapper around the RESTCONF server parameters
    to avoid name collisions.";
  uses rcs:restconf-server-grouping;
}
}
case https {
  if-feature "https-listen";
  container https {
    description
      "Configures RESTCONF server stack assuming that
      TLS-termination is handled internally.";
    container tcp-server-parameters {
      description
        "A wrapper around the TCP server parameters
        to avoid name collisions.";
      uses tcps:tcp-server-grouping {
        refine "local-port" {
          default "443";
        }
      }
    }
  }
}
```

```
        description
        "The RESTCONF server will listen on the IANA-
        assigned well-known port value for 'https'
        (443) if no value is specified.";
    }
}
container tls-server-parameters {
    description
    "A wrapper around the TLS server parameters
    to avoid name collisions.";
    uses tlss:tls-server-grouping;
}
container http-server-parameters {
    description
    "A wrapper around the HTTP server parameters
    to avoid name collisions.";
    uses https:http-server-grouping;
}
container restconf-server-parameters {
    description
    "A wrapper around the RESTCONF server parameters
    to avoid name collisions.";
    uses rcs:restconf-server-grouping;
}
}
}
}

grouping restconf-server-callhome-stack-grouping {
    description
    "A reusable grouping for configuring a RESTCONF server
    'call-home' protocol stack, for a single connection.";
    choice transport {
        mandatory true;
        description
        "Selects between available transports. This is a
        'choice' statement so as to support additional
        transport options to be augmented in.";
        case https {
            if-feature "https-listen";
            container https {
                description
                "Configures RESTCONF server stack assuming that
                TLS-termination is handled internally.";
                container tcp-client-parameters {
                    description
```

```
        "A wrapper around the TCP client parameters
        to avoid name collisions.";
    uses tcpc:tcp-client-grouping {
        refine "remote-port" {
            default "4336";
            description
                "The RESTCONF server will attempt to
                connect to the IANA-assigned well-known
                port for 'restconf-ch-tls' (4336) if no
                value is specified.";
        }
    }
}
container tls-server-parameters {
    description
        "A wrapper around the TLS server parameters
        to avoid name collisions.";
    uses tlss:tls-server-grouping;
}
container http-server-parameters {
    description
        "A wrapper around the HTTP server parameters
        to avoid name collisions.";
    uses https:http-server-grouping;
}
container restconf-server-parameters {
    description
        "A wrapper around the RESTCONF server parameters
        to avoid name collisions.";
    uses rcs:restconf-server-grouping;
}
}
}
}

grouping restconf-server-app-grouping {
    description
        "A reusable grouping for configuring a RESTCONF server
        application that supports both 'listen' and 'call-home'
        protocol stacks for a multiplicity of connections.";
    container listen {
        if-feature "http-listen or https-listen";
        presence
            "Enables the RESTCONF server to listen for RESTCONF
            client connections.";
        description "Configures listen behavior";
    }
}
```



```
list endpoint {
  key "name";
  min-elements 1;
  description
    "List of endpoints to listen for RESTCONF connections.";
  leaf name {
    type string;
    description
      "An arbitrary name for the RESTCONF listen endpoint.";
  }
  uses restconf-server-listen-stack-grouping;
}

container call-home {
  if-feature "https-call-home";
  presence
    "Enables the RESTCONF server to initiate the underlying
    transport connection to RESTCONF clients.";
  description "Configures call-home behavior";
  list restconf-client {
    key "name";
    min-elements 1;
    description
      "List of RESTCONF clients the RESTCONF server is to
      maintain simultaneous call-home connections with.";
    leaf name {
      type string;
      description
        "An arbitrary name for the remote RESTCONF client.";
    }
  }
  container endpoints {
    description
      "Container for the list of endpoints.";
    list endpoint {
      key "name";
      min-elements 1;
      ordered-by user;
      description
        "User-ordered list of endpoints for this RESTCONF
        client. Defining more than one enables high-
        availability.";
      leaf name {
        type string;
        description
          "An arbitrary name for this endpoint.";
      }
    }
    uses restconf-server-callhome-stack-grouping;
  }
}
```

```
}
container connection-type {
  description
    "Indicates the RESTCONF server's preference for how the
    RESTCONF connection is maintained.";
  choice connection-type {
    mandatory true;
    description
      "Selects between available connection types.";
    case persistent-connection {
      container persistent {
        presence "Indicates that a persistent connection is
        to be maintained.";
        description
          "Maintain a persistent connection to the RESTCONF
          client. If the connection goes down, immediately
          start trying to reconnect to the RESTCONF server,
          using the reconnection strategy.

          This connection type minimizes any RESTCONF
          client to RESTCONF server data-transfer delay,
          albeit at the expense of holding resources
          longer.";
      }
    }
    case periodic-connection {
      container periodic {
        presence "Indicates that a periodic connection is
        to be maintained.";
        description
          "Periodically connect to the RESTCONF client.

          This connection type increases resource
          utilization, albeit with increased delay in
          RESTCONF client to RESTCONF client interactions.

          The RESTCONF client SHOULD gracefully close
          the underlying TLS connection upon completing
          planned activities. If the underlying TLS
          connection is not closed gracefully, the
          RESTCONF server MUST immediately attempt
          to reestablish the connection.

          In the case that the previous connection is
          still active (i.e., the RESTCONF client has not
          closed it yet), establishing a new connection
          is NOT RECOMMENDED.";
```

```
leaf period {
  type uint16;
  units "minutes";
  default "60";
  description
    "Duration of time between periodic connections.";
}
leaf anchor-time {
  type yang:date-and-time {
    // constrained to minute-level granularity
    pattern '\d{4}-\d{2}-\d{2}T\d{2}:\d{2}'
      + '(Z|[\+|-]\d{2}:\d{2})';
  }
  description
    "Designates a timestamp before or after which a
    series of periodic connections are determined.
    The periodic connections occur at a whole
    multiple interval from the anchor time. For
    example, for an anchor time is 15 minutes past
    midnight and a period interval of 24 hours, then
    a periodic connection will occur 15 minutes past
    midnight everyday.";
}
leaf idle-timeout {
  type uint16;
  units "seconds";
  default 120; // two minutes
  description
    "Specifies the maximum number of seconds that
    the underlying TCP session may remain idle.
    A TCP session will be dropped if it is idle
    for an interval longer than this number of
    seconds. If set to zero, then the server
    will never drop a session because it is idle.";
}
}
}
}
}
container reconnect-strategy {
  description
    "The reconnection strategy directs how a RESTCONF server
    reconnects to a RESTCONF client after discovering its
    connection to the client has dropped, even if due to a
    reboot. The RESTCONF server starts with the specified
    endpoint and tries to connect to it max-attempts times
    before trying the next endpoint in the list (round
    robin).";
}
```

```
leaf start-with {
  type enumeration {
    enum first-listed {
      description
        "Indicates that reconnections should start with
        the first endpoint listed.";
    }
    enum last-connected {
      description
        "Indicates that reconnections should start with
        the endpoint last connected to. If no previous
        connection has ever been established, then the
        first endpoint configured is used. RESTCONF
        servers SHOULD be able to remember the last
        endpoint connected to across reboots.";
    }
    enum random-selection {
      description
        "Indicates that reconnections should start with
        a random endpoint.";
    }
  }
  default "first-listed";
  description
    "Specifies which of the RESTCONF client's endpoints
    the RESTCONF server should start with when trying
    to connect to the RESTCONF client.";
}
leaf max-attempts {
  type uint8 {
    range "1..max";
  }
  default "3";
  description
    "Specifies the number times the RESTCONF server tries
    to connect to a specific endpoint before moving on to
    the next endpoint in the list (round robin).";
}
} // restconf-client
} // call-home
} // restconf-server-app-grouping

// Protocol accessible node, for servers that implement
// this module.
container restconf-server {
```

```
    uses restconf-server-app-grouping;
    description
      "Top-level container for RESTCONF server configuration.";
  }

}

<CODE ENDS>
```

4. Security Considerations

4.1. The "ietf-restconf-client" YANG Module

The "ietf-restconf-client" YANG module defines data nodes that are designed to be accessed via YANG based management protocols, such as NETCONF [RFC6241] and RESTCONF [RFC8040]. Both of these protocols have mandatory-to-implement secure transport layers (e.g., SSH, TLS) with mutual authentication.

The NETCONF access control model (NACM) [RFC8341] provides the means to restrict access for particular users to a pre-configured subset of all available protocol operations and content.

None of the readable data nodes in this YANG module are considered sensitive or vulnerable in network environments. The NACM "default-deny-all" extension has not been set for any data nodes defined in this module.

None of the writable data nodes in this YANG module are considered sensitive or vulnerable in network environments. The NACM "default-deny-write" extension has not been set for any data nodes defined in this module.

This module does not define any RPCs, actions, or notifications, and thus the security consideration for such is not provided here.

Please be aware that this module uses groupings defined in other RFCs that define data nodes that do set the NACM "default-deny-all" and "default-deny-write" extensions.

4.2. The "ietf-restconf-server" YANG Module

The "ietf-restconf-server" YANG module defines data nodes that are designed to be accessed via YANG based management protocols, such as NETCONF [RFC6241] and RESTCONF [RFC8040]. Both of these protocols have mandatory-to-implement secure transport layers (e.g., SSH, TLS) with mutual authentication.

The NETCONF access control model (NACM) [RFC8341] provides the means to restrict access for particular users to a pre-configured subset of all available protocol operations and content.

None of the readable data nodes in this YANG module are considered sensitive or vulnerable in network environments. The NACM "default-deny-all" extension has not been set for any data nodes defined in this module.

None of the writable data nodes in this YANG module are considered sensitive or vulnerable in network environments. The NACM "default-deny-write" extension has not been set for any data nodes defined in this module.

This module does not define any RPCs, actions, or notifications, and thus the security consideration for such is not provided here.

Please be aware that this module uses groupings defined in other RFCs that define data nodes that do set the NACM "default-deny-all" and "default-deny-write" extensions.

5. IANA Considerations

5.1. The IETF XML Registry

This document registers two URIs in the "ns" subregistry of the IETF XML Registry [RFC3688]. Following the format in [RFC3688], the following registrations are requested:

URI: urn:ietf:params:xml:ns:yang:ietf-restconf-client
Registrant Contact: The NETCONF WG of the IETF.
XML: N/A, the requested URI is an XML namespace.

URI: urn:ietf:params:xml:ns:yang:ietf-restconf-server
Registrant Contact: The NETCONF WG of the IETF.
XML: N/A, the requested URI is an XML namespace.

5.2. The YANG Module Names Registry

This document registers two YANG modules in the YANG Module Names registry [RFC6020]. Following the format in [RFC6020], the the following registrations are requested:

```
name:      ietf-restconf-client
namespace: urn:ietf:params:xml:ns:yang:ietf-restconf-client
prefix:    ncc
reference:  RFC IIII

name:      ietf-restconf-server
namespace: urn:ietf:params:xml:ns:yang:ietf-restconf-server
prefix:    ncs
reference:  RFC IIII
```

6. References

6.1. Normative References

- [I-D.ietf-netconf-http-client-server]
Watsen, K., "YANG Groupings for HTTP Clients and HTTP Servers", Work in Progress, Internet-Draft, draft-ietf-netconf-http-client-server-03, 20 May 2020, <<https://tools.ietf.org/html/draft-ietf-netconf-http-client-server-03>>.
- [I-D.ietf-netconf-keystore]
Watsen, K., "A YANG Data Model for a Keystore", Work in Progress, Internet-Draft, draft-ietf-netconf-keystore-17, 20 May 2020, <<https://tools.ietf.org/html/draft-ietf-netconf-keystore-17>>.
- [I-D.ietf-netconf-tcp-client-server]
Watsen, K. and M. Scharf, "YANG Groupings for TCP Clients and TCP Servers", Work in Progress, Internet-Draft, draft-ietf-netconf-tcp-client-server-06, 16 June 2020, <<https://tools.ietf.org/html/draft-ietf-netconf-tcp-client-server-06>>.
- [I-D.ietf-netconf-tls-client-server]
Watsen, K. and G. Wu, "YANG Groupings for TLS Clients and TLS Servers", Work in Progress, Internet-Draft, draft-ietf-netconf-tls-client-server-19, 20 May 2020, <<https://tools.ietf.org/html/draft-ietf-netconf-tls-client-server-19>>.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.

- [RFC6020] Bjorklund, M., Ed., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", RFC 6020, DOI 10.17487/RFC6020, October 2010, <<https://www.rfc-editor.org/info/rfc6020>>.
- [RFC6991] Schoenwaelder, J., Ed., "Common YANG Data Types", RFC 6991, DOI 10.17487/RFC6991, July 2013, <<https://www.rfc-editor.org/info/rfc6991>>.
- [RFC7407] Bjorklund, M. and J. Schoenwaelder, "A YANG Data Model for SNMP Configuration", RFC 7407, DOI 10.17487/RFC7407, December 2014, <<https://www.rfc-editor.org/info/rfc7407>>.
- [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", RFC 7950, DOI 10.17487/RFC7950, August 2016, <<https://www.rfc-editor.org/info/rfc7950>>.
- [RFC8040] Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Protocol", RFC 8040, DOI 10.17487/RFC8040, January 2017, <<https://www.rfc-editor.org/info/rfc8040>>.
- [RFC8071] Watsen, K., "NETCONF Call Home and RESTCONF Call Home", RFC 8071, DOI 10.17487/RFC8071, February 2017, <<https://www.rfc-editor.org/info/rfc8071>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.

6.2. Informative References

- [I-D.ietf-netconf-crypto-types]
Watsen, K., "Common YANG Data Types for Cryptography", Work in Progress, Internet-Draft, draft-ietf-netconf-crypto-types-15, 20 May 2020, <<https://tools.ietf.org/html/draft-ietf-netconf-crypto-types-15>>.
- [I-D.ietf-netconf-netconf-client-server]
Watsen, K., "NETCONF Client and Server Models", Work in Progress, Internet-Draft, draft-ietf-netconf-netconf-client-server-19, 20 May 2020, <<https://tools.ietf.org/html/draft-ietf-netconf-netconf-client-server-19>>.
- [I-D.ietf-netconf-restconf-client-server]
Watsen, K., "RESTCONF Client and Server Models", Work in Progress, Internet-Draft, draft-ietf-netconf-restconf-

client-server-19, 20 May 2020,
<<https://tools.ietf.org/html/draft-ietf-netconf-restconf-client-server-19>>.

[I-D.ietf-netconf-ssh-client-server]

Watsen, K. and G. Wu, "YANG Groupings for SSH Clients and SSH Servers", Work in Progress, Internet-Draft, draft-ietf-netconf-ssh-client-server-19, 20 May 2020, <<https://tools.ietf.org/html/draft-ietf-netconf-ssh-client-server-19>>.

[I-D.ietf-netconf-trust-anchors]

Watsen, K., "A YANG Data Model for a Truststore", Work in Progress, Internet-Draft, draft-ietf-netconf-trust-anchors-10, 20 May 2020, <<https://tools.ietf.org/html/draft-ietf-netconf-trust-anchors-10>>.

[RFC3688] Mealling, M., "The IETF XML Registry", BCP 81, RFC 3688, DOI 10.17487/RFC3688, January 2004, <<https://www.rfc-editor.org/info/rfc3688>>.

[RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", RFC 6241, DOI 10.17487/RFC6241, June 2011, <<https://www.rfc-editor.org/info/rfc6241>>.

[RFC8340] Bjorklund, M. and L. Berger, Ed., "YANG Tree Diagrams", BCP 215, RFC 8340, DOI 10.17487/RFC8340, March 2018, <<https://www.rfc-editor.org/info/rfc8340>>.

[RFC8341] Bierman, A. and M. Bjorklund, "Network Configuration Access Control Model", STD 91, RFC 8341, DOI 10.17487/RFC8341, March 2018, <<https://www.rfc-editor.org/info/rfc8341>>.

[RFC8342] Bjorklund, M., Schoenwaelder, J., Shafer, P., Watsen, K., and R. Wilton, "Network Management Datastore Architecture (NMDA)", RFC 8342, DOI 10.17487/RFC8342, March 2018, <<https://www.rfc-editor.org/info/rfc8342>>.

[RFC8446] Rescorla, E., "The Transport Layer Security (TLS) Protocol Version 1.3", RFC 8446, DOI 10.17487/RFC8446, August 2018, <<https://www.rfc-editor.org/info/rfc8446>>.

Appendix A. Expanded Tree Diagrams

A.1. Expanded Tree Diagram for 'ietf-restconf-client'

The following tree diagram [RFC8340] provides an overview of the data model for the "ietf-restconf-client" module.

This tree diagram shows all the nodes defined in this module, including those defined by "grouping" statements used by this module.

Please see Section 2.1 for a tree diagram that illustrates what the module looks like without all the "grouping" statements expanded.

XNSERT_TEXT_FROM_FILE(refs/ietf-restconf-client-tree.txt)

A.2. Expanded Tree Diagram for 'ietf-restconf-server'

The following tree diagram [RFC8340] provides an overview of the data model for the "ietf-restconf-server" module.

This tree diagram shows all the nodes defined in this module, including those defined by "grouping" statements used by this module.

Please see Section 3.1 for a tree diagram that illustrates what the module looks like without all the "grouping" statements expanded.

XNSERT_TEXT_FROM_FILE(refs/ietf-restconf-server-tree.txt)

Appendix B. Change Log

This section is to be removed before publishing as an RFC.

B.1. 00 to 01

- * Renamed "keychain" to "keystore".

B.2. 01 to 02

- * Filled in previously missing 'ietf-restconf-client' module.
- * Updated the ietf-restconf-server module to accommodate new grouping 'ietf-tls-server-grouping'.

B.3. 02 to 03

- * Refined use of tls-client-grouping to add a must statement indicating that the TLS client must specify a client-certificate.
- * Changed restconf-client??? to be a grouping (not a container).

B.4. 03 to 04

- * Added RFC 8174 to Requirements Language Section.
- * Replaced refine statement in ietf-restconf-client to add a mandatory true.
- * Added refine statement in ietf-restconf-server to add a must statement.
- * Now there are containers and groupings, for both the client and server models.
- * Now tree diagrams reference ietf-netmod-yang-tree-diagrams
- * Updated examples to inline key and certificates (no longer a leafref to keystore)

B.5. 04 to 05

- * Now tree diagrams reference ietf-netmod-yang-tree-diagrams
- * Updated examples to inline key and certificates (no longer a leafref to keystore)

B.6. 05 to 06

- * Fixed change log missing section issue.
- * Updated examples to match latest updates to the crypto-types, trust-anchors, and keystore drafts.
- * Reduced line length of the YANG modules to fit within 69 columns.

B.7. 06 to 07

- * removed "idle-timeout" from "persistent" connection config.
- * Added "random-selection" for reconnection-strategy's "starts-with" enum.
- * Replaced "connection-type" choice default (persistent) with "mandatory true".
- * Reduced the periodic-connection's "idle-timeout" from 5 to 2 minutes.
- * Replaced reconnect-timeout with period/anchor-time combo.

B.8. 07 to 08

- * Modified examples to be compatible with new crypto-types algs

B.9. 08 to 09

- * Corrected use of "mandatory true" for "address" leafs.
- * Updated examples to reflect update to groupings defined in the keystore draft.
- * Updated to use groupings defined in new TCP and HTTP drafts.
- * Updated copyright date, boilerplate template, affiliation, and folding algorithm.

B.10. 09 to 10

- * Reformatted YANG modules.

B.11. 10 to 11

- * Adjusted for the top-level "demux container" added to groupings imported from other modules.
- * Added "must" expressions to ensure that keepalives are not configured for "periodic" connections.
- * Updated the boilerplate text in module-level "description" statement to match copyeditor convention.
- * Moved "expanded" tree diagrams to the Appendix.

B.12. 11 to 12

- * Removed the 'must' statement limiting keepalives in periodic connections.
- * Updated models and examples to reflect removal of the "demux" containers in the imported models.
- * Updated the "periodic-connection" description statements to better describe behavior when connections are not closed gracefully.
- * Updated text to better reference where certain examples come from (e.g., which Section in which draft).

- * In the server model, commented out the "must 'pinned-ca-certs or pinned-client-certs'" statement to reflect change made in the TLS draft whereby the trust anchors MAY be defined externally.
- * Replaced the 'listen', 'initiate', and 'call-home' features with boolean expressions.

B.13. 12 to 13

- * Updated to reflect changes in trust-anchors drafts (e.g., s/trust-anchors/truststore/g + s/pinned.//)
- * In ietf-restconf-server, Added 'http-listen' (not https-listen) choice, to support case when server is behind a TLS-terminator.
- * Refactored server module to be more like other 'server' models. If folks like it, will also apply to the client model, as well as to both the netconf client/server models. Now the 'restconf-server-grouping' is just the RC-specific bits (i.e., the "demux" container minus the container), 'restconf-server-[listen|callhome]-stack-grouping' is the protocol stack for a single connection, and 'restconf-server-app-grouping' is effectively what was before (both listen+callhome for many inbound/outbound endpoints).

B.14. 13 to 14

- * Updated examples to reflect ietf-crypto-types change (e.g., identities --> enumerations)
- * Adjusting from change in TLS client model (removing the top-level 'certificate' container).
- * Added "external-endpoint" to the "http-listen" choice in ietf-restconf-server.

B.15. 14 to 15

- * Added missing "or https-listen" clause in a "must" expression.
- * Refactored the client module similar to how the server module was refactored in -13. Now the 'restconf-client-grouping' is just the RC-specific bits, the 'restconf-client-[initiate|listen]-stack-grouping' is the protocol stack for a single connection, and 'restconf-client-app-grouping' is effectively what was before (both listen+callhome for many inbound/outbound endpoints).

B.16. 15 to 16

- * Added refinement to make "cert-to-name/fingerprint" be mandatory false.
- * Commented out refinement to "tls-server-grouping/client-authentication" until a better "must" expression is defined.
- * Updated restconf-client example to reflect that http-client-grouping no longer has a "protocol-version" leaf.

B.17. 16 to 17

- * Updated examples to include the "*-key-format" nodes.
- * Updated examples to remove the "required" nodes.

B.18. 17 to 18

- * Updated examples to reflect new "bag" addition to truststore.

B.19. 18 to 19

- * Updated examples to remove the 'algorithm' nodes.
- * Updated examples to reflect the new TLS keepalives structure.
- * Removed the 'protocol-versions' node from the restconf-server examples.
- * Added a "Note to Reviewers" note to first page.

B.20. 19 to 20

- * Moved and changed "must" statement so that either TLS *or* HTTP auth must be configured.
- * Expanded "Data Model Overview section(s) [remove "wall" of tree diagrams].
- * Updated the Security Considerations section.

Acknowledgements

The authors would like to thank for following for lively discussions on list and in the halls (ordered by last name): Andy Bierman, Martin Bjorklund, Benoit Claise, Mehmet Ersue, Ramkumar Dhanapal, Balazs Kovacs, Radek Krejci, David Lamparter, Ladislav Lhotka, Alan Luchuk, Tom Petch, Juergen Schoenwaelder, Phil Shafer, Sean Turner, Bert Wijnen.

Author's Address

Kent Watsen
Watsen Networks

Email: kent+ietf@watsen.net