

CCAMP Working Group
Internet-Draft
Intended status: Standards Track
Expires: May 6, 2021

Y. Lee
Samsung
K. Lee
Korea Telecom
H. Zheng
Huawei Technologies
O. Gonzalez de Dios
Telefonica
D. Ceccarelli
Ericsson
November 2, 2020

A YANG Data Model for L1 Connectivity Service Model (L1CSM)
draft-ietf-ccamp-llcsm-yang-13

Abstract

This document provides a YANG data model for Layer 1 Connectivity Service Model (L1CSM). The intent of this document is to provide a Layer 1 service model exploiting YANG data model, which can be utilized by a customer network controller to initiate a service request connectivity as well as retrieving service states toward a Layer 1 network controller communicating with its customer network controller. This YANG model is NMDA-compliant.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on May 6, 2021.

Copyright Notice

Copyright (c) 2020 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1. Introduction	2
1.1. Deployment Scenarios	3
1.2. Terminology	6
1.3. Tree Diagram	6
1.4. Prefixes in Data Node Names	6
2. Definitions	7
3. L1CSM YANG Model (Tree Structure)	7
4. L1CSM YANG Code	8
5. JSON Example	14
6. Security Considerations	16
7. IANA Considerations	16
8. Acknowledgements	17
9. Contributors	17
10. References	17
10.1. Normative References	17
10.2. Informative References	18
Authors' Addresses	19

1. Introduction

This document provides a YANG data model for L1VPN Connectivity Service Model (L1CSM) which can be classified as Network Service YANG module per [RFC8199]. The intent of this document is to provide a transport service model exploiting YANG data model, which can be utilized by a client network controller to initiate a service request connectivity request as well as retrieving service states toward a transport network controller communicating with the client controller via a NETCONF [RFC8341] or a RESTCONF [RFC8040] interface.

[RFC4847] provides a framework and service level requirements for Layer 1 Virtual Private Networks (L1VPNs). It classifies service models as management-based service model, signaling-based service model (Basic Mode) and signaling and routing service model (Enhanced Mode).

In the management-based service model, customer management systems and provider management systems communicate with each other. Customer management systems access provider management systems to request layer 1 connection setup/deletion between a pair of CEs. Customer management systems may obtain additional information, such as resource availability information and monitoring information, from provider management systems. There is no control message exchange between a CE and PE.

In the signaling-based service model (Basic Model), the CE-PE interface's functional repertoire is limited to path setup signaling only. In the Signaling and routing service model (Enhanced Mode), the CE-PE interface provides the signaling capabilities as in the Basic Mode, plus permits limited exchange of information between the control planes of the provider and the customer to help such functions as discovery of customer network routing information (i.e., reachability or TE information in remote customer sites), or parameters of the part of the provider's network dedicated to the customer.

The primary focus of this document is to describe L1CS YANG model required for the instantiation of point-to-point L1VPN service. A L1VPN is a service offered by a core layer 1 network to provide layer 1 connectivity between two or more customer sites where the customer has some control over the establishment and type of the connectivity.

The data model presented in Section 3 is in consistent with [MEF63]. The data model includes configuration and state data according to the new Network Management Datastore Architecture [RFC8342].

1.1. Deployment Scenarios

Figure 1 depicts a deployment scenario of the L1VPN SDN control-based service model for an external customer instantiating L1 point-to-point connectivity to the provider.




Figure 1: L1VPN SDN Controller/EMS/NMS-Based Service Model: External Customer

With this scenario, the customer service orchestrator interfaces with the network SDN controller of the provider using Customer Service Model as defined in [RFC8309].

Figure 2 depicts another deployment scenario for internal customer (e.g., higher-layer service management department(s)) interfacing the layer 1 transport network department. With this scenario, a multi-service backbone is characterized such that each service department of a provider (e.g., L2/3 services) that receives the same provider's L1VPN service provides a different kind of higher-layer service. The customer receiving the L1VPN service (i.e., each service department) can offer its own services, whose payloads can be any layer (e.g., ATM, IP, TDM). The layer 1 transport network and each service

network belong to the same organization, but may be managed separately. The Service SDN Controller is the control/management entity owned by higher-layer service department (e.g., L2/3 VPN) whereas the Network SDN Controller is the control/management entity responsible for Layer 1 connectivity service. The CEs in Figure 2 are L2/3 devices that interface with L1 PE devices.




Figure 2: L1VPN SDN Controller/EMS/NMS-Based Service Model: Internal Customer

The benefit is that the same layer 1 transport network resources are shared by multiple services. A large capacity backbone network (data plane) can be built economically by having the resources shared by multiple services usually with flexibility to modify topologies, while separating the control functions for each service department. Thus, each customer can select a specific set of features that are needed to provide their own service [RFC4847].

1.2. Terminology

Refer to [RFC4847] and [RFC5253] for the key terms used in this document.

The following terms are defined in [RFC7950] and are not redefined here:

- o client
- o server
- o augment
- o data model
- o data node

The following terms are defined in [RFC6241] and are not redefined here:

- o configuration data
- o state data

The terminology for describing YANG data models is found in [RFC7950].

1.3. Tree Diagram

A simplified graphical representation of the data model is used in Section 3 of this document. The meaning of the symbols in these diagrams is defined in [RFC8340].

1.4. Prefixes in Data Node Names

In this document, names of data nodes and other data model objects are prefixed using the standard prefix associated with the corresponding YANG imported modules. The module ietf-layer1-types

specified in [I-D.ietf-ccamp-layer1-types] and ietf-yang-types specified in [RFC6991] are imported in this module.

Prefix	YANG module	Reference
l1csm	ietf-l1csm	[RFC XXXX]
l1-types	ietf-layer1-types	[I-D.ietf-ccamp-layer1-types]
yang	ietf-yang-types	[RFC6991]

Note: The RFC Editor will replace XXXX with the number assigned to the RFC once this document becomes an RFC.

2. Definitions

L1VC Layer 1 Virtual Connection

SLS Service Level Specification

UNI User Network Interface

PE Provider Edge

CE Customer Edge

EP End Point

P Protocol

C Coding

O Optical Interface

3. L1CSM YANG Model (Tree Structure)

```

module: ietf-llcsm
  +--rw ll-connectivity
    +--rw access
      +--rw unis
        +--rw uni* [id]
          +--rw id string
          +--rw (uni-access-type)?
            +--:(mef)
              +--rw protocol identityref
              +--rw coding identityref
              +--rw optical-interface identityref
            +--:(itu)
              +--rw client-signal identityref
      +--rw services
        +--rw service* [service-id]
          +--rw service-id string
          +--rw endpoint-1
            +--rw id string
            +--rw uni -> /ll-connectivity/access/unis/uni/id
          +--rw endpoint-2
            +--rw id string
            +--rw uni -> /ll-connectivity/access/unis/uni/id
          +--rw start-time? yang:date-and-time
          +--rw time-interval? int32
          +--rw performance-metric* identityref

```

4. L1CSM YANG Code

```

<CODE BEGINS>file "ietf-llcsm@2020-10-27.yang"
module ietf-llcsm {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-llcsm";
  prefix "llcsm";

  import ietf-yang-types {
    prefix "yang";
  }

  import ietf-layer1-types {
    prefix "l1-types";
  }

  organization
    "Internet Engineering Task Force (IETF) CCAMP WG";

```


contact

```
"Editor: Y. Lee (younglee.tx@gmail.com)
Editor: K. Lee (kwangkoog.lee@kt.com)
Editor: H. Zheng (zhenghaomian@huawei.com)
Editor: D. Dhody (dhruv.ietf@gmail.com)
Editor: O. G. de-Dios (oscar.gonzalezdedios@telefonica.com)
Editor: D. Ceccarelli (daniele.ceccarelli@ericsson.com)";
```

description

```
"This module describes L1 connectivity service based on MEF 63:
Subscriber Layer 1 Service Attribute Technical Specification.
Refer to MEF 63 for all terms and the original references
used in the module.
```

```
Copyright (c) 2020 IETF Trust and the persons identified as
authors of the code. All rights reserved.
Redistribution and use in source and binary forms, with or
without modification, is permitted pursuant to, and subject
to the license terms contained in, the Simplified BSD
License set forth in Section 4.c of the IETF Trust's Legal
Provisions Relating to IETF Documents
(http://trustee.ietf.org/license-info).
```

```
This version of this YANG module is part of RFC XXXX; see
the RFC itself for full legal notices.";
```

```
revision "2020-10-27" {
  description "Initial revision.";
  reference "RFC XXXX: A Yang Data Model for L1 Connectivity
    Service Model (L1CSM)";
// Note: The RFC Editor will replace XXXX with the number
// assigned to the RFC once this draft becomes an RFC.
}
```

```
/*
 * Identities
 */
```

```
identity service-performance-metric {
  description
    "Base identity of service-specific performance metric";
  reference "MEF63: Subscriber Layer 1 Service Attributes";
}
```

```
identity one-way-delay {
  base "service-performance-metric";
  description "one way delay.";
```

```
    reference "MEF63: Subscriber Layer 1 Service Attributes";
}

identity one-way-errored-second {
    base "service-performance-metric";
    description "one way errored second";
    reference "MEF63: Subscriber Layer 1 Service Attributes";
}

identity one-way-severely-errored-second {
    base "service-performance-metric";
    description "one way severely errored second";
    reference "MEF63: Subscriber Layer 1 Service Attributes";
}

identity one-way-unavailable-second {
    base "service-performance-metric";
    description "one way unavailable second";
    reference "MEF63: Subscriber Layer 1 Service Attributes";
}

identity one-way-availability {
    base "service-performance-metric";
    description "one way availability";
    reference "MEF63: Subscriber Layer 1 Service Attributes";
}

/*
 * Groupings
 */

grouping protocol-coding-optical-interface {
    description
        "The 3-tuple <p,c,o> where p:protocol type;
        c:coding function; o:optical interface function.

        Valid combinations are defined in Tables 4, 5, 6 and 7
        of MEF 63.";
    reference "MEF 63";

    leaf protocol {
        type identityref {
            base "l1-types:protocol";
        }
        mandatory true;
        description "The protocol being used at the UNI.";
    }
    leaf coding {
```

```
    type identityref {
      base "l1-types:coding-func";
    }
    mandatory true;
    description "The coding function being used at the UNI.";
  }
  leaf optical-interface {
    type identityref {
      base "l1-types:optical-interface-func";
    }
    mandatory true;
    description
      "The optical interface function being used at the UNI.";
  }
}

grouping subscriber-llvc-sls-service-attribute {
  description
    "The value of the Subscriber L1VC SLS (Service Level
    Specification) Service Attribute";
  reference "MEF 63";

  leaf start-time {
    type yang:date-and-time;
    description "a time that represent the date and time
      for the start of the SLS";
  }
  leaf time-interval {
    type int32;
    units seconds;
    description
      "a time interval (e.g., 2,419,200 seconds which is 28 days)
      that is used in conjunction wuth time-start to specify a
      contiguous sequence of time intervals T for determining
      when performance objectives are met.";
  }
  leaf-list performance-metric {
    type identityref {
      base "service-performance-metric";
    }
    description "list of service performance metric.";
  }
}

grouping subscriber-llvc-endpoint-attributes {
  description
    "subscriber layer 1 connection endpoint attributes";
  reference "MEF 63";
```

```
    container endpoint-1 {
      description "One end of UNI id's - string and id";
      leaf id {
        type string;
        mandatory true;
        description "subscriber end point ID of one end";
      }
      leaf uni {
        type leafref {
          path "/l1-connectivity/access/unis/uni/id";
        }
        mandatory true;
        description "this is one end of subscriber L1VC end point
                     ID value = UNI-1";
      }
    }
    container endpoint-2 {
      description "One end of UNI id's - string and id";
      leaf id {
        type string;
        mandatory true;
        description "subscriber end point ID of the other end";
      }
      leaf uni {
        type leafref {
          path "/l1-connectivity/access/unis/uni/id";
        }
        mandatory true;
        description
          "this is one other end of subscriber L1VC end point
           ID value = UNI-2";
      }
    }
  }
}

/*
 * Data nodes
 */

container l1-connectivity {
  description
    "serves as a top-level container for a list of layer 1
     connection services (l1cs)";

  container access {
    description "UNI configurations for access networks";

    container unis {
```

```
description "the list of UNI's to be configured";

list uni {
  key "id";
  description "UNI identifier";
  leaf id {
    type string;
    description "the UNI id of UNI Service Attributes";
  }
  choice uni-access-type {
    description
      "The UNI access type can be specified either by the
      protocol, coding function and optical interface
      function, defined in MEF, or by the client-signal,
      defined in ITU-T.";
    case mef {
      uses protocol-coding-optical-interface;
    }
    case itu {
      leaf client-signal {
        type identityref {
          base "l1-types:client-signal";
        }
        mandatory true;
        description
          "The client signal being used at the UNI";
      }
    }
  }
}

}

}

}

container services {
  description "L1VC services";
  list service {
    key "service-id";
    description
      "an unique identifier of a subscriber L1VC service";

    leaf service-id {
      type string;
      mandatory true;
      description "a unique service identifier for
        subscriber L1VC.";
    }
    uses subscriber-l1vc-endpoint-attributes;
    uses subscriber-l1vc-sls-service-attribute;
  }
}
```

```
        } //end of service list
      } //end of service container
    } //service top container
  }
<CODE ENDS>
```

5. JSON Example

This section provides a JSON example of the YANG module described in Section 4. This example configures one L1VC service with two UNIs that describe the UNI endpoints. The service is configured with the starting time to be 06:06:09 on 2018-09-13 for the service life time of 2419200 seconds (which corresponds to 28 days). In addition, the service is configured to collect one performance metric, One-way-Delay.

```
{
  "l1-connectivity": {
    "access": {
      "unis": {
        "uni": [
          {
            "id": "MTL-HQ-Node3-Slot2-Port1",
            "protocol": "ETH-10GigE_LAN ",
            "coding": "ETH-10GR-PCS-49 ",
            "optical_interface": "LR-PMD-clause-52 "
          },
          {
            "id": "MTL-STL-Node5-Slot4-Port3",
            "protocol": "ETH-10GigE_LAN ",
            "coding": "ETH-10GR-PCS-49 ",
            "optical_interface": "ER-PMD-clause-52 "
          }
        ]
      },
    },
    "services": {
      "service": [
        {
          "service-id": "Sub-L1VC-1867-LT-MEGAMART",
          "endpoint-1": {
            "id": "MTL-HQ_1867-MEGAMART",
            "uni": "MTL-HQ-Node3-Slot2-Port1"
          },
          "endpoint-2": {
            "id": "MTL-STL_1867-MEGAMART",
            "uni": "MTL-STL-Node5-Slot4-Port3"
          },
          "start-time": "2018-09-13T06:06:09Z",
          "time-interval": 2419200,
          "performance-metric": "One-way-Delay "
        }
      ]
    },
  },
}
```

6. Security Considerations

The YANG module specified in this document defines a schema for data that is designed to be accessed via network management protocols such as NETCONF [RFC6241] or RESTCONF [RFC8040]. The lowest NETCONF layer is the secure transport layer, and the mandatory-to-implement secure transport is Secure Shell (SSH) [RFC6242]. The lowest RESTCONF layer is HTTPS, and the mandatory-to-implement secure transport is TLS [RFC8446].

The NETCONF access control model [RFC8341] provides the means to restrict access for particular NETCONF or RESTCONF users to a preconfigured subset of all available NETCONF or RESTCONF protocol operations and content.

A number of configuration data nodes defined in this document are writable/deletable (i.e., "config true") These data nodes may be considered sensitive or vulnerable in some network environments.

These are the subtrees and data nodes and their sensitivity/vulnerability:

unis:

- id

Service:

- service-id

- endpoint-1

- endpoint-2

- start-time

- time-interval

- performance-metric

The security considerations spelled out in the YANG 1.1 specification [RFC7950] apply for this document as well.

7. IANA Considerations

It is proposed that IANA should assign new URIs from the "IETF XML Registry" [RFC3688] as follows:

URI: urn:ietf:params:xml:ns:yang:ietf-llcsm
Registrant Contact: The IESG
XML: N/A; the requested URI is an XML namespace.

This document registers following YANG modules in the YANG Module Names registry [RFC7950].

name: iETF-llcsm
namespace: urn:ietf:params:xml:ns:yang:ietf-llcsm
prefix: llcsm
reference: RFC XXXX

8. Acknowledgements

The authors would like to thank Tom Petch for his helpful comments and valuable contributions and Robert Wilton for his review that improved the model significantly.

9. Contributors

Italo Busi
Huawei Technologies
Email: Italo.Busi@huawei.com

Giuseppe Fioccola
Huawei Technologies
Email: giuseppe.fioccola@huawei.com

Dhruv Dhody
Huawei Technologies
Email: dhruv.ietf@gmail.com

10. References

10.1. Normative References

- [MEF63] Metro Ethernet Forum, "Subscriber Layer1 Service Attributes Technical Specification", MEF 63, August 2018.
- [RFC3688] Mealling, M., "The IETF XML Registry", BCP 81, RFC 3688, DOI 10.17487/RFC3688, January 2004, <<https://www.rfc-editor.org/info/rfc3688>>.

- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", RFC 6241, DOI 10.17487/RFC6241, June 2011, <<https://www.rfc-editor.org/info/rfc6241>>.
- [RFC6242] Wasserman, M., "Using the NETCONF Protocol over Secure Shell (SSH)", RFC 6242, DOI 10.17487/RFC6242, June 2011, <<https://www.rfc-editor.org/info/rfc6242>>.
- [RFC6991] Schoenwaelder, J., Ed., "Common YANG Data Types", RFC 6991, DOI 10.17487/RFC6991, July 2013, <<https://www.rfc-editor.org/info/rfc6991>>.
- [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", RFC 7950, DOI 10.17487/RFC7950, August 2016, <<https://www.rfc-editor.org/info/rfc7950>>.
- [RFC8040] Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Protocol", RFC 8040, DOI 10.17487/RFC8040, January 2017, <<https://www.rfc-editor.org/info/rfc8040>>.
- [RFC8340] Bjorklund, M. and L. Berger, Ed., "YANG Tree Diagrams", BCP 215, RFC 8340, DOI 10.17487/RFC8340, March 2018, <<https://www.rfc-editor.org/info/rfc8340>>.
- [RFC8341] Bierman, A. and M. Bjorklund, "Network Configuration Access Control Model", STD 91, RFC 8341, DOI 10.17487/RFC8341, March 2018, <<https://www.rfc-editor.org/info/rfc8341>>.
- [RFC8342] Bjorklund, M., Schoenwaelder, J., Shafer, P., Watsen, K., and R. Wilton, "Network Management Datastore Architecture (NMDA)", RFC 8342, DOI 10.17487/RFC8342, March 2018, <<https://www.rfc-editor.org/info/rfc8342>>.
- [RFC8446] Rescorla, E., "The Transport Layer Security (TLS) Protocol Version 1.3", RFC 8446, DOI 10.17487/RFC8446, August 2018, <<https://www.rfc-editor.org/info/rfc8446>>.

10.2. Informative References

- [I-D.ietf-ccamp-layer1-types]
Zheng, H. and I. Busi, "A YANG Data Model for Layer 1 Types", draft-ietf-ccamp-layer1-types-07 (work in progress), September 2020.

- [RFC4847] Takeda, T., Ed., "Framework and Requirements for Layer 1 Virtual Private Networks", RFC 4847, DOI 10.17487/RFC4847, April 2007, <<https://www.rfc-editor.org/info/rfc4847>>.
- [RFC5253] Takeda, T., Ed., "Applicability Statement for Layer 1 Virtual Private Network (L1VPN) Basic Mode", RFC 5253, DOI 10.17487/RFC5253, July 2008, <<https://www.rfc-editor.org/info/rfc5253>>.
- [RFC8199] Bogdanovic, D., Claise, B., and C. Moberg, "YANG Module Classification", RFC 8199, DOI 10.17487/RFC8199, July 2017, <<https://www.rfc-editor.org/info/rfc8199>>.
- [RFC8309] Wu, Q., Liu, W., and A. Farrel, "Service Models Explained", RFC 8309, DOI 10.17487/RFC8309, January 2018, <<https://www.rfc-editor.org/info/rfc8309>>.

Authors' Addresses

Young Lee
Samsung
Samsung
Seoul
South Korea

Email: younglee.tx@gmail.com

KwangKoog Lee
Korea Telecom
South Korea

Email: kwangkoog.lee@kt.com

Haomian Zheng
Huawei Technologies
H1, Huawei Xiliu Beipo Village, Songshan Lake
Dongguan, Guangdong 523808
China

Email: zhenghaomian@huawei.com

Oscar Gonzalez de Dios
Telefonica

Email: oscar.gonzalezdedios@telefonica.com

Daniele Ceccarelli
Ericsson

Email: daniele.ceccarelli@ericsson.com