

MLDP Signaling over BIER

Draft-ietf-bier-mldp-signaling-over-bier-00

Authors:

Hooman Bidgoli, Nokia

IJsbrand Wijnands, Individual

Jayant Kotalwar, Nokia

Mankamana Mishra, Cisco

Jeffrey Zhang, Juniper

IETF110, March 2021

Presenter Hooman Bidgoli



I E T F[®]

The Background

- mLDP signaling over BIER via Targeted LDP [RFC 7060]
 - Extending the work of signaling legacy multicast protocols over a BIER core.
- Some MNO/MSO providers are creating the Next Generation Converge Core for wireless and wireline services.
 - “Lean core”, Simplified underlay IGP and overlay BGP without any of the legacy MPLS protocols, in short relying on Segment Routing and BIER.
 - BIER is ideal for these network but extending it to all PEs (1000s) is operationally difficult and not necessarily desired. The access networks design are proven and work.
 - Operators are concentrating with upgrade of the core historically
- Problem:
 - Gradual upgrade to BIER starting with a desired network segment (Mostly Core).
 - Minimum interruption and disruption to mLDP portion of the network from signaling, services and image upgrade point of view

mLDP Signaling over BIER

- Use TLDP as per RFC 7060 to signal mLDP over BIER
- These procedures can be used for point-to-multipoint and multipoint-to-multipoint LSPs established via mLDP RFC 6388
- TLDP sessions between BIER edge routers and is used for signaling mLDP FEC over a BIER domain
- EBBRs can be discovered via the same procedures as draft-ietf-bier-pim-signaling
- On EBBRs same procedure as draft-ietf-bier-pim-signaling to build the list of IBBRs interested in the tree.
- TLDP can be pre-established manually or initiated automatically (When EBBRs are discovered) on the IBBR

Datapath Traffic Flow

- On BFIR when the MPLS label for P2MP/MP2MP LSP arrives from the source, a lookup in ILM table is performed and label is swapped with tLDP upstream assigned label.
- The BFIR will build the BIER Header based on all the BFER that are interested in this P2MP/MP2MP FEC.
- BFIR will set the BIERHeader.Proto = MPLS and forward the packet into Bier domain
- On BFER, based on the BIERHeader.Proto the BIER header will be removed and a lookup in the ILM for the upstream assigned label is performed the corresponding action is executed.
- It should be noted as that BFIR and BFER can be ILER and ELER respectively.

Next Steps

- The solution is considered complete
- Any additional comments?
- Asking for last call