

TEEP Architecture

draft-ietf-teep-architecture-14

Dave Thaler (presenting)

Ming Pei, David Wheeler, Hannes Tschofenig

Timeline

- JAN 2020: WGLC completed
- NOV 2020: IETF 109 last issues discussed
- Draft -14 posted with resolutions from IETF 109:
 - Issue #213: Added UnrequestTA conceptual API
 - Issue #214: Remove obsolete paragraph implicitly about secure domains
 - Issue #217: Added applicability text
- PR #219 is trivial editorial (fix typo, and alphabetical ordering in glossary)
- Doc is ready to go to IESG whenever shepherd directs
 - We believe the protocol spec is complete enough that any arch doc changes are unlikely

TEEP over HTTP: Agent-to-TAM Communication

draft-ietf-teep-otrp-over-http-10

Dave Thaler <dthaler@microsoft.com>

Timeline

- FEB 2020: WGLC completed, with reviews from Russ and Tiru
- JUL 2020: IETF 108 discussed subsequent reviews from Hannes, Ming, Mark Nottingham
- NOV 2020: IETF 109 last issue discussed
- Changes in Draft -10:
 - Issue #30: Added UnrequestTA conceptual API, per IETF 109 discussion
 - Issue #32: RequestPolicyCheck API and multiple TAMs (next slide)

RequestPolicyCheck API and multiple TAMs

- Per arch draft, a TEEP Agent may need to talk to multiple TAMs
 - e.g., one to get a TA, and a second one to get personalization data
- Problem: transport spec previously only implied one TAM
 - The TEEP/HTTP Client informs the TEEP Agent by invoking an appropriate "RequestPolicyCheck" API. The TEEP Agent will either (a) pass no data back, (b) pass back a **TAM URI** to connect to, or (c) pass back a **message buffer and TAM URI** to send it to.
- Resolution:
 - The TEEP Agent might need to talk to multiple TAMs, however, as shown in Figure 1 of [I-D.ietf-teep-architecture]. To accomplish this, the TEEP/HTTP Client keeps invoking the "RequestPolicyCheck" API until the TEEP Agent passes no data back, so that the TEEP Agent can return each TAM URI in response to a separate API call.
- Corresponding change was made in TEEP protocol spec