

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: 24 April 2023

D. Fedyk
E. Kinzie
LabN Consulting, L.L.C.
21 October 2022

Definitions of Managed Objects for IP Traffic Flow Security
draft-ietf-ipsecme-mib-iptfs-11

Abstract

This document describes managed objects for the management of IP Traffic Flow Security additions to IKEv2 and IPsec. This document provides a read only version of the objects defined in the YANG module for the same purpose.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 24 April 2023.

Copyright Notice

Copyright (c) 2022 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

Table of Contents

1. Introduction	2
2. Terminology & Concepts	3
3. Overview	3
4. Management Objects	3
4.1. MIB Tree	3
4.2. SNMP	5
5. IANA Considerations	19
6. Security Considerations	19
7. Acknowledgements	20
8. References	20
8.1. Normative References	20
8.2. Informative References	22
Authors' Addresses	22

1. Introduction

This document defines a Management Information Base (MIB) module for use with network management protocols in the Internet community. Traffic Flow Security (IP-TFS) extensions as defined in [I-D.ietf-ipsecme-iptfs] are enhancements to an IPsec tunnel Security Association to provide improved traffic confidentiality.

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to section 7 of [RFC3410].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIv2, which is described in STD 58, [RFC2578], STD 58, [RFC2579] and STD 58, [RFC2580].

The objects defined here are the same as [I-D.ietf-ipsecme-yang-iptfs] with the exception that only operational or state data is supported. By making operational data accessible via SNMP existing network management systems can monitor IP-TFS. This data is listed in the MIB tree in Section 4.1. This module uses the YANG model as a reference point for managed objects. Note an IETF MIB model for IPsec was never standardized however the structures here could be adapted to existing proprietary MIB implementations where SNMP is used to manage networks.

2. Terminology & Concepts

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

3. Overview

This document defines the MIB for access to operational parameters of IP traffic flow security (IP-TFS). IP-TFS, defined in [I-D.ietf-ipsecme-iptfs], configures a security association for tunnel mode IPsec with characteristics that improve traffic confidentiality and reduce bandwidth efficiency loss.

This document is based on the concepts and management model defined in [I-D.ietf-ipsecme-yang-iptfs]. This document assumes familiarity with IP security concepts described in [RFC4301], IP-TFS as described in [I-D.ietf-ipsecme-iptfs] and the IP-TFS management model described in [I-D.ietf-ipsecme-yang-iptfs].

This document specifies an extensible operational model for IP-TFS. It reuses the management model defined in [I-D.ietf-ipsecme-yang-iptfs]. It allows SNMP systems to read operational objects (which includes configured objects) from IP-TFS.

4. Management Objects

4.1. MIB Tree

The following is the MIB registration tree diagram for the IP-TFS extensions.

IP-TRAFFIC-FLOW-SECURITY-MIB registration tree

```
--iptfsMIB(1.3.6.1.2.1.500)
+--iptfsMIBObjects(1)
|   +--iptfsGroup(1)
|   |   +--iptfsConfigTable(1)
|   |   |   +--iptfsConfigTableEntry(1) [iptfsConfigSaIndex]
|   |   |   |
|   |   |   +-- --- Integer32          iptfsConfigSaIndex(1)
|   |   |   +-- r-n TruthValue         congestionControl(2)
|   |   |   +-- r-n TruthValue         usePathMtuDiscovery(3)
|   |   |   +-- r-n UnsignedShort      outerPacketSize(4)
|   |   |   +-- r-n CounterBasedGauge64 l2FixedRate(5)
|   |   |   +-- r-n CounterBasedGauge64 l3FixedRate(6)
```

```

    +-- r-n TruthValue          dontFragment (7)
    +-- r-n NanoSeconds         maxAggregationTime (8)
    +-- r-n UnsignedShort      windowSize (9)
    +-- r-n TruthValue         sendImmediately (10)
    +-- r-n NanoSeconds        lostPacketTimerInterval (11)
+--ipsecStatsGroup (2)
  +--ipsecStatsTable (1)
    +--ipsecStatsTableEntry (1) [ipsecSaIndex]
      +-- --- Integer32 ipsecSaIndex (1)
      +-- r-n Counter64 txPkts (2)
      +-- r-n Counter64 txOctets (3)
      +-- r-n Counter64 txDropPkts (4)
      +-- r-n Counter64 rxPkts (5)
      +-- r-n Counter64 rxOctets (6)
      +-- r-n Counter64 rxDropPkts (7)
+--iptfsInnerStatsGroup (3)
  +--iptfsInnerStatsTable (1)
    +--iptfsInnerStatsTableEntry (1) [iptfsInnerSaIndex]
      +-- --- Integer32 iptfsInnerSaIndex (1)
      +-- r-n Counter64 txInnerPkts (2)
      +-- r-n Counter64 txInnerOctets (3)
      +-- r-n Counter64 rxInnerPkts (4)
      +-- r-n Counter64 rxInnerOctets (5)
      +-- r-n Counter64 rxIncompleteInnerPkts (6)
+--iptfsOuterStatsGroup (4)
  +--iptfsOuterStatsTable (1)
    +--iptfsOuterStatsTableEntry (1) [iptfsSaIndex]
      +-- --- Integer32 iptfsSaIndex (1)
      +-- r-n Counter64 txExtraPadPkts (2)
      +-- r-n Counter64 txExtraPadOctets (3)
      +-- r-n Counter64 txAllPadPkts (4)
      +-- r-n Counter64 txAllPadOctets (5)
      +-- r-n Counter64 rxExtraPadPkts (6)
      +-- r-n Counter64 rxExtraPadOctets (7)
      +-- r-n Counter64 rxAllPadPkts (8)
      +-- r-n Counter64 rxAllPadOctets (9)
      +-- r-n Counter64 rxErroredPkts (10)
      +-- r-n Counter64 rxMissedPkts (11)
+--iptfsMIBConformance (2)
  +--iptfsMIBConformances (1)
  | +--iptfsMIBCompliance (1)
  +--iptfsMIBGroups (2)
    +--iptfsMIBConfGroup (1)
    +--ipsecStatsConfGroup (2)
    +--iptfsInnerStatsConfGroup (3)
    +--iptfsOuterStatsConfGroup (4)
```

4.2. SNMP

The following is the MIB for IP-TFS. The Congestion control algorithm in [RFC5348] is referenced in the MIB text.

```
<CODE BEGINS> file "iptfs-mib.mib"
=-->
-- *-----
-- * IP-TRAFFIC-FLOW-SECURITY-MIB Module
-- *-----

IP-TRAFFIC-FLOW-SECURITY-MIB DEFINITIONS ::= BEGIN
IMPORTS
    MODULE-IDENTITY, OBJECT-TYPE,
    Integer32, Unsigned32, Counter64, mib-2
        FROM SNMPv2-SMI
    CounterBasedGauge64
        FROM HCNUM-TC
    MODULE-COMPLIANCE, OBJECT-GROUP
        FROM SNMPv2-CONF
    TEXTUAL-CONVENTION,
    TruthValue
        FROM SNMPv2-TC;

iptfsMIB MODULE-IDENTITY
    LAST-UPDATED "202210210000Z"
    ORGANIZATION "IETF IPsecme Working Group"
    CONTACT-INFO
        "
            Author: Don Fedyk
            <mailto:dfedyk@labn.net>

            Author: Eric Kinzie
            <mailto:ekinzie@labn.net>"

-- RFC Ed.: replace XXXX with actual RFC number, update mib-2
-- entry and remove this note.

DESCRIPTION
    "This module defines the configuration and operational
    state for managing the IP Traffic Flow Security
    functionality [RFC XXXX]. Copyright (c) 2022 IETF
    Trust and the persons identified as authors of the
    code. All rights reserved.

    Redistribution and use in source and binary forms,
    with or without modification, is permitted pursuant
    to, and subject to the license terms contained in,
```

the Simplified BSD License set forth in Section 4.c of the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>).

This version of this SNMP MIB module is part of RFC XXXX (<https://tools.ietf.org/html/rfcXXXX>); see the RFC itself for full legal notices."

```
REVISION "202210210000Z"
DESCRIPTION
    "Initial revision. Derived from the IP-TFS Yang Model."
 ::= { mib-2 500}
--
-- Textual Conventions
--
UnsignedShort ::= TEXTUAL-CONVENTION
    DISPLAY-HINT "d"
    STATUS      current
    DESCRIPTION "xs:unsignedShort"
    SYNTAX      Unsigned32 (0 .. 65535)

NanoSeconds ::= TEXTUAL-CONVENTION
    DISPLAY-HINT "d-6"
    STATUS      current
    DESCRIPTION
        "Represents time unit value in nanoseconds."
    SYNTAX      Integer32

-- Objects, Notifications & Conformances

iptfsMIBObjects      OBJECT IDENTIFIER
    ::= { iptfsMIB 1 }
iptfsMIBConformance OBJECT IDENTIFIER
    ::= { iptfsMIB 2}

--
-- IP-TFS MIB Object Groups
--
iptfsGroup OBJECT IDENTIFIER
    ::= { iptfsMIBObjects 1 }

ipsecStatsGroup OBJECT IDENTIFIER
    ::= { iptfsMIBObjects 2 }
```

```
iptfsInnerStatsGroup OBJECT IDENTIFIER
    ::= { iptfsMIBObjects 3 }

iptfsOuterStatsGroup OBJECT IDENTIFIER
    ::= { iptfsMIBObjects 4 }

iptfsConfigTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF IptfsConfigTableEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The table containing configuration information for
        IP-TFS."
    ::= { iptfsGroup 1 }

iptfsConfigTableEntry OBJECT-TYPE
    SYNTAX      IptfsConfigTableEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An entry (conceptual row) containing the information on
        a particular IP-TFS SA."
    INDEX       { iptfsConfigSaIndex }
    ::= { iptfsConfigTable 1 }

IptfsConfigTableEntry ::= SEQUENCE {
    iptfsConfigSaIndex      Integer32,

    -- identifier information
    congestionControl       TruthValue,
    usePathMtuDiscovery     TruthValue,
    outerPacketSize        UnsignedShort,
    l2FixedRate             CounterBasedGauge64,
    l3FixedRate             CounterBasedGauge64,
    dontFragment           TruthValue,
    maxAggregationTime      NanoSeconds,
    windowSize             UnsignedShort,
    sendImmediately        TruthValue,
    lostPacketTimerInterval NanoSeconds
}

iptfsConfigSaIndex OBJECT-TYPE
    SYNTAX      Integer32 (1..16777215)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A unique value, greater than zero, for each SA.
        It is recommended that values are assigned contiguously
```

starting from 1.

The value for each entry must remain constant at least from one re-initialization of entity's network management system to the next re-initialization."

```
::= { iptfsConfigTableEntry 1 }
```

congestionControl OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"When set to true, the default, this enables the congestion control on-the-wire exchange of data that is required by congestion control algorithms as defined by RFC 5348. When set to false, IP-TFS sends fixed-sized packets over an IP-TFS tunnel at a constant rate."

```
::= { iptfsConfigTableEntry 2 }
```

usePathMtuDiscovery OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Packet size is either auto-discovered or manually configured. If usePathMtuDiscovery is true the system utilizes path-mtu to determine maximum IP-TFS packet size. If the packet size is explicitly configured then it will only be adjusted downward if use-path-mtu is set."

```
::= { iptfsConfigTableEntry 3 }
```

outerPacketSize OBJECT-TYPE

SYNTAX UnsignedShort

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"On Transmission, the size of the outer encapsulating tunnel packet (i.e., the IP packet containing the ESP payload)."

```
::= { iptfsConfigTableEntry 4 }
```

l2FixedRate OBJECT-TYPE

SYNTAX CounterBasedGauge64

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"IP-TFS bit rate may be specified as a layer 2 wire rate."

On transmission, target bandwidth/bit rate in bps for IP-TFS tunnel. This rate is the nominal timing for the fixed size packet. If congestion control is enabled the rate may be adjusted down."
 ::= { iptfsConfigTableEntry 5 }

13FixedRate OBJECT-TYPE
SYNTAX CounterBasedGauge64
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"IP-TFS bit rate may be specified as a layer 3 packet rate. On Transmission, target bandwidth/bit rate in bps for IP-TFS tunnel. This rate is the nominal timing for the fixed size packet. If congestion control is enabled the rate may be adjusted down."
 ::= { iptfsConfigTableEntry 6 }

dontFragment OBJECT-TYPE
SYNTAX TruthValue
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"On transmission, disable packet fragmentation across consecutive IP-TFS tunnel packets; inner packets larger than what can be transmitted in outer packets will be dropped."
 ::= { iptfsConfigTableEntry 7 }

maxAggregationTime OBJECT-TYPE
SYNTAX NanoSeconds
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"On transmission, maximum aggregation time is the maximum length of time a received inner packet can be held prior to transmission in the IP-TFS tunnel. Inner packets that would be held longer than this time, based on the current tunnel configuration will be dropped rather than be queued for transmission."
 ::= { iptfsConfigTableEntry 8 }

windowSize OBJECT-TYPE
SYNTAX UnsignedShort
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"On reception, the maximum number of out-of-order

```
    packets that will be reordered by an IP-TFS receiver
    while performing the reordering operation. The value 0
    disables any reordering."
 ::= { iptfsConfigTableEntry 9 }

sendImmediately OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "On reception, send inner packets as soon as possible, do
        not wait for lost or misordered outer packets.
        Selecting this option reduces the inner (user) packet
        delay but can amplify out-of-order delivery of the inner
        packet stream in the presence of packet aggregation and
        any reordering."
 ::= { iptfsConfigTableEntry 10 }

lostPacketTimerInterval OBJECT-TYPE
    SYNTAX      NanoSeconds
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "On reception, this interval defines the length of time
        an IP-TFS receiver will wait for a missing packet before
        considering it lost. If not using send-immediately,
        then each lost packet will delay inner (user) packets
        until this timer expires. Setting this value too low can
        impact reordering and reassembly."
 ::= { iptfsConfigTableEntry 11 }

ipsecStatsTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF IpsecStatsTableEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The table containing basic statistics on IPsec."
 ::= { ipsecStatsGroup 1 }

ipsecStatsTableEntry OBJECT-TYPE
    SYNTAX      IpsecStatsTableEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An entry (conceptual row) containing the information on
        a particular IKE SA."
    INDEX      { ipsecSaIndex }
```

```
 ::= { ipsecStatsTable 1 }

IpssecStatsTableEntry ::= SEQUENCE {
  ipsecSaIndex          Integer32,
-- packet statistics information
  txPkts               Counter64,
  txOctets             Counter64,
  txDropPkts          Counter64,
  rxPkts              Counter64,
  rxOctets            Counter64,
  rxDropPkts         Counter64
}

ipsecSaIndex OBJECT-TYPE
  SYNTAX          Integer32 (1..16777215)
  MAX-ACCESS     not-accessible
  STATUS         current
  DESCRIPTION
    "A unique value, greater than zero, for each SA.
    It is recommended that values are assigned contiguously
    starting from 1.

    The value for each entry must remain constant at least
    from one re-initialization of entity's network management
    system to the next re-initialization."
 ::= { ipsecStatsTableEntry 1 }

txPkts OBJECT-TYPE
  SYNTAX          Counter64
  MAX-ACCESS     read-only
  STATUS         current
  DESCRIPTION
    "Outbound Packet count."
 ::= { ipsecStatsTableEntry 2 }

txOctets OBJECT-TYPE
  SYNTAX          Counter64
  MAX-ACCESS     read-only
  STATUS         current
  DESCRIPTION
    "Outbound Packet bytes."
 ::= { ipsecStatsTableEntry 3 }

txDropPkts OBJECT-TYPE
  SYNTAX          Counter64
  MAX-ACCESS     read-only
  STATUS         current
```

```
DESCRIPTION
    "Outbound dropped packets count."
 ::= { ipsecStatsTableEntry 4 }

rxPkts OBJECT-TYPE
    SYNTAX      Counter64
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Inbound Packet count."
 ::= { ipsecStatsTableEntry 5 }

rxOctets OBJECT-TYPE
    SYNTAX      Counter64
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Inbound Packet bytes."
 ::= { ipsecStatsTableEntry 6 }

rxDropPkts OBJECT-TYPE
    SYNTAX      Counter64
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Inbound Dropped packets"
 ::= { ipsecStatsTableEntry 7 }

iptfsInnerStatsTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF IptfsInnerSaEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The table containing information on IP-TFS
        Inner Packets."
 ::= { iptfsInnerStatsGroup 1 }

iptfsInnerStatsTableEntry OBJECT-TYPE
    SYNTAX      IptfsInnerSaEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An entry containing the information on
        a particular IP-TFS SA."
    INDEX      { iptfsInnerSaIndex }
 ::= { iptfsInnerStatsTable 1 }

IptfsInnerSaEntry ::= SEQUENCE {
```

```
    iptfsInnerSaIndex      Integer32,

    txInnerPkts            Counter64,
    txInnerOctets          Counter64,
    rxInnerPkts            Counter64,
    rxInnerOctets          Counter64,
    rxIncompleteInnerPkts Counter64
  }

iptfsInnerSaIndex OBJECT-TYPE
    SYNTAX      Integer32 (1..16777215)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A unique value, greater than zero, for each SA.
        It is recommended that values are assigned contiguously
        starting from 1.

        The value for each entry must remain constant at least
        from one re-initialization of entity's network management
        system to the next re-initialization."
    ::= { iptfsInnerStatsTableEntry 1 }

txInnerPkts OBJECT-TYPE
    SYNTAX      Counter64
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Total number of IP-TFS inner packets sent. This count
        is whole packets only. A fragmented packet counts as
        one packet."
    ::= { iptfsInnerStatsTableEntry 2 }

txInnerOctets OBJECT-TYPE
    SYNTAX      Counter64
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Total number of IP-TFS inner octets sent. This is
        inner packet octets only. Does not count padding."
    ::= { iptfsInnerStatsTableEntry 3 }

rxInnerPkts OBJECT-TYPE
    SYNTAX      Counter64
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Total number of IP-TFS inner packets received."
```

```
 ::= { iptfsInnerStatsTableEntry 4 }

rxInnerOctets OBJECT-TYPE
SYNTAX      Counter64
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "Total number of IP-TFS inner octets received. Does
    not include padding or overhead."
 ::= { iptfsInnerStatsTableEntry 5 }

rxIncompleteInnerPkts OBJECT-TYPE
SYNTAX      Counter64
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "Total number of IP-TFS inner packets that were
    incomplete. Usually this is due to fragments not
    received. Also, this may be due to misordering or
    errors in received outer packets."
 ::= { iptfsInnerStatsTableEntry 6 }

iptfsOuterStatsTable OBJECT-TYPE
SYNTAX      SEQUENCE OF IptfsOuterSaEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "The table containing information on IP-TFS."
 ::= { iptfsOuterStatsGroup 1 }

iptfsOuterStatsTableEntry OBJECT-TYPE
SYNTAX      IptfsOuterSaEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "An entry containing the information on
    a particular IP-TFS SA."
INDEX      { iptfsSaIndex }
 ::= { iptfsOuterStatsTable 1 }

IptfsOuterSaEntry ::= SEQUENCE {
    iptfsSaIndex      Integer32,

-- iptfs packet statistics information
    txExtraPadPkts      Counter64,
    txExtraPadOctets    Counter64,
    txAllPadPkts        Counter64,
    txAllPadOctets      Counter64,
```

```
rxExtraPadPkts          Counter64,
rxExtraPadOctets        Counter64,
rxAllPadPkts            Counter64,
rxAllPadOctets          Counter64,
rxErroredPkts           Counter64,
rxMissedPkts            Counter64
}
```

iptfsSaIndex OBJECT-TYPE

SYNTAX Integer32 (1..16777215)

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"A unique value, greater than zero, for each SA.

It is recommended that values are assigned contiguously starting from 1.

The value for each entry must remain constant at least from one re-initialization of entity's network management system to the next re-initialization."

::= { iptfsOuterStatsTableEntry 1 }

txExtraPadPkts OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Total number of transmitted outer IP-TFS packets that included some padding."

::= { iptfsOuterStatsTableEntry 2 }

txExtraPadOctets OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Total number of transmitted octets of padding added to outer IP-TFS packets with data."

::= { iptfsOuterStatsTableEntry 3 }

txAllPadPkts OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Total number of transmitted IP-TFS packets that were all padding with no inner packet data."

```
 ::= { iptfsOuterStatsTableEntry 4 }

txAllPadOctets OBJECT-TYPE
    SYNTAX      Counter64
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Total number transmitted octets of padding added to
        IP-TFS packets with no inner packet data."
    ::= { iptfsOuterStatsTableEntry 5 }

rxExtraPadPkts OBJECT-TYPE
    SYNTAX      Counter64
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Total number of received outer IP-TFS packets that
        included some padding."
    ::= { iptfsOuterStatsTableEntry 6 }

rxExtraPadOctets OBJECT-TYPE
    SYNTAX      Counter64
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Total number of received octets of padding added to
        outer IP-TFS packets with data."
    ::= { iptfsOuterStatsTableEntry 7 }

rxAllPadPkts OBJECT-TYPE
    SYNTAX      Counter64
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Total number of received IP-TFS packets that were all
        padding with no inner packet data."
    ::= { iptfsOuterStatsTableEntry 8 }

rxAllPadOctets OBJECT-TYPE
    SYNTAX      Counter64
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Total number received octets of padding added to
        IP-TFS packets with no inner packet data."
    ::= { iptfsOuterStatsTableEntry 9 }

rxErroredPkts OBJECT-TYPE
```

```
SYNTAX      Counter64
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "Total number of IP-TFS outer packets dropped due to
    errors."
 ::= { iptfsOuterStatsTableEntry 10 }

rxMissedPkts OBJECT-TYPE
SYNTAX      Counter64
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "Total number of IP-TFS outer packets missing indicated
    by missing sequence number."
 ::= { iptfsOuterStatsTableEntry 11 }

--
-- Iptfs Module Compliance
--

iptfsMIBConformances OBJECT IDENTIFIER
    ::= { iptfsMIBConformance 1 }

iptfsMIBGroups OBJECT IDENTIFIER
    ::= { iptfsMIBConformance 2 }

iptfsMIBCompliance MODULE-COMPLIANCE
    STATUS      current
    DESCRIPTION
        "The compliance statement for entities which
        implement the IP-TFS MIB"
    MODULE      -- this module
        MANDATORY-GROUPS {
            iptfsMIBConfGroup,
            ipsecStatsConfGroup,
            iptfsInnerStatsConfGroup,
            iptfsOuterStatsConfGroup
        }

    ::= { iptfsMIBConformances 1 }

--
-- MIB Groups (Units of Conformance)
--

iptfsMIBConfGroup OBJECT-GROUP
    OBJECTS {
```

```
        congestionControl,
        usePathMtuDiscovery,
        outerPacketSize ,
        l2FixedRate ,
        l3FixedRate ,
        dontFragment,
        maxAggregationTime,
        windowSize,
        sendImmediately,
        lostPacketTimerInterval
    }
    STATUS current
    DESCRIPTION
        "A collection of objects providing per SA IP-TFS
        Configuration."
    ::= { iptfsMIBGroups 1 }

ipsecStatsConfGroup OBJECT-GROUP
    OBJECTS {
        txPkts,
        txOctets,
        txDropPkts,
        rxPkts,
        rxOctets,
        rxDropPkts
    }
    STATUS current
    DESCRIPTION
        "A collection of objects providing per SA Basic
        Stats."
    ::= { iptfsMIBGroups 2 }

iptfsInnerStatsConfGroup OBJECT-GROUP
    OBJECTS {
        txInnerPkts,
        txInnerOctets,
        rxInnerPkts,
        rxInnerOctets,
        rxIncompleteInnerPkts
    }
    STATUS current
    DESCRIPTION
        "A collection of objects providing per SA IP-TFS
        Inner Packet Statistics."
    ::= { iptfsMIBGroups 3 }

iptfsOuterStatsConfGroup OBJECT-GROUP
```

```

OBJECTS {
    txExtraPadPkts,
    txExtraPadOctets,
    txAllPadPkts,
    txAllPadOctets,
    rxExtraPadPkts,
    rxExtraPadOctets,
    rxAllPadPkts,
    rxAllPadOctets,
    rxErroredPkts,
    rxMissedPkts
}
STATUS current
DESCRIPTION
    "A collection of objects providing per SA IP-TFS
    Outer Packet Statistics."
 ::= { iptfsMIBGroups 4 }

```

```

END
<CODE ENDS>

```

5. IANA Considerations

The MIB module in this document uses the following IANA-assigned OBJECT IDENTIFIER value, recorded in the SMI Network Management MGMT Codes Internet-standard MIB - registry:

Name	Description	OBJECT IDENTIFIER value
iptfsMIB	IP-TRAFFIC-FLOW-SECURITY-MIB	{ mib-2 TBA-IANA }

6. Security Considerations

The MIB specified in this document can read the operational behavior of IP traffic flow security. For the implications regarding write configuration consult the [I-D.ietf-ipsecme-iptfs] which defines the functionality.

There are no management objects defined in this MIB module that have a MAX-ACCESS clause of read-write and/or read-create. So, if this MIB module is implemented correctly, then there is no risk that an intruder can alter or create any management objects of this MIB module via direct SNMP SET operations.

Some of the objects in this MIB module may be considered sensitive or vulnerable in some network environments. This includes INDEX objects with a MAX-ACCESS of not-accessible, and any indices from other

modules exposed via AUGMENTS. It is thus important to control even GET and/or NOTIFY access to these objects and possibly to even encrypt the values of these objects when sending them over the network via SNMP. These are the tables and objects and their sensitivity/vulnerability:

- * iptfsInnerStatsTable and iptfsOuterStatsTable- Access to IP inner and outer traffic flow security statistics can provide information that IP traffic flow security obscures such as the true activity of the flows using IP traffic flow security.

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure (for example by using IPsec), there is no control as to who on the secure network is allowed to access and GET (read) the objects in this MIB module.

To prevent unauthorized access to SNMP including access to IP-TFS sensitive objects:

- * Implementations SHOULD provide the security features described by the SNMPv3 framework (see [RFC3410]), and implementations claiming compliance to the SNMPv3 standard MUST include full support for authentication and privacy via the User-based Security Model (USM) [RFC3414] with the AES cipher algorithm [RFC3826]. Implementations MAY also provide support for the Transport Security Model (TSM) [RFC5591] in combination with a secure transport such as SSH [RFC5592] or TLS/DTLS [RFC6353].
- * Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

7. Acknowledgements

The authors would like to thank Chris Hopps, Lou Berger and Tero Kivinen for their help and feedback on the MIB model.

8. References

8.1. Normative References

- [I-D.ietf-ipsecme-iptfs]
Hopps, C., "IP-TFS: Aggregation and Fragmentation Mode for ESP and its Use for IP Traffic Flow Security", Work in Progress, Internet-Draft, draft-ietf-ipsecme-iptfs-19, 4 September 2022, <<https://www.ietf.org/archive/id/draft-ietf-ipsecme-iptfs-19.txt>>.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIv2)", STD 58, RFC 2578, DOI 10.17487/RFC2578, April 1999, <<https://www.rfc-editor.org/info/rfc2578>>.
- [RFC2579] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIv2", STD 58, RFC 2579, DOI 10.17487/RFC2579, April 1999, <<https://www.rfc-editor.org/info/rfc2579>>.
- [RFC3414] Blumenthal, U. and B. Wijnen, "User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3)", STD 62, RFC 3414, DOI 10.17487/RFC3414, December 2002, <<https://www.rfc-editor.org/info/rfc3414>>.
- [RFC3826] Blumenthal, U., Maino, F., and K. McCloghrie, "The Advanced Encryption Standard (AES) Cipher Algorithm in the SNMP User-based Security Model", RFC 3826, DOI 10.17487/RFC3826, June 2004, <<https://www.rfc-editor.org/info/rfc3826>>.
- [RFC5591] Harrington, D. and W. Hardaker, "Transport Security Model for the Simple Network Management Protocol (SNMP)", STD 78, RFC 5591, DOI 10.17487/RFC5591, June 2009, <<https://www.rfc-editor.org/info/rfc5591>>.
- [RFC5592] Harrington, D., Salowey, J., and W. Hardaker, "Secure Shell Transport Model for the Simple Network Management Protocol (SNMP)", RFC 5592, DOI 10.17487/RFC5592, June 2009, <<https://www.rfc-editor.org/info/rfc5592>>.

- [RFC6353] Hardaker, W., "Transport Layer Security (TLS) Transport Model for the Simple Network Management Protocol (SNMP)", STD 78, RFC 6353, DOI 10.17487/RFC6353, July 2011, <<https://www.rfc-editor.org/info/rfc6353>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.

8.2. Informative References

- [I-D.ietf-ipsecme-yang-iptfs]
Fedyk, D. and C. Hopps, "A YANG Data Model for IP Traffic Flow Security", Work in Progress, Internet-Draft, draft-ietf-ipsecme-yang-iptfs-11, 31 August 2022, <<https://www.ietf.org/archive/id/draft-ietf-ipsecme-yang-iptfs-11.txt>>.
- [RFC2580] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Conformance Statements for SMIPv2", STD 58, RFC 2580, DOI 10.17487/RFC2580, April 1999, <<https://www.rfc-editor.org/info/rfc2580>>.
- [RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework", RFC 3410, DOI 10.17487/RFC3410, December 2002, <<https://www.rfc-editor.org/info/rfc3410>>.
- [RFC4301] Kent, S. and K. Seo, "Security Architecture for the Internet Protocol", RFC 4301, DOI 10.17487/RFC4301, December 2005, <<https://www.rfc-editor.org/info/rfc4301>>.
- [RFC5348] Floyd, S., Handley, M., Padhye, J., and J. Widmer, "TCP Friendly Rate Control (TFRC): Protocol Specification", RFC 5348, DOI 10.17487/RFC5348, September 2008, <<https://www.rfc-editor.org/info/rfc5348>>.

Authors' Addresses

Don Fedyk
LabN Consulting, L.L.C.
Email: dfedyk@labn.net

Eric Kinzie
LabN Consulting, L.L.C.
Email: ekinzie@labn.net