

A YANG Data Model for Layer 0 Types – Revision 2

draft-ietf-ccamp-layer0-types-ext-01

Co-authors (frontpage):

- Dieter Beller (Nokia)
- Sergio Belotti (Nokia)
- Haomian Zheng (Huawei)
- Italo Busi (Huawei)
- Esther Le Rouzic (Orange)

Contributors

- Gabriele Galimberti (Cisco)
- Aihua Guo (Futurewei)
- Enrico Griseri (Nokia)

Status of the new document

- The document was adopted as WG draft and was submitted as 00 version in Aug 2021.
- Updates related to issue [#42](#) of draft-ietf-ccamp-optical-impairment-topology-yang regarding minimum-channel-spacing parameter :
 - Removed otsi-carrier-bandwidth and nyquist-spacing-factor
 - Added min-carrier-spacing
 - Clarified names and descriptions of min-central-frequency, max-central-frequency and central-frequency-step in line with the text in section 2.5.4 of the draft-ietf-ccamp-optical-impairment-topology-yang-08

Next Steps

- Add other YANG structures (grouping, identities, etc) as needed promoting the sharing of the same YANG structures among LO YANG models in CCAMP
- Waiting to incorporate updates from layer0-types as soon as it will have been published as RFC9093

backup

