

Root initiated routing state in RPL

draft-ietf-roll-dao-projection

Pascal Thubert, Rahul Arvind Jadhav, Matthew Gillmore

IETF 112

Virtual

Status of the draft

- Latest rev is [draft-ietf-roll-dao-projection-21](#)
- Includes IOT-DIR review by Toerless (next slide)
 - ↳ Deep, excellent review: kudos to Toerless
 - ↳ No final ack?
- Now formally updates RFC 6553
 - for the new RPL Option Flags subregistry
- Ready for WGLC (Editor's assessment)
 - Chairs called for the pre-WGLC review by Remous-Aris
- Also pending co-author final review before WGLC
 - After the deep changes during CoViD and IOT-DIR review

IOT-DIR review (1): shuffled sections for readability

Shorter, moved to Section 3

Expanded for Path Maintenance

Moved up in Context and Goal Section

Moved back to Main Text in Section 3

| | | |
|-------------|--|----|
| 1. | Introduction | 3 |
| 2. | Terminology | 5 |
| 2.1. | Requirements Language | 5 |
| 2.2. | Glossary | 5 |
| 2.3. | Other Terms | 6 |
| 2.4. | References | 6 |
| 3. | Extending RFC 6550 | 6 |
| 3.1. | Projected DAO | 7 |
| 3.2. | Sibling Information Option | 8 |
| 3.3. | P-DAO Request | 9 |
| 3.4. | Extending the RPI | 9 |
| 4. | Extending RFC 6553 | 9 |
| 5. | Extending RFC 8138 | 10 |
| 6. | New RPL Control Messages and Options | 11 |
| 6.1. | New P-DAO Request Control Message | 11 |
| 6.2. | New PDR-ACK Control Message | 12 |
| 6.3. | Via Information Options | 13 |
| 6.4. | Sibling Information Option | 13 |
| 7. | Projected DAO | 13 |
| 7.1. | Requesting a Track | 13 |
| 7.2. | Identifying a Track | 13 |
| 7.3. | Installing a Track | 13 |
| 7.3.1. | Storing-Mode P-Route | 13 |
| 7.3.2. | Non-Storing-Mode P-Route | 13 |
| 7.4. | Forwarding Along a Track | 13 |
| 8. | Profiles | 27 |
| 9. | Example Track Signaling | 28 |
| 9.1. | Using Storing-Mode Segments | 29 |
| 9.1.1. | Stitched Segments | 29 |
| 9.1.2. | External routes | 31 |
| 9.1.3. | Segment Routing | 32 |
| 9.2. | Using Non-Storing-Mode joining Tracks | 34 |
| 9.2.1. | Stitched Tracks | 36 |
| 9.2.2. | External routes | 36 |
| 9.2.3. | Segment Routing | 38 |
| 10. | Security Considerations | 41 |
| 11. | IANA Considerations | 41 |
| 11.1. | New Elective 6LoWPAN Routing Header Type | 41 |
| 11.2. | New Critical 6LoWPAN Routing Header Type | 42 |
| 11.3. | New Subregistry For The RPL Option Flags | 42 |
| 11.4. | New RPL Control Codes | 43 |
| 11.5. | New RPL Control Message Options | 43 |
| 11.6. | SubRegistry for the Projected DAO Request Flags | 43 |
| 11.7. | SubRegistry for the PDR-ACK Flags | 44 |
| 11.8. | Subregistry for the PDR-ACK Acceptance Status Values | 44 |
| 11.9. | Subregistry for the PDR-ACK Rejection Status Values | 44 |
| 11.10. | SubRegistry for the Via Information Options Flags | 45 |
| 11.11. | SubRegistry for the Sibling Information Option Flags | 45 |
| 11.12. | New Destination Advertisement Object Flag | 46 |
| 11.13. | Error in Projected Route ICMPv6 Code | 46 |
| 12. | Acknowledgments | 46 |
| 13. | Normative References | 46 |
| 14. | Informative References | 47 |
| Appendix A. | Applications | 49 |
| A.1. | Loose Source Routing | 49 |
| A.2. | Transversal Routes | 51 |
| | Authors' Addresses | 52 |

| | | |
|--------|--|----|
| 1. | Introduction | 3 |
| 2. | Terminology | 4 |
| 2.1. | Requirements Language | 4 |
| 2.2. | References | 4 |
| 2.3. | Glossary | 4 |
| 2.4. | Domain Terms | 5 |
| 3. | Context and Goal | 6 |
| 3.1. | RPL Applicability | 7 |
| 3.2. | RPL Routing Modes | 8 |
| 3.3. | Requirements | 9 |
| 3.3.1. | Loose Source Routing | 9 |
| 3.3.2. | East-West Routes | 10 |
| 3.4. | On Tracks | 12 |
| 3.5. | Serial Track Signaling | 13 |
| 3.5.1. | Using Storing Mode Segments | 14 |
| 3.5.2. | Using Non-Storing Mode joining Tracks | 20 |
| 3.6. | Complex Tracks | 27 |
| 3.7. | Scope and Expectations | 29 |
| 4. | Extending existing RFCs | 31 |
| 4.1. | Extending RFC 6550 | 31 |
| 4.1.1. | Projected DAO | 31 |
| 4.1.2. | Via Information Option | 33 |
| 4.1.3. | Sibling Information Option | 33 |
| 4.1.4. | P-DAO Request | 33 |
| 4.1.5. | Extending the RPI | 33 |
| 4.2. | Extending RFC 6553 | 34 |
| 4.3. | Extending RFC 8138 | 35 |
| 5. | New RPL Control Messages and Options | 36 |
| 5.1. | New P-DAO Request Control Message | 36 |
| 5.2. | New PDR-ACK Control Message | 37 |
| 5.3. | Via Information Options | 39 |
| 5.4. | Sibling Information Option | 42 |
| 6. | Root Initiated Routing State | 44 |
| 6.1. | Requesting a Track | 44 |
| 6.2. | Identifying a Track | 45 |
| 6.3. | Installing a Track | 46 |
| 6.3.1. | Signaling a Projected Route | 47 |
| 6.3.2. | Installing a Track Segment with a Storing Mode P-Route | 48 |
| 6.3.3. | Installing a Track Leg with a Non-Storing Mode P-Route | 50 |
| 6.4. | Tearing Down a P-Route | 52 |
| 6.5. | Maintaining a Track | 52 |
| 6.5.1. | Maintaining a Track Segment | 53 |
| 6.5.2. | Maintaining a Track Leg | 53 |
| 6.6. | Encapsulating and Forwarding Along a Track | 54 |
| 6.7. | Compression of the RPL Artifacts | 56 |
| 7. | Lesser Constrained Variations | 58 |
| 7.1. | Storing Mode Main DODAG | 58 |
| 7.2. | A Track as a Full DODAG | 60 |
| 8. | Profiles | 61 |
| 9. | Security Considerations | 63 |
| 10. | IANA Considerations | 63 |
| 10.1. | New Elective 6LoWPAN Routing Header Type | 64 |
| 10.2. | New Critical 6LoWPAN Routing Header Type | 64 |
| 10.3. | New Subregistry For The RPL Option Flags | 64 |

More Terms

New and Moved Text

More Cases

Protocol Operation in one big Section

New variations non-LLN Cases