

# **jscontact & jscontact-vcard**

**IETF 113 Vienna, calext**

**March 22, 2022**

# Status

- Adopted by calext
- New property `speakToAs`: defines grammatical gender and pronouns
- Discussion items: `contexts` and `label` properties
- Next: interop testing for `jscontact-vcard` mappings
- Target is WGLC at IETF 114

# contexts property

- contexts describes in which situations the use a specific contact method is appropriate.
- E.g. A business phone number might have a “work” context. The same Contact may also have another phone number with context “private”.
- Currently, only “work” and “private” context defined, new contexts require IANA registration.
- Thoughts: allow “other” context, as some address book applications do? Or allow any free text value?

# Label property

- label is a free-text value assigned to a contact method. A UI could display it along with the phone number, email address, etc.
- Currently, jscontact-vcard mapping uses label to indicate which VCARD property the contact method was mapped from. E.g. CALURI from VCARD maps to an Online resource

```
{“type”: “uri”, “resource”: “webcal://...”, “label”: “caluri”}
```

- Thoughts: Add calendarURI and freeBusyURI types for CALURI, FBURI, likewise for any other VCARD property. label should stay editable by user (no magic strings).
- Could come up with a general scheme to indicate which VCARD property maps where to JSContact.