Delay-Tolerant Networking Architecture

• RFC4838

- Published April, 2007
- Basis for work in DTNRG
- Observations
 - Some of this material is no longer considered best practice.
 - From experiments with BPv6
 - Changes to BPv7
 - New elements of the architecture emerging

Should DTNWG consider a refresh of this document?

Table of Contents

1.	Introduction	3
2.	Why an Architecture for Delay-Tolerant Networking?	4
	DTN Architectural Description	
_	3.1. Virtual Message Switching Using Store-and-Forward	_
	Operation	5
	3.2. Nodes and Endpoints	
	3.3. Endpoint Identifiers (EIDs) and Registrations	
	<u>3.4</u> . Anycast and Multicast	
	3.5. Priority Classes	
	3.6. Postal-Style Delivery Options and Administrative Records .	
	3.7. Primary Bundle Fields	
	3.8. Routing and Forwarding	
	3.9. Fragmentation and Reassembly	
	3.10. Reliability and Custody Transfer	
	3.11. DTN Support for Proxies and Application Layer Gateways	
	3.12. Timestamps and Time Synchronization	
	3.13. Congestion and Flow Control at the Bundle Layer	
	3.14. Security	
4	State Management Considerations	
Ξ.	<u>4.1</u> . Application Registration State	
	<u>4.2</u> . Custody Transfer State	
	4.3. Bundle Routing and Forwarding State	
	4.4. Security-Related State	
	4.5. Policy and Configuration State	
5	Application Structuring Issues	
	Convergence Layer Considerations for Use of Underlying	· <u>20</u>
۰.	Protocols	28
7	Summary	
	Security Considerations	
	IANA Considerations	
	. Normative References	
-	. Informative References	_
	. Acknowledgments	
12.	. ACKNOWIEUgmenus	. 24