

CoAP: Non-traditional response forms

bormann-core-responses-02

Carsten Bormann, *Christian Amsüss*

2024-03-20

CoRE at IETF 119 in Brisbane

Non-traditional responses

Non-traditional response

A response that is not the single response generated for a request received on the same transport.

- Define new versatile non-traditional responses
- *Define behavior of non-traditional responses in general*

Behavior definition: OSCORE

New in -02

- Explicit request or not: Request needs sender and sequence number.
- Request nonce can only be used in one response.
- If order matters, responses are ordered by sequence number.
- If replaying matters, responses are subjected to the replay window.
- If follow-up requests were made, transiently tolerate erroneous responses.

... and that's it on the OSCORE side?

Next steps

- Interop based on concrete documents adopting this?
- Future in the WG?

Backup slide: Potential users

Adapted from IETF113 slide set

RFC7252 simplest case	Single request, single response
RFC7252 multicast	Single request, different responses with different source addresses
RFC7641	Observe notifications come in until further notice ¹
core-coap-sms	Response-To-Uri-Host/-Port – triangular requests
core-coap-endpoint-id	Observations across server address changes
core-responses-00	Configured requests, Response-For
RFC9177	Responding with multiple blocks
core-groupcomm-proxy	Multicast-Timeout

¹No intent to redefine, but implementers may use common mechanisms